A-A-50147
January 6, 1988

COMMERCIAL ITEM DESCRIPTION

DISPENSER, ICE, AUTOMATIC DISPENSING HEAD, MOBILE

The General Services Administration has authorized the use of this commercial item description in preference to type II, size I and size II of MIL-D-43593.

1. SALIENT CHARACTERISTICS

1.1 Design and construction. The ice dispenser shall be designed to store approximately 200 pounds of ice in cube, cubelet, cracked, flaked, or shaved form. The ice dispenser shall be a manual loading and automatic dispensing model. The dispenser shall be equipped with a tower, auger, ice agitator, push handle, bumper guard, drain, removable drain pan, and removable lid. The dispenser shall be mounted on four casters, two of which shall have a braking mechanism. The dispensing storage cabinet, tower, auger, ice agitator, and push handle shall be constructed of stainless steel. The space between the double walled bottom and sides of the cabinet shall be filled with insulation or shall be of the air insulation type. The lid shall be constructed of either stainless steel or plastic and be a double hinged door or a single structured piece. The lid shall be double walled and shall be filled with insulation or shall be of the air insulation type. The insulation shall be fiberglass, expanded polystyrene, or fluorocarbon expanded polyurethane preformed or foamed-in-place. The cabinet shall be water tight and shall have a drain with petcock or shut off valve and shall be provided with a minimum 1/2 inch IPS drain opening with valve or plug. The bumper guards shall be vinyl and be installed around the outer perimeter of the dispensing cabinet (panel). The maximum dimensions of the ice dispenser shall be 45 inches long by 30 inches wide by 60 inches high.

1.2 Dispensing tower. The dispensing tower shall be located over the dispensing storage cabinet. The tower shall be equipped with an ice dispensing outlet and a pressure activated switch for automatic dispensing. The tower shall have a drain trough beneath the automatic ice dispensing outlet. The tower shall be easy to remove or dismantle for cleaning and servicing purposes.

1.3 Tray rail. When specified (see 4.2), the dispenser shall have a drop type tray rail mounted the full length of the ice dispensing side of the cabinet. The tray rail shall be constructed of stainless steel and shall be adjustable from 34 to 36 inches from the floor.

FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

1.4 Components. The necessary components (auger, ice agitator, controls, and motor) shall be furnished to provide for a smooth operation in the dispensing of ice.

1.5 Electrical. The ice dispenser shall be capable of operating on 115 volts, 60 hertz, single phase on 208/230 volts, 60 hertz, single phase a.c. Controls shall be designed for operating on either a nominal 115 volt or 208/230 volt power source. The transformer when supplied shall not be used to step up or step down the voltage for end item use and shall not be used where specifically prohibited, but may be used as part of the control system. When a 50 hertz frequency is specified and the end item is to be operated on that frequency, all systems shall be rated at that frequency. Controls rated at 115 volt, 60 hertz, 1-phase, may be used with a 50 hertz power source, provided that the power can be obtained from a hot line and neutral, or through a transformer. Relay transformers; or any other component housing for a complete control system shall be transferred as an integral part of the end item. Motors shall conform to NEMA MG1. Cords and outlets shall conform to UL 471.

1.6 Standards compliance. The dispenser shall comply with Underwriters Laboratories, Inc. Standard No. 73 and National Sanitation Foundation Standard No. 12.

1.7 Identification plate. In addition to the marking requirements of UL 471, the identification plate shall include the manufacturer's model, and name, address, and telephone number and serial number, contract number, and national stock number.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, complies with the marking requirements of UL 471 and 1.7 of this document and is the same as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3. PACKAGING

3.1 Packaging and packing. Packaging and packing shall be commercial or export, as specified.

3.2 Commercial packaging and packing. Each dispenser shall be cleaned, preserved, packaged, and unitized in accordance with ASTM 3951.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:39Z
Check the source to verify that this is the currentversion before use.

3.3 Export packaging. Each dispenser shall be cleaned, preserved, and cushioned to protect against corrosion, deterioration, and physical damage during shipping and storage. Disassembled parts and accessories shall be packaged in a fiberboard box conforming to style optional, type CF or SF, class domestic of PPP-B-636.

3.4 Export packing. Each dispenser with its parts packaged, shall be packed in a cleated plywood box conforming to PPP-B-601, type domestic, style optional, or a cleated fiberboard box conforming to PPP-B-591, class II. Each box shall be closed and strapped in accordance with PPP-B-601 or PPP-B-591, as applicable. When specified, shipping containers shall be palletized in accordance with MIL-STD-147.

3.5 Marking (commercial and export). Marking of unit pack, shipping container and unit load shall be in accordance with MIL-STD-129.

4. NOTES

4.1 Intended use. The dispenser covered by this commercial item description is intended for storing and automatically dispensing ice in dining facilities.

4.2 Ordering data.

a. Title, number, and date of this document.
b. When tray rail is required (see 1.3).
c. When electrical characteristics other than specified are required, the contracting officer shall provide voltage, phase, hertz and other necessary requirements to facilitate operation and installation (see 1.5).
d. Selection of applicable level of packaging and packing (see 3.1).

4.3 Sources for nongovernment association documents.

NEMA - National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037.

UL 471 - Motor Operated Appliances, Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

ASTM D 3951 - Standard Practice for Commercial Packaging, American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

A-A-50147

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 84

Review activities

Army - MD
Navy - MC

User activity

Navy - MS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0807

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:39Z
Check the source to verify that this is the current version before use.