A-A-50180
October 20, 1988

COMMERCIAL ITEM DESCRIPTION

FRYERS, DEEP FAT, ELECTRIC

The General Services Administration has authorized the use of this commercial item description in preference to type I and type II, sizes 3, 4, and 5 of S-F-695.

1. Classification. This commercial item description covers deep fat fryers in the following types and sizes:

Type I - Counter Model
Size 1 - 27 pounds minimum production capacity

Type II - Floor Model
Size 1 - 60 pounds minimum production capacity
Size 2 - 90 pounds minimum production capacity
Size 3 - 125 pounds minimum production capacity

2. Salient characteristics.

2.1 Design and construction. Each fryer shall be equipped with a stainless steel cover with handle for covering the cooking vessel and with one large and two half baskets. Baskets shall be made of stainless steel or steel tinned using at least 95% pure tin, or steel plated with a material meeting the requirements of National Sanitation Foundation (NSF) Standard No. 4. Automatic basket lifts shall be furnished upon request. Fryers shall be equipped with stainless steel swing-up heating elements. A device shall be provided to hold or lock the elements in the raised position. The type I fryer shall be desingewd for counter use and comply with the requirements of table I. The cabinet front door and sides shall be stainless steel. The back and bottom shall be stainless steel, aluminum steel, galvanized steel, or steel treated to resist corrosion. The type I cabinet shall be equipped with 4-inch high adjustable steel legs. The type II cabinet shall be equipped with the option of either 6-inch adjustable stainless steel legs or two rigid and two swivel casters with brakes. A removable nickel plated cooking vessel shall be provided with each fryer. A die stamped oil capacity indicating mark shall be provided on the rear wall inside the cooking vessel. The cabinet shall be enclosed and have a door or drawer and have a shelf or other means at the bottom to accommodate a fat draining vessel. The cabinet front shall be stainless steel with the remaining side and back finished in accordance with the manufacturer's practice. Cooking vessels should be of stainless steel or nickle plated steel, be removable or nonremovable, equipped with a hand operated drain valve. Type II fryers shall be provided with a stainless steel fat draining vessel with carrying handle(s) and a minimum capacity of 35 percent of the cooking capacity. The type II fryers shall comply with the requirements of table I.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

TABLE I. Fryer Requirements

	Production capacity 1/ Lbs/Hr(min)	Preheat time 70°F to 350°F minutes (max)	Total KW (min)	Dimensions, inches (max) Height 2/	Width	Depth
Type I, size 1	27	7	5.5	14	18	24-1/2
Type II, size 1	60	7	12.0	37	20	39
Type II, size 2	90	7	16.0	37	20	39
Type II, size 3	125	7	16.5	37	20	39

1/ Production capacity of raw to done, 1/2 inch by 1/2 inch, french fries that can be processed in 1 hour.

2/ Height to top of cooking vessel including legs.

2.2 Electrical requirement. Type I fryer shall operate on a nominal 208 volt, 60 hertz, 1 phase power source or a nominal 220 volt, 50 hertz, 1 phase power source as specified (see 5.2). The type II fryers shall operate on a nominal 208 volt, 60 hertz, 3 phase power source or a nominal 380 volt, 50 hertz, 3 phase power source as specified (see 5.2). All fryers shall have provisions for permanent electrical connection.

2.2.1 Solid-state. The solid-state control system shall incorporate as a minimum, a temperature dial, power ON-OFF switch, start/reset switch, test switch, melt/fry switch and fuse holder and fuse. All switches shall be located on a single control panel located on the front to the fryer. Switches to be of the toggle, rocker or membrane type. Toggle type switches when provided in fryers for naval shipboard installations shall be protected with a gasket. As each system is energized, the indicator light for that function shall operate as intended by the manufacturer, i.e., glows, flashes or goes out.

2.3 Thermostats. The fryers shall be equipped with an adjustable thermostat having a temperature range of 200°/275°F to 375°/400°F. The thermostat shall have a positive "OFF" position with the temperature marked at 50°F intervals and with graduated markings at 25°F intervals. A separate "ON-OFF" switch may be provided in addition to or in lieu of a positive "OFF" position to control power to the thermostat. In addition, the fryer shall be equipped with a non-adjustable overtemperature thermostat of the manual reset type. A signal light shall indicate when the overtemperature thermostat is activated. A test circuit with a signal light shall be provided to ensure the operation of the overtemperature circuit when the primary thermostat fails or is by-passed.

2.3.1 Signal lights. The fryer shall be equipped with a signal light to indicate that power is available at the fryer when "ON-OFF" switch is in the "ON" position. The fryer shall have a signal light that glows when the heating elements are heating and goes out whenever the dialed temperature is reached. Signal lights shall be of such size and located in such a manner as to be readily visible by the operator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

2.4 Standards compliance. The fryers shall comply with Underwriters Laboratories Standard (UL) 197 and the National Sanitation Foundation (NSF) Standard No. 4.

2.5 Data name plate (Government unique requirement (see 5.4)). The rack shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the rack by rivets, screws or welding in such a manner as to meet the applicable National Sanitary Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (See 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the rack.

3. Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producers' own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial.

4.2.1 Commercial packaging and packing. Each fryer shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

4.3 Export.

4.3.1 Export packaging. Each fryer shall be disassembled to the extent determined by the contractor to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be packaged in a domestic fiberboard box constructed and closed in accordance with PPP-B-636. Parts not removed shall be secured in place with cushioning or pressure-sensitive tape. Doors and drawers shall be secured in a closed position with filament reinforced pressure-sensitive tape. The fryer and parts shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration, and physical damage during shipment and storage.

4.3.2 Export packing. Each fryer shall be packed in a snug-fitting wood-cleated, plywood box, conforming to domestic type, style A or J, grade B, type 2, load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. The contents of each box shall be blocked and braced to prevent movement while the box is in transit. When legs or casters are not disassembled, the fryer shall be blocked in a manner to provide approximately 1 inch clearance between the legs or casters and the bottom of the box. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 and PPP-B-621, as applicable.

4.4 Marking (commercial and export). Marking of unit pack and shipping container shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The fryers are intended for use in kitchens or galleys for deep fat frying of food products.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Type and size of fryer required (see 1).
c. Power source required (see 2.2).
d. Government approved manual number to be included on data name plate (see 2.5).
e. Selection of applicable packaging and packing required (see 4.1).

5.3 Sources of documents.

5.3.1 Sources for nongovernment associated documents.

Underwriters Laboratories, Inc. (UL)

No. UL 197 - Commercial Electric Cooking Appliances

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

National Sanitation Foundation (NSF)

No. 4 - Commercial Cooking and Hot Food Storage Equipment

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.)

American Society for Testing and Materials (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

5.3.2 Sources of governmental documents.

Military documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

5.5 Classification comparison.

S-F-695G	CID A-A-50180
Type I	Type I
Type II	
Size 2	------
Size 3	Size 1
Size 4	Size 2
Size 5	Size 3

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD, TS
Navy - SA, MC
Air Force - 50
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITIES

GSA - FSS
VA - OSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0723

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.