A-A-50187
December 2, 1988

COMMERCIAL ITEM DESCRIPTION

PREFLUSHING MACHINE, DISH

The General Services Administration has authorized the use of this commercial item description in preference to MIL-P-12390.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers one type of preflushing machine used in conjunction with a dishwashing machine.

2. SALIENT CHARACTERISTICS

2.1 Design. The preflushing machine shall be designed to remove waste food particles from dishes and tableware before they are placed in a dishwashing machine. The machine shall consist of a rinser tank and a gusher tube through which water shall flow. Provisions for collecting food waste, a drain pipe for draining grease particles, and a mixing valve for maintaining water temperature shall be provided. The top of the unit shall be adaptable to a table height of 32 to 35-1/2 inches and shall be self supporting.

2.2 Standards compliance. The preflushing machine shall conform to National Sanitation Foundation (NSF) Criteria C-2 and Underwriters Laboratory (UL) Standard UL 73.

2.3 Tank. The tank shall be fabricated from 300 series stainless steel with a minimum thickness of 0.0512 inches.

2.4 Gusher tube. The gusher tube shall provide the water to remove the food soil and shall be cast of brass.

2.5 Scrap basket. A scrap basket shall be provided for collecting food waste particles and shall be fabricated of stainless steel. Provisions for easy removal and emptying of scrap basket shall be made.

AMSC/NA FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

2.6 Pump. The pump shall be capable of delivering at least 20 gallons of water per minute and a gusher stream at a height of not less than 5 inches and not more than 7 inches above the rim of the tank. The entire system when operated in accordance with the manufacturer's instructions shall not show any evidence of leakage.

2.7 Motor. Unless otherwise specified (see 5.2), the motor shall be rated for operation on a nominal 120 volt, 60 hertz, single-phase, alternating current power system. The motor shall be rated no less than 1/6 horsepower.

2.8 Base. The tank, motor, and pump assembly shall be mounted on a base which is either case or fabricated from aluminum. The base shall be provided with not less then three legs and one of the legs shall be located directly below the pump.

2.9 Water mixing valve. The water mixing valve shall automatically blend hot and cold incoming water to a temperature of 115°F plus or minus 5°F at a flow rate of 1-1/2 gallons per minute.

2.10 Drive belt guard. Pulleys and drive belts shall be covered by an aluminum or corrosion-resisting steel removable guard.

2.11 Data name plate (Government unique requirement, see 5.4) The heater shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information shall not apply. The data name plate shall be made of minimum 20-gauge corrosion-resisting metal and attached to the heater by rivets, screws, or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

National stock number
Procurement instrument identification number
Specification data
Manufacturer's name, address, and telephone number
Supplier's name, address, and telephone number (list only if different from manufacturer)
Manufacturer's model number
Government approved manual number (see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the preflushing machine.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the currentversion before use.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of the description and except for those government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The contractor shall certify the product meets the "Government unique" requirements except when specific quality assurance provisions are specified for the Government unique requirements. In this case, the contractor shall provide data resulting from inspection conducted in accordance with the specified quality assurance. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and Packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each item shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Export packaging. Each preflushing machine shall be cleaned, preserved, and cushioned to protect against corrosion, deterioration, and physical damage during shipping and storage. All openings shall be taped. Parts shall be packaged in a fiberboard box conforming to PPP-B-636, type CF or SF, class domestic, style optional. Movable components shall be secured to prevent movement.

4.3.1 Export packing. Each preflushing machine, with its parts packaged, shall be packed in a cleated plywood box conforming to overseas type, style optional, type 2 load of PPP-B-601. Each box shall be closed and strapped in accordance with PPP-B-601. When specified (see 5.2), shipping containers shall be palletized in accordance with MIL-STD-147.

4.4 Marking (commercial and export). Marking of shipping container and unit load shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The preflushing machines are intended for use in removing waste food particles from dishes and tableware before they are placed in a mechanical dishwashing machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

5.2 Ordering data.

a. Title, number, and date of this document
b. Electrical requirements, if other than specified (see 2.7)
c. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.11)
d. Selection of applicable packaging and packing (see 4.1)
e. When palletization is required (see 4.3.1)

5.3 Sources for nongovernment associated documents.

Underwriters Laboratories Standard UL 73 - Copies are available from: The Underwriters Laboratories, Inc., 333 Pfingsten Rd., Northbrook, IL 60062.

National Sanitation Foundation NSF Criteria C-2 - Copies are available from: The National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "Salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 99

Review activities

Army - MD
Air Force - 84
DLA - GS

User activity

Army - CE

CIVIL AGENCY COORDINATING ACTIVITY

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7320-0836

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:40Z
Check the source to verify that this is the currentversion before use.