INCH POUND

A-A-50362B
July 20, 2000
SUPERSEEDING
A-A-50362A
October 10, 1995

COMMERCIAL ITEM DESCRIPTION

OVERSHOES, MEN'S, RUBBER, 5 BUCKLE TYPE

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE. This commercial item description covers the requirements for one type of black, medium weight, rubber, 5 buckle overshoes, for land and shipboard use.

2. CLASSIFICATION. The overshoes are available in sizes 5 through 15 (inclusive).

3. SALIENT CHARACTERISTICS.

3.1 Description. The overshoes shall be waterproof, of medium weight construction, with a semi-blucher throat opening, closed with 5 buckles and a corrugated and cleated chevron-type outersole/heel design.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Supply Center Philadelphia, Clothing and Textiles Directorate, Attn: DSCP-CRFD, 700 Robbins Avenue, Bldg. 6D, Philadelphia, PA 19111-5092.

AMSC N/A FSC 8430

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

3.2 Materials.

3.2.1 Rubber compound. The rubber compound shall be natural and/or synthetic, colored black, meeting applicable requirements of 3.2.1.1 and 3.2.1.2.

3.2.1.1 Upper compound. The rubber upper compound shall meet the following requirements:

Tensile strength		
Initial	1450 lb./in.^{2} (minimum)	ASTM-D-412
After aging	75% of original (minimum)	ASTM-D-412 1/
Ultimate elongation	350% (minimum)	ASTM-D-412

3.2.1.2 Outsole and heel. The outsole and heels shall be rubber, non-marking, and shall meet the following requirements:

Abrasive index		
Initial	45 (minimum)	ASTM-D-1630
After aging	75% of original (minimum)	ASTM-D-1630 1/
Hardness		
Initial	55 ± 5	ASTM-D-2240
After aging	65 (maximum)	ASTM-D-2240 1/

1/ The aging test shall consist of 16 hours at 212°F (±2°F) using Test Method 7221 of FED-STD-601.

3.2.2 Lining fabric. The lining fabric shall be of a commercial/industry construction and type. When visible inside the boot, the color shall be black or brown, show a rating equal to or better than the rating of "3-4" on AATCC Gray Scale for Color Change and Color Transfer when tested for colorfastness to water in accordance with AATCC-107. Crocking shall show a rating equal to or better than the rating of "3.5" on AATCC Chromatic Transference Scale when tested in accordance with AATCC-8.

3.2.3 Buckles. The buckles shall be a ladder and clasp type, commercial size, cold and rolled sheet steel with either a black enamel finish or a black chemical finish and which has been lacquered or epoxy finished.

3.2.4 Fabric for rubber buckle strap reinforcement. The fabric shall be cotton osnaburg with a weight of 4.9 oz./sq. yd. with reinforcement cords placed inside the strap, one cord at each edge.

3.3 Construction. The overshoes shall be constructed in accordance with approved patterns and molds utilizing commercial methods. All overlapped parts shall be substantially rolled or pressed before vulcanization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

3.3.1 Pattern and molds. The contractor's patterns and molds shall be approved by the contracting officer prior to production.

3.3.1.1 Height. The overshoes shall be 13-1/2 (±1/2) inches high for size 10. The measuring device shall be placed in the inside of the overshoe where the heel seat and the backseam meet measuring up to the top of the boot. The contractor's grading is allowed for the remaining sizes.

3.3.1.2 Vulcanization. The overshoes shall be vulcanized under pressure. Blisters or air pockets are not allowed in the seams. All parts shall be cured into one piece.

3.4 Labeling. In addition to any commercial markings, each overshoe shall have the size and contract number indicated. The overshoe shall have the size incised or branded on the outsole in the shank area near the heel. As an alternate, the size may be pin stamped on the top edge of the back strip and the contract number may be stamped or printed on the leg or pocket lining of the overshoe, approximately 1 inch below the top of the overshoe.

3.4.1 Label/tag. Each pair of overshoes shall be individually bar-coded with a paper tag. The paper tag shall be standard bleached sulfate having a basis weight of 100 pounds. The paper used for the tags shall have a smooth finish to accept thermal transfer to direct printing. The tags shall have a hole and shall be attached to each item by a fastener, clearly legible and readable by a scanner. The bar coding element shall be a 13 digit national stock number (NSN) and there shall be a 12 digit UPC symbol for each NSN as specified in each solicitation. The "UPC" must appear beneath the code. The bar-code for NSN and UPC type shall be a medium to high code density and shall be located so that it is completely visible on the item when it is packaged as specified and causes no damage to the item. This UPC code must also be placed on all shipping cartons on which the NSN appears.

3.5 Leakage requirement. After vulcanization, the overshoes shall show no leakage when tested as specified in 5.3.

3.6 Finish. The overshoes shall have a smooth finish.

4. REGULATORY REQUIREMENTS.

4.1 Recycled, recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. PRODUCT CONFORMACE PROVISIONS.

5.1 Product conformance. The contractor shall meet the salient characteristics of the commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance .

5.2 Visual examination. Each pair of overshoes shall be examined for the defects listed below.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

5.2.1 Defects. Color not as specified; any ladder or clasp (buckle) omitted, misplaced, damaged, or malformed interfering with proper functioning; any air pocket or channel in any seam; poor or uneven lasting affecting serviceability or appearance; design not fabricated in accordance with production demonstration model; label missing, incorrect, illegible, or misplaced; measurement of item not as specified; NSN or UPC bar-code omitted or not readable by scanner; human-readable interpretation (HRI) omitted or illegible; bar code not visible on packaged item; bar code causes damage to the item; any items not packaged in accordance with the contract or purchase order.

5.3 End item performance testing. The overshoes shall be tested as specified in paragraphs 3.5 and 5.3.1. The sample size shall be five overshoes, regardless of lot size.

5.3.1 Leakage test. Dry specimens shall be filled with water to within three (3) inches to the top of the overshoe and allowed to stand for five (5) minutes before examination. Evidence of leakage shall be indicated by the appearance of water on the exterior surface of the overshoe.

5.4 Acceptance criteria. Acceptance criteria shall be as specified in the contract or purchase order.

6. PACKAGING.

6.1 Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or purchase order.

7. NOTES:

7.1 Source of Government documents. Copies of military and Federal documents are available from:

FED-STD-601 -Rubber: Sampling and Testing
Method 7221 Air Heat Test, Air Heating Medium

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

7.2 Source of non-Government documents

ASTM Test Methods

ASTM-D- 412 - Rubber Vulcanized and Thermoplastic Elastomers-Tension
ASTM-D-1630 - Rubber Property- Abrasion Resistance
ASTM-D-2240 - Rubber Property- Durometer Hardness

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

(Applications for copies should be addressed to American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428.)

AATCC T- Test Methods

AATCC-8 -Colorfastness to Crocking: AATCC Crockmeter Method
AATCC-107 -Colorfasteness to Water

(Applications for copies should be addressed to American Association of Textile Chemists and Colorists (AATCC), PO Box 12215, Research Triangle Park, NC 27709-2215.)

7.2 Suggested manufactures. In a limited market search for overshoes that meet the salient characteristics of this commercial item description, the following manufacturers are listed below. It must be noted that this list is not all-inclusive and that there may be other manufactures in the market place with a suitable product.

Boss Manufacturing Company, Kewannee, IL 61443
Norcross Safety Products, Rock Island, IL 61201
Bata Shoe Company, Belcamp, MD 21017
LaCrosse Footwear, inc., LaCrosse, WI 54602
Rainfair, Inc., Racine WI 53403

MILITARY INTERESTS:

Custodians
Navy - NU
Army – GL
Air Force – 99

Review Activity

Army – MD
Air Force – 11.6

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

PREPARING ACTIVITY:
DLA - CT

Project 8430-0450

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.