INCH-POUND
A-A-50363A
7 January 1991
SUPERSEDING
A-A-50363
12 February 1985

COMMERCIAL ITEM DESCRIPTION

JUMPER, RADIOACTIVE CONTAMINANTS PROTECTIVE (VINYL)

This Commercial Item Description is authorized for use by all Departments and Agencies of the Department of Defense.

Description - The jumper shall be a pullover body style with elastic attached at the neck, waist and wrist openings of the full length sleeves. The elastic shall be attached with a seam or may be encased in heat sealed tunnels. The joining seams shall be heat sealed (non-embossed) to finish on the inside of the garment.

Material - The material for the jumper shall be made of a yellow plastic film, flexible, vinylchloride, 0.0080 (±0.0008) inch thick, conforming to type I, class 2 of L-P-375, except that the requirements for extraction in soapy water, volatility, resistance to weathering, cold crack, and lacquer lifting shall not apply. No pinholes are allowed.

Sizes and measurements - The jumper shall be one type in one size. All measurements and tolerances are expressed in inches. The finished jumper shall have the following measurements when measured flat:

Chest (across front at armpit)	- 35
Waist (fully expanded across bottom - minimum	- 25
Sleeve	
Inseam	- 22-1/2
Width (6 inches above elastic)	- 9
Length (shoulder to bottom of jumper)	- 35-1/2
Tolerances	- ±1

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Officer in Charge, Navy Clothing and Textile Research Facility, Post Office Box 59, Natick, MA 01760-0001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

Labels. Each jumper shall be labeled in a permanent and visible manner with the manufacturer's name, contract number, and national stock number.

Workmanship - After completion, the jumper shall be thoroughly cleaned and all foreign matter removed.

Product demonstration model - Offerers are required to submit 2 (two) jumpers of their intended production and style. Product demonstration model will consist of units independently developed. Product demonstration models will be analyzed and evaluated by the Government. Evaluation criteria and basis for award are contained in the solicitation. Production demonstration models will be retained by the Government. One (1) product demonstration model approved by DPSC under the resultant contract will serve as a manufacturing standard for the corresponding production items delivered under this contract. Offerers are advised that the product demonstration model does not relieve the successful offerer of his responsiblity to perform in accordance with the Commercial Item Description specified above.

Responsiblity for inspection - The supplier is responsible for assuring the product conforms to the requirements. Jumper lots will be inspected to determine conformance with the Commercial Item Description and the successful offerer's technical proposal as negotiated. Acceptability of jumper lots will be determined by the use of "Sampling Procedures and Tables for Inspection by Attributes", ANSI Z1.4, published by the American Society for Quality Control. Sampling procedures will be designated by the Government at the time of award. The sample unit is one jumper. The jumper will be examined for commercial type defects only.

Defects - The jumpers shall be examined for the following defects: any hole, cut tear, open seam; any inadequte heat seal, i.e., incomplete or irregular such that the seam can be pulled apart with moderate hand pressure; any component omitted or not as specified; any measurement not as specified; design other than specified; any defect not otherwise classified herein but at variance with the product demonstration model; not fabricated in accordance with the product demonstration model; label omitted, incorrect, or illegible.

Preservation. The jumpers shall be packaged in accordance with normal commercial practice. The use of polyethylene film bags is not allowed.

Packing. Thirty (30) jumpers, preserved as above, shall be packed in a fiberboard shipping container assembled, closed, and reinforced comforming to type CF, class domestic, variety DW, grade 275, size 3A of MIL-B-17757. The fiberboard for the liner shall conform to type CF, class domestic of MIL-B-17757. Each container shall have the contents completely covered on the top and bottom with a sheet of commercial grade kraft paper.

Marking - The unit package, intermediate, outer container, and the palletized load, as applicable, shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:41Z
Check the source to verify that this is the currentversion before use.

Palletization - When specified in the contract, item packed as specified above shall be palletized on a 4-way entry pallet in accordance with load type 1A of MIL-STD-147. Each prepared load shall be bonded in accordance with the bonding methods C and D or film bonding F or G. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. The pallet shall be 4-way, type IV, class 1, size 2; or fabricated from wood group I, II, III or IV, grade A of NN-P-71, or 4-way, style 1, size A, type I, class 1 fabricated from wood groups of MIL-P-15011. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

Suggested source - Nuclear Power Outfitters and Lancs Industries have been found to meet the requirements of this Commercial Item Description.

Custodian:
Navy - NU

Preparing Activity:
Navy - NU

Review Activity:
DLA - CT
Navy - SH

Project No. 8415-N787

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.