A-A-50364
12 February 1985
SEE NOTE

COMMERCIAL ITEM DESCRIPTION

TROUSERS, RADIOACTIVE CONTAMINANTS PROTECTIVE (VINYL)

The Navy Clothing and Textile Research Facility has authorized the use of this commercial item description.

Salient Characteristics

Trouser, radioactive contaminants protective, shall be made of 8 guage (0.0080 inch) polyvinyl chloride film, yellow in color and free of pin holes. The waist of the trousers shall be finished with elastic and the leg openings may be finished with or without elastic. The elastic shall be attached with a 301, 304 or 401 stitch and a BSa-1 seam or it can be encased in heat sealed tunnels. The joining seams shall be SSa-1 type, heat sealed (non-embossed) to finish on the inside of the garment. The trousers shall be extra large size having the following dimensions when measured flat:

Waist (fully expanded across top)	- 24 inches
Seat (6 inches down from top)	- 25 1/2 inches
Length (from top of waist band to crotch joining seam)	- 17 inches
Leg	
Inseam	- 28 inches
Width (6 inches up from bottom)	- 14 inches
Width (at crotch joining seam)	- 16 inches

NOTE: A $\pm$ 1 inch tolerance is allowed for all measurements.

Quality Assurance Provisions

Defects- Sampling and end item inspection shall be in accordance with MIL-STD-105. The inspection level shall be Level I and the AQL shall be 2.5. The lot size shall be expressed in single units. During the manufacturing process, the manufacturer shall remove parts with defective materials and workmanship damages and replace with non-defective components.

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:41Z
Check the source to verify that this is the current version before use.

Defects are as follows:

1. Any hole, cut or tear
2. Any open seam
3. Any inadequate heat seal, i.e., incomplete or irregular such that the seam can be pulled apart with moderate hand pressure
4. Any component omitted
5. Any component not as specified
6. Any measurement out of tolerance
7. Design other than specified

Labeling

Each vinyl trouser shall be labeled in a permanent and visible manner with the manufacturer's name and identifying number.

Packaging, Packing and Marking

The trousers shall be packaged in accordance with normal commercial practice. Forty (40) trousers shall be packed in a fiberboard shipping container conforming to type CF, class domestic, variety DW, grade 275, size 3A of MIL-B-17757. The liner shall be type CF, class domestic, in accordance with the requirements of MIL-B-17757. The box shall be closed in accordance with the box specification. The shipping containers shall be marked as specified by MIL-STD-129.

Palletization

Packaged trousers shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or bonding means O. Pallet patternshall be in accordance with load pattern number 3 of the appendix of MIL-STD-147. Interlocking of loads shall be affected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

Conformance

The Government reserves the right to require proof of conformance to this commercial item description prior to the first delivery and thereafter, if necessary.

NOTES

This COMMERCIAL ITEM DESCRIPTION replaces the trousers of A-A-50361 Suit, Radioactive Contaminants Protective (Vinyl), dated 20 October 1983.

Custodian:
Navy - NU

Preparing Activity:
Navy - NU

Review Activities:
Navy - SH
DLA - CT

Project Number:
8415-0450

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.