INCH POUND

A-A-50423
20 February 1995

COMMERCIAL ITEM DESCRIPTION

APPLICATOR, SELF-PRESSURIZED CAN, BRUSH-TYPE, FOR USE WITH ISOPROPYL ALCOHOL SOLVENT (AEROSOL BRUSH APPLICATOR FOR ISOPROPYL ALCOHOL)

The General Services Administration has authorized the use of this Commercial Item Description

1.0 Scope. This description covers an assembly that dispenses a pressurized solvent (isopropyl alcohol) for used in cleaning electrical components on aircraft.

2.0 Classification. The assembly shall be a hand-held assembly with an activating trigger, a nozzle embedded in a bristle brush and a 3 foot long feed tube that connects to a 16-ounce, self pressurized can of isopropyl alcohol.

3.0 Salient characteristics.

3.1 Hand held assembly.

3.1.1 Spray head. The assembly shall be an ESD safe polypropylene/aluminum nozzle spray head mounted on an unpainted aluminum cylinder with a 1.25 inch diameter connected to a 3 foot long feed tube. The assembly length shall be 6 inches and have an easily operated finger trigger which releases solvent flow from the pressurized can through the feed tube.

3.1.2 Feed tube. The feed tube shall be a nylon tube encased in braided insulation covered with an ESD safe stainless steel wire overjacket. The end of the feed tube shall have a clip which locks the tube onto the self-pressurized can nozzle. The length of the feed tube shall be 3 feet.

3.1.3 Steel ferrule. The brush tips shall be held tightly in place using a plated steel ferrule with a length of 1.25 inch and a diameter of 0.45 inch.

3.1.4 Attachment instructions. The unpainted cylinder portion of the assembly shall be printed with pictorial and written instructions for correct attachment of the assembly to the self-pressurized can of solvent.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Systems Standardization, Code 45.1.11B120-3, Naval Air Warfare Center Aircraft Division, Highway 547, Lakehurst, NJ 08733-5100, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6850

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:42Z
Check the source to verify that this is the current version before use.

3.2 Brush tips. The assembly shall be furnished with 3 natural bristle tips as follows:

a. Brush tip No. 1. Regular texture bristles that when fitted in the steel ferrule shall extend 1.0 inch from the end of the ferrule. This brush tip is safe for use on ESD sensitive parts.

b. Brush tip No. 2. Regular texture bristles that when fitted in the steel ferrule shall extend 0.375 inch from the end of the ferrule.

c. Brush tip No. 3. Soft texture bristles that when fitted in the steel ferrule shall extend 0.375 inch from the end of the ferrule. The soft texture bristle provides only slow solvent flow.

3.3 Solvent. The solvent shall be furnished in a self-pressurized metal container with 90% by weight reagent grade, anhydrous isopropyl alcohol and 10% by weight HFC-134a propellant. The net weight of each container shall be not less than 10 ounces.

3.3.1 Container labels. Each container shall be labeled in accordance with CFR Title 49 and other applicable regulations and shall include the following directions for use and precautions:

CAUTION: FLAMMABLE LIQUID. Contents under pressure. Keep away from heat or flame. Turn power off prior to use.

DIRECTIONS FOR USE: After the power is turned off, the applicator with Brush Tip No. 1 may be used to clean electrical connector plugs: Place brush on male or female plug, activate solvent flow while agitating the brush. Repeat to rinse. The same procedure may be used to clean solder flux from spot repairs. IMPORTANT: Allow solvent to evaporate prior to assembling plugs or applying power to equipment.

4.0 Regulatory requirements.

4.1 Metric products. Assemblies manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest version of Federal Standard No. 376, and all other requirements of this Commercial Item Description are met. When an assembly is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the preparing activity to determine if the assembly is acceptable. The preparing activity has the option of accepting or rejecting the assembly.

5.0 Quality assurance provisions.

5.1 Contractor certification. The contractor shall certify and maintain substantiating evidence that the assembly offered meets the salient

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:42Z
Check the source to verify that this is the current version before use.

characteristics of the Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Market acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this Commercial Item Description:

a. The company furnishing the assembly item must have been producing a product meeting the requirements of this Commercial Item Description for at least 2 years.

b. The company must have offered the assembly to a government laboratory for inspection.

6.0 Packaging. Preservation, packing and marking shall be as specified in the contract or order.

7.0 Notes.

7.1 Source of documents.

7.1.1 The code of Federal Regulations (CFR) may be obtained from the Superintendent of Documents, US Government Printing Office, Washington DC 20402.

7.1.2 Federal Government activities may obtain copies of Federal Standard No. 376 from established distribution points within their agencies. Other activities may obtain the standard for bidding purposes from the General Services Administration, Federal Supply Service Bureau, Specification section, Suite 8100, 479 L'Enfant Plaza, SW, Washington, DC 20407.

7.2 Government laboratory. Manufacturers wanting to have their assembly inspected may do so by contacting the Naval Air Warfare Center Aircraft Division, Code 6.3.4.2, Box 5152, Warminster, PA 18974-5091.

MILITARY INTERESTS:

Custodians
Army - EA
Navy -AS
Air Force - 68

Preparing Activity:
NAVY - AS
DoD Project 6850-1152

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:42Z
Check the source to verify that this is the current version before use.