
FED. SUP. CLASS
6240

This standard establishes the overall dimensions and detail engineering requirements for incandescent lamps, types T8-98 and T8-114. The item covered hereon is standard for use in the design of new equipment procured by the Bureau of Ships.



MS part number	Type	FIIN
(A) MS15557-1	T8-98	143-0w8w
MS15557-3	T8-114	155-8854

Characteristic	Type T8-98	Type T8-114
~~Amperes~~	8.5	4
Volts	6	8.6
Bulb	T-8	T-8
Finish	Clear	---
Base	Candelabra, prefocusing single contact	Candelabra, prefocusing single contact
Filaments	C-8	C-8
Light center length (inches)✓	1-5/8	1-5/8
Hours life (approximate)	50	100
Lumen output (approximate)	(A) 365	---
Use	Type "H" - Victor Animatograph model 40B and 40C.	Holmes, type "12" - 16 mm. sound motion picture equipment, type "H" (exciter lamp)

✓ Distance from center of light source to plane of locating bosses of prefocusing collar.

(A) Deleted overall length data in characteristics.

(A) Deleted Type T8-10b.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

APPROVED 13 MAY 1954 REVISED (A) 10 DEC 1958

CUSTODIANS	OTHER INT.
Ships	A - N - AF -

MILITARY STANDARD

LAMP, INCANDESCENT, T-8 CANDELABRA, PREFOCUSING, SINGLE CONTACT

MS15557 (SHIPS)

PROCUREMENT SPECIFICATION	SUPERSEDES:	SHEET 1 OF 1
NONE		

DD FORM 672-1
1 OCT 52

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:48Z
Check the source to verify that this is the current version before use.