DOD-STD-35-112(MI)
5 May 1978

MILITARY STANDARD

LUBRICANTS, OIL AND GREASE

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

FSC EDS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY
U.S. ARMY MATERIEL
DEVELOPMENT AND READINESS COMMAND
ALEXANDRIA, VA 22333

Lubricants, Oil and Grease
Automated Engineering
Document Preparation System

DOD-STD-35-112(MI)

1. This Military Standard is approved for use by DARCOM, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S. Army Missile Research and Development Command, ATTN: DRDMI-ESD, Redstone Arsenal, Alabama 35809, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

FOREWORD

1. The purpose of DOD-STD-35-112(MI) is to provide instructions for the preparation of Specification Requirements Sheets (SRS) in order to produce Military Specification Exceptions for Lubricants, Oil and Grease.

2. In order to properly utilize this document, it is necessary to have a complete and thorough understanding of the DOD-STD-35.

3. It is important that the procedures described in the basic document (DOD-STD-35D and subsequent revisions) be followed explicitly in order to produce a document suitable for procurement. Information which is standard for all dash-numbered parts has been included in the basic document at the issuance of DOD-STD-35D. This information is not repeated in each dash-numbered part.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	REFERENCED DOCUMENTS	11
	2.1	Issues of documents	11
	2.2	Other publications	11
	3.	DEFINITIONS	15
	4.	GENERAL REQUIREMENTS	17
	4.1	Introduction	17
	4.2	Specification Requirement Sheet (SRS)	17
	4.3	Units of measure	17
	5.	DETAILED REQUIREMENTS	19
	5.1	Introduction	19
	5.2	MSE Formats	19
	5.3	Referenced documents	19
	5.4	Test matrix	19
	5.5	Tabulation	20
	5.6	Keyword Code Index (KCI) and Standard Paragraphs	21
	5.6.1	Interrelationship of Codes	21
	5.6.2	Automatic MSE Data	21
	5.6.3	DOD-STD-35 Tables	21

TABLES

Table	I.	Title Index	3
	II.	Test matrix	20
	III.	Tabulation candidates	20

APPENDICES

Appendix	A.	Characteristics Code Index	95
		Index	101

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Lubricants, Oil and Grease.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX.

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
GREASE, AIRCRAFT	610001	VV-G-632	GENERAL PURPOSE
		MIL-G-3545	HIGH TEMP
		MIL-G-4343	PNEUMATIC
		MIL-G-23827	INSTRUMENT
		MIL-G-24139	MULTIPURPOSE
		MIL-G-25013	BALL AND ROLL BEARING
		MIL-G-25537	HELICOPTER OSC BEARING
		MIL-G-38277	HIGH SPEED
		MIL-G-81322	GENERAL PURPOSE
		MIL-G-81827	HIGH LOAD CAP
		MIL-G-83261	EXTREME PRESS
		MIL-G-83363	TRANSMISSION
		MIL-G-83414	GUNMOUNT
GREASE, AIRCRAFT AND INSTRUMENT	610002	MIL-G-3545	HIGH TEMP
		MIL-G-23827	GEAR AND ACT SCREW
		MIL-G-24139	QUIET SERV
		MIL-G-27617	FUEL AND OIL RESISTANT
		MIL-G-81937	ULTRA CLEAN
GREASE, AIRCRAFT ORDNANCE	610003	VV-G-632	INDUST GENERAL PURPOSE
		MIL-G-3545	HIGH TEMP
		MIL-G-10924	AUTO AND ARTIL
		MIL-G-23827	GEAR AND ACT SCREW
		MIL-G-25013	BALL AND ROLL BEARING

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
GREASE, AIRCRAFT ORDNANCE	610003 (CONT)	MIL-G-25537	HELICOPTER OSC BEARING
		MIL-G-47219	LUBRICATING
		MIL-G-83414	GUNMOUNT
GREASE, AUTOMOTIVE	610004	MIL-G-10924	MULTIPURPOSE
		MIL-G-21164	MOLYBDENUM LOW AND HIGH TEMP
		MIL-G-23549	GENERAL PURPOSE
		MIL-G-46003	RIFLE
		MIL-G-46886	SILICONE
GREASE, AUTOMOTIVE AND ARTILLERY	610005	MIL-G-10924	MULTIPURPOSE
		MIL-G-21164	MOLYBDENUM HI. LOW TEMP
		MIL-G-23549	GENERAL PURPOSE
		MIL-G-46003	RIFLE
		MIL-G-46886	SILICONE
		MIL-G-83414	GUNMOUNT
GREASE, BALL AND ROLLER BEARING	610006	MIL-G-24508	HIGH PERFORM
		MIL-G-25013	LOW TORQUE EQ
		MIL-G-25537	HILICOP OSCIL
		MIL-G-38220	HIGH SPEED
		MIL-G-38277	HIGH SPEED 600°F
		MIL-G-83261	EXTREME PRESS, ANTI-WEAR
GREASE, GENERAL PURPOSE	610007	VV-G-632	INDUSTRIAL
		MIL-G-4343	PNEUM SYSTEM

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
GREASE, GENERAL PURPOSE	610007 (CONT)	MIL-G-23549	MOLYBDENUM DISULFIDE
		MIL-G-23827	INSTRUMENT AND ACTUATOR SCREW
		MIL-G-46886	LUBRICATING SILICONE
		MIL-G-47219	LUBRICATING
		MIL-G-81322	AIRCRAFT, WIDE TEMP RANGE
GREASE, INSTRUMENT	610010	MIL-G-23827	GEAR AND ACTU SCREW
		MIL-G-46886	SILICONE
		MIL-G-81937	ULTRA CLEAN
GREASE, LAB. APPARATUS STOPCOCK	610011	MIL-G-6032	PLUG VALVE GAS AND OIL RESISTANT
GREASE, MOLYBDENUM DISULFIDE	610012	MIL-G-21164	LOW AND HIGH TEMP
		MIL-G-23549	GENERAL PURPOSE
		MIL-G-81827	HIGH LOAD CAP WIDE TEMP RANGE
GREASE, ORDNANCE BEARING AND AMMUNITION	610013	MIL-G-24139	MILTIPURPOSE
		MIL-G-24508	HIGH PERFORM
		MIL-G-25013	AIRCRAFT
		MIL-G-25537	AIRCRAFT, HEL
		MIL-G-38220	HI. SPEED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
GREASE, ORDNANCE BEARING AND AMMUNITION	610013 (CONT)	MIL-G-38277	HI. SPEED 600°F
		MIL-G-81322	WIDE TEMP RAN
GREASE, ORDNANCE, EXTREME PRESSURE	610014	MIL-G-83261	TEMP -100°F TO 450°F
GREASE, OUTBOARD MOTOR	610015	MIL-G-23549	GENERAL PURPOSE
		MIL-G-24139	MULTIPURPOSE
		MIL-G-46886	SILICONE
GREASE, PLUG VALVE	610016	MIL-G-6032	GASOLINE AND OIL RESISTANT
GREASE, RAILWAY	610017	VV-G-679	FRICTION TYPE, DRIVING JOURNAL, CRANKPINS
		MIL-G-18458	EXPOSED GEAR
		MIL-G-38220	ANTIFRICTION -40° TO +400°F
GREASE, RIFLE	610018	MIL-G-46003	SUSTAINED RAIN
GREASE, SILICONE INSULATED ELECTRIC MOTOR	610019	MIL-G-24139	MULTIPURPOSE
		MIL-G-46886	LIGHT AND MED CONSISTENCE
		MIL-G-81937	ULTRA CLEAN
GREASE, TORPEDO TAIL	610020	MIL-G-23549	GENERAL PURPOSE
GREASE, WIRE ROPE EXPOSED GEAR	610021	MIL-G-18458	EXTERNALLY APPL
		MIL-G-81827	HIGH LOAD CAP., WIDE TEMP RANGE
		MIL-G-83414	GUNMOUNT, AIRC

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
LUBRICATING OIL, AIR COMPRESSOR	610022	VV-L-820	GENERAL PURPOSE (LIGHT)
		MIL-L-24435	TWO STROKE CYCLE
		MIL-L-24484	SHIPBOARD RECI
		MIL-L-46152	SPARK-IGNITION AND COMPRESS. IGN TYPE
		MIL-K-46167	INTERNAL COMB. ENGINE
		MIL-L-83767	PUMP, VAC MEC EJECTOR AND DIFFUS-EJECTOR
LUBRICATING OIL, AIRCRAFT PISTON ENGINE	610023	MIL-L-22851	ASHLESS DISPER
		MIL-K-24435	TWO STROKE CYC
LUBRICATING OIL, AIRCRAFT TURBINE ENGINE, SYNTHETIC	610025	MIL-L-7808	TEMP 24°C TO 93°C
		MIL-L-23699	TEMP -40°C TO 200°C
		MIL-L-27502	TEMP -40°C TO 220°C
LUBRICATING OIL, AIRCRAFT TURBOSHAFT ENGINE, SYNTHETIC	610026	MIL-L-7808	TEMP 24°C TO 93°C
		MIL-L-23699	TEMP -40°C TO 200°C
		MIL-L-27502	TEMP -40°C TO 220°C

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
LUBRICATING OIL, COLLOIDAL	610027	MIL-L-24131	METAL PARTS, LIMITED CLEARANCES
		MIL-L-25681	SILICONE
		MIL-L-46014	SPINDLE
LUBRICATING OIL, COMPOUNDED	610028	VV-L-751	ENVIRONMENTAL CONDITIONS
		VV-L-795	STEAM-CYLINDER
		VV-L-800	GENERAL PURPOSE
		MIL-L-3150	PRESERVATIVE, MEDIUM
LUBRICATING OIL, ENGINE	610029	MIL-L-2104	SPARK-IGN AND COMPRESSION ENGINES
		MIL-L-9000	HIGH OUTPUT DIESEL
		MIL-L-21260	BREAK-IN
		MIL-L-24435	TWO STROKE GAS
		MIL-L-46152	COMMERCIAL-TYPE VEHICLE
LUBRICATING OIL, EXPOSED GEAR	610030	VV-L-751	EXPOSED UNDER MOST ENVIRON CONDITIONS
		MIL-L-13914	LOCOMOTIVE TRACTION
LUBRICATING OIL, GEAR	610031	MIL-L-10324	SUB-ZERO
		MIL-L-18486	WORM, SPUR OR MOTION TRAN
		MIL-L-2105	MULTIPURPOSE

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
LUBRICATING OIL, GENERAL PURPOSE	610032	VV-L-800	WATER-DISPLAC, LOW TEMP
		VV-L-820	LIGHT
LUBRICATING OIL, HYDRAULIC	610033	MIL-L-17672	LIGHT TURBINE, NONCORROSIVE
LUBRICATING OIL, INSTRUMENT	610034	MIL-L-3918	LOW TEMP NON-SPREADING
		MIL-L-27694	-65° TO +400°F
		MIL-L-81846	HIGH FLASH POINT
LUBRICATING OIL, MINERAL, STEAM CYLINDER	610035	VV-L-1071	SATURATED AND SUPERHEATED
		MIL-L-17331	NONCORROSIVE
		MIL-L-19224	-20°F TO +165°F
LUBRICATING OIL, MOLYBDENUM	610036	MIL-L-25681	AIRCRAFT, HIGH TEMP
LUBRICATING OIL, PRESERVATIVE, CORROSION INHIBITED	610037	VV-L-800	WATER-DISPLAC, LOW TEMP
		MIL-L-3150	MEDIUM
		MIL-L-21260	BREAK-IN
LUBRICATING OIL, RAILWAY CAR AND LOCOMOTIVE	610038	VV-L-822	JOURNAL BEAR.
		MIL-L-13914	TRACTION MT GEARS
LUBRICATING OIL, REFRIGERANT	610039	VV-L-825	COMPRESSION UNIT

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
LUBRICATING OIL, SEMIFLUID	610040	MIL-L-19701	-54°C TO 71°C
		MIL-L-2105	AUTOMOTIVE, HEAVY DUTY IND TYPE, AND STEER
		MIL-L-46000	-54°C TO +127°C
LUBRICATING OIL, STEAM TURBINE	610041	MIL-L-17331	NONCORROSIVE
		MIL-L-17672	ANTICORROSION AND ANTIOXID
		MIL-L-24467	MAIN PROP. AND AUXILIARY MACH
LUBRICATING OIL, VACUUM PUMP	610042	MIL-L-83767	VISCOSITY; LIGHT MEDIUM, HEAVY, AND EXTRA HEAVY
LUBRICATING OIL, WATCH	610043	MIL-L-3918	JEWEL BEARING
LUBRICATING OIL, WEAPONS	610044	MIL-L-14107	LOW TEMP
		MIL-L-46000	-54°C TO +127°C

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-L-1107	Lubricating Oil, Weapons, Low Temperature
MIL-G-18458	Grease, Wire Rope-exposed Gear

STANDARDS

FEDERAL

FED-STD-141	Paint, Varnish, Lacquer and Related Materials, Methods of Inspection, Sampling and Testing
FED-STD-791	Lubricant, Liquid Fuel and Related Products, Methods of Testing

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this standard to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASTMD88	Saybolt Viscosity
ASTMD92	Flash and Fire Points by Cleveland Open Cup
ASTMD95	Water in Petroleum Products and Bituminous Materials by Distillation
ASTMD97	Pour Point of Petroleum Oils

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

ASTMD129	Sulfur in Petroleum Products by the Bomb Method
ASTMD217	Cone Penetration of Lubricating Grease
ASTMD287	API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)
ASTMD445	Kinematic Viscosity of Transparent and Opaque Liquids (And The Calculation of Dynamic Viscosity)
ASTMD524	Ramsbottom Carbon Residue of Petroleum Products
ASTMD566	Dropping Point of Lubricating Grease
ASTMD664	Neutralization Number by Potentiometric Titration
ASTMD808	Chlorine in New and Used Petroleum Products (Bomb Method)
ASTMD877	Dielectric Breakdown Voltage of Insulating Liquids Using Disk Electrodes
ASTMD892	Foaming Characteristics of Lubricating Oils
ASTMD941	Density and Specific Gravity of Liquids by Lipkin Bicapillary Pycnometer
ASTMD942	Oxidation Stability of Lubricating Greases by the Oxygen Bomb Method
ASTMD974	Neutralization Number by Color Indicator Titration
ASTMD1092	Apparent Viscosity of Lubricating Greases
ASTMD1264	Water Washout Characteristics of Lubricating Greases

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

ASTMD1478	Low-Temperature Torque of Ball Bearing Greases
ASTMD1500	ASTM Color of Petroleum Products (ASTM Color Scale)
ASTMD2270	Calculating Viscosity Index From Kinematic Viscosity
ASTMD2595	Evaporation Loss of Lubricating Greases Over Wide-Temperature Range
ASTMD2983	Apparent Viscosity of Gear Oils at Low Temperature Using the Brookfield Viscometer
ASTME380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

3. DEFINITIONS

Definitions contained in DOD-STD-35 are applicable to Lubricants, Oil and Grease.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

4. GENERAL REQUIREMENTS

4.1 Introduction. In order to properly prepare an SRS for Lubricants, Oil and Grease, it is necessary to use DOD-STD-35 in conjunction with this dash-numbered part. In the event the instructions or the writing methodology are not followed, an AEDPS edit routine will print error messages rather than the desired MSE document.

4.2 Specification Requirement Sheet (SRS). SRS requirements described in DOD-STD-35 are applicable to Lubricants, Oil and Grease.

4.3 Units of measure. The International System of Units (SI) or inch-pound units (U.S.), may be used to specify characteristics (e.g. weight, dimensions). Refer to ASTME380 for guidance in using SI. However, when different units of measure are available for specifying a characteristic, only one may be used. Both units of measure cannot appear in the same MSE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Test matrix. A test matrix is supplied as a guide for selecting documents to specify tests (see table II). The test matrix presents documents most applicable for use to satisfy the statement "TEST PER (DOC DES)". Any document listed in the Title Index may be used to satisfy the statement. However, the selected document from the Title Index must contain the desired test. Government test method documents and approved industry standards such as ASTM test methods may also be used to satisfy the statement "TEST PER (DOC DES)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

Table II. Test matrix.

DOCUMENT	TEST CODE	Immersion 1965	Rubber Swell 2120	Temperature, High 2232
MIL-G-23549		X		
MIL-G-81827			X	
MIL-G-81322				X

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for Lubricants, Oil and Grease characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

TABLE III. TABULATION CANDIDATES.

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1564	TYPE (DES)	1566	CLASS (DES)	1568	GRADE (DES)

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

5.6 Keyword Code Index (KCI) and Standard Paragraphs. The KCI provides codes, to be entered on an SRS, that are unique for the type part covered by this dash-numbered part of DOD-STD-35. The left-hand page presents the information in outline form using keywords and codes. The right-hand page presents the words that will appear in the MSE. To find the code to be entered on the SRS, find the subject in the index at the back of this dash-numbered part. Find the keyword on the KCI and its associated code. Enter, on the SRS, the code and the characteristic value required. After the part unique characteristics have been specified, refer to DOD-STD-35 when exceptions are required to Quality Assurance, Packaging, Notes, etc. Instructions are in DOD-STD-35 on how to enter any type characteristic value. Appendix A, Characteristic Code Index, provides a numerical list of codes used in this dash-numbered part. This index identifies the location of codes by page number.

5.6.1 Interrelationship of codes. The interrelationship of the codes is shown by the indentation level of characteristic names on the KCI. The kind of characteristic value is shown by a colon, parentheses, period or underline. The paragraph, of which the code is a part, is shown by the standard paragraph adjacent to the code on a right-hand page. When a characteristic value entered with a code becomes part of the paragraph, the code is shown in the paragraph where the characteristic value will print. The MSE will contain the exact entry as supplied with the code, except for "X" entries.

5.6.2 Automatic MSE data. Some statements, such as Altitude and Temperature, will appear in the printed MSE without having to make additional entries. These statements are linked by data base logic to characteristic codes listed under them and will print when one of the codes listed is used. Other statements may print automatically depending on the type MSE selected. Explanations are noted on the KCI as required.

5.6.3 DOD-STD-35 Tables. The KCI of this document contains references to tables in Appendix A of DOD-STD-35. Most of the tables are in preprinted form and should be reproduced, applicable data entered, and attached to the SRS for submittal. Refer to DOD-STD-35 for a general explanation in the generation of tables.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
*Requester's Name	0101
*Company Name/Command	0102
*Street/Building	0103
*City, State, Zip	0104
*Phone Number, Include Area Code, Autovon If Applicable	0105
*Date	1003
*Requester FSCM	1004
*Contract Number/Office Symbol	1005
*Base Document	1006
*System Application	1008
*Government Design Activity FSCM	6369
*Format (Select One)	
Six section document.	0700
One section document.	0800
*Control (Select One)	
Source.	6873

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
0101	0101.
0102	0102.
0103	0103.
0104	0104.
0105	0105.
1003	1003.
1004	USER(S) FSCM(S) 1004.
1005	CONTRACT NUMBER OR OFFICE SYMBOL 1005.
1006	THE COMPLETE REQUIREMENTS FOR PROCURING THE ITEM(S) DESCRIBED HEREIN SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT(S), 1006, EXCEPT AS SPECIFIED IN THIS DOCUMENT. IN THE EVENT OF CONFLICT, THIS DOCUMENT SHALL GOVERN.
1008	SYSTEM APPLICATION 1008.
6369	GOVERNMENT DESIGN ACTIVITY FSCM 6369.
0700	
0800	
	SOURCE(S).
6873	THE FOLLOWING SOURCE(S) SHOWN WITH THE PART NUMBER(S) IS/ARE THE ONLY APPROVED SOURCE(S) FOR THE ITEM(S) DESCRIBED BY THIS DOCUMENT. IDENTIFICATION OF THE APPROVED SOURCE(S) HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM DESCRIBED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Control (Cont)	
Specification.	6874
*Source Table	
Note: Refer to Table V of DOD-STD-35.	
Aperture Cards Required.	0107
Revision of AEDPS Document Number	0108
Scope	
Note: This entry is automatic and determined by the title code used.	
Part Number	
Note: Automatic with a single item MSE.	
Note: Automatic with a multi-item MSE.	
Units of Measure (Select One)	
U.S.	6941
SI.	6942

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6874	THE FOLLOWING SUGGESTED SOURCE(S) SHOWN WITH THEIR PART NUMBER(S) HAVE BEEN KNOWN TO MEET THE REQUIREMENT(S) OF THIS DOCUMENT. IDENTIFICATION OF THE 'SUGGESTED SOURCE(S) OF SUPPLY' HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM(S).
0107	
0108	0108.
	SCOPE.
	SCOPE. THIS DOCUMENT COVERS THE DETAILED REQUIREMENTS FOR TITLE CODE.
	PART NUMBER. THE PART NUMBER FOR THE ITEM IS SUPPLIED BY COMPUTER.
	PART NUMBER. THE PART NUMBER FOR THE ITEMS IS THE SAME AS THE NUMBER OF THIS DOCUMENT PLUS THE SUFFIX NUMBER FROM THE TABULATED CHARACTERISTIC TABLE. REVISION AND ACTIVITY SYMBOLS ARE NOT INCLUDED IN THE PART NUMBER.
6941	UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INCH-POUND UNITS (U.S.) OR DEGREES.
6942	UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INTERNATIONAL SYSTEM OF UNITS (SI) OR DEGREES.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Classification	
Type	
Base document type (designation)	1564
Class	
Base document class (designation)	1566
Grade	
Base document grade (designation)	1568
Temperature Rating	
Maximum operating (degrees Celsius)	5069
Maximum storage (degrees Celsius)	7302
Maximum service (degrees Celsius)	4905
Minimum operating (degrees Celsius)	5068
Minimum storage (degrees Celsius)	7301
Minimum service (degrees Celsius)	4904
Nominal operating (degrees Celsius)	5046
Nominal storage (degrees Celsius)	5048

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	CLASSIFICATION.
1564	TYPE DESIGNATION SHALL BE 1564 IN ACCORDANCE WITH THE BASE DOCUMENT.
1566	CLASS DESIGNATION SHALL BE 1566 IN ACCORDANCE WITH THE BASE DOCUMENT.
1568	GRADE DESIGNATION SHALL BE 1568 IN ACCORDANCE WITH THE BASE DOCUMENT.
	TEMPERATURE RATING.
5069	THE MAXIMUM OPERATING TEMPERATURE RATING SHALL BE 5069 DEGREES CELSIUS.
7302	THE MAXIMUM STORAGE TEMPERATURE RATING SHALL BE 7302 DEGREES CELSIUS.
4905	THE MAXIMUM SERVICE TEMPERATURE RATING SHALL BE 4905 DEGREES CELSIUS.
5068	THE MINIMUM OPERATING TEMPERATURE RATING SHALL BE 5068 DEGREES CELSIUS.
7301	THE MINIMUM STORAGE TEMPERATURE RATING SHALL BE 7301 DEGREES CELSIUS.
4904	THE MINIMUM SERVICE TEMPERATURE RATING SHALL BE 4904 DEGREES CELSIUS.
5046	THE NOMINAL OPERATING TEMPERATURE RATING SHALL BE 5046 DEGREES CELSIUS.
5048	THE NOMINAL STORAGE TEMPERATURE RATING SHALL BE 5048 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Tabulated Characteristics (See Table IV, DOD-STD-35)	
Materials (See Tables VI and VII, DOD-STD-35)	
Note: Automatic when Table VII is used.	
Composition	
Composition, formulation or mixture.	6375
*Ingredient Table, (See Table XI, DOD-STD-35)	
Design and Construction	
Appearance	
Completely homogeneous and free from lumps or granulation.	1570
Toxicity	
No adverse effects on human health.	1572
Accelerated Weathering	
Requirements (select one)	
Per base document except ____	1576

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH

MATERIAL(S). MATERIAL(S) SHALL BE AS SPECIFIED IN THE MATERIAL TABLE. (NOTE: THE COMPONENT REFERENCE NUMBER(S) ARE ONLY TO REFERENCE THE SAME COMPONENT WHEN TABLE CONTINUATION IS NECESSARY.)

6375 COMPOSITION. THE COMPOSITION, FORMULATION OR MIXTURE (AS APPLICABLE) SHALL BE AS SPECIFIED HEREIN. THE INGREDIENT QUANTITIES SHALL BE SHOWN IN INTERNATIONAL (SI) SYSTEM OF UNITS SUCH AS GRAMS, LITERS, ETC., OR U.S. STANDARDS SUCH AS PINTS, QUARTS OR GALLONS, AS SPECIFIED IN THE TABLE.

DESIGN AND CONSTRUCTION.

1570 APPEARANCE. THE APPEARANCE SHALL BE COMPLETELY HOMOGENEOUS AND FREE FROM LUMPS OR GRANULATION.

1572 TOXICITY. THERE SHALL BE NO ADVERSE EFFECTS ON HUMAN HEALTH.

1576 ACCELERATED WEATHERING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1576.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Accelerated Weathering (Cont)	
Requirements (Cont)	
As follows:	1577
Maximum number of corrosion spots (quantity)	1578
Maximum diameter (select one)	
(inches)	1580
(millimeters)	1582
Test methods (select one)	
Per base document except ____	1586
Per FED-STD-141, Method 6151.	1588
Exposure duration (select one)	
(hours)	1590
(days)	1591
Number of test specimens (quantity)	1592
Specimen preparation per MIL-G-18458.	1594

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1577	ACCELERATED WEATHERING. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1578	THE NUMBER OF CORROSION SPOTS SHALL BE NOT GREATER THAN 1578.
1580	CORROSION SPOT DIAMETER SHALL BE NOT GREATER THAN 1580 INCH(S).
1582	CORROSION SPOT DIAMETER SHALL BE NOT GREATER THAN 1582 MILLIMETER(S).
1586	ACCELERATED WEATHERING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1586.
1588	ACCELERATED WEATHERING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 6151 OF FED-STD-141.
1590	THE EXPOSURE DURATION SHALL BE 1590 HOUR(S).
1591	THE EXPOSURE DURATION SHALL BE 1591 DAY(S).
1592	THE NUMBER OF TEST SPECIMENS SHALL BE 1592.
1594	THE SPECIMEN SHALL BE PREPARED IN ACCORDANCE WITH MIL-G-18458.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Carbon Residue	
Requirements (select one)	
Per base document except ____	1602
Maximum carbon residue (percent)	1604
Test methods (select one)	
Per base document except ____	1608
Per ASTMD524.	1610
Chlorine	
Requirements (select one)	
Per base document except ____	1614
Maximum chlorine content (percent)	1616
Test methods (select one)	
Per base document except ____	1620
Per ASTMD808.	1622

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1602	CARBON RESIDUE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1602.
1604	CARBON RESIDUE. THE CARBON RESIDUE SHALL BE NOT GREATER THAN 1604 PERCENT.
1608	CARBON RESIDUE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1608.
1610	CARBON RESIDUE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD524.
1614	CHLORINE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1614.
1616	CHLORINE. THE CHLORINE CONTENT SHALL BE NOT GREATER THAN 1616 PERCENT.
1620	CHLORINE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1620.
1622	CHLORINE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD808.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Color	
Requirements (select one)	
Per base document except ____	1626
Maximum (no.)	1628
Test methods (select one)	
Per base document except ____	1632
Per ASTMD1500.	1634
Contaminant	
Requirements (select one)	
Per base document except ____	1638
Maximum solid material (milligrams per liter of oil)	1640
Test methods (select one)	
Per base document except ____	1644

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1626	COLOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1626.
1628	COLOR. THE COLOR NUMBER SHALL BE NOT GREATER THAN 1628.
1632	COLOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1632.
1634	COLOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1500.
1638	CONTAMINANT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1638.
1640	CONTAMINANT. THE SOLID MATERIAL SHALL BE NOT GREATER THAN 1640 MILLIGRAM(S) PER LITER OF OIL.
1644	CONTAMINANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1644.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Contaminant (Cont)	
Test methods (Cont)	
Per FED-STD-791, Method 3006.	1646
Sieve mesh size (no.)	1648
Drying temperature (degrees Celsius)	1650
Mix media (name)	1652
Sample (quantity)	1654
Drying temperature after rinsing (degrees Celsius)	1656
Cooling temperature (degrees Celsius)	1658
Corrosiveness/Oxidation	
Requirements (select one)	
Per base document except ____	1662
As follows:	1664
Maximum change in weight of specimen (milligrams per square centimeter of surface)	1666
Maximum change from original viscosity (percent)	1668

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1646	CONTAMINANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3006 OF FED-STD-791.
1648	THE SIEVE MESH SIZE NUMBER SHALL BE 1648.
1650	THE DRYING TEMPERATURE SHALL BE 1650 DEGREES CELSIUS.
1652	THE MIX MEDIA SHALL BE 1652.
1654	THE NUMBER OF SAMPLES SHALL BE 1654.
1656	THE DRYING TEMPERATURE AFTER RINSING SHALL BE 1656 DEGREES CELSIUS.
1658	THE COOLING TEMPERATURE SHALL BE 1658 DEGREES CELSIUS.
1662	CORROSIVENESS/OXIDATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1662.
1664	CORROSIVENESS/OXIDATION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1666	THE CHANGE IN WEIGHT OF SPECIMEN SHALL BE NOT GREATER THAN 1666 MILLIGRAM(S) PER SQUARE CENTIMETER OF SURFACE.
1668	THE CHANGE FROM ORIGINAL VISCOSITY SHALL BE NOT GREATER THAN 1668 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Corrosiveness/Oxidation (Cont)	
As Follows: (Cont)	
Maximum acid number increase (quantity)	1670
Maximum pressure drop (select one)	
(psi)	1672
(kilopascals)	1674
Test methods (select one)	
Per base document except ____	1678
Per ASTMD942.	1680
Per FED-STD-791.	1682
Method (des)	1684
Test temperature (degrees Celsius)	1694
Tolerance plus or minus (degrees Celsius)	1696
Duration of test (hours)	1698
Cycling Performance	
Requirements (select one)	
Per base document except ____	1701

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1670	THE INCREASE IN ACID NUMBER SHALL BE NOT GREATER THAN 1670.
1672	THE PRESSURE DROP SHALL BE NOT GREATER THAN 1672 POUND(S) PER SQUARE INCH.
1674	THE PRESSURE DROP SHALL BE NOT GREATER THAN 1674 KILOPASCAL(S).
1678	CORROSIVENESS/OXIDATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1678.
1680	CORROSIVENESS/OXIDATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD942.
1682	CORROSIVENESS/OXIDATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH FED-STD-791.
1684	THE APPLICABLE TEST METHOD SHALL BE 1684.
1694	THE TEST TEMPERATURE SHALL BE 1694 DEGREES CELSIUS.
1696	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1696 DEGREES CELSIUS.
1698	THE DURATION OF TEST SHALL BE 1698 HOUR(S).
1701	CYCLING PERFORMANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1701.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Cycling Performance (Cont)	
Requirements (Cont)	
Minimum number of cycles (quantity)	1702
Test methods (select one)	
Per base document except ____	1706
Per FED-STD-791, Method 5413.	1708
Cycle Stroke (inches)	1710
Rate (cycles per minute)	1712
Velocity (inches per second)	1714
Test duation (hours)	1716
Density	
Requirements (select one)	
Per base document except ____	1720
As follows:	1721
Minimum density (grams per cubic centimeter)	1722
Maximum density (grams per cubic centimeter)	1724
Test methods (select one)	
Per base document except ____	1728

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1702	CYCLING PERFORMANCE. THERE SHALL BE NOT LESS THAN 1702 CYCLE(S).
1706	CYCLING PERFORMANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1706.
1708	CYCLING PERFORMANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 5413 OF FED-STD-791.
1710	THE CYCLE STROKE SHALL BE 1710 INCH(S).
1712	THE CYCLE RATE SHALL BE 1712 CYCLE(S) PER MINUTE.
1714	THE VELOCITY SHALL BE 1714 INCH(S) PER SECOND.
1716	THE TEST DURATION SHALL BE 1716 HOUR(S).
1720	DENSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1720.
1721	DENSITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1722	THE DENSITY SHALL BE NOT LESS THAN 1722 GRAM(S) PER CUBIC CENTIMETER.
1724	THE DENSITY SHALL BE NOT GREATER THAN 1724 GRAM(S) PER CUBIC CENTIMETER.
1728	DENSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1728.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currenversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Density (Cont)	
Test methods (Cont)	
Per ASTMD941.	1730
Dielectric Strength	
Requirements (select one)	
Per base document except ____	1734
Minimum strength (kilovolts)	1736
Test methods (select one)	
Per base document except ____	1740
Per ASTMD877.	1742
Dirt Content	
Requirements (select one)	
Per base document except ____	1746
As follows:	1747
Maximum number of particles per milliliter (quantity)	1748

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1730	DENSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD941.
1734	DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1734.
1736	DIELECTRIC STRENGTH. THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 1736 KILOVOLT(S).
1740	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1740.
1742	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD877.
1746	DIRT CONTENT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1746.
1747	DIRT CONTENT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1748	THE NUMBER OF PARTICLES SHALL BE NOT GREATER THAN 1748 PARTICLES PER MILLILITER.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Dirt Content (Cont)	
Maximum number of particles per milliliter (Cont)	
*Particle diameter (micrometers)	1750
None larger than (micrometers)	1752
Test methods (select one)	
Per base document except ____	1756
Per FED-STD-791, Method 3005.	1758
Dropping Point	
Requirements (select one)	
Per base document except ____	1762
Minimum temperature (degrees Celsius)	1764
Test methods (select one)	
Per base document except ____	1768
Per ASTMD566.	1770

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1750	THE PARTICLE DIAMETER SHALL BE 1750 MICROMETER(S).
1752	THE LARGEST PARTICLE SHALL BE NOT GREATER THAN 1752 MICROMETER(S).
1756	DIRT CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1756.
1758	DIRT CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3005 OF FED-STD-791.
1762	DROPPING POINT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1762.
1764	DROPPING POINT. THE DROPPING POINT TEMPERATURE SHALL BE NOT LESS THAN 1764 DEGREES CELSIUS.
1768	DROPPING POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1768.
1770	DROPPING POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD566.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Evaporation Loss	
Requirements (select one)	
Per base document except ____	1774
Maximum weight loss (percent)	1776
Test methods (select one)	
Per base document except ____	1780
Per ASTMD2595.	1782
Test temperature (degrees Celsius)	1784
Tolerance plus or minus (degrees Celsius)	1786
Duration (hours)	1788
Flash Point	
Requirements (select one)	
Per base document except ____	1802
Minimum temperature (degrees Celsius)	1804

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1774	EVAPORATION LOSS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1774.
1776	EVAPORATION LOSS. THE WEIGHT LOSS SHALL BE NOT GREATER THAN 1776 PERCENT.
1780	EVAPORATION LOSS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1780.
1782	EVAPORATION LOSS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD2595.
1784	THE TEST TEMPERATURE SHALL BE 1784 DEGREES CELSIUS.
1786	THE TOLERANCE SHALL BE PLUS OR MINUS 1786 DEGREES CELSIUS.
1788	THE TEST DURATION SHALL BE 1788 HOUR(S).
1802	FLASH POINT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1802.
1804	FLASH POINT. THE FLASH POINT TEMPERATURE SHALL BE NOT LESS THAN 1804 DEGREES CELSIUS.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Flash Point (Cont)	
Test methods (select one)	
Per base document except ____	1808
Per ASTMD92.	1810
Foaming	
Requirements (select one)	
Per base document except ____	1822
As follows:	1824
Maximum foam volume at end of blow period.	
Sequence one (milliliters)	1826
Sequence two (milliliters)	1828
Sequence three (milliliters)	1830
Maximum foam volume at end of settling period.	
Sequence one (milliliters)	1832
Sequence two (milliliters)	1834
Sequence three (milliliters)	1836

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1808	FLASH POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1808.
1810	FLASH POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD92.
1822	FOAMING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1822.
1824	FOAMING. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1826	THE FOAM VOLUME AT END OF BLOW PERIOD FOR SEQUENCE ONE SHALL BE NOT GREATER THAN 1826 MILLILETER(S).
1828	THE FOAM VOLUME AT END OF BLOW PERIOD FOR SEQUENCE TWO SHALL BE NOT GREATER THAN 1828 MILLILITER(S).
1830	THE FOAM VOLUME AT END OF BLOW PERIOD FOR SEQUENCE THREE SHALL BE NOT GREATER THAN 1830 MILLILITER(S).
1832	THE FOAM VOLUME AT END OF SETTLING PERIOD FOR SEQUENCE ONE SHALL BE NOT GREATER THAN 1832 MILLILITER(S).
1834	THE FOAM VOLUME AT END OF SETTLING PERIOD FOR SEQUENCE TWO SHALL BE NOT GREATER THAN 1834 MILLILITER(S).
1836	THE FOAM VOLUME AT END OF SETTLING PERIOD FOR SEQUENCE THREE SHALL BE NOT GREATER THAN 1836 MILLILITER(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Foaming (Cont)	
Test methods (select one)	
Per base document except ____	1814
Per ASTMD892.	1816
Option A permitted.	1818
Gear Wear	
Requirements (select one)	
Per base document except ____	1840
Maximum gear wear (milligrams)	1842
Test methods (select one)	
Per base document except ____	1846
Per FED-STD-791, Method 335.	1848
Maximum load (select one)	
(pounds)	1850
(newtons)	1852
Number of cycles (quantity)	1854

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
1814	FOAMING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1814.
1816	FOAMING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD892.
1818	THE TEST USING OPTION A IS PERMITTED.
1840	GEAR WEAR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1840.
1842	GEAR WEAR. THE GEAR WEAR SHALL BE NOT GREATER THAN 1842 MILLIGRAM(S).
1846	GEAR WEAR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1846.
1848	GEAR WEAR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 335 OF FED-STD-791.
1850	THE GEAR WEAR LOAD SHALL BE NOT GREATER THAN 1850 POUND(S).
1852	THE GEAR WEAR LOAD SHALL BE NOT GREATER THAN 1852 NEWTON(S).
1854	THERE SHALL BE 1854 TEST CYCLE(S) APPLIED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Gravity, API	
Requirements (select one)	
Per base document except ____	1858
As follows:	1859
Minimum (degrees API)	1860
Maximum (degrees API)	1862
Test methods (select one)	
Per base document except ____	1866
Per ASTMD287.	1868
Humidity	
Requirements (select one)	
Per base document except ____	1902
Maximum number of corrosion spots (quantity)	1904
Maximum dimension (select one)	
(inches)	1906
(millimeters)	1908

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1858	GRAVITY, API. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1858.
1859	GRAVITY, API. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1860	THE GRAVITY SHALL BE NOT LESS THAN 1860 DEGREE(S) API.
1862	THE GRAVITY SHALL BE NOT GREATER THAN 1862 DEGREE(S) API.
1866	GRAVITY, API. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1866.
1868	GRAVITY, API. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD287.
1902	HUMIDITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1902.
1904	HUMIDITY. THE NUMBER OF CORROSION SPOTS SHALL BE NOT GREATER THAN 1904.
1906	THE CORROSION SPOT DIMENSION SHALL BE NOT GREATER THAN 1906 INCH(S).
1908	THE CORROSION SPOT DIMENSION SHALL BE NOT GREATER THAN 1908 MILLIMETER(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Humidity (Cont)	
Test methods (select one)	
Per base document except ____	1912
Per base FED-STD-791, Method 5329.	1914
Exposure duration (hours)	1916
Hydrolytic Stability	
Requirements (select one)	
Per base document except ____	1920
As follows:	1922
Maximum weight change of the metal strip before brushing (milligrams)	1924
Maximum weight change of the metal strip after brushing (milligrams)	1926
Maximum change in acid number of the sample (no.)	1928
Maximum acid number of the water layer after hydrolysis (no.)	1930
Maximum change in viscosity of the oil (percent)	1932

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1912	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1912.
1914	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 5329 OF FED-STD-791.
1916	THE EXPOSURE DURATION SHALL BE 1916 HOUR(S).
1920	HYDROLYTIC STABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1920.
1922	HYDROLYTIC STABILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1924	THE WEIGHT CHANGE OF THE METAL STRIP BEFORE BRUSHING SHALL BE NOT GREATER THAN 1924 MILLIGRAM(S).
1926	THE WEIGHT CHANGE OF THE METAL STRIP AFTER BRUSHING SHALL BE NOT GREATER THAN 1926 MILLIGRAM(S).
1928	THE CHANGE IN ACID NUMBER OF THE SAMPLE SHALL BE NOT GREATER THAN 1928.
1930	THE ACID NUMBER OF THE WATER LAYER AFTER HYDROLYSIS SHALL BE NOT GREATER THAN 1930.
1932	THE CHANGE IN VISCOSITY OF THE OIL SHALL BE NOT GREATER THAN 1932 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Hydrolytic Stability (cont)	
As follows: (Cont)	
Maximum weight of insolubles formed during hydrolysis (grams)	1934
Maximum color number of the oil after hydrolysis (no.)	1936
Test methods (select one)	
Per base document except ____	1940
Per FED-STD-791, Method 3457.	1942
Test temperature (degrees Celsius)	1944
Test duration (minutes)	1946
Tolerance plus or minus (minutes)	1948
Prepare specimen per MIL-L-14107.	1950
Immersion	
Requirements (select one)	
Per base document except ____	1954
No disintegration.	1956

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1934	THE WEIGHT OF INSOLUBLES FORMED DURING HYDROLYSIS SHALL BE NOT GREATER THAN 1934 GRAM(S).
1936	THE COLOR NUMBER OF THE OIL AFTER HYDROLYSIS SHALL BE NOT GREATER THAN 1936.
1940	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1940.
1942	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3457 OF FED-STD-791.
1944	THE TEST TEMPERATURE SHALL BE 1944 DEGREES CELSIUS.
1946	THE TEST DURATION SHALL BE 1946 MINUTE(S).
1948	THE TOLERANCE SHALL BE PLUS OR MINUS 1948 MINUTE(S).
1950	THE SPECIMEN SHALL BE PREPARED IN ACCORDANCE WITH MIL-L-14107.
1954	IMMERSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1954.
1956	IMMERSION. THE SPECIMEN SHALL SHOW NO DISINTEGRATION.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Immersion (Cont)	
Test methods (select one)	
Per base document except ____	1960
Per FED-STD-791, Method 3463.	1962
Test media (name)	1964
(doc des)	1965
Test temperature (degrees Celsius)	1966
Duration (minutes)	1968
Molybdenum Disulfide Content	
Requirements (select one)	
Per base document except ____	2002
As follows:	2004
Molybdenum content	
Minimum (percent)	2006
Maximum (percent)	2008
Test methods (select one)	
Per base document except _____	2012
Per FED-STD-791, Method 3722.	2014

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1960	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1960.
1962	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3463 OF FED-STD-791.
1964	THE TEST MEDIA SHALL BE 1964.
1965	THE TEST MEDIA SHALL BE IN ACCORDANCE WITH 1965.
1966	THE TEMPERATURE SHALL BE 1966 DEGREES CELSIUS.
1968	THE DURATION SHALL BE 1968 MINUTE(S).
2002	MOLYBDENUM DISULFIDE CONTENT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2002.
2004	MOLYBDENUM DISULFIDE CONTENT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2006	THE CONTENT SHALL BE NOT LESS THAN 2006 PERCENT.
2008	THE CONTENT SHALL BE NOT GREATER THAN 2008 PERCENT.
2012	MOLYBDENUM DISULFIDE CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2012.
2014	MOLYBDENUM DISULFIDE CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3722 OF FED-STD-791.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Neutralization Number	
Requirements (select one)	
Per base document except ____	2030
Maximum neutralization number (no.)	2032
Test methods (select one)	
Per base document except ____	2036
Per ASTMD974.	2038
Per ASTMD664.	2040
Odor	
Requirements (select one)	
Per base document except ____	2018
No odor of rancidity, perfume or free alcohol.	2020
Test methods (select one)	
Per base document except ____	2024
Determine odor by sniffing.	2026

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2030	NEUTRALIZATION NUMBER. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2030.
2032	NEUTRALIZATION NUMBER. THE NEUTRALIZATION NUMBER SHALL BE NOT GREATER THAN 2032.
2036	NEUTRALIZATION NUMBER. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2036.
2038	NEUTRALIZATION NUMBER. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD974.
2040	NEUTRALIZATION NUMBER. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD664.
2018	ODOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2018.
2020	ODOR. THERE SHALL BE NO ODOR OF RANCIDITY, PERFUME OR FREE ALCOHOL.
2024	ODOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2024.
2026	ODOR. THE ODOR SHALL BE DETERMINED BY SNIFFING.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Oscillation	
Requirements (select one)	
Per base document except ____	2044
Minimum number of cycles (quantity)	2046
Test methods (select one)	
Per base document except ____	2050
Per FED-STD-791, Method 6516.	2052
Penetration	
Requirements (select one)	
Per base document except ____	2056
As follows:	2058
Worked penetration	
Minimum (units)	2060
Maximum (units)	2062
Prolonged worked penetration	
Minimum (units)	2064
Maximum (units)	2066

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2044	OSCILLATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2044.
2046	OSCILLATION. THE NUMBER OF CYCLES SHALL BE NOT LESS THAN 2046.
2050	OSCILLATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2050.
2052	OSCILLATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 6516 OF FED-STD-791.
2056	PENETRATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2056.
2058	PENETRATION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2060	THE WORKED PENETRATION SHALL BE NOT LESS THAN 2060 UNIT(S).
2062	THE WORKED PENETRATION SHALL BE NOT GREATER THAN 2062 UNIT(S).
2064	THE PROLONGED WORKED PENETRATION SHALL BE NOT LESS THAN 2064 UNIT(S).
2066	THE PROLONGED WORKED PENETRATION SHALL BE NOT GREATER THAN 2066 UNIT(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Penetration (Cont)	
As follows: (Cont)	
Unworked penetration	
Minimum (units)	2068
Maximum (units)	2070
Test methods (select one)	
Per base document except ____	2074
Per ASTMD217.	2076
Number of double strokes (quantity)	2078
Pour Point	
Requirements (select one)	
Per base document except ____	2082
Maximum temperature (degrees Celsius)	2084
Test methods (select one)	
Per base document except ____	2088
Per ASTMD97.	2090

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2068	THE UNWORKED PENETRATION SHALL BE NOT LESS THAN 2068 UNIT(S).
2070	THE UNWORKED PENETRATION SHALL BE NOT GREATER THAN 2070 UNIT(S).
2074	PENETRATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2074.
2076	PENETRATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD217.
2078	THE NUMBER OF DOUBLE STROKES SHALL BE 2078.
2082	POUR POINT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2082.
2084	POUR POINT. THE POUR POINT TEMPERATURE SHALL BE NOT GREATER THAN 2084 DEGREES CELSIUS.
2088	POUR POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2088.
2090	POUR POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD97.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Rubber Swell	
Requirements (select one)	
Per base document except ____	2102
Maximum average volume change (percent)	2104
Test methods (select one)	
Per base document except ____	2108
Per FED-STD-791, Method 3603.	2110
Sample immersion duration (hours)	2112
Number of samples (quantity)	2114
Test temperature (degrees Celsius)	2116
Sample type (letter)	2118
Per document (doc des)	2120
Salt Spray	
Requirements (select one)	
Per base document except ____	2124
Maximum number of corrosion spots (quantity)	2127

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2102	RUBBER SWELL. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2102.
2104	RUBBER SWELL. THE AVERAGE VOLUME CHANGE SHALL BE NOT GREATER THAN 2104 PERCENT.
2108	RUBBER SWELL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2108.
2110	RUBBER SWELL. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3603 OF FED-STD-791.
2112	THE SAMPLE IMMERSION DURATION SHALL BE 2112 HOUR(S).
2114	THE NUMBER OF SAMPLES SHALL BE 2114.
2116	THE TEST TEMPERATURE SHALL BE 2116 DEGREES CELSIUS.
2118	SAMPLE TYPE LETTER 2118 SHALL APPLY.
2120	SAMPLE TYPE SHALL BE IN ACCORDANCE WITH 2120.
2124	SALT SPRAY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2124.
2127	SALT SPRAY. THE NUMBER OF CORROSION SPOTS SHALL BE BE NOT GREATER THAN 2127.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Salt Spray (Cont)	
Maximum number of corrosion spots (Cont)	
Maximum diameter of corrosion spots (select one)	
(inches)	2128
(millimeters)	2130
Test methods (select one)	
Per base document except ____	2134
Per FED-STD-791.	2136
*Method (select one)	
4001.	2138
5322.	2140
5329.	2142
Number of specimens (quantity)	2144
Exposure duration (days)	2146
Separation	
Requirements (select one)	
Per base document except ____	2152

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2128	THE DIAMETER OF CORROSION SPOTS SHALL BE NOT GREATER THAN 2128 INCH(S).
2130	THE DIAMETER OF CORROSION SPOTS SHALL BE NOT GREATER THAN 2130 MILLIMETER(S).
2134	SALT SPRAY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2134.
2136	SALT SPRAY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH FED-STD-791.
2138	TEST METHOD 4001 SHALL APPLY.
2140	TEST METHOD 5322 SHALL APPLY.
2142	TEST METHOD 5329 SHALL APPLY.
2144	THE NUMBER OF SPECIMEN(S) SHALL BE 2144.
2146	THE EXPOSURE DURATION SHALL BE 2146 DAY(S).
2152	SEPARATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2152.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Separation (Cont)	
Requirements (Cont)	
Maximum weight loss (percent)	2154
Test methods (select one)	
Per base document except ____	2158
FED-STD-791, Method 321.	2160
Test duration (hours)	2162
Test temperature (degrees Celsius)	2164
Tolerance plus or minus (degrees Celsius)	2166
Storage Stability	
Requirements (select one)	
Per base document except ____	2170
As follows:	2172
Minimum unworked penetration change (points)	2174
Maximum worked penetration change (points)	2176
Shows no separation.	2178

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2154	SEPARATION. THE WEIGHT LOSS SHALL BE NOT GREATER THAN 2154 PERCENT.
2158	SEPARATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2158.
2160	SEPARATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 321 OF FED-STD-791.
2162	THE TEST DURATION SHALL BE 2162 HOUR(S).
2164	THE TEST TEMPERATURE SHALL BE 2164 DEGREES CELSIUS.
2166	THE TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2166 DEGREES CELSIUS.
2170	STORAGE STABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2170.
2172	STORAGE STABILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2174	THE UNWORKED PENETRATION CHANGE SHALL BE NOT LESS THAN 2174 POINT(S).
2176	THE WORKED PENETRATION CHANGE SHALL BE NOT GREATER THAN 2176 POINT(S).
2178	THE MATERIAL SHALL SHOW NO SEPARATION.

Source: https://assist.dla.mil -- Downloaded: 2026-04-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Storage Stability (Cont)	
Test methods (select one)	
Per base document except ____	2182
Per FED-STD-791, Method 3467.	2184
Per ASTMD217.	2186
Storage temperature (degrees Celsius)	2188
Tolerance plus or minus (degrees Celsius)	2190
Storage duration (select one)	
(hours)	2192
(days)	2194
(months)	2196
Minimum cooling temperature (degrees Celsius)	2200
Storage container.	2201
Pint.	2202
Quart.	2204
Gallon.	2206

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2182	STORAGE STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2182.
2184	STORAGE STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3467 OF FED-STD-791.
2186	STORAGE STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD217.
2188	THE STORAGE TEMPERATURE SHALL BE 2188 DEGREES CELSIUS.
2190	THE TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2190 DEGREES CELSIUS.
2192	THE STORAGE DURATION SHALL BE 2192 HOUR(S).
2194	THE STORAGE DURATION SHALL BE 2194 DAY(S).
2196	THE STORAGE DURATION SHALL BE 2196 MONTH(S).
2200	THE COOLING TEMPERATURE SHALL BE NOT LESS THAN 2200 DEGREES CELSIUS.
2201	THE STORAGE CONTAINER SHALL BE AS FOLLOWS:
2202	PINT(S).
2204	QUART(S).
2206	GALLON(S).

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Storage Stability (Cont)	
Per ASTMD217. (Cont)	
Container weight (select one)	
U.S. (select one)	
(ounces)	2208
(pounds)	2210
SI (select one)	
(grams)	2212
(kilograms)	2214
Sulfur	
Requirements (select one)	
Per base document except ____	2218
Maximum sulfur content (percent)	2220
Test methods (select one)	
Per base document except ____	2224
Per ASTMD129.	2226

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2208	THE CONTAINER WEIGHT SHALL BE 2208 OUNCE(S).
2210	THE CONTAINER WEIGHT SHALL BE 2210 POUND(S).
2212	THE CONTAINER WEIGHT SHALL BE 2212 GRAM(S).
2214	THE CONTAINER WEIGHT SHALL BE 2214 KILOGRAM(S).
2218	SULFUR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2218.
2220	SULFUR. THE SULFUR CONTENT SHALL BE NOT GREATER THAN 2220 PERCENT.
2224	SULFUR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2224.
2226	SULFUR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD129.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Temperature, High	
Requirements (select one)	
Per base document except ____	2227
Minimum lubricating duration (hours)	2228
No evidence of failure.	2230
Test methods (select one)	
Per base document except ____	2233
Per document (doc des)	2232
Test temperature (degrees Celsius)	2234
Test method (des)	2236
Minimum operation time (select one)	
(minutes)	2238
(hours)	2240
Temperature, Low	
Requirements (select one)	
Per base document except ____	2244
As follows:	2245

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2227	TEMPERATURE, HIGH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2227.
2228	TEMPERATURE, HIGH. THE LUBRICATING DURATION SHALL BE NOT LESS THAN 2228 HOUR(S).
2230	THERE SHALL BE NO EVIDENCE OF FAILURE.
2233	TEMPERATURE, HIGH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2233.
2232	TEMPERATURE, HIGH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2232.
2234	THE TEST TEMPERATURE SHALL BE 2234 DEGREES CELSIUS.
2236	THE TEST METHOD SHALL BE 2236.
2238	THE OPERATION TIME SHALL BE NOT LESS THAN 2238 MINUTE(S).
2240	THE OPERATION TIME SHALL BE NOT LESS THAN 2240 HOUR(S).
2244	TEMPERATURE, LOW. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2244.
2245	TEMPERATURE, LOW. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Temperature, Low (Cont)	
As follows: (Cont)	
No skidding or ball sliding during test.	2246
Shall not crystallize, separate or show evidence of precipitation.	2248
Maximum starting torque (select one)	
(inch-ounces)	2250
(newton meters)	2252
Maximum running torque (select one)	
(inch-ounces)	2254
(newton meters)	2256
Test methods (select one)	
Per base document except ____	2260
Per FED-STD-791, Method 3459.	2262
Test temperature (degrees Celsius)	2264
Duration of test temperature (hours)	2266

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2246	THERE SHALL BE NO SKIDDING OR BALL SLIDING DURING TEST.
2248	THERE SHALL BE NO CRYSTALLIZATION, SEPARATION OR EVIDENCE OF PRECIPITATION.
2250	THE STARTING TORQUE SHALL BE NOT GREATER THAN 2250 INCH-OUNCE(S).
2252	THE STARTING TORQUE SHALL BE NOT GREATER THAN 2252 NEWTON METER(S).
2254	THE RUNNING TORQUE SHALL BE NOT GREATER THAN 2254 INCH-OUNCE(S).
2256	THE RUNNING TORQUE SHALL BE NOT GREATER THAN 2256 NEWTON METER(S).
2260	TEMPERATURE, LOW. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2260.
2262	TEMPERATURE, LOW. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 3459 OF FED-STD-791.
2264	THE TEST TEMPERATURE SHALL BE 2264 DEGREES CELSIUS.
2266	THE DURATION OF TEST TEMPERATURE SHALL BE 2266 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Temperature, Low (Cont)	
Test methods (Cont)	
Per ASTMD1478.	2268
Duration (hours)	2284
Viscosity	
Requirements (select one)	
Per base document except ____	2318
As follows:	2320
Apparent	
First temperature (degrees Celsius)	2322
Minimum (centipoises)	2324
Maximum (centipoises)	2326
Shear rate (reciprocals per second)	2328
Second temperature (degrees Celsius)	2330
Minimum (centipoises)	2332

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2268	TEMPERATURE, LOW. TESTING SHALL BE IN ACCORDANCE WITH ASTMD1478.
2284	THE DURATION SHALL BE 2284 HOUR(S).
2318	VISCOSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2318.
2320	VISCOSITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2322	THE APPARENT VISCOSITY FIRST TEST TEMPERATURE SHALL BE 2322 DEGREES CELSIUS.
2324	THE APPARENT VISCOSITY AT FIRST TEMPERATURE SHALL BE NOT LESS THAN 2324 CENTIPOISE(S).
2326	THE APPARENT VISCOSITY AT FIRST TEMPERATURE SHALL BE NOT GREATER THAN 2326 CENTIPOISE(S).
2328	THE SHEAR RATE AT FIRST TEMPERATURE SHALL BE 2328 RECIPROCALS PER SECOND.
2330	THE APPARENT VISCOSITY SECOND TEMPERATURE SHALL BE 2330 DEGREES CELSIUS.
2332	THE APPARENT VISCOSITY AT SECOND TEMPERATURE SHALL BE NOT LESS THAN 2332 CENTIPOISE(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Viscosity (Cont)	
Second temperature (Cont)	
Maximum (centipoises)	2334
Shear rate (reciprocals per second)	2336
Kinematic	
First temperature (degrees Celsius)	2338
Minimum (centistokes)	2340
Maximum (centistokes)	2342
Second temperature (degrees Celsius)	2344
Minimum (centistokes)	2346
Maximum (centistokes)	2348
Third temperature (degrees Celsius)	2350
Minimum (centistokes)	2352
Maximum (centistokes)	2354

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2334	THE APPARENT VISCOSITY AT SECOND TEMPERATURE SHALL BE NOT GREATER THAN 2334 CENTIPOISE(S).
2336	THE SHEAR RATE AT SECOND TEMPERATURE SHALL BE 2336 RECIPROCALS PER SECOND.
2338	THE KINEMATIC VISCOSITY FIRST TEMPERATURE SHALL BE 2338 DEGREES CELSIUS.
2340	THE KINEMATIC VISCOSITY AT FIRST TEMPERATURE SHALL BE NOT LESS THAN 2340 CENTISTOKE(S).
2342	THE KINEMATIC VISCOSITY AT FIRST TEMPERATURE SHALL BE NOT GREATER THAN 2342 CENTISTOKE(S).
2344	THE KINEMATIC VISCOSITY SECOND TEMPERATURE SHALL BE 2344 DEGREES CELSIUS.
2346	THE KINEMATIC VISCOSITY SECOND TEMPERATURE SHALL BE NOT LESS THAN 2346 CENTISTOKE(S).
2348	THE KINEMATIC VISCOSITY AT SECOND TEMPERATURE SHALL BE NOT GREATER THAN 2348 CENTISTOKE(S).
2350	THE KINEMATIC VISCOSITY AT THIRD TEMPERATURE SHALL BE 2350 DEGREES CELSIUS.
2352	THE KINEMATIC VISCOSITY AT THIRD TEMPERATURE SHALL BE NOT LESS THAN 2352 CENTISTOKE(S).
2354	THE KINEMATIC VISCOSITY AT THIRD TEMPERATURE SHALL BE NOT GREATER THAN 2354 CENTISTOKE(S).

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Viscosity (Cont)	
As follows: (Cont)	
Index	
Test temperature (degrees Celsius)	2356
Minimum (no.)	2358
Maximum (no.)	2360
Saybolt	
First temperature (degrees Celsius)	2362
Minimum (seconds)	2364
Maximum (seconds)	2366
Second temperature (degrees Celsius)	2368
Minimum (seconds)	2370
Maximum (seconds)	2372
Test methods (select one)	
Per base document except ___	2302

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2356	THE INDEX VICOSITY TEMPERATURE SHALL BE 2356 DEGREES CELSIUS.
2358	THE INDEX VISCOSITY SHALL BE NOT LESS THAN 2358.
2360	THE INDEX VISCOSITY SHALL BE NOT GREATER THAN 2360.
2362	THE SAYBOLT VISCOSITY TEST TEMPERATURE SHALL BE 2362 DEGREES CELSIUS.
2364	THE SAYBOLT VISCOSITY AT FIRST TEMPERATURE SHALL BE NOT LESS THAN 2364 SECOND(S).
2366	THE SAYBOLT VISCOSITY AT FIRST TEMPERATURE SHALL BE NOT GREATER THAN 2366 SECOND(S).
2368	THE SAYBOLT VISCOSITY TEST TEMPERATURE SHALL BE 2368 DEGREES CELSIUS.
2370	THE SAYBOLT VISCOSITY AT SECOND TEMPERATURE SHALL BE NOT LESS THAN 2370 SECOND(S).
2372	THE SAYBOLT VISCOSITY AT SECOND TEMPERATURE SHALL BE NOT GREATER THAN 2372 SECOND(S).
2302	VISCOSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2302.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Viscosity (Cont)	
Test methods (Cont)	
As follows:	2304
Apparent (select one)	
ASTMD1092.	2306
ASTMD2983.	2308
Kinematic	
ASTMD445.	2310
Index	
ASTMD2270.	2312
Saybolt	
ASTMD88.	2314
Water Content	
Requirements (select one)	
Per base document except ___	2402
Maximum water content (percent)	2404

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2304	VISCOSITY. TESTING SHALL BE PERFORMED AS FOLLOWS:
2306	THE APPARENT VISCOSITY TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1092.
2308	THE APPARENT VISCOSITY TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD2983.
2310	THE KINEMATIC VISCOSITY TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD445.
2312	THE INDEX VISCOSITY TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD2270.
2314	THE SAYBOLT VISCOSITY TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD88.
2402	WATER CONTENT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2402.
2404	WATER CONTENT. THE WATER CONTENT SHALL BE NOT GREATER THAN 2404 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Water Content (Cont)	
Test methods (select one)	
Per base document except ____	2408
Per ASTMD95.	2410
Test temperature (degrees Celsius)	2412
Tolerance plus or minus (degrees Celsius)	2414
Water Washout	
Requirement (select one)	
Per base document except ____	2418
Maximum grease loss (percent)	2420
Test methods (select one)	
Per base document except ____	2424
Per ASTMD1264.	2426
Test temperature (degrees Celsius)	2428
Tolerance plus or minus (degrees Celsius)	2430

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2408	WATER CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2408.
2410	WATER CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD95.
2412	THE TEST TEMPERATURE SHALL BE 2412 DEGREES CELSIUS.
2414	THE TOLERANCE SHALL BE PLUS OR MINUS 2414 DEGREES CELSIUS.
2418	WATER WASHOUT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2418.
2420	WATER WASHOUT. THE GREASE LOSS SHALL BE NOT GREATER THAN 2420 PERCENT.
2424	WATER WASHOUT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2424.
2426	WATER WASHOUT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1264.
2428	THE TEST TEMPERATURE SHALL BE 2428 DEGREES CELSIUS.
2430	THE TOLERANCE SHALL BE PLUS OR MINUS 2430 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Storage Conditions	
(Years)	1529
Certify maximum cure date to delivery (quarters)	4942
Certify minimum shelf life after delivery (quarters)	4943
Certify maximum manufacture date to delivery (quarters)	4944
Age limitations per MIL-STD-1523.	5209
Additional Requirements	
A____	7001
B____	7002
C____	7003
D____	7004
E____	7005

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	STORAGE CONDITIONS.
1529	ITEMS SHALL WITHSTAND 1529 YEARS OF STORAGE WHEN PROPERLY PRESERVED, PACKAGED AND MECHANICALLY PROTECTED WITHOUT REQUIRING MAJOR REPAIR.
4942	MANUFACTURER SHALL CERTIFY THAT THE CURE DATE SHALL BE NOT GREATER THAN 4942 QUARTERS PRIOR TO DELIVERY DATE.
4943	MANUFACTURER SHALL CERTIFY THAT THERE SHALL BE NOT LESS THAN 4943 QUARTERS OF SHELF LIFE AFTER DELIVERY.
4944	MANUFACTURER SHALL CERTIFY THAT THE DATE OF MANUFACTURE SHALL BE NOT GREATER THAN 4944 QUARTERS PRIOR TO DATE OF DELIVERY.
5209	AGE LIMITATIONS OF THE FINISHED PRODUCT SHALL BE IN ACCORDANCE WITH MIL-STD-1523.
	ADDITIONAL REQUIREMENTS.
7001	(A) 7001.
7002	(B) 7002.
7003	(C) 7003.
7004	(D) 7004.
7005	(E) 7005.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Part Marking (Select One)	
(doc des)	6372
MIL-STD-1285.	7630
MIL-STD-130.	7629
Additional Part Marking	
A____	6991
B____	6992
C____	6993
D____	6994
E____	6995
Applicable Documents (See DOD-STD-35)	
Quality Assurance Provisions (See DOD-STD-35)	
Packaging (See DOD-STD-35)	
Notes (See DOD-STD-35)	
Nomenclature (See DOD-STD-35)	
Superseded Document (See DOD-STD-35)	
Part Number Cross-Reference (See DOD-STD-35)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6372	PART MARKING. PART IDENTIFICATION MARKING SHALL BE IN ACCORDANCE WITH 6372, USING THE PART NUMBER AS THE IDENTIFYING NUMBER.
7630	PART MARKING. PART IDENTIFICATION MARKING SHALL BE IN ACCORDANCE WITH MIL-STD-1285.
7629	PART MARKING. PART IDENTIFICATION MARKING SHALL BE IN ACCORDANCE WITH MIL-STD-130.
	ADDITIONAL PART MARKING.
6991	(A) 6991.
6992	(B) 6992.
6993	(C) 6993.
6994	(D) 6994.
6995	(E) 6995.

Custodians:
Army-MI

Review activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User activity:
Army-MU

Preparing activity:
Army-MI

(Project EDS-A205)

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

APPENDIX A

CHARACTERISTIC CODE INDEX

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
0101	22	1628	34	1730	42	1846	50
0102	22	1632	34	1734	42	1848	50
0103	22	1634	34	1736	42	1850	50
0104	22	1638	34	1740	42	1852	50
0105	22	1640	34	1742	42	1854	50
0107	24	1644	34	1746	42	1858	52
0108	24	1646	36	1747	42	1859	52
0700	22	1648	36	1748	42	1860	52
0800	22	1650	36	1750	44	1862	52
1003	22	1652	36	1752	44	1866	52
1004	22	1654	36	1756	44	1868	52
1005	22	1656	36	1758	44	1902	52
1006	22	1658	36	1762	44	1904	52
1008	22	1662	36	1764	44	1906	52
1529	90	1664	36	1768	44	1908	52
1564	26	1666	36	1770	44	1912	54
1566	26	1668	36	1774	46	1914	54
1568	26	1670	38	1776	46	1916	54
1570	28	1672	38	1780	46	1920	54
1572	28	1674	38	1782	46	1922	54
1576	28	1678	38	1784	46	1924	54
1577	30	1680	38	1786	46	1926	54
1578	30	1682	38	1788	46	1928	54
1580	30	1684	38	1802	46	1930	54
1582	30	1694	38	1804	46	1932	54
1586	30	1696	38	1808	48	1934	56
1588	30	1698	36	1810	48	1936	56
1598	30	1701	38	1814	50	1940	56
1591	30	1702	40	1816	50	1942	56
1592	30	1706	40	1818	50	1944	56
1594	30	1708	40	1822	48	1946	56
1602	32	1710	40	1824	48	1948	56
1604	32	1712	40	1826	48	1950	56
1608	32	1714	40	1828	48	1954	56
1610	32	1716	40	1830	48	1956	56
1614	32	1720	40	1832	48	1960	58
1616	32	1721	40	1834	48	1962	58
1620	32	1722	40	1836	48	1964	85
1622	32	1724	40	1840	50	1965	58
1626	34	1728	40	1842	50	1966	58

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
1968	58	2114	60	2208	74	2322	80
2002	58	2116	66	2210	74	2324	80
2004	58	2118	66	2212	74	2326	80
2006	58	2120	66	2214	74	2328	80
2008	58	2124	66	2218	74	2330	80
2012	58	2127	66	2220	74	2332	80
2014	58	2128	68	2224	74	2334	82
2018	60	2130	68	2226	74	2336	82
2020	60	2134	68	2227	76	2338	82
2024	60	2136	68	2228	76	2340	82
2026	60	2138	68	2230	76	2342	82
2030	60	2140	68	2232	76	2344	82
2032	60	2142	68	2233	76	2346	82
2036	60	2144	68	2234	76	2348	80
2038	60	2146	68	2236	76	2350	80
2040	60	2152	68	2238	76	2352	80
2044	62	2154	70	2240	76	2354	82
2046	62	2158	70	2244	76	2356	84
2050	62	2160	70	2245	76	2358	84
2052	62	2162	70	2246	78	2360	84
2056	62	2164	70	2248	78	2362	84
2058	62	2166	70	2250	78	2364	84
2060	62	2170	70	2252	78	2366	84
2062	62	2172	70	2254	78	2368	84
2064	62	2174	70	2256	78	2370	84
2066	62	2176	70	2260	78	2372	84
2068	64	2178	70	2262	78	2402	86
2070	64	2182	72	2264	78	2404	86
2074	64	2184	72	2266	78	2408	88
2076	64	2186	72	2268	80	2410	88
2078	64	2188	72	2284	80	2412	88
2082	64	2190	72	2302	84	2414	88
2084	64	2192	72	2304	86	2418	88
2088	64	2194	72	2306	86	2420	88
2090	64	2196	72	2308	86	2424	88
2102	66	2200	72	2310	86	2426	88
2104	66	2201	72	2312	86	2428	88
2108	66	2202	72	2314	86	2430	88
2110	66	2204	72	2318	80	4904	26
2112	60	2206	72	2320	80	4905	26

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
4942	90						
4943	90						
4944	90						
5046	26						
5048	26						
5068	26						
5069	26						
5209	90						
6369	22						
6372	92						
6375	28						
6873	22						
6874	24						
6941	24						
6942	24						
6991	92						
6992	92						
6993	92						
6994	92						
6995	92						
7001	90						
7002	90						
7003	90						
7004	90						
7005	90						
7301	26						
7302	26						
7629	92						
7638	92						

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX (CONT)

	Page
Materials	28
Molybdenum Disulfide Content	58
Neutralization Number	60
Nomenclature	92
Notes	92
Odor	60
Oscillation	62
Packaging	92
Part Marking	92
Part Number	24
Part Number Cross-Reference	92
Penetration	62
Phone Number	22
Pour Point	64
Quality Assurance Provisions	92
Requester FSCM	22
Requester's Name	22
Revision of AEDPS Document Number	24
Rubber Swell	66
Salt Spray	66
Scope	24
Separation	68
Source Table	24
Street/Building	22
Storage Conditions	90
Storage Stability	70
Sulfur	74
Superseded Document	92
System Application	22
Tabulated Characteristics	28
Temperature, High	76
Temperature, Low	76
Temperature Rating	26
Toxicity	28
Units of Measure	24
Viscosity	80

Source: https://assist.dla.mil Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX

	Page
Accelerated Weathering	28
Additional Part Marking	92
Additional Requirements	90
Aperture Cards Required	24
Appearance	28
Applicable Documents	92
Base Document	22
Carbon Residue	32
Chlorine	32
City, State, Zip	22
Classification	26
Company Name/Command	22
Composition	28
Color	34
Contaminant	34
Contract Number/Office Symbol	22
Control	22
Corrosiveness/Oxidation	36
Cycling Performance	38
Date	22
Density	40
Design and Construction	28
Dielectric Strength	42
Dirt Content	42
Dropping Point	44
Evaporation Loss	46
Flash Point	46
Foaming	48
Format	22
Gear Wear	50
Government Design Activity FSCM	22
Gravity, API	52
Humidity	52
Hydrolytic Stability	54
Immersion	56

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX (CONT)

Page

Water Content - - -

The digital copy of DOD-STD-35-112 (MI), dated 05-MAY-1978 does not include the foldout page for the Specification Requirement Sheet (SRS). If you need a copy , please call the ASSIST SERVICE DESK at 215-737-8000.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

The digital copy of DOD-STD-35-112 (MI), dated 05-MAY-1978 does not include the foldout page for the Specification Requirement Sheet (SRS). If you need a copy , please call the ASSIST SERVICE DESK at 215-737-8000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
DOD-STD-35-112	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander,
U.S. Army Missile R & D Command,
ATTN: DRDMI-ESD,
Redstone Arsenal, Alabama 35809

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.