DOD-STD-35-116(MI)
7 July 1978

MILITARY STANDARD

POTTING COMPOUNDS

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

FSC EDS

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF THE ARMY
U.S. ARMY MATERIEL
DEVELOPMENT AND READINESS COMMAND
ALEXANDRIA, VA 22333

Potting Compounds
Automated Engineering
Document Preparation System

DOD-STD-35-116(MI)

1. This Military Standard is approved for use by DARCOM, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S. Army Missile Research and Development Command, ATTN: DRDMI-ESD, Redstone Arsenal, Alabama 35809, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

FOREWORD

1. The purpose of DOD-STD-35-116(MI) is to provide instructions for the preparation of Specification Requirements Sheets (SRS) in order to produce Military Specification Exceptions for Potting Compounds.

2. In order to properly utilize this document, it is necessary to have a complete and thorough understanding of the DOD-STD-35.

3. It is important that the procedures described in the basic document (DOD-STD-35D and subsequent revisions) be followed explicitly in order to produce a document suitable for procurement. Information which is standard for all dash-numbered parts has been included in the basic document at the issuance of DOD-STD-35D. This information is not repeated in each dash-numbered part.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	REFERENCED DOCUMENT	5
	2.1	Issues of Documents	5
	2.2	Other publications	5
	3.	DEFINITIONS	7
	4.	GENERAL REQUIREMENTS	9
	4.1	Introduction	9
	4.2	Specification Requirements Sheet (SRS)	9
	4.3	Units of measure	9
	5.	DETAILED REQUIREMENTS	11
	5.1	Introduction	11
	5.2	MSE formats	11
	5.3	Referenced documents	11
	5.4	Test matrix	11
	5.5	Tabulation	12
	5.6	Keyword Code Index (KCI) and Standard Paragraph	15
	5.6.1	Interrelationship of codes	15
	5.6.2	Automatic MSE Data	15
	5.6.3	DOD-STD-35 Tables	15

TABLES

Tables	I.	Title index	3
	II.	Test matrix	12
	III.	Tabulation candidates	13

APPENDIX

Appendix	A.	Characteristic Code Index	163
		Index	171

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Potting Compounds.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX.

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
POTTING COMPOUND, EPOXY	615001	MIL-C-22608	HIGH TEMP
		MIL-P-46067	EMBEDDING
		MIL-I-46865	COLLOIDAL SILICA FILLED
		MIL-C-46881	TRANSPARENT
		MIL-C-82644	ENCAPSULATING
POTTING COMPOUND, POLYSULFIDE	615002	MIL-C-22608	HIGH TEMP
POTTING COMPOUND, POLYURETHANE	615003	MIL-M-24041	MOLDING CHEM CURED
		MIL-P-43081	LOW MOLECULAR WEIGHT
		MIL-P-46847	FOAMED ENCAPSULATING
		MIL-C-47002	COATING, SINGLE COMPONENT
		MIL-F-47095	FOAMED FOR IMBEDDING
		MIL-C-47131	COMPOUNDS, MOLDING
		MIL-P-47298	MOLDING, CHEM CURED
		MIL-M-81999	AIRCRAFT STRUC

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
POTTING COMPOUND, SILICONE	615004	MIL-R-46092	ENCAPSULATING COMPOUND
		MIL-P-46838	RTV
		MIL-I-47096	TWO-COMPONENT ROOM TEMP CURE
		MIL-P-83455	TWO COMPONENT, RTC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-M-81999	Molding Compound, Reversion Resistant, Non Carcinogers Curing Polyurethane, Aircraft Structure

STANDARDS

FEDERAL

FED-STD-141	Paint, Varnish, Lacquer and Related Materials, Methods of Inspection, Sampling and Testing
FED-STD-406	Plastic, Methods of Testing

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this standard to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASTMC177	Thermal Conductivity of Materials by Means of the Guarded Hot Plate, Method of Test for
ASTMD395	Compression Set of Rubber
ASTMD412	Rubber, Determination of Tension Characteristics
ASTMD618	Conditioning Plastics and Electrical Insulating Materials for Testing
ASTMD732	Shear Strength of Plastics

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

ASTMD746	Brittleness Temperature of Plastics and Elastomers by Impact
ASTMD1149	Accelerated Ozone Cracking of Vulcanized Rubber
ASTMD1621	Compressive Properties of Rigid Cellular Plastics
ASTMD2471	Gel Time and Peak Exothermic Temperature of Reacting Thermosetting Resins
ASTME380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

3. DEFINITIONS

Definitions contained in DOD-STD-35 are applicable to Potting Compounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

4. GENERAL REQUIREMENTS

4.1 Introduction. In order to properly prepare an SRS for Potting Compounds, it is necessary to use DOD-STD-35 in conjunction with this dash-numbered part. In the event the instructions or the writing methodology are not followed, an AEDPS edit routine will print error messages rather than the desired MSE document.

4.2 Specification Requirement Sheet (SRS). SRS requirements described in DOD-STD-35 are applicable to Potting Compounds.

4.3 Units of measure. The International System of Units (SI) or inch-pound units (U.S.), may be used to specify characteristics (e.g. weight, dimensions). Refer to ASTME380 for guidance in using SI. However, when different units of measure are available for specifying a characteristic, only one may be used. Both units of measure cannot appear in the same MSE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Test matrix. A test matrix is supplied as a guide for selecting documents to specify tests (see table II). The test matrix presents documents most applicable for use to satisfy the statement "TEST PER (DOC DES)". Any document listed in the Title Index may be used to satisfy the statement. However, the selected document from the Title Index must contain the desired test. Government test method documents and approved industry standards such as ASTM test methods may also be used to satisfy the statement "TEST PER (DOC DES)".

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE II. TEST MATRIX

DOCUMENT	Code	1704	1744	1804	1906	2004	3302	2046	2166	2216	2304	3310	2436	2526	3442	3742	2559	2682	2764	2854	2904	3043
	Test	Test Specimen Preparation	Adhesion	Breaking Strength	Chemical/Composition	Corrosion	Density/Specific Gravity	Dielectric Constant	Dissipation Factor	Drying	Flammability	Fungus	Hardness	Hydrolytic Stability	Immersion	Low Temperature	Non Volatile Content	Oil and Solvent Resistance	Peel Strength	Shelf Storage Life	Tear Resistance	Viscosity
MIL-M-24041		X	X					X				X				X					X	
MIL-P-43081		X						X														
MIL-P-46067										X			X									X
MIL-F-47095							X	X	X											X		X
MIL-I-47096				X			X					X	X									X
MIL-C-47131								X				X	X			X	X		X	X		
MIL-I-47293					X																	
MIL-P-47298								X				X		X	X						X	
MIL-M-81999											X	X		X		X					X	
MIL-P-83455						X												X				

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for Potting Compounds characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

TABLE III. TABULATION CANDIDATES.

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1562	TYPE (DES)	1564	CLASS (DES)	1568	COLOR (NAME)
1576	SOLIDS CONTENT (PCT)	1580	MESH (NUMBER)	1650	RISE TIME (MIN)
1654	TACK FREE TIME (MIN)	1660	MIX RATIO PARTS CATY (MINIMUM)	1662	MIX RATIO PARTS CATY (MAXIMUM)

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

5.6 Keyword Code Index (KCI) and Standard Paragraphs. The KCI provides codes, to be entered on an SRS, that are unique for the type part covered by this dash-numbered part of DOD-STD-35. The left-hand page presents the information in outline form using keywords and codes. The right-hand page presents the words that will appear in the MSE. To find the code to be entered on the SRS, find the subject in the index at the back of this dash-numbered part. Find the keyword on the KCI and its associated code. Enter, on the SRS, the code and the characteristic value required. After the part unique characteristics have been specified, refer to DOD-STD-35 when exceptions are required to Quality Assurance, Packaging, Notes, etc. Instructions are in DOD-STD-35 on how to enter any type characteristic value. Appendix A, Characteristic Code Index, provides a numerical list of codes used in this dash-numbered part. This index identifies the location of codes by page number.

5.6.1 Interrelationship of codes. The interrelationship of the codes is shown by the indentation level of characteristic names on the KCI. The kind of characteristic value is shown by a colon, parentheses, period or underline. The paragraph, of which the code is a part, is shown by the standard paragraph adjacent to the code on a right-hand page. When a characteristic value entered with a code becomes part of the paragraph, the code is shown in the paragraph where the characteristic value will print. The MSE will contain the exact entry as supplied with the code, except for "X" entries.

5.6.2 Automatic MSE data. Some statements, such as Altitude and Temperature, will appear in the printed MSE without having to make additional entries. These statements are linked by data base logic to characteristic codes listed under them and will print when one of the codes listed is used. Other statements may print automatically depending on the type MSE selected. Explanations are noted on the KCI as required.

5.6.3 DOD-STD-35 Tables. The KCI of this document contains references to tables in Appendix A of DOD-STD-35. Most of the tables are in preprinted form and should be reproduced, applicable data entered, and attached to the SRS for submittal. Refer to DOD-STD-35 for a general explanation in the generation of tables.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
*Requester's Name	0101
*Company Name/Command	0102
*Street/Building	0103
*City, State, Zip	0104
*Phone Number, Include Area Code, Autovon If Applicable	0105
*Date	1003
*Requester FSCM	1004
*Contract Number/Office Symbol	1005
*Base Document	1006
*System Application	1008
*Government Design Activity FSCM	6369
*Format (Select One)	
Six section document.	0700
One section document.	0800
*Control (Select One)	
Source.	6873

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
0101	0101.
0102	0102.
0103	0103.
0104	0104.
0105	0105.
1003	1003.
1004	USER(S) FSCM(S) 1004.
1005	CONTRACT NUMBER OR OFFICE SYMBOL 1005.
1006	THE COMPLETE REQUIREMENTS FOR PROCURING THE ITEM(S) DESCRIBED HEREIN SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT(S), 1006, EXCEPT AS SPECIFIED IN THIS DOCUMENT. IN THE EVENT OF CONFLICT, THIS DOCUMENT SHALL GOVERN.
1008	SYSTEM APPLICATION 1008.
6369	GOVERNMENT DESIGN ACTIVITY FSCM 6369.
0700	
0800	
	SOURCE(S).
6873	THE FOLLOWING SOURCE(S) SHOWN WITH THE PART NUMBER(S) IS/ARE THE ONLY APPROVED SOURCE(S) FOR THE ITEM(S) DESCRIBED BY THIS DOCUMENT. IDENTIFICATION OF THE APPROVED SOURCE(S) HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM DESCRIBED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Control (Cont)	
Specification.	6874
*Source Table	
Note: Refer to Table V of DOD-STD-35.	
Aperture Cards Required.	0107
Revision of AEDPS Document Number	0108
Scope	
Note: This entry is automatic and determined by the title code used.	
Part Number	
Note: Automatic with a single item MSE.	
Note: Automatic with a multi-item MSE.	
Units of Measure (Select One)	
U.S.	6941
SI.	6942

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6874	THE FOLLOWING SUGGESTED SOURCE(S) SHOWN WITH THEIR PART NUMBER(S) HAVE BEEN KNOWN TO MEET THE REQUIREMENT(S) OF THIS DOCUMENT. IDENTIFICATION OF THE 'SUGGESTED SOURCE(S) OF SUPPLY' HEREIN IS NOT TO BE CONSTRUED AS A GUARANTEE OF PRESENT OR CONTINUED AVAILABILITY AS A SOURCE OF SUPPLY FOR THE ITEM(S).
0107	
0108	0108.
	SCOPE.
	SCOPE. THIS DOCUMENT COVERS THE DETAILED REQUIREMENTS FOR TITLE CODE.
	PART NUMBER. THE PART NUMBER FOR THE ITEM IS SUPPLIED BY COMPUTER.
	PART NUMBER. THE PART NUMBER FOR THE ITEMS IS THE SAME AS THE NUMBER OF THIS DOCUMENT PLUS THE SUFFIX NUMBER FROM THE TABULATED CHARACTERISTIC TABLE. REVISION AND ACTIVITY SYMBOLS ARE NOT INCLUDED IN THE PART NUMBER.
6941	UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INCH-POUND UNITS (U.S.) OR DEGREES.
6942	UNIT OF MEASURE. ALL UNITS OF MEASURE ARE IN INTERNATIONAL SYSTEM OF UNITS (SI) OR DEGREES.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Classification	
Type	
Base document type (des)	1562
Class	
Base document class (des)	1564
Temperature Rating	
Maximum storage (degrees Celsius)	7302
Minimum storage (degrees Celsius)	7301
Nominal storage (degrees Celsius)	5048
Tabulated Characteristics (see Table IV, DOD-STD-35)	
Materials (see Tables VI and VII, DOD-STD-35)	
Note: Automatic when Table VII is used.	
Composition	
Composition, formulation or mixture.	6375

*Ingredient table, (see Table XI, DOD-STD-35)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	CLASSIFICATION.
1562	TYPE. THE TYPE DESIGNATION SHALL BE 1562 IN ACCORDANCE WITH THE BASE DOCUMENT.
1564	CLASS. THE CLASS DESIGNATION SHALL BE 1564 IN ACCORDANCE WITH THE BASE DOCUMENT.
	TEMPERATURE RATING.
7302	THE MAXIMUM STORAGE TEMPERATURE RATING SHALL BE 7302 DEGREES CELSIUS.
7301	THE MINIMUM STORAGE TEMPERATURE RATING SHALL BE 7301 DEGREES CELSIUS.
5048	THE NOMINAL STORAGE TEMPERATURE RATING SHALL BE 5048 DEGREES CELSIUS.
	MATERIAL(S). MATERIAL(S) SHALL BE AS SPECIFIED IN THE MATERIAL TABLE. (NOTE: THE COMPONENT REFERENCE NUMBER(S) ARE ONLY TO REFERENCE THE SAME COMPONENT WHEN TABLE CONTINUATION IS NECESSARY.)
6375	COMPOSITION. THE COMPOSITION, FORMULATION OR MIXTURE (AS APPLICABLE) SHALL BE AS SPECIFIED HEREIN. THE INGREDIENT QUANTITIES SHALL BE SHOWN IN INTERNATIONAL (SI) SYSTEM OF UNITS SUCH AS GRAMS, LITERS, ETC., OR U.S. STANDARDS SUCH AS PINTS, QUARTS OR GALLONS, AS SPECIFIED IN THE TABLE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Design and Construction	
Appearance	
The material shall have uniform homogenious texture.	1566
Color	
(name)	1568
(doc des)	1570
(designation)	1572
(class number)	1574
Solids Content	
(percent)	1576
tolerance (percent)	1578
Particle Size	
Mesh (number)	1580
(doc des)	1582
Rise Time	
(minutes)	1650
Tolerance (seconds)	1652

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	DESIGN AND CONSTRUCTION.
1566	APPEARANCE. THE COMPOUND SHALL BE FREE OF LUMPS, COARSE PARTICLES, AND AIR BUBBLES BEFORE MOLDING OR POTTING, AND AFTER CURING IT SHALL HAVE AN EVEN TEXTURE FREE OF LUMPS AND AIR BUBBLES.
1568	COLOR. THE COLOR SHALL BE 1568.
1570	THE COLOR SHALL BE IN ACCORDANCE WITH 1570.
1572	THE COLOR DESIGNATION 1572 SHALL APPLY.
1574	THE COLOR CLASS NUMBER 1574 SHALL APPLY.
1576	SOLIDS CONTENT. THE SOLIDS CONTENT SHALL BE 1576 PERCENT.
1578	THE SOLIDS CONTENT TOLERANCE SHALL BE PLUS OR MINUS 1578 PERCENT.
1580	PARTICLE SIZE. ALL PARTICLES SHALL PASS THROUGH A SCREEN OF MESH SIZE 1580.
1582	THE MESH SCREEN SHALL BE IN ACCORDANCE WITH 1582.
1650	RISE TIME. THE RISE TIME SHALL BE 1650 MINUTE(S).
1652	THE RISE TIME TOLERANCE SHALL BE PLUS OR MINUS 1652 SECOND(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Design and Construction (Cont)	
Tack-Free Time	
(minutes)	1654
Tolerance (seconds)	1656
Mixing Ratio	
Parts catalyst	
Minimum (quantity)	1660
Maximum (quantity)	1662
Toxicity	
Toxicity of material shall not present health hazard.	1628
Test Specimen Preparation	
Requirements (select one)	
Per base document except ____	1726
As follows:	1727

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1654	TACK-FREE TIME. THE TACK-FREE TIME SHALL BE 1654 MINUTE(S).
1656	THE TACK-FREE TIME TOLERANCE SHALL BE PLUS OR MINUS 1656 SECOND(S).
	MIXING RATIO.
1660	THE CATALYST SHALL BE NOT LESS THAN 1660 PARTS PER 100 PARTS OF COMPOUND.
1662	THE CATALYST SHALL BE NOT GREATER THAN 1662 PARTS PER 100 PARTS OF COMPOUND.
1628	TOXICITY. THE TOXICITY OF THE MATERIAL SHALL BE SUCH THAT IT WILL NOT PRESENT A HEALTH HAZARD TO INDIVIDUALS FROM INHALATION, SKIN CONTACT, OR INGESTION, WHEN USED IN THE MANNER INTENDED OR AS A RESULT OF EXPOSURE AFTER APPLICATION.
1726	TEST SPECIMEN PREPARATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1726.
1727	TEST SPECIMEN PREPARATION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Test Specimen Preparation (Cont)	
As follows: (Cont)	
Material cured throughout.	1728
Material has no voids.	1730
Material supports embedded part.	1732
Material causes no deterioration of embedded part.	1734
Material causes no discoloration of embedded part.	1736
Material requires no external support after curing.	1738
Test methods (select one)	
Per base document except ____	1702
Per document (doc des)	1704
Specimen size (select one)	
(square inches)	1706
(square millimeters)	1708

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1728	THE MATERIAL SHALL BE CURED THROUGHOUT.
1730	THE MATERIAL SHALL HAVE NO VOIDS.
1732	THE MATERIAL SHALL SUPPORT THE EMBEDDED PART.
1734	THE MATERIAL SHALL NOT CAUSE DETERIORATION OF THE EMBEDDED PART.
1736	THE MATERIAL SHALL NOT CAUSE DISCOLORATION OF THE EMBEDDED PART.
1738	THE MATERIAL SHALL NOT REQUIRE EXTERNAL SUPPORT AFTER CURING.
1702	TEST SPECIMEN PREPARATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1702.
1704	TEST SPECIMEN PREPARATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1704.
1706	THE TEST SPECIMEN SIZE SHALL BE 1706 SQUARE INCH(S).
1708	THE TEST SPECIMEN SIZE SHALL BE 1708 SQUARE MILLIMETER(S).

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Test Specimen Preparation (Cont)	
Per document (Cont)	
Specimen thickness (select one)	
(inches)	1710
(millimeters)	1712
Cure temperature (degrees Celsius)	1714
Temperature tolerance, plus or minus (degrees Celsius)	1716
Cure relative humidity (percent)	1718
Humidity tolerance, plus or minus (percent)	1720
Cure period	
Minimum (hours)	1737
Maximum (hours)	1739

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1710	THE TEST SPECIMEN SHALL BE 1710 INCH(S) IN THICKNESS.
1712	THE TEST SPECIMEN SHALL BE 1712 MILLIMETER(S) IN THICKNESS.
1714	THE CURING TEMPERATURE SHALL BE 1714 DEGREES CELSIUS.
1716	THE CURING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1716 DEGREES CELSIUS.
1718	THE CURING RELATIVE HUMIDITY SHALL BE 1718 PERCENT.
1720	THE CURING RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 1720 PERCENT.
1737	THE CURING PERIOD SHALL BE NOT LESS THAN 1737 HOUR(S).
1739	THE CURING PERIOD SHALL BE NOT GREATER THAN 1739 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Abrasion Resistance	
Requirements (select one)	
Per base document except ____	1725
As follows:	1735
Maximum weight loss (select one)	
(grams)	1721
(ounces)	1729
Maximum wear loss (select one)	
(inches)	1731
(millimeters)	1733
Test method (select one)	
Per base document except ____	1832
Per FED-STD-141, Method 6192.	1834
Number of test specimens (quantity)	1836
Specimen size	
Width (select one)	
(inches)	1838
(millimeters)	1840

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1725	ABRASION RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1725.
1735	ABRASION RESISTANCE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1721	THE WEIGHT LOSS SHALL BE NOT GREATER THAN 1721 GRAM(S).
1729	THE WEIGHT LOSS SHALL BE NOT GREATER THAN 1729 OUNCE(S).
1731	THE WEAR LOSS SHALL BE NOT GREATER THAN 1731 INCH(S).
1733	THE WEAR LOSS SHALL BE NOT GREATER THAN 1733 MILLIMETER(S).
1832	ABRASION RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1832.
1834	ABRASION RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 6192 OF FED-STD-141.
1836	THERE SHALL BE 1836 SPECIMENS TESTED.
1838	THE TEST SPECIMEN SHALL BE 1838 INCH(S) IN WIDTH.
1840	THE TEST SPECIMEN SHALL BE 1840 MILLIMETER(S) IN WIDTH.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Abrasion Resistance (Cont)	
Specimen size (Cont)	
Thickness (select one)	
(inches)	1842
(millimeters)	1844
Length (select one)	
(inches)	1846
(millimeters)	1848
Diameter (select one)	
(inches)	1850
(millimeters)	1852
Test cycles (quantity)	1854
Calibrase wheel (name)	1856
Pressure of wheel against test film (select one)	
(grams)	1858
(ounces)	1859

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRPAH
1842	THE TEST SPECIMEN SHALL BE 1842 INCH(S) IN THICKNESS.
1844	THE TEST SPECIMEN SHALL BE 1844 MILLIMETER(S) IN THICKNESS.
1846	THE TEST SPECIMEN SHALL BE 1846 INCH(S) IN LENGTH.
1848	THE TEST SPECIMEN SHALL BE 1848 MILLIMETER(S) IN LENGTH.
1850	THE TEST SPECIMEN SHALL BE 1850 INCH(S) IN DIAMETER.
1852	THE TEST SPECIMEN SHALL BE 1852 MILLIMETER(S) IN DIAMETER.
1854	THERE SHALL BE 1854 TEST CYCLE(S).
1856	THE CALIBRASE WHEEL 1856 SHALL APPLY.
1858	THE PRESSURE OF THE CALIBRASE WHEEL SHALL BE 1858 GRAM(S).
1859	THE PRESSURE OF THE CALIBRASE WHEEL SHALL BE 1859 OUNCE(S).

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Adhesion	
Requirements (select one)	
Per base document except ____	1770
As follows:	1771
Minimum shear strength (select one)	
(psi)	1772
(kilopascals)	1774
Minimum separation force (select one)	
U.S. (select one)	
(pounds per foot of width)	1776
(ounces per inch of width)	1777
SI (select one)	
(newtons per meter of width)	1778
(millinewtons per millimeter of width)	1779
No affect by contact with distilled water.	1782
Adhere tightly without lifting or scaling.	1784

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1770	ADHESION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1770.
1771	ADHESION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1772	THE SHEAR STRENGTH SHALL BE NOT LESS THAN 1772 POUND(S) PER SQUARE INCH.
1774	THE SHEAR STRENGTH SHALL BE NOT LESS THAN 1774 KILOPASCAL(S).
1776	THE SEPARATION FORCE SHALL BE NOT LESS THAN 1776 POUND(S) PER FOOT OF WIDTH.
1777	THE SEPARATION FORCE SHALL BE NOT LESS THAN 1777 OUNCE(S) PER INCH OF WIDTH.
1778	THE SEPARATION OF FORCE SHALL BE NOT LESS THAN 1778 NEWTON(S) PER METER OF WIDTH.
1779	THE SEPARATION FORCE SHALL BE NOT LESS THAN 1779 MILLINEWTON(S) PER MILLIMETER OF WIDTH.
1782	CONTACT WITH DISTILLED WATER SHALL NOT CAUSE ADVERSE AFFECT.
1784	ITEM SHALL ADHERE TIGHTLY WITHOUT LIFTING OR SCALING.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Adhesion (Cont)	
As follows: (Cont)	
No flaking, chipping, or powdering.	1786
Minimum separation force at low temperature (select one)	
(ounces per inch of width)	1788
(millinewtons per millimeter of width)	1790
Minimum separation force at high temperature (select one)	
(ounces per inch of width)	1792
(millinewtons per millimeter of width)	1794
Maximum cohesive failure (percent)	1793
Test methods (select one)	
Per base document except ____	1742
Per document (doc des)	1744
Number of specimens to be tested (quantity)	1930
Test specimen width (select one)	
(inches)	1932
(millimeters)	1934

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1786	THERE SHALL BE NO FLAKING, CHIPPING, OR POWDERING.
1788	THE SEPARATION FORCE AT LOW TEMPERATURE SHALL BE NOT LESS THAN 1788 OUNCE(S) PER INCH OF WIDTH.
1790	THE SEPARATION FORCE AT LOW TEMPERATURE SHALL BE NOT LESS THAN 1790 MILLINEWTON(S) PER MILLIMETER OF WIDTH.
1792	THE SEPARATION FORCE AT HIGH TEMPERATURE SHALL BE NOT LESS THAN 1792 OUNCE(S) PER INCH OF WIDTH.
1794	THE SEPARATION FORCE AT HIGH TEMPERATURE SHALL BE NOT LESS THAN 1794 MILLINEWTON(S) PER MILLIMETER OF WIDTH.
1793	THE ADHESION FAILURE RATE SHALL BE NOT GREATER THAN 1793 PERCENT.
1742	ADHESION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1742.
1744	ADHESION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1744.
1930	THERE SHALL BE 1930 SPECIMENS TESTED.
1932	THE TEST SPECIMEN SHALL BE 1932 INCH(S) IN WIDTH.
1934	THE TEST SPECIMEN SHALL BE 1934 MILLIMETER(S) IN WIDTH.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Adhesion (Cont)	
Per document (Cont)	
Test specimen thickness (select one)	
(inches)	1936
(millimeters)	1938
Test specimen length (select one)	
(inches)	1940
(millimeters)	1942
Number of test cycles (quantity)	1943
Maximum cure period (select one)	
(hours)	1752
(minutes)	1754
Curing relative humidity (percent)	1756
Tolerance plus or minus (percent)	1758
Maximum curing temperature (degrees Celsius)	1755

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE STANDARD PARAGRAPH

1936 THE TEST SPECIMEN SHALL BE 1936 INCH(S) IN THICKNESS.

1938 THE TEST SPECIMEN SHALL BE 1938 MILLIMETER(S) IN THICKNESS.

1940 THE TEST SPECIMEN SHALL BE 1940 INCH(S) IN LENGTH.

1942 THE TEST SPECIMEN SHALL BE 1942 MILLIMETER(S) IN LENGTH.

1943 THERE SHALL BE 1943 CYCLE(S).

1752 THE CURING PERIOD SHALL BE NOT GREATER THAN 1752 HOUR(S).

1754 THE CURING PERIOD SHALL BE NOT GREATER THAN 1754 MINUTE(S).

1756 THE CURING RELATIVE HUMIDITY SHALL BE 1756 PERCENT.

1758 THE CURING RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 1758 PERCENT.

1755 THE CURING TEMPERATURE SHALL BE NOT GREATER THAN 1755 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Adhesion (Cont)	
Per document (Cont)	
Perform testing at high temperature (degrees Celsius)	1766
Perform testing at low temperature (degrees Celsius)	1764
Breaking Strength	
Requirements (select one)	
Per base document except ____	1816
As follows:	1818
Minimum strength (select one)	
(pounds per inch width)	1820
(newtons per millimeter width)	1822
Test methods (select one)	
Per base document except ____	1802
Per document (doc des)	1804

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1766	THE HIGH TEMPERATURE TESTING SHALL BE PERFORMED AT 1766 DEGREES CELSIUS.
1764	THE LOW TEMPERATURE TESTING SHALL BE PERFORMED AT 1764 DEGREES CELSIUS.
1816	BREAKING STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1816.
1818	BREAKING STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1820	THE BREAKING STRENGTH SHALL BE NOT LESS THAN 1820 POUND(S) PER INCH OF WIDTH.
1822	THE BREAKING STRENGTH SHALL BE NOT LESS THAN 1822 NEWTON(S) PER MILLIMETER OF WIDTH.
1802	BREAKING STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1802.
1804	BREAKING STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1804.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Brittle Point	
Requirements (select one)	
Per base document except ____	1952
Maximum temperature (degrees Celsius)	1954
Test methods (select one)	
Per base document except ____	1958
Per ASTMD746, Method B.	1960
Chemical Composition	
Requirements (select one)	
Per base document except ____	1912

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1952	BRITTLE POINT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1952.
1954	BRITTLE POINT. THE TEMPERATURE SHALL BE NOT GREATER THAN 1954 DEGREES CELSIUS.
1958	BRITTLE POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1958.
1960	BRITTLE POINT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD B OF ASTMD746.
1912	CHEMICAL COMPOSITION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1912.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Chemical Composition (Cont)	
Requirements (Cont)	
Per Chemical Composition Table.	1914
Test methods (select one)	
Per base document except ____	1902
Suppliers certification instead of test.	1904
Per document (doc des)	1906
Test method (des)	1908

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE | STANDARD PARAGRAPH

1914 CHEMICAL COMPOSITION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE CHEMICAL COMPOSITION TABLE.

CHEMICAL COMPOSITION TABLE

INGREDIENT	QUANTITY	UNITS
6715	6716	6717
6718	6719	6720
6721	6722	6723
6724	6725	6726
6727	6728	6729
6730	6731	6732
6733	6734	6735
6736	6737	6738
6739	6740	6741
6742	6743	6744
6745	6746	6747
6748	6749	6750
6751	6752	6753
6754	6755	6756

1902 CHEMICAL COMPOSITION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1902.

1904 CHEMICAL COMPOSITION. SUPPLIERS CERTIFICATE OF COMPLIANCE WITH THE CHEMICAL COMPOSITION REQUIREMENT(S) MAY BE ACCEPTED IN LIEU OF A SPECIFIC TEST.

1906 CHEMICAL COMPOSITION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1906.

1908 TEST METHOD 1908 SHALL APPLY.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Coefficient of Linear Expansion	
Requirements (select one)	
Per base document except ____	1964
As follows: (select one)	1966
U.S.	
Minimum (inch per inch per degree Celsius X 10^{-6})	1968
Maximum (inch per inch per degree Celsius X 10^{-6})	1971
SI	
Minimum (millimeter per millimeter per degree Celsius x 10^{-6})	1970
Maximum (millimeter per millimeter per degree Celsius X 10^{-6})	1973
Test methods (select one)	
Per base document except ____	1974
Per FED-STD-406, Method 2031.	1976
Number of specimens to be tested (quantity)	1982

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1964	COEFFICIENT OF LINEAR EXPANSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1964.
1966	COEFFICIENT OF LINEAR EXPANSION. THE AVERAGE COEFFICIENT SHALL BE AS FOLLOWS:
1968	NOT LESS THAN 1968 INCH PER INCH PER DEGREE CELSIUS TIMES 10 TO THE NEGATIVE 6 POWER.
1971	NOT GREATER THAN 1971 INCH PER INCH PER DEGREE CELSIUS TIMES 10 TO THE NEGATIVE 6 POWER.
1970	NOT LESS THAN 1970 MILLIMETER PER MILLIMETER PER DEGREE CELSIUS TIMES 10 TO THE NEGATIVE 6 POWER.
1973	NOT GREATER THAN 1973 MILLIMETER PER MILLIMETER PER DEGREE CELSIUS TIMES 10 TO THE NEGATIVE 6 POWER.
1974	COEFFICIENT OF LINEAR EXPANSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1974.
1976	COEFFICIENT OF LINEAR EXPANSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 2031 OF FED-STD-406.
1982	THERE SHALL BE 1982 SPECIMENS TESTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Coefficient of Linear Expansion (Cont)	
Per FED-STD-406, Method 2031. (Cont)	
Specimen width (select one)	
(inches)	1984
(millimeters)	1986
Specimen thickness (select one)	
(inches)	1988
(millimeters)	1989
Specimen length (select one)	
(inches)	1991
(millimeters)	1992
Number of test cycles (quantity)	1994
Test temperature (degrees Celsius)	1996
Tolerance plus or minus (degrees Celsius)	1998
Compression Set	
Requirements (select one)	
Per base document except ____	1922
Maximum compression set (percent)	1924

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1984	THE TEST SPECIMEN SHALL BE 1984 INCH(S) IN WIDTH.
1986	THE TEST SPECIMEN SHALL BE 1986 MILLIMETER(S) IN WIDTH.
1988	THE TEST SPECIMEN SHALL BE 1988 INCH(S) IN THICKNESS.
1989	THE TEST SPECIMEN SHALL BE 1989 MILLIMETER(S) IN THICKNESS.
1991	THE TEST SPECIMEN SHALL BE 1991 INCH(S) IN LENGTH.
1992	THE TEST SPECIMEN SHALL BE 1992 MILLIMET (S) IN LENGTH.
1994	THERE SHALL BE 1994 TEST CYCLE(S).
1996	THE TEST TEMPERATURE SHALL BE 1996 DEGREES CELSIUS.
1998	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 1998 DEGREES CELSIUS.
1922	COMPRESSION SET. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1922.
1924	COMPRESSION SET. THE COMPRESSION SET SHALL BE NOT GREATER THAN 1924 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Compression Set (Cont)	
Test methods (select one)	
Per base document except ____	1928
Per ASTMD395, Method B.	1931
Number of specimens to be tested (quantity)	1944
Specimen width (select one)	
(inches)	1946
(millimeters)	1948
Specimen thickness (select one)	
(inches)	1949
(millimeters)	1951
Specimen length (select one)	
(inches)	1953
(millimeters)	1955
Specimen Diameter (select one)	
(inches)	1959
(millimeters)	1961
Number of test cycles (quantity)	1957

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
1928	COMPRESSION SET. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1928.
1931	COMPRESSION SET. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD B OF ASTMD395.
1944	THERE SHALL BE 1944 SPECIMENS TESTED.
1946	THE TEST SPECIMEN SHALL BE 1946 INCH(S) IN WIDTH.
1948	THE TEST SPECIMEN SHALL BE 1948 MILLIMETER(S) IN WIDTH.
1949	THE TEST SPECIMEN SHALL BE 1949 INCH(S) IN THICKNESS.
1951	THE TEST SPECIMEN SHALL BE 1951 MILLIMETER(S) IN THICKNESS.
1953	THE TEST SPECIMEN SHALL BE 1953 INCH(S) IN LENGTH.
1955	THE TEST SPECIMEN SHALL BE 1955 MILLIMETER(S) IN LENGTH.
1959	THE TEST SPECIMEN SHALL BE 1959 INCH(S) IN DIAMETER.
1961	THE TEST SPECIMEN SHALL BE 1961 MILLIMETER(S) IN DIAMETER.
1957	THERE SHALL BE 1957 TEST CYCLE(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Compression Strength	
Requirements (select one)	
Per base document except ____	2352
As follows: (select one)	2353
(psi)	2354
Tolerance plus or minus (psi)	2356
(kilopascals)	2358
Tolerance plus or minus (kilopascals)	2360
Test methods (select one)	
Per base document except ____	2364
Per ASTMD1621.	2366
Number of specimens to be tested (quantity)	2368
Specimen width (select one)	
(inches)	2370
(millimeters)	2372
Specimen thickness (select one)	
(inches)	2374
(millimeters)	2376

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2352	COMPRESSION STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2352.
2353	COMPRESSION STRENGTH. THE COMPRESSION STRENGTH SHALL BE AS FOLLOWS:
2354	THE COMPRESSION STRENGTH SHALL BE 2354 POUND(S) PER SQUARE INCH.
2356	THE TOLERANCE SHALL BE PLUS OR MINUS 2356 POUND(S) PER SQUARE INCH.
2358	THE COMPRESSION STRENGTH SHALL BE 2358 KILOPASCAL(S).
2360	THE TOLERANCE SHALL BE PLUS OR MINUS 2360 KILOPASCAL(S).
2364	COMPRESSION STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2364.
2366	COMPRESSION STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1621.
2368	THERE SHALL BE 2368 SPECIMEN(S) TESTED.
2370	THE TEST SPECIMEN SHALL BE 2370 INCH(S) IN WIDTH.
2372	THE TEST SPECIMEN SHALL BE 2372 MILLIMETER(S) IN WIDTH.
2374	THE TEST SPECIMEN SHALL BE 2374 INCH(S) IN THICKNESS.
2376	THE TEST SPECIMEN SHALL BE 2376 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Compression Strength (Cont)	
Per ASTMD1621. (Cont)	
Specimen length (select one)	
(inches)	2378
(millimeters)	2380
Specimen diameter (select one)	
(inches)	2384
(millimeters)	2386
Number of test cycles (quantity)	2382
Corrosion	
Requirements (select one)	
Per base document except ____	2036
No pitting, corrosion, or adverse affect.	2038
Test methods (select one)	
Per base document except ____	2002
Per document (doc des)	2004

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2378	THE TEST SPECIMEN SHALL BE 2378 INCH(S) IN LENGTH.
2380	THE TEST SPECIMEN SHALL BE 2380 MILLIMETER(S) IN LENGTH.
2384	THE TEST SPECIMEN SHALL BE 2384 INCH(S) IN DIAMETER.
2386	THE TEST SPECIMEN SHALL BE 2386 MILLIMETER(S) IN DIAMETER.
2382	THERE SHALL BE 2382 TEST CYCLE(S).
2036	CORROSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2036.
2038	CORROSION. THERE SHALL BE NO PITTING, CORROSION, OR ADVERSE AFFECT.
2002	CORROSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2002.
2004	CORROSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2004.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Corrosion (Cont)	
Per document (Cont)	
Specimen length (select one)	
(inches)	2006
(millimeters)	2008
Specimen width (select one)	
(inches)	2010
(millimeters)	2012
Specimen thickness (select one)	
(inches)	2014
(millimeters)	2016
Test period (select one)	
(hours)	2018
(days)	2020
Test temperature (degrees Celsius)	2022
Test relative humidity (percent)	2024
Number of specimens to be tested (quantity)	2026
Curing	
Requirements (select one)	
Per base document except ____	3222

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2006	THE TEST SPECIMEN SHALL BE 2006 INCH(S) IN LENGTH.
2008	THE TEST SPECIMEN SHALL BE 2008 MILLIMETER(S) IN LENGTH.
2010	THE TEST SPECIMEN SHALL BE 2010 INCH(S) IN WIDTH.
2012	THE TEST SPECIMEN SHALL BE 2012 MILLIMETER(S) IN WIDTH.
2014	THE TEST SPECIMEN SHALL BE 2014 INCH(S) IN THICKNESS.
2016	THE TEST SPECIMEN SHALL BE 2016 MILLIMETER(S) IN THICKNESS.
2018	THE TEST PERIOD SHALL BE 2018 HOUR(S).
2020	THE TEST PERIOD SHALL BE 2020 DAY(S).
2022	THE TEST TEMPERATURE SHALL BE 2022 DEGREES CELSIUS.
2024	THE TEST RELATIVE HUMIDITY SHALL BE 2024 PERCENT.
2026	THERE SHALL BE 2026 SPECIMEN(S) TESTED.
3222	CURING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3222.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Curing (Cont)	
Requirements (Cont)	
As follows:	3224
Curing recommended by the manufacturer.	3226
Minimum shore "A" hardness (value)	3228
No deformation of specimen.	3230
No evidence of running or rippling.	3232
Test methods (select one)	
Per base document except ____	3238
Per ASTMD618.	3240
Number of specimens to be tested (quantity)	3242
Specimen width (select one)	
(inches)	3244
(millimeters)	3246
Specimen thickness (select one)	
(inches)	3248
(millimeters)	3250

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3224	CURING. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
3226	THE CURING SHALL BE AS RECOMMENDED BY THE MANUFACTURER.
3228	HARDNESS SHALL BE NOT LESS THAN 3228 SHORE A.
3230	THERE SHALL BE NO DEFORMATION OF THE SPECIMEN.
3232	THERE SHALL BE NO EVIDENCE OF RUNNING OR RIPPLING.
3238	CURING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3238.
3240	CURING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD618.
3242	THERE SHALL BE 3242 SPECIMEN(S) TESTED.
3244	THE TEST SPECIMEN SHALL BE 3244 INCH(S) IN WIDTH.
3246	THE TEST SPECIMEN SHALL BE 3246 MILLIMETER(S) IN WIDTH.
3248	THE TEST SPECIMEN SHALL BE 3248 INCH(S) IN THICKNESS.
3250	THE TEST SPECIMEN SHALL BE 3250 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Curing (Cont)	
Per ASTMD618. (Cont)	
Specimen length (select one)	
(inches)	3252
(millimeters)	3254
Specimen diameter (select one)	
(inches)	3262
(millimeters)	3264
Cure temperature (degrees Celsius)	3256
Tolerance plus or minus (degrees Celsius)	3258
Number of durometer readings (quantity)	3260
Curing period (select one)	
(minutes)	3274
(hours)	3272
(days)	3270
Test relative humidity (percent)	3276
Tolerance plus or minus (percent)	3278
Deformation period (minutes)	3280

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3252	THE TEST SPECIMEN SHALL BE 3252 INCH(S) IN LENGTH.
3254	THE TEST SPECIMEN SHALL BE 3254 MILLIMETER(S) IN LENGTH.
3262	THE TEST SPECIMEN SHALL BE 3262 INCH(S) IN DIAMETER.
3264	THE TEST SPECIMEN SHALL BE 3264 MILLIMETER(S) IN DIAMETER.
3256	THE CURE TEMPERATURE SHALL BE 3256 DEGREES CELSIUS.
3258	THE CURE TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3258 DEGREES CELSIUS.
3260	AFTER FIRM CONTACT THERE SHALL BE 3260 DUROMETER READINGS TAKEN.
3274	THE CURING DURATION SHALL BE 3274 MINUTE(S).
3272	THE CURING DURATION SHALL BE 3272 HOUR(S).
3270	THE CURING DURATION SHALL BE 3270 DAY(S).
3276	THE TEST RELATIVE HUMIDITY SHALL BE 3276 PERCENT.
3278	THE TEST RELATIVE HUMIDTY TOLERANCE SHALL BE PLUS OR MINUS 3278 PERCENT.
3280	THE SPECIMEN SHALL BE DEFORMED FOR A PERIOD OF 3280 MINUTES, AND THEN SHALL RETURN TO NORMAL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Density/Specific Gravity	
Requirements (select one)	
Per base document except ____	3284
As follows:	3286
Minimum density (select one	
(grams/centimeter^3)	3292
(pounds/foot^3)	3294
Specific gravity (number)	3296
Test methods (select one)	
Per base document except ____	3300
Per document (doc des)	3302
Test temperature (degrees Celsius)	3304
Dielectric Constant	
Requirements (select one)	
Per base document except ____	2082

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3284	DENSITY/SPECIFIC GRAVITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3284.
3286	DENSITY/SPECIFIC GRAVITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
3292	THE DENSITY SHALL BE NOT LESS THAN 3292 GRAM(S) PER CUBIC CENTIMETER.
3294	THE DENSITY SHALL BE NOT LESS THAN 3294 POUND(S) PER CUBIC FOOT.
3296	THE SPECIFIC GRAVITY SHALL BE 3296.
3300	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3300.
3302	DENSITY/SPECIFIC GRAVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3302.
3304	TEST TEMPERATURE SHALL BE 3304 DEGREES CELSIUS.
2082	DIELECTRIC CONSTANT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2082.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Dielectric Constant (Cont)	
Requirements (Cont)	
As follows:	2084
Maximum dielectric constant at 60 Hertz (value)	2086
Maximum dielectric constant at 1 kilohertz (value)	2087
Maximum dielectric constant at 1 megahertz (value)	2089
Test methods (select one)	
Per base document except ____	2044
Per document (doc des)	2046
Number of specimens to be tested (quantity)	2048
Specimen width (select one)	
(inches)	2064
(millimeters)	2066
Specimen thickness (select one)	
(inches)	2054
(millimeters)	2056

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGARAPH
2084	DIELECTRIC CONSTANT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2086	THE DIELECTRIC CONSTANT AT 60 HERTZ SHALL BE NOT GREATER THAN 2086.
2087	THE DIELECTRIC CONSTANT AT 1 KILOHERTZ SHALL BE NOT GREATER THAN 2087.
2089	THE DIELECTRIC CONSTANT AT 1 MEGAHERTZ SHALL BE NOT GREATER THAN 2089.
2044	DIELECTRIC CONSTANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2044.
2046	DIELECTRIC CONSTANT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2046.
2048	THERE SHALL BE 2048 SPECIMEN(S) TESTED.
2064	THE TEST SPECIMEN SHALL BE 2064 INCH(S) IN WIDTH.
2066	THE TEST SPECIMEN SHALL BE 2066 MILLIMETER(S) IN WIDTH.
2054	THE TEST SPECIMEN SHALL BE 2054 INCH(S) IN THICKNESS.
2056	THE TEST SPECIMEN SHALL BE 2056 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Dielectric Constant (Cont)	
Per document (Cont)	
Specimen length (select one)	
(inches)	2060
(millimeters)	2062
Specimen diameter (select one)	
(inches)	2050
(millimeters)	2052
Test temperature (degrees Celsius)	2061
Tolerance plus or minus (degrees Celsius)	2063
Test relative humidity (percent)	2065
Tolerance plus or minus (percent)	2067
Dielectric Strength	
Requirements (select one)	
Per base document except ____	2152
As follows: (select one)	2154

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2060	THE TEST SPECIMEN SHALL BE 2060 INCH(S) IN LENGTH.
2062	THE TEST SPECIMEN SHALL BE 2062 MILLIMETER(S) IN LENGTH.
2050	THE TEST SPECIMEN SHALL BE 2050 INCH(S) IN DIAMETER.
2052	THE TEST SPECIMEN SHALL BE 2052 MILLIMETER(S) IN DIAMETER.
2061	THE TEST TEMPERATURE SHALL BE 2061 DEGREES CELSIUS.
2063	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2063 DEGREES CELSIUS.
2065	THE TEST RELATIVE HUMIDITY SHALL BE 2065 PERCENT.
2067	THE TEST RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2067 PERCENT.
2152	DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2152.
2154	DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Dielectric Strength (Cont)	
As follows: (Cont)	
Minimum dielectric strength (select one)	
(volts per 0.001 inch)	2156
(volts per millimeter)	2158
Minimum breakdown voltage (volts)	2160
Test methods (select one)	
Per base document except ____	2102
Per FED-STD-406, Method 4031.	2104
Number of specimens to be tested (quantity)	2106
Specimen width (select one)	
(inches)	2112
(millimeters)	2114
Specimen thickness (select one)	
(inches)	2116
(millimeters)	2118

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2156	THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2156 VOLT(S) PER 0.001 INCH.
2158	THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2158 VOLT(S) PER MILLIMETER.
2160	THE BREAKDOWN VOLTAGE SHALL BE NOT LESS THAN 2160 VOLT(S).
2102	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2102.
2104	DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 4031 OF FED-STD-406.
2106	THERE SHALL BE 2106 SPECIMEN(S) TESTED.
2112	THE TEST SPECIMEN SHALL BE 2112 INCH(S) IN WIDTH.
2114	THE TEST SPECIMEN SHALL BE 2114 MILLIMETER(S) IN WIDTH.
2116	THE TEST SPECIMEN SHALL BE 2116 INCH(S) IN THICKNESS.
2118	THE TEST SPECIMEN SHALL BE 2118 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Dielectric Strength (Cont)	
Per FED-STD-406, Method 4031. (Cont)	
Specimen length (select one)	
(inches)	2108
(millimeters)	2110
Specimen diameter (select one)	
(inches)	2120
(millimeters)	2122
Number of specimens to be tested (quantity)	2123
Short time test to breakdown.	2134
Maximum voltage application rate (volts per second)	2136
Test voltage (select one)	
(volts, dc)	2128
(volts, ac)	2130
Frequency (hertz)	2132
Test medium (select one)	
Oil.	2124
Air.	2126

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2108	THE TEST SPECIMEN SHALL BE 2108 INCH(S) IN LENGTH.
2110	THE TEST SPECIMEN SHALL BE 2110 MILLIMETER(S) IN LENGTH.
2120	THE TEST SPECIMEN SHALL BE 2120 INCH(S) IN DIAMETER.
2122	THE TEST SPECIMEN SHALL BE 2122 MILLIMETER(S) IN DIAMETER.
2123	THERE SHALL BE 2123 TEST CYCLE(S).
2134	THE SHORT TIME TEST TO BREAKDOWN METHOD SHALL BE USED.
2136	THE VOLTAGE APPLICATION RATE SHALL BE NOT GREATER THAN 2136 VOLT(S) PER SECOND.
2128	THE TEST VOLTAGE SHALL BE 2128 VOLT(S), DC.
2130	THE TEST VOLTAGE SHALL BE 2130 VOLT(S), AC.
2132	THE TEST FREQUENCY SHALL BE 2132 HERTZ.
2124	THE TEST MEDIUM SHALL BE OIL.
2126	THE TEST MEDIUM SHALL BE AIR.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Dielectric Strength (Cont)	
Per FED-STD-406, Method 4031. (Cont)	
Test temperature (degrees Celsius)	2138
Tolerance plus or minus (degrees Celsius)	2140
Test relative humidity (percent)	2142
Dissipation Factor	
Requirements (select one)	
Per base document except ____	2202
As follows:	2204
Minimum dissipation factor at 60 Hertz (value)	2206
Minimum dissipation factor at kilohertz (value)	2208
Minimum dissipation factor at megahertz (value)	2210
Test methods (select one)	
Per base document except ____	2164
Per document (doc des)	2166

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2138	THE TEST TEMPERATURE SHALL BE 2138 DEGREES CELSIUS.
2140	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2140 DEGREES CELSIUS.
2142	THE RELATIVE HUMIDITY SHALL BE 2142 PERCENT.
2202	DISSIPATION FACTOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2202.
2204	DISSIPATION FACTOR. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2206	THE DISSIPATION FACTOR AT 60 HERTZ SHALL BE NOT LESS THAN 2206.
2208	THE DISSIPATION FACTOR AT 1 KILOHERTZ SHALL BE NOT LESS THAN 2208.
2210	THE DISSIPATION FACTOR AT 1 MEGAHERTZ SHALL BE NOT LESS THAN 2210.
2164	DISSIPATION FACTOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2164.
2166	DISSIPATION FACTOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2166.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Dissipation Factor (Cont)	
Per document (Cont)	
Number of specimens to be tested (quantity)	2168
Specimen width (select one)	
(inches)	2182
(millimeters)	2184
Specimen thickness (select one)	
(inches)	2174
(millimeters)	2176
Specimen length (select one)	
(inches)	2178
(millimeters)	2180
Specimen diameter (select one)	
(inches)	2170
(millimeters)	2172
Number of test cycles (quantity)	2177

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2168	THERE SHALL BE 2168 SPECIMEN(S) TESTED.
2182	THE TEST SPECIMEN SHALL BE 2182 INCH(S) IN WIDTH.
2184	THE TEST SPECIMEN SHALL BE 2184 MILLIMETER(S) IN WIDTH.
2174	THE TEST SPECIMEN SHALL BE 2174 INCH(S) IN THICKNESS.
2176	THE TEST SPECIMEN SHALL BE 2176 MILLIMETER(S) IN THICKNESS.
2178	THE TEST SPECIMEN SHALL BE 2178 INCH(S) IN LENGTH.
2180	THE TEST SPECIMEN SHALL BE 2180 MILLIMETER(S) IN LENGTH.
2170	THE TEST SPECIMEN SHALL BE 2170 INCH(S) IN DIAMETER.
2172	THE TEST SPECIMEN SHALL BE 2172 MILLIMETER(S) IN DIAMETER.
2177	THERE SHALL BE 2177 TEST CYCLE(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Drying	
Requirements (select one)	
Per base document except ____	2246
Period to reach full cure (select one)	
(minutes)	2252
(hours)	2250
Test methods (select one)	
Per base document except ____	2214
Per document (doc des)	2216
Number of specimens to be tested (quantity)	2217
Specimen width (select one)	
(inches)	2222
(millimeters)	2224
Specimen thickness (select one)	
(inches)	2226
(millimeters)	2228

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2246	DRYING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2246.
2252	DRYING. THE TIME TO REACH FULL CURE SHALL BE 2252 MINUTE(S).
2250	DRYING. THE TIME TO REACH FULL CURE SHALL BE 2250 HOUR(S).
2214	DRYING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2214.
2216	DRYING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2216.
2217	THERE SHALL BE 2217 SPECIMEN(S) TESTED.
2222	THE TEST SPECIMEN SHALL BE 2222 INCH(S) IN WIDTH.
2224	THE TEST SPECIMEN SHALL BE 2224 MILLIMETER(S) IN WIDTH.
2226	THE TEST SPECIMEN SHALL BE 2226 INCH(S) IN THICKNESS.
2228	THE TEST SPECIMEN SHALL BE 2228 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Drying (Cont)	
Per document (Cont)	
Specimen length (select one)	
(inches)	2218
(millimeters)	2220
Specimen diameter (select one)	
(inches)	2243
(millimeters)	2245
Maximum drying temperature (degrees Celsius)	2234
Test specimen amount (select one)	
(grams)	2242
(ounces)	2240
Elongation	
Requirements (select one)	
Per base document except ____	2280
Minimum elongation (percent)	2282

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2218	THE TEST SPECIMEN SHALL BE 2218 INCH(S) IN LENGTH.
2220	THE TEST SPECIMEN SHALL BE 2220 MILLIMETER(S) IN LENGTH.
2243	THE TEST SPECIMEN SHALL BE 2243 INCH(S) IN DIAMETER.
2245	THE TEST SPECIMEN SHALL BE 2245 MILLIMETER(S) IN DIAMETER.
2234	THE DRYING TEMPERATURE SHALL BE NOT GREATER THAN 2234 DEGREES CELSIUS.
2242	THE TEST SPECIMEN QUANTITY TO BE DRIED SHALL BE 2242 GRAM(S).
2240	THE TEST SPECIMEN QUANTITY TO BE DRIED SHALL BE 2240 OUNCE(S).
2280	ELONGATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2280.
2282	ELONGATION. THE ELONGATION SHALL BE NOT LESS THAN 2282 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Elongation (Cont)	
Test methods (select one)	
Per base document except ____	2268
Per ASTMD412.	2269
Number of specimens to be tested (quantity)	2276
Specimen width (select one)	
(inches)	2270
(millimeters)	2271
Specimen thickness (select one)	
(inches)	2273
(millimeters)	2275
Specimen length (select one)	
(inches)	2281
(millimeters)	2283
Specimen diameter (select one)	
(inches)	2286
(millimeters)	2287

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2268	ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2268.
2269	ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD412.
2276	THERE SHALL BE 2276 SPECIMEN(S) TESTED.
2270	THE TEST SPECIMEN SHALL BE 2270 INCH(S) IN WIDTH.
2271	THE TEST SPECIMEN SHALL BE 2271 MILLIMETER(S) IN WIDTH.
2273	THE TEST SPECIMEN SHALL BE 2273 INCH(S) IN THICKNESS.
2275	THE TEST SPECIMEN SHALL BE 2275 MILLIMETER(S) IN THICKNESS.
2281	THE TEST SPECIMEN SHALL BE 2281 INCH(S) IN LENGTH.
2283	THE TEST SPECIMEN SHALL BE 2283 MILLIMETER(S) IN LENGTH.
2286	THE TEST SPECIMEN SHALL BE 2286 INCH(S) IN DIAMETER.
2287	THE TEST SPECIMEN SHALL BE 2287 MILLIMETER(S) IN DIAMETER.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Elongation (Cont)	
Per ASTMD412. (Cont)	
Number of test cycles (quantity)	2284
Bench mark distance (select one)	
(inches)	2272
(millimeters)	2274
Flammability	
Requirements (select one)	
Per base document except ____	2332
As follows:	2334
Specimen (select one)	
Self-extinguishing.	2336
Non-burning.	2338
Maximum burn distance (select one)	
(inches)	2340
(millimeters)	2342
Maximum burn period (seconds)	2344
Maximum smoldering period (seconds)	2346

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2284	THERE SHALL BE 2284 TEST CYCLE(S).
2272	THE DISTANCE BETWEEN BENCH MARKS SHALL BE 2272 INCH(S).
2274	THE DISTANCE BETWEEN BENCH MARKS SHALL BE 2274 MILLIMETER(S).
2332	FLAMMABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2332.
2334	FLAMMABILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2336	THE SPECIMEN SHALL BE SELF-EXTINGUISHING.
2338	THE SPECIMEN SHALL BE NON-BURNING.
2340	THE BURNING DISTANCE SHALL BE NOT GREATER THAN 2340 INCH(S).
2342	THE BURNING DISTANCE SHALL BE NOT GREATER THAN 2342 MILLIMETER(S).
2344	THE BURNING PERIOD SHALL BE NOT GREATER THAN 2344 SECOND(S).
2346	THE SMOLDERING PERIOD SHALL BE NOT GREATER THAN 2346 SECOND(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Flammability (Cont)	
Test methods (select one)	
Per base document except ____	2302
Per document (doc des)	2304
Test method (des)	2306
Specimen width (select one)	
(inches)	2314
(millimeters)	2316
Specimen thickness (select one)	
(inches)	2318
(millimeters)	2320
Specimen length (select one)	
(inches)	2310
(millimeters)	2312
Specimen diameter (select one)	
(inches)	2321
(millimeters)	2323

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2302	FLAMMABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2302.
2304	FLAMMABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2304.
2306	TEST METHOD 2306 SHALL APPLY.
2314	THE TEST SPECIMEN SHALL BE 2314 INCH(S) IN WIDTH.
2316	THE TEST SPECIMEN SHALL BE 2316 MILLIMETER(S) IN WIDTH.
2318	THE TEST SPECIMEN SHALL BE 2318 INCH(S) IN THICKNESS.
2320	THE TEST SPECIMEN SHALL BE 2320 MILLIMETER(S) IN THICKNESS.
2310	THE TEST SPECIMEN SHALL BE 2310 INCH(S) IN LENGTH.
2312	THE TEST SPECIMEN SHALL BE 2312 MILLIMETER(S) IN LENGTH.
2321	THE TEST SPECIMEN SHALL BE 2321 INCH(S) IN DIAMETER.
2323	THE TEST SPECIMEN SHALL BE 2323 MILLIMETER(S) IN DIAMETER.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Flamability (Cont)	
Per document (Cont)	
Number of test cycles (quantity)	2325
Number of specimens to be tested (quantity)	2308
Specimen weight (select one)	
(grams)	2324
(ounces)	2322
Times flame applied (quantity)	2326
Flame application period (seconds)	2328
Fungus	
Requirements (select one)	
Per base document except ____	4760
Fungus resistance by certification or by test.	4761
No evidence of fungus growth by test.	4762

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2325	THERE SHALL BE 2325 TEST CYCLE(S).
2308	THERE SHALL BE 2308 SPECIMEN(S) TESTED.
2324	THE TEST SPECIMEN WEIGHT SHALL BE 2324 GRAM(S).
2322	THE TEST SPECIMEN WEIGHT SHALL BE 2322 OUNCE(S).
2326	THE FLAME SHALL BE APPLIED TO THE SPECIMEN 2326 TIME(S).
2328	THE FLAME SHALL BE APPLIED FOR A DURATION OF 2328 SECOND(S)
4760	FUNGUS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4760.
4761	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THE MANUFACTURER SHALL VERIFY BY CERTIFICATION THAT ALL EXTERNAL MATERIALS ARE FUNGUS RESISTANT OR SHALL PERFORM THE FUNGUS TEST. WHEN THE FUNGUS TEST IS PERFORMED THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4762	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Fungus (Cont)	
Test methods (select one)	
Per base document except ____	4754
Per document (doc des)	3310
Test period (days)	4756
Test method (des)	3312
Number of specimens to be tested (quantity)	3317
Hardness	
Requirements (select one)	
Per base document except ____	2466
As follows:	2468
Minimum average durometer reading (no.)	2470
Minimum durometer readings (no.)	2472
Applicable durometer scale (letter)	2442
Test method (select one)	
Per base document except ____	2434
Per document (doc des)	2436

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4754	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4754.
3310	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3310.
4756	TEST PERIOD SHALL BE 4756 DAY(S).
3312	TEST METHOD 3312 SHALL APPLY.
3317	THERE SHALL BE 3317 SPECIMEN(S) TESTED.
2466	HARDNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2466.
2468	HARDNESS. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2470	THE AVERAGE DUROMETER READING SHALL BE NOT LESS THAN 2470.
2472	THE DUROMETER READING SHALL BE NOT LESS THAN 2472.
2442	THE DUROMETER SCALE LETTER 2442 SHALL APPLY.
2434	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2434.
2436	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2436.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Hardness (Cont)	
Per document (Cont)	
Number of specimens to be tested (quantity)	2462
Specimen width (select one)	
(inches)	2450
(millimeters)	2452
Specimen thickness (select one)	
(inches)	2454
(millimeters)	2456
Specimen length (select one)	
(inches)	2446
(millimeters)	2448
Specimen diameter (select one)	
(inches)	2449
(millimeters)	2451
Indentation duration (seconds)	2444
Test temperature (degrees Celsius)	2445
Tolerance plus or minus (degrees Celsius)	2447

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2462	THERE SHALL BE 2462 SPECIMEN(S) TESTED.
2450	THE TEST SPECIMEN SHALL BE 2450 INCH(S) IN WIDTH.
2452	THE TEST SPECIMEN SHALL BE 2452 MILLIMETER(S) IN WIDTH.
2454	THE TEST SPECIMEN SHALL BE 2454 INCH(S) IN THICKNESS.
2456	THE TEST SPECIMEN SHALL BE 2456 MILLIMETER(S) IN THICKNESS.
2446	THE TEST SPECIMEN SHALL BE 2446 INCH(S) IN LENGTH.
2448	THE TEST SPECIMEN SHALL BE 2448 MILLIMETER(S) IN LENGTH.
2449	THE TEST SPECIMEN SHALL BE 2449 INCH(S) IN DIAMETER.
2451	THE TEST SPECIMEN SHALL BE 2451 MILLIMETER(S) IN DIAMETER.
2444	THE INDENTATION DURATION SHALL BE 2444 SECOND(S).
2445	THE TEST TEMPERATURE SHALL BE 2445 DEGREES CELSIUS.
2447	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2447 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Humidity	
Requirements (select one)	
Per base document except ____	4798
As follows:	3381
Maximum weight loss (percent)	3380
Maximum moisture absorption (percent)	3382
Test methods (select one)	
Per base document except ____	4788
Per FED-STD-406, Method 7031.	3384
Specimen width (select one)	
(inches)	3386
(millimeters)	3388
Specimen thickness (select one)	
(inches)	3400
(millimeters)	3402
Specimen length (select one)	
(inches)	3403
(millimeters)	3405

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4798	HUMIDITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4798.
3381	HUMIDITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
3380	THE WEIGHT LOSS SHALL BE NOT GREATER THAN 3380 PERCENT.
3382	THE MOISTURE ABSORPTION SHALL BE NOT GREATER THAN 3382 PERCENT.
4788	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4788.
3384	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORANCE WITH METHOD 7031 OF FED-STD-406.
3386	THE TEST SPECIMEN SHALL BE 3386 INCH(S) IN WIDTH.
3388	THE TEST SPECIMEN SHALL BE 3388 MILLIMETER(S) IN WIDTH.
3400	TEST SPECIMEN SHALL BE 3400 INCH(S) IN THICKNESS.
3402	THE TEST SPECIMEN SHALL BE 3402 MILLIMETER(S) IN THICKNESS.
3403	THE TEST SPECIMEN SHALL BE 3403 INCH(S) IN LENGTH.
3405	THE TEST SPECIMEN SHALL BE 3405 MILLIMETER(S) IN LENGTH.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Humidity (Cont)	
Per FED-STD-406, Method 7031. (Cont)	
Specimen diameter (select one)	
(inches)	3404
(millimeters)	3406
First specimen test media (name)	3408
First media temperature (degrees Celsius)	3410
First duration (select one)	
(hours)	3412
(days)	3414
(weeks)	3416
First tolerance, plus or minus (hours)	3418
First relative humidity (percent)	3420
Second test media (name)	3426
Second test media temperature (degrees Celsius)	3427

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3404	THE TEST SPECIMEN SHALL BE 3404 INCH(S) IN DIAMETER.
3406	THE TEST SPECIMEN SHALL BE 3406 MILLIMETER(S) IN DIAMETER.
3408	THE FIRST TEST MEDIA SHALL BE 3408.
3410	THE FIRST TEST MEDIA TEMPERATURE SHALL BE 3410 DEGREES CELSIUS.
3412	THE FIRST TEST DURATION SHALL BE 3412 HOUR(S).
3414	THE FIRST TEST DURATION SHALL BE 3414 DAY(S).
3416	THE FIRST TEST DURATION SHALL BE 3416 WEEK(S).
3418	THE FIRST TEST DURATION TOLERANCE SHALL BE PLUS OR MINUS 3418 HOUR(S).
3420	THE FIRST TEST RELATIVE HUMIDITY SHALL BE 3420 PERCENT.
3426	THE SECOND TEST MEDIA SHALL BE 3426.
3427	THE SECOND TEST MEDIA TEMPERATURE SHALL BE 3427 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Humidity (Cont)	
Per FED-STD-406, Method 7031. (Cont)	
Second duration (select one)	
(hours)	3428
(days)	3430
(weeks)	3432
Maximum duration before measurements (minutes)	3436
Hydrolytic Stability	
Requirements (select one)	
Per base document except ____	2566
No evidence of reversion, tackiness, flow, or softening.	2568
Minimum hardness reading (value)	2569
Test methods (select one)	
Per base document except ____	2524
Per document (doc des)	2526

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3428	THE SECOND TEST DURATION SHALL BE 3428 HOUR(S).
3430	THE SECOND TEST DURATION SHALL BE 3430 DAY(S).
3432	THE SECOND TEST DURATION SHALL BE 3432 WEEK(S).
3436	THE ELAPSED TIME BETWEEN IMMERSION AND HUMIDITY TEST SHALL BE NOT GREATER THAN 3436 MINUTE(S).
2566	HYDROLYTIC STABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2566.
2568	HYDROLYTIC STABILITY. THERE SHALL BE NOT EVIDENCE OF REVERSION, TACKINESS, FLOW, OR SOFTENING OF THE MATERIAL.
2569	THE HARDNESS SHALL BE NOT LESS THAN 2569.
2524	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2524.
2526	HYDROLYTIC STABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2526.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Hydrolytic Stability (Cont)	
Per document (Cont)	
Number of specimens to be tested (quantity)	2527
Specimen width (select one)	
(inches)	2532
(millimeters)	2534
Specimen thickness (select one)	
(inches)	2536
(millimeters)	2538
Specimen length (select one)	
(inches)	2528
(millimeters)	2530
Specimen diameter (select one)	
(inches)	2540
(millimeters)	2542
Test temperature (degrees Celsius)	2543
Tolerance, plus or minus (degrees Celsius)	2545

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2527	THERE SHALL BE 2527 SPECIMEN(S) TESTED.
2532	THE TEST SPECIMEN SHALL BE 2532 INCH(S) IN WIDTH.
2534	THE TEST SPECIMEN SHALL BE 2534 MILLIMETER(S) IN WIDTH.
2536	THE TEST SPECIMEN SHALL BE 2536 INCH(S) IN THICKNESS.
2538	THE TEST SPECIMEN SHALL BE 2538 MILLIMETER(S) IN THICKNESS.
2528	THE TEST SPECIMEN SHALL BE 2528 INCH(S) IN LENGTH.
2530	THE TEST SPECIMEN SHALL BE 2530 MILLIMETER(S) IN LENGTH.
2540	THE TEST SPECIMEN SHALL BE 2540 INCH(S) IN DIAMETER.
2542	THE TEST SPECIMEN SHALL BE 2542 MILLIMETER(S) IN DIAMETER.
2543	THE TEST TEMPERATURE SHALL BE 2543 DEGREES CELSIUS.
2545	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2545 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Hydrolytic Stability (Cont)	
Per Document (Cont)	
Duration of test (select one)	
(hours)	2550
Tolerance plus or minus (hours)	2551
(days)	2552
Tolerance plus or minus (hours)	2554
Test chamber cooling temperature (degrees Celsius)	2556
Tolerance plus or minus (degrees Celsius)	2558
Duration (select one)	
(minutes)	2562
(hours)	2560
Test relative humidity (percent)	2563
Tolerance, plus or minus (percent)	2567

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2550	THE TEST DURATION SHALL BE 2550 HOUR(S).
2551	THE TEST DURATION TOLERANCE SHALL BE PLUS OR MINUS 2551 HOUR(S).
2552	THE TEST DURATION SHALL BE 2552 DAY(S).
2554	THE TEST DURATION TOLERANCE SHALL BE PLUS OR MINUS 2554 HOUR(S).
2556	THE TEST CHAMBER SHALL BE COOLED TO 2556 DEGREES CELSIUS.
2558	THE COOLED TEST CHAMBER TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2558 DEGREES CELSIUS.
2562	THE TEST CHAMBER SHALL BE COOLED WITHIN 2562 MINUTE(S).
2560	THE TEST CHAMBER SHALL BE COOLED WITHIN 2560 HOUR(S).
2563	THE TEST RELATIVE HUMIDITY SHALL BE 2563 PERCENT.
2567	THE TEST RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2567 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Immersion	
Requirements (select one)	
Per base document except ____	4819
No evidence of physical damage.	4820
Per Immersion Table	3800
Test methods (select one)	
Per base document except ____	4809
Per document (doc des)	3443
Media-1 (name)	3442

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

4819 IMMERSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4819.

4820 IMMERSION. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.

3800 IMMERSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE IMMERSION TABLE.

IMMERSION TABLE

TEST	MEDIA-1	MEDIA-2	MEDIA-3	MEDIA-4
TENSILE STRENGTH MIN PSI	3801	3802	3803	3804
TENSILE STRENGTH MIN MPA	3805	3806	3807	3808
ULT. ELONGATION MIN PCT	3809	3810	3811	3812
TEAR STRENGTH MIN LB/IN	3813	3814	3815	3816
TEAR STRENGTH MIN N/M	3817	3818	3819	3820
PEEL STRENGTH MIN LB/IN	3821	3822	3823	3824
PEEL STRENGTH MIN N/M	3825	3826	3827	3828
DIELECTRIC STRENGTH V/MIL	3829	3830	3831	3832
DIELECTRIC STRENGTH V/MM	3833	3834	3835	3836
MAX DIMENSION CHANGE PCT	3837	3838	3839	3840

4809 IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4809.

3443 IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3443.

3442 MEDIA-1 SHALL BE 3442.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Immersion (Cont)	
Media-1 (Cont)	
Document (doc des)	3444
Type (des)	3446
Immersion duration (hour)	3448
Media temperature (degrees Celsius)	3450
Tolerance, plus or minus (degrees Celsius)	3452
Cooling duration at standard condition (select one)	
(minutes)	3456
(hours)	3458
Maximum duration before test (hours)	3460
Media-2 (name)	3462
Document (doc des)	3464
Type (des)	3466
Immersion duration (hours)	3468
Media temperature (degrees Celsius)	3470
Tolerance, plus or minus (degrees Celsius)	3472

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3444	MEDIA-1 SHALL BE IN ACCORDANCE WITH 3444.
3446	TYPE 3446 SHALL APPLY TO MEDIA-1.
3448	DURATION OF IMMERSION IN MEDIA-1 SHALL BE 3448 HOUR(S).
3450	MEDIA-1 TEMPERATURE SHALL BE 3450 DEGREES CELSIUS.
3452	MEDIA-1 TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3452 DEGREES CELSIUS.
3456	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3456 MINUTE(S).
3458	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3458 HOUR(S).
3460	THE DURATION FROM IMMERSION TO TEST SHALL BE NOT GREATER THAN 3460 HOUR(S).
3462	MEDIA-2 SHALL BE 3462.
3464	MEDIA-2 SHALL BE IN ACCORDANCE WITH 3464.
3466	TYPE 3466 SHALL APPLY TO MEDIA-2.
3468	DURATION OF IMMERSION IN MEDIA-2 SHALL BE 3468 HOUR(S).
3470	MEDIA-2 TEMPERATURE SHALL BE 3470 DEGREES CELSIUS.
3472	MEDIA-2 TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3472 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Immersion (Cont)	
Media-2 (Cont)	
Cooling duration at standard condition (select one)	
(minutes)	3476
(hours)	3478
Maximum duration before test (hours)	3480
Media-3 (name)	3482
Document (doc des)	3484
Type (des)	3486
Immersion duration (hours)	3488
Media temperature (degrees Celsius)	3490
Tolerance, plus or minus (degrees Celsius)	3492
Cooling duration at standard condition (select one)	
(minutes)	3496
(hours)	3498

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3476	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3476 MINUTE(S).
3478	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3478 HOUR(S).
3480	THE DURATION FROM IMMERSION TO TEST SHALL BE NOT GREATER THAN 3480 HOUR(S).
3482	MEDIA-3 SHALL BE 3482.
3484	MEDIA-3 SHALL BE IN ACCORDANCE WITH 3484.
3486	TYPE 3486 SHALL APPLY TO MEDIA-3.
3488	DURATION OF IMMERSION IN MEDIA-3 SHALL BE 3488 HOUR(S).
3490	MEDIA-3 TEMPERATURE SHALL BE 3490 DEGREES CELSIUS.
3492	MEDIA-3 TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3492 DEGREES CELSIUS.
3496	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3496 MINUTE(S).
3498	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3498 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Immersion (Cont)	
Media-3 (Cont)	
Maximum duration before test (hours)	3700
Media-4 (name)	3701
Document (doc des)	3703
Type (des)	3705
Immersion duration (hours)	3707
Media temperature (degrees Celsius)	3709
Tolerance, plus or minus (degrees Celsius)	3711
Cooling duration at standard conditions (select one)	
(minutes)	3715
(hours)	3717
Maximum duration before test (hours)	3719
Insulation Resistance	
Requirements (select one)	
Per base document except ____	1380

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3700	THE DURATION FROM IMMERSION TO TEST SHALL BE NOT GREATER THAN 3700 HOUR(S).
3701	MEDIA-4 SHALL BE 3701.
3703	MEDIA-4 SHALL BE IN ACCORDANCE WITH 3703.
3705	TYPE 3705 SHALL APPLY TO MEDIA-4.
3707	DURATION OF IMMERSION IN MEDIA-4 SHALL BE 3707 HOUR(S).
3709	MEDIA-4 TEMPERATURE SHALL BE 3709 DEGREES CELSIUS.
3711	MEDIA-4 TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3711 DEGREES CELSIUS.
3715	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3715 MINUTE(S).
3717	THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3717 HOUR(S).
3719	THE DURATION FROM IMMERSION TO TEST SHALL BE NOT GREATER THAN 3719 HOUR(S).
1380	INSULATION RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1380.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Insulation Resistance (Cont)	
Requirements (Cont)	
As follows:	6359
No evidence of physical damage.	1407
Minimum insulation resistance (megohms)	1386
Test methods (select one)	
Per base document except ____	1371
Per FED-STD-406, Method 4041.	2581
Number of specimens tested (quantity)	2583
Specimen width (select one)	
(inches)	2580
(millimeters)	2582
Specimen thickness (select one)	
(inches)	2584
(millimeters)	2586

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6359	INSULATION RESISTANCE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1407	THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
1386	INSULATION RESISTANCE AFTER TEST SHALL BE NOT LESS THAN 1386 MEGOHMS.
1371	INSULATION RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1371.
2581	INSULATION RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 4041 OF FED-STD-406.
2583	THERE SHALL BE 2583 SPECIMEN(S) TESTED.
2580	THE TEST SPECIMEN SHALL BE 2580 INCH(S) IN WIDTH.
2582	THE TEST SPECIMEN SHALL BE 2582 MILLIMETER(S) IN WIDTH.
2584	THE TEST SPECIMEN SHALL BE 2584 INCH(S) IN THICKNESS.
2586	THE TEST SPECIMEN SHALL BE 2586 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Insulation Resistance (Cont)	
Per FED-STD-406, Method 4041. (Cont)	
Specimen length (select one)	
(inches)	2588
(millimeters)	2590
Specimen diameter (select one)	
(inches)	2592
(millimeters)	2594
K Factor	
Requirements (select one)	
Per base document except ____	3732
K factor (number)	3734
Test methods (select one)	
Per base document except ____	3738
Per ASTMC177.	3740

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the currenversion before use.

CHAR CODE	STANDARD PARAGRAPH
2588	THE TEST SPECIMEN SHALL BE 2588 INCH(S) IN LENGTH.
2590	THE TEST SPECIMEN SHALL BE 2590 MILLIMETER(S) IN LENGTH.
2592	THE TEST SPECIMEN SHALL BE 2592 INCH(S) IN DIAMETER.
2594	THE TEST SPECIMEN SHALL BE 2594 MILLIMETER(S) IN DIAMETER.
3732	K FACTOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3732.
3734	K FACTOR. THE K FACTOR SHALL BE 3734.
3738	K FACTOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3738.
3740	K FACTOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMC177.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Nonvolatile Content	
Requirements (select one)	
Per base document except ____	2670
As follows:	2672
Minimum nonvolatile content (percent)	2674
Maximum nonvolatile content (percent)	2676
Maximum weight loss (select one)	
(ounces)	2677
(milligrams)	2679
Test methods (select one)	
Per base document except ____	2658
Per document (doc des)	2559
Compound test temperature (degrees Celsius)	2662
Tolerance, plus or minus (degrees Celsius)	2664
Duration (select one)	
(minutes)	2668
(hours)	2666

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2670	NONVOLATILE CONTENT. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2670.
2672	NONVOLATILE CONTENT. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2674	THE NONVOLATILE CONTENT SHALL BE NOT LESS THAN 2674 PERCENT.
2676	THE NONVOLATILE CONTENT SHALL BE NOT GREATER THAN 2676 PERCENT.
2677	THE WEIGHT LOSS SHALL BE NOT GREATER THAN 2677 OUNCE(S).
2679	THE WEIGHT LOSS SHALL BE NOT GREATER THAN 2679 MILLIGRAM(S).
2658	NONVOLATILE CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2658.
2559	NONVOLATILE CONTENT. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2559.
2662	THE COMPOUND TEST TEMPERATURE SHALL BE 2662 DEGREES CELSIUS.
2664	THE COMPOUND TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2664 DEGREES CELSIUS.
2668	THE TEST PERIOD SHALL BE 2668 MINUTE(S).
2666	THE TEST PERIOD SHALL BE 2666 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Oil and Solvent Resistance	
Requirements (select one)	
Per base document except ____	2709
No evidence of warping, splitting, or softening of material.	2711
Maximum dimension change (percent)	2713
Test methods (select one)	
Per base document except ____	2680
Per document (doc des)	2682
Media (select one)	
Per designated document.	2684
Per designated document except ____	2686
Exposed per document (doc des)	2690
Temperature (degrees Celsius)	2692
Duration (hours)	2694
Portion of solution (percent)	2696

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2709	OIL AND SOLVENT RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2709.
2711	OIL AND SOLVENT RESISTANCE. THERE SHALL BE NO EVIDENCE OF WARPING, SPLITTING, OR SOFTENING OF MATERIALS.
2713	OIL AND SOLVENT RESISTANCE. THE CHANGE IN ANY DIMENSION FROM INITIAL DIMENSION SHALL BE NOT GREATER THAN 2713 PERCENT.
2680	OIL AND SOLVENT RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2680.
2682	OIL AND SOLVENT RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2682.
2684	THE TEST MEDIA SHALL BE IN ACCORDANCE WITH THE TEST DOCUMENT.
2686	THE TEST MEDIA SHALL BE IN ACCORDANCE WITH THE TEST DOCUMENT EXCEPT 2686.
2690	THE TEST SPECIMEN SHALL BE EXPOSED TO OIL OR SOLVENT IN ACCORDANCE WITH 2690.
2692	THE TEST MEDIA TEMPERATURE SHALL BE 2692 DEGREES CELSIUS.
2694	THE DURATION OF EXPOSURE TO THE TEST MEDIA SHALL BE 2694 HOUR(S).
2696	THE PERCENTAGE OF THE TEST MEDIA IN A SOLUTION SHALL BE 2696 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Oil and Solvent Resistance (Cont)	
Per document (Cont)	
Exposed per document (doc des)	2698
Temperature (degrees Celsius)	2700
Duration (hours)	2702
Portion of solution (percent)	2704
Exposed per document (doc des)	2706
Temperature (degrees Celsius)	2708
Duration (hours)	2710
Portion of solution (percent)	2712
Number of specimens to be tested (quantity)	2715
Ozone Resistance	
Requirements (select one)	
Per base document except ____	2748
No cracking.	2750

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2698	THE TEST SPECIMEN SHALL BE EXPOSED TO OIL OR SOLVENT IN ACCORDANCE WITH 2698.
2700	THE TEST MEDIA TEMPERATURE SHALL BE 2700 DEGREES CELSIUS.
2702	THE DURATION OF THE EXPOSURE TO THE TEST MEDIA SHALL BE 2702 HOUR(S).
2704	THE PERCENTAGE OF THE TEST MEDIA IN THE SOLUTION SHALL BE 2704 PERCENT.
2706	THE TEST SPECIMEN SHALL BE EXPOSED TO OIL OR SOLVENT IN ACCORDANCE WITH 2706.
2708	THE TEST MEDIA TEMPERATURE SHALL BE 2708 DEGREES CELSIUS.
2710	THE DURATION OF THE EXPOSURE TO THE TEST MEDIA SHALL BE 2710 HOUR(S).
2712	THE PERCENTAGE OF THE TEST MEDIA IN THE SOLUTION SHALL BE 2712 PERCENT.
2715	THERE SHALL BE 2715 SPECIMEN(S) TESTED.
2748	OZONE RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2748.
2750	OZONE RESISTANCE. THERE SHALL BE NO EVIDENCE OF CRACKING.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Ozone Resistance (Cont)	
Test methods (select one)	
Per base document except ____	2716
Per ASTMD1149.	2717
Minimum ozone concentration by volumne (parts per 100 million)	2736
Ozone concentration temperature (degrees Celsius)	2738
Tolerance, plus or minus (degrees Celsius)	2740
Exposure duration (select one)	
(minutes)	2744
(hours)	2742
Peel Strength	
Requirements (select one)	
Per base document except ____	2743
As follows:	2745
Minimum peel strength, width (select one)	
(pounds/inch)	2747
(newtons/millimeter)	2749

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR. CODE	STANDARD PARAGRAPH
2716	OZONE RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2716.
2717	OZONE RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1149.
2736	THE OZONE CONCENTRATION SHALL BE NOT LESS THAN 2736 PARTS PER 100 MILLION BY VOLUME.
2738	THE OZONE CONCENTRATION TEMPERATURE SHALL BE 2738 DEGREES CELSIUS.
2740	THE OZONE CONCENTRATION TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2740 DEGREES CELSIUS.
2744	THE EXPOSURE DURATION SHALL BE 2744 MINUTE(S).
2742	THE EXPOSURE DURATION SHALL BE 2742 HOUR(S).
2743	PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2743.
2745	PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2747	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2747 POUND(S) PER INCH OF WIDTH.
2749	THE PEEL STRENGTH SHALL BE NOT LESS THAN 2749 NEWTON(S) PER MILLIMETER OF WIDTH.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Peel Strength (Cont)	
Test methods (select one)	
Per base document except ____	2762
Per document (doc des)	2764
Test specimen temperature (degrees Celsius)	2766
Tolerance, plus or minus (degrees Celsius)	2768
Porosity	
Requirements (select one)	
Per base document except ____	2772
Open cell porosity (percent)	2774
Tolerance (percent)	2776
Test methods (select one)	
Per base document except ____	2782
Per FED-STD-406, Method 5021.	2784

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
2762	PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2762.
2764	PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2764.
2766	THE TEST SPECIMEN TEMPERATURE SHALL BE 2766 DEGREES CELSIUS.
2768	THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2768 DEGREES CELSIUS.
2772	POROSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2772.
2774	POROSITY. THE OPEN CELL POROSITY SHALL BE 2774 PERCENT.
2776	THE TOLERANCE SHALL BE PLUS OR MINUS 2776 PERCENT.
2782	POROSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2782.
2784	POROSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 5021 OF FED-STD-406.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Pot Life	
Requirements (select one)	
Per base document except ____	2788
Minimum pot life (hours)	2790
Temperature (degrees Celsius)	2792
Free of cracks and bubbles.	2794
Proper mixing instruction by manufacturer.	2796
Test methods (select one)	
Per base document except ____	2801
Per ASTMD2471.	2803
Sample size (select one)	
(milliliters)	2805
(ounces)	2807
Shear Strength	
Requirements (select one)	
Per base document except ____	2811

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2788	POT LIFE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2788.
2790	POT LIFE. THE POT LIFE SHALL BE NOT LESS THAN 2790 HOUR(S).
2792	THE TEMPERATURE SHALL BE 2792 DEGREES CELSIUS.
2794	THE COMPOUND SHALL BE FREE OF CRACKS AND BUBBLES.
2796	PROPER MIXING INSTRUCTIONS SHALL BE FURNISHED BY THE MANUFACTURER.
2801	POT LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2801.
2803	POT LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD2471.
2805	SAMPLE SIZE SHALL BE 2805 MILLILITER(S).
2807	SAMPLE SIZE SHALL BE 2807 OUNCE(S).
2811	SHEAR STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2811.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Shear Strength (Cont)	
Requirements (Cont)	
As follows:	2812
Average shear strength (select one)	
(psi)	2813
(kilopascals)	2815
Test methods (select one)	
Per base document except ____	2822
Per ASTMD732.	2824
Test specimen temperature (degrees Celsius)	2826
Tolerance, plus or minus (degrees Celsius)	2828
Test relative humidity (percent)	2830
Tolerance, plus or minus (percent)	2832
Shelf/Storage Life	
Requirements (select one)	
Per base document except ____	2836

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE | STANDARD PARAGRAPH

2812 SHEAR STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

2813 THE MATERIAL SHALL HAVE AN AVERAGE SHEAR STRENGTH OF 2813 POUNDS PER SQUARE INCH.

2815 THE MATERIAL SHALL HAVE AN AVERAGE SHEAR STRENGTH OF 2815 KILOPASCAL(S).

2822 SHEAR STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2822.

2824 SHEAR STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD732.

2826 THE TEST SPECIMEN TEMPERATURE SHALL BE 2826 DEGREES CELSIUS.

2828 THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2828 DEGREES CELSIUS.

2830 THE TEST RELATIVE HUMIDITY SHALL BE 2830 PERCENT.

2832 THE TEST RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2832 PERCENT.

2836 SHELF/STORAGE LIFE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2836.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Shelf/Storage Life (Cont)	
Requirements (Cont)	
As follows:	2838
Maximum storage period (months)	2842
Storage temperature as specified.	2843
Manufacturer certification of material.	2844
Material shall conform to insulation resistance and dielectric strength.	2846
Material shall conform to viscosity and hardness.	2848
Test methods (select one)	
Per base document except ____	2852
Per document (doc des)	2854
Storage temperature as specified by manufacturer.	2856

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2838	SHELF/STORAGE LIFE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2842	THE STORAGE PERIOD SHALL BE NOT GREATER THAN 2842 MONTH(S).
2843	THE STORAGE TEMPERATURE SHALL BE AS SPECIFIED.
2844	THE MANUFACTURER SHALL CERTIFY THE MATERIAL MEETS ALL PHYSICAL AND ELECTRICAL REQUIREMENTS AT THE END OF THE SHELF LIFE.
2846	THE MATERIAL SHALL CONFORM TO THE INSULATION RESISTANCE AND DIELECTRIC STRENGTH REQUIREMENTS AT THE END OF THE SHELF LIFE.
2848	THE MATERIAL SHALL CONFORM TO THE VISCOSITY AND HARDNESS REQUIREMENTS AT THE END OF THE SHELF LIFE.
2852	SHELF/STORAGE LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2852.
2854	SHELF/STORAGE LIFE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2854.
2856	THE STORAGE TEMPERATURE SHALL BE AS SPECIFIED BY THE MANUFACTURER.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Shrinkage	
Requirements (select one)	
Per base document except ____	2859
Maximum shrinkage (percent)	2861
Test methods (select one)	
Per base document except ____	2865
Per MIL-M-81999.	2867
After cure specimen conditioning (degrees Celsius)	2869
Duration (hours)	2871
Volume calculated by water displacement method.	2873
Shrinkage calculation.	2875
Test relative humidity (percent)	2879
Tolerance, plus or minus (percent)	2881

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2859	SHRINKAGE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2859
2861	SHRINKAGE. THE SHRINKAGE SHALL NOT BE GREATER THAN 2861 PERCENT.
2865	SHRINKAGE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2865.
2867	SHRINKAGE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-M-81999.
2869	AFTER CURING THE SPECIMEN SHALL BE PLACED IN A CIRCULATING AIR OVEN AT 2869 DEGREES CELSIUS.
2871	THE DURATION SHALL BE 2871 HOUR(S).
2873	THE SPECIMEN SHALL BE REMOVED AND COOLED AND ITS VOLUME DETERMINED BY THE WATER DISPLACEMENT METHOD AT AMBIENT TEMPERATURE.
2875	THE PERCENT SHRINKAGE SHALL BE CALCULATED BY SUBTRACTING FINAL VOLUME OF MOLD DIVIDED BY VOLUME OF MOLD TIMES 100.
2879	THE RELATIVE HUMIDITY SHALL BE 2879 PERCENT.
2881	THE RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2881 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Tear Resistance	
Requirements (select one)	
Per base document except ____	2920
As follows: (select one)	2921
Minimum (pounds/inch of thickness)	2930
Minimum (newtons/millimeter of thickness)	2931
Test methods (select one)	
Per base document except ____	2902
Per document (doc des)	2904
Test methods (des)	2905
Die (letter)	2906
Test specimen conditioning period (hours)	2908
Condition temperature (degrees Celsius)	2910
Tolerance (degrees Celsius)	2912
Relative humidity (percent)	2914
Tolerance (percent)	2916

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2920	TEAR RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2920.
2921	TEAR RESISTANCE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2930	THE MATERIAL SHALL WITHSTAND A FORCE OF 2930 POUNDS PER INCH OF THICKNESS.
2931	THE MATERIAL SHALL WITHSTAND A FORCE OF 2931 NEWTON(S) PER MILLIMETER OF THICKNESS.
2902	TEAR RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2902.
2904	TEAR RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2904.
2905	TEST METHOD 2905 SHALL APPLY.
2906	DIE LETTER 2906 SHALL APPLY.
2908	CONDITIONING PERIOD SHALL BE 2908 HOUR(S).
2910	CONDITIONING TEMPERATURE SHALL BE 2910 DEGREES CELSIUS.
2912	CONDITIONING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2912 DEGREES CELSIUS.
2914	RELATIVE HUMIDITY SHALL BE 2914 PERCENT.
2916	RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2916 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Temperature, High	
Requirements (select one)	
Per base document except ____	6228
No evidence of physical damage.	6229
Minimum shore "A" hardness (no.)	3344
Minimum tensile strength (select one)	
(psi)	3340
(kilopascals)	3342
Test methods (select one)	
Per base document except ____	6217
As follows:	3346
Number of specimens to be tested (quantity)	3348
Specimen width (select one)	
(inches)	3350
(millimeters)	3352
Specimen thickness (select one)	
(inches)	3354
(millimeters)	3356

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6228	TEMPERATURE, HIGH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6228.
6229	TEMPERATURE, HIGH. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
3344	THE SHORE A HARDNESS SHALL BE NOT LESS THAN 3344.
3340	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 3340 POUNDS PER SQUARE INCH.
3342	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 3342 KILOPASCAL(S).
6217	TEMPERATURE, HIGH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6217.
3346	TEMPERATURE, HIGH. TESTING SHALL BE PERFORMED AS FOLLOWS:
3348	THERE SHALL BE 3348 SPECIMEN(S) TESTED.
3350	THE TEST SPECIMEN SHALL BE 3350 INCH(S) IN WIDTH.
3352	THE TEST SPECIMEN SHALL BE 3352 MILLIMETER(S) IN WIDTH.
3354	THE TEST SPECIMEN SHALL BE 3354 INCH(S) IN THICKNESS.
3356	THE TEST SPECIMEN SHALL BE 3356 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Temperature, High (Cont)	
As follows: (Cont)	
Specimen length (select one)	
(inches)	3358
(millimeters)	3360
Specimen diameter (select one)	
(inches)	3362
(millimeters)	3364
Test temperature (degrees Celsius)	3366
Tolerance plus or minus (degrees Celsius)	3368
Duration at high temperature (hours)	3370
Cooling temperature (degrees Celsius)	3372
Tolerance plus or minus (degrees Celsius)	3374
Cooling duration (select one)	
(minutes)	3378
(hours)	3376

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3358	THE TEST SPECIMEN SHALL BE 3358 INCH(S) IN LENGTH.
3360	THE TEST SPECIMEN SHALL BE 3360 MILLIMETER(S) IN LENGTH.
3362	THE TEST SPECIMEN SHALL BE 3362 INCH(S) IN DIAMETER.
3364	THE TEST SPECIMEN SHALL BE 3364 MILLIMETER(S) IN DIAMETER.
3366	THE TEST TEMPERATURE SHALL BE 3366 DEGREES CELSIUS.
3368	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3368 DEGREES CELSIUS.
3370	DURATION AT HIGH TEMPERATURE SHALL BE 3370 HOUR(S).
3372	THE COOLING TEMPERATURE SHALL BE 3372 DEGREES CELSIUS.
3374	THE COOLING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3374 DEGREES CELSIUS.
3378	COOLING DURATION SHALL BE 3378 MINUTE(S)
3376	COOLING DURATION SHALL BE 3376 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Temperature, Low	
Requirements (select one)	
Per base document except ____	6318
No evidence of physical damage.	6319
Test methods (select one)	
Per base document except ____	6231
Per document (doc des)	3742
Type (des)	3743
Number of specimens to be tested (quantity)	3746
Specimen width (select one)	
(inches)	3748
(millimeters)	3750
Specimen thickness (select one)	
(inches)	3752
(millimeters)	3754
Specimen length (select one)	
(inches)	3756
(millimeters)	3758

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6318	TEMPERATURE, LOW. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6318.
6319	TEMPERATURE, LOW. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
6231	TEMPERATURE, LOW. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6231.
3742	TEMPERATURE, LOW. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3742.
3743	TYPE 3743 SHALL APPLY.
3746	THERE SHALL BE 3746 SPECIMEN(S) TESTED.
3748	THE TEST SPECIMEN SHALL BE 3748 INCH(S) IN WIDTH.
3750	THE TEST SPECIMEN SHALL BE 3750 MILLIMETER(S) IN WIDTH.
3752	THE TEST SPECIMEN SHALL BE 3752 INCH(S) IN THICKNESS.
3754	THE TEST SPECIMEN SHALL BE 3754 MILLIMETER(S) IN THICKNESS.
3756	THE TEST SPECIMEN SHALL BE 3756 INCH(S) IN LENGTH.
3758	THE TEST SPECIMEN SHALL BE 3758 MILLIMETER(S) IN LENGTH.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3760	THE TEST SPECIMEN SHALL BE 3760 INCH(S) IN DIAMETER.
3762	THE TEST SPECIMEN SHALL BE 3762 MILLIMETER(S) IN DIAMETER.
3764	THERE SHALL BE 3764 TEST CYCLE(S).
3766	THE IMMERSION SOLUTION AFTER CURING SHALL BE 3766.
3768	THE DURATION OF IMMERSION SHALL BE 3768 HOUR(S).
3771	THE DURATION OF IMMERSION SHALL BE 3771 DAY(S).
3770	THE DURATION OF IMMERSION SHALL BE 3770 WEEK(S).
3772	THE DURATION OF IMMERSION TOLERANCE SHALL BE PLUS OR MINUS 3772 HOUR(S).
3774	THE CONDITIONING TEMPERATURE AFTER CURING SHALL BE 3774 DEGREES CELSIUS.
3776	THE CONDITIONING TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3776 DEGREES CELSIUS.
3778	THE TEMPERATURE DURATION SHALL BE 3778 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2988	TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2988.
2990	TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2992	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2992 POUNDS PER SQUARE INCH.
2994	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 2994 KILOPASCAL(S).
2974	TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2974.
2973	TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD412.
2984	THERE SHALL BE 2984 SPECIMEN(S) TESTED.
3600	THE TEST SPECIMEN SHALL BE 3600 INCH(S) IN WIDTH.
3601	THE TEST SPECIMEN SHALL BE 3601 MILLIMETER(S) IN WIDTH.
3603	THE TEST SPECIMEN SHALL BE 3603 INCH(S) IN THICKNESS.
3605	THE TEST SPECIMEN SHALL BE 3605 MILLIMETER(S) IN THICKNESS.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3607	THE TEST SPECIMEN SHALL BE 3607 INCH(S) IN LENGTH.
3609	THE TEST SPECIMEN SHALL BE 3609 MILLIMETER(S) IN LENGTH.
3611	THE TEST SPECIMEN SHALL BE 3611 INCH(S) IN DIAMETER.
3613	THE TEST SPECIMEN SHALL BE 3613 MILLIMETER(S) IN DIAMETER.
3614	THE TEST SPECIMEN TEMPERATURE SHALL BE 3614 DEGREES CELSIUS.
3615	THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3615 DEGREES CELSIUS.
3617	DIE LETTER 3617 OF ASTMD412 SHALL APPLY.
3038	ULTIMATE ELONGATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3038.
3040	ULTIMATE ELONGATION. THE ULTIMATE ELONGATION OF THE UNAGED SPECIMEN SHALL BE NOT LESS THAN 3040 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3028	ULTIMATE ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3028.
3024	ULTIMATE ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD412.
3020	THERE SHALL BE 3020 SPECIMEN(S) TESTED.
3022	THE TEST TEMPERATURE SHALL BE 3022 DEGREES CELSIUS.
3023	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3023 DEGREES CELSIUS.
3025	DIE LETTER 3025 OF ASTMD412 SHALL APPLY.
3062	VISCOSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3062.
3064	VISCOSITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
3066	THE MIXED MATERIAL EFFLUX PERIOD SHALL BE 3066 SECONDS.
3068	THE MIXED MATERIAL EFFLUX PERIOD TOLERANCE SHALL BE PLUS OR MINUS 3068 SECOND(S).
3070	THE MIXED MATERIAL FRICTION SHALL BE 3070 CENTIPOISES.
3072	THE MIXED MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3072 CENTIPOISE(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3074	THE MIXED MATERIAL FRICTION SHALL BE 3074 PASCALS PER SECOND.
3076	THE MIXED MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3076 PASCALS PER SECOND.
3078	THE BASE MATERIAL EFFLUX PERIOD SHALL BE 3078 SECONDS.
3080	THE BASE MATERIAL EFFLUX PERIOD TOLERANCE SHALL BE PLUS OR MINUS 3080 SECOND(S).
3082	THE BASE MATERIAL FRICTION SHALL BE 3082 CENTIPOISES.
3084	THE BASE MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3084 CENTIPOISE(S).
3086	THE BASE MATERIAL FRICTION SHALL BE 3086 PASCALS PER SECOND.
3090	THE BASE MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3090 PASCALS PER SECOND.
3092	THE EPOXY MATERIAL EFFLUX PERIOD SHALL BE 3092 SECONDS.
3094	THE EPOXY MATERIAL EFFLUX PERIOD TOLERANCE SHALL BE PLUS OR MINUS 3094 SECOND(S).

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3096	THE EPOXY MATERIAL FRICTION SHALL BE 3096 CENTIPOISES.
3098	THE EPOXY MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3098 CENTIPOISE(S).
3100	THE EPOXY MATERIAL FRICTION SHALL BE 3100 PASCALS PER SECOND.
3102	THE EPOXY MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3102 PASCAL(S) PER SECOND.
3104	THE THINNER MATERIAL EFFLUX PERIOD SHALL BE 3104 SECOND(S).
3106	THE THINNER MATERIAL EFFLUX PERIOD TOLERANCE SHALL BE PLUS OR MINUS 3106 SECOND(S).
3108	THE THINNER MATERIAL FRICTION SHALL BE 3108 CENTIPOISES.
3110	THE THINNER MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3110 CENTIPOISE(S).
3112	THE THINNER MATERIAL FRICTION SHALL BE 3112 PASCALS PER SECOND.
3114	THE THINNER MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3114 PASCAL(S) PER SECOND.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3118	THE INGREDIENT MATERIAL EFFLUX PERIOD SHALL BE 3118 SECONDS.
3120	THE INGREDIENT MATERIAL EFFLUX PERIOD TOLERANCE SHALL BE PLUS OR MINUS 3120 SECOND(S).
3122	THE INGREDIENT MATERIAL FRICTION SHALL BE 3122 CENTIPOISES.
3124	THE INGREDIENT MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3124 CENTIPOISE(S).
3126	THE INGREDIENT MATERIAL FRICTION SHALL BE 3126 PASCALS PER SECOND.
3128	THE INGREDIENT MATERIAL FRICTION TOLERANCE SHALL BE PLUS OR MINUS 3128 PASCAL(S) PER SECOND.
3044	VISCOSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3044.
3043	VISCOSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3043.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3050	THE TEST TEMPERATURE SHALL BE 3050 DEGREES CELSIUS.
3052	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3052 DEGREES CELSIUS.
3054	THE TEST RELATIVE HUMIDITY SHALL BE 3054 PERCENT.
3056	THE TEST RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 3056 PERCENT.
3176	VOLUME RESISTIVITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3176.
3178	VOLUME RESISTIVITY. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
3180	THE VOLUME RESISTIVITY AT THE INITIAL MEASUREMENT SHALL BE NOT LESS THAN 3180 OHM(S) PER INCH.
3182	THE VOLUME RESISTIVITY AT THE INITIAL MEASUREMENT SHALL BE NOT LESS THAN 3182 OHM(S) PER MILLIMETER.
3184	THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE NOT LESS THAN 3184 OHM(S) PER INCH.
3186	THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE 3186 OHM(S) PER MILLIMETER.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Volume Resistivity (Cont)	
Test methods (select one)	
Per base document except ____	3132
Per FED-STD-406, Method 4041.	3153
Number of specimens to be tested (quantity)	3154
Specimen width (select one)	
(inches)	3160
(millimeters)	3162
Specimen thickness (select one)	
(inches)	3164
(millimeters)	3166
Specimen length (select one)	
(inches)	3156
(millimeters)	3158
Specimen diameter (select one)	
(inches)	3168
(millimeters)	3170

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3132	VOLUME RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3132.
3153	VOLUME RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 4041 OF FED-STD-406.
3154	THERE SHALL BE 3154 SPECIMEN(S) TESTED.
3160	THE TEST SPECIMEN SHALL BE 3160 INCH(S) IN WIDTH.
3162	THE TEST SPECIMEN SHALL BE 3162 MILLIMETER(S) IN WIDTH.
3164	THE TEST SPECIMEN SHALL BE 3164 INCH(S) IN THICKNESS.
3166	THE TEST SPECIMEN SHALL BE 3166 MILLIMETER(S) IN THICKNESS.
3156	THE TEST SPECIMEN SHALL BE 3156 INCH(S) IN LENGTH.
3158	THE TEST SPECIMEN SHALL BE 3158 MILLIMETER(S) IN LENGTH.
3168	THE TEST SPECIMEN SHALL BE 3168 INCH(S) IN DIAMETER.
3170	THE TEST SPECIMEN SHALL BE 3170 MILLIMETER(S) IN DIAMETER.

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Volume Resistivity (Cont)	
Per FED-STD-406, Method 4041. (Cont)	
Test temperature (degrees Celsius)	3171
Tolerance, plus or minus (degrees Celsius)	3172
Conditioning period (select one)	
(hours)	3173
(days)	3175
Storage Conditions	
(years)	1529
Certify maximum cure date to delivery (quarters)	4942
Certify minimum shelf life after delivery (quarters)	4943
Certify maximum manufacture date to delivery (quarters)	4944
Age limitation per MIL-STD-1523.	5209

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3171	THE TEST TEMPERATURE SHALL BE 3171 DEGREES CELSIUS.
3172	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3172 DEGREES CELSIUS.
3173	THE CONDITIONING PERIOD SHALL BE 3173 HOUR(S).
3175	THE CONDITIONING PERIOD SHALL BE 3175 DAY(S).
	STORAGE CONDITIONS.
1529	ITEMS SHALL WITHSTAND 1529 YEARS OF STORAGE WHEN PROPERLY PRESERVED, PACKAGED AND MECHANICALLY PROTECTED WITHOUT REQUIRING MAJOR REPAIR.
4942	MANUFACTURER SHALL CERTIFY THAT THE CURE DATE SHALL BE NOT GREATER THAN 4942 QUARTERS PRIOR TO DELIVERY DATE.
4943	MANUFACTURER SHALL CERTIFY THAT THERE SHALL BE NOT LESS THAN 4943 QUARTERS OF SHELF LIFE AFTER DELIVERY.
4944	MANUFACTURER SHALL CERTIFY THAT THE DATE OF MANUFACTURE SHALL BE NOT GREATER THAN 4944 QUARTERS PRIOR TO DATE OF DELIVERY.
5209	AGE LIMITATIONS OF THE FINISHED PRODUCT SHALL BE IN ACCORDANCE WITH MIL-STD-1523.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
Additional Requirements	
A____	7001
B____	7002
C____	7003
D____	7004
E____	7005
Part Marking (Select One)	
(doc des)	6372
MIL-STD-1285.	7630
MIL-STD-130.	7629

Applicable Documents (See DOD-STD-35)

Quality Assurance Provisions (See DOD-STD-35)

Packaging (See DOD-STD-35)

Notes (See DOD-STD-35)

Nomenclature (See DOD-STD-35)

Superseded Document (See DOD-STD-35)

Part Number Cross-Reference (See DOD-STD-35)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
	ADDITIONAL REQUIREMENTS.
7001	(A) 7001.
7002	(B) 7002.
7003	(C) 7003.
7004	(D) 7004.
7005	(E) 7005.
6372	PART MARKING. PART IDENTIFICATION MARKING SHALL BE IN ACCORDANCE WITH 6372, USING THE PART NUMBER AS THE IDENTIFYING NUMBER.
7630	PART MARKING. PART IDENTIFICATION MARKING SHALL BE IN ACCORDANCE WITH MIL-STD-1285.
7629	PART MARKING. PART IDENTIFICATION MARKING SHALL BE IN ACCORDANCE WITH MIL-STD-130.

Custodians:
Army-MI

Review activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User activity:
Army-MU

Preparing activity:
Army-MI

(Project EDS-A209)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

APPENDIX A

CHARACTERISTIC CODE INDEX

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
0101	16	1708	26	1782	34	1932	36
0102	16	1710	28	1784	34	1934	36
0103	16	1712	28	1786	36	1936	38
0104	16	1714	28	1788	36	1938	38
0105	16	1716	28	1790	36	1940	36
0107	18	1718	28	1792	36	1942	38
0108	18	1720	28	1793	36	1943	38
0700	16	1721	30	1794	36	1944	50
0800	16	1725	30	1802	40	1946	50
1003	16	1726	24	1804	40	1948	50
1004	16	1727	24	1816	40	1949	50
1005	16	1728	26	1818	40	1951	50
1006	16	1729	30	1820	40	1952	42
1008	16	1730	26	1822	40	1953	50
1371	110	1731	30	1832	30	1954	42
1380	108	1732	26	1834	30	1955	50
1386	110	1733	30	1836	30	1957	50
1407	110	1734	26	1838	30	1958	42
1529	158	1735	30	1840	30	1959	50
1562	20	1736	26	1842	32	1960	42
1564	20	1737	28	1844	32	1961	50
1566	22	1738	26	1846	32	1964	46
1568	22	1739	28	1848	32	1966	46
1570	22	1742	36	1850	32	1968	46
1572	22	1744	36	1852	32	1970	46
1574	22	1752	38	1854	32	1971	46
1576	22	1754	38	1856	32	1973	46
1578	22	1755	38	1858	32	1974	46
1580	22	1756	38	1859	32	1976	46
1582	22	1758	38	1902	44	1982	46
1628	24	1764	40	1904	44	1984	48
1650	22	1766	40	1906	44	1986	48
1652	22	1770	34	1908	44	1988	48
1654	24	1771	34	1912	42	1989	48
1656	24	1772	34	1914	44	1991	48
1660	24	1774	34	1922	48	1992	48
1662	24	1776	34	1924	48	1994	48
1702	26	1777	34	1928	50	1996	48
1704	26	1778	34	1930	36	1998	48
1706	26	1779	34	1931	50	2002	54

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
2004	54	2114	68	2217	76	2320	84
2006	56	2116	68	2218	78	2321	84
2008	56	2118	68	2220	78	2322	86
2010	56	2120	70	2222	76	2323	84
2012	56	2122	70	2224	76	2324	86
2014	56	2123	70	2226	76	2325	86
2016	56	2124	70	2228	76	2326	86
2018	56	2126	70	2234	78	2328	86
2020	56	2128	70	2240	78	2332	82
2022	56	2130	70	2242	78	2334	82
2024	56	2132	70	2243	78	2336	82
2026	56	2134	70	2245	78	2338	82
2036	54	2136	70	2246	76	2340	82
2038	54	2138	72	2250	76	2342	82
2044	64	2140	72	2252	76	2344	82
2046	64	2142	72	2268	80	2346	82
2048	64	2152	66	2269	80	2352	52
2050	66	2154	66	2270	80	2353	52
2052	66	2156	68	2271	80	2354	52
2054	64	2158	68	2272	82	2356	52
2056	64	2160	68	2273	80	2358	52
2060	66	2164	72	2274	82	2360	52
2061	66	2166	72	2275	80	2364	52
2062	66	2168	74	2276	80	2366	52
2063	66	2170	74	2280	78	2368	52
2064	64	2172	74	2281	80	2370	52
2065	66	2174	74	2282	78	2372	52
2066	64	2176	74	2283	80	2374	52
2067	66	2177	74	2284	82	2376	52
2082	62	2178	74	2286	80	2378	54
2084	64	2180	74	2287	80	2380	54
2086	64	2182	74	2302	84	2382	54
2087	64	2184	74	2304	84	2384	54
2088	64	2202	72	2306	84	2386	54
2102	68	2204	72	2308	86	2434	88
2104	68	2206	72	2310	84	2436	88
2106	68	2208	72	2312	84	2442	88
2108	70	2210	72	2314	84	2444	90
2110	70	2214	76	2316	84	2445	90
2112	68	2216	76	2318	84	2446	90

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
2447	96	2580	114	2715	118	2830	126
2448	96	2581	114	2716	120	2832	126
2449	96	2582	114	2717	120	2836	126
2450	96	2583	114	2736	120	2838	128
2451	96	2584	114	2738	120	2842	128
2452	96	2586	114	2740	120	2843	128
2454	96	2588	112	2742	120	2844	128
2456	96	2590	112	2743	120	2846	128
2462	96	2592	112	2744	120	2848	128
2466	98	2594	112	2745	120	2852	128
2468	98	2658	114	2747	120	2854	128
2470	98	2662	114	2748	118	2856	128
2472	98	2664	114	2749	120	2859	130
2524	96	2666	114	2750	118	2861	130
2526	96	2668	114	2762	122	2865	130
2527	98	2670	114	2764	122	2867	130
2528	98	2672	114	2766	122	2869	130
2530	98	2674	114	2768	122	2871	130
2532	98	2676	114	2772	122	2873	130
2534	98	2677	114	2774	122	2875	130
2536	98	2679	114	2776	122	2879	130
2538	98	2680	116	2782	122	2881	130
2540	98	2682	116	2784	122	2902	132
2542	98	2684	116	2788	124	2904	132
2543	98	2686	116	2790	124	2905	132
2545	98	2690	116	2792	124	2906	132
2550	100	2692	116	2794	124	2908	132
2551	100	2694	116	2796	124	2910	132
2552	100	2696	116	2801	124	2912	132
2554	100	2698	118	2803	124	2914	132
2556	100	2700	118	2805	124	2916	132
2558	100	2702	118	2807	124	2920	132
2559	114	2704	118	2811	124	2921	132
2560	100	2706	118	2812	126	2930	132
2562	100	2708	118	2813	126	2931	132
2563	100	2709	116	2815	126	2973	142
2566	96	2710	118	2822	126	2974	142
2567	100	2711	116	2824	126	2984	142
2568	96	2712	118	2826	126	2988	142
2569	96	2713	116	2828	126	2990	142

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
2992	142	3112	150	3248	58	3366	136
2994	142	3114	150	3250	58	3370	136
3020	146	3118	152	3252	60	3372	136
3022	146	3120	152	3254	60	3374	136
3023	146	3122	152	3256	60	3376	136
3024	146	3124	152	3258	60	3378	136
3025	146	3126	152	3260	60	3380	92
3028	146	3128	152	3262	60	3381	92
3038	144	3132	156	3264	60	3382	92
3041	144	3153	156	3270	60	3384	92
3043	152	3154	156	3272	60	3386	92
3044	152	3156	156	3274	60	3388	92
3050	154	3158	156	3276	60	3400	92
3052	154	3160	156	3278	60	3402	92
3054	154	3162	156	3280	60	3403	92
3056	154	3164	156	3284	62	3404	94
3062	146	3166	156	3286	62	3405	92
3064	146	3168	156	3292	62	3406	94
3066	146	3170	156	3294	62	3408	94
3068	146	3171	158	3296	62	3410	94
3071	146	3172	158	3300	62	3412	94
3072	146	3173	158	3302	62	3414	94
3074	148	3175	158	3304	62	3416	94
3076	148	3176	154	3310	88	3418	94
3078	148	3178	154	3312	88	3420	94
3081	148	3180	154	3317	88	3426	94
3082	148	3182	154	3340	134	3427	94
3084	148	3184	154	3342	134	3428	96
3086	148	3186	154	3344	134	3430	96
3091	148	3222	56	3346	134	3432	96
3092	148	3224	58	3348	134	3436	96
3094	148	3226	58	3350	134	3442	102
3096	150	3228	58	3352	134	3443	102
3098	150	3230	58	3354	134	3444	104
3100	150	3232	58	3356	134	3446	104
3102	150	3238	58	3358	136	3448	104
3104	150	3240	58	3360	136	3450	104
3106	150	3242	58	3362	136	3452	104
3108	150	3244	58	3364	136	3456	104
3110	150	3246	58	3366	136	3458	104

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
3460	104	3734	112	3817	103	6228	134
3462	104	3738	112	3818	103	6229	134
3464	104	3740	112	3819	103	6231	138
3466	104	3742	138	3820	103	6318	138
3468	104	3743	138	3821	103	6319	138
3470	104	3746	138	3822	103	6359	110
3472	104	3748	138	3823	103	6369	16
3476	106	3750	138	3824	103	6372	160
3479	106	3752	138	3825	103	6375	20
3480	106	3754	138	3826	103	6715	
3482	106	3756	138	3827	103	THRU	
3484	106	3758	138	3828	103	6756	45
3486	106	3760	140	3829	103	6716	45
3488	106	3762	140	3830	103	6717	45
3490	106	3764	140	3831	103	6718	45
3492	106	3766	140	3832	103	6719	45
3496	106	3768	140	3833	103	6720	45
3498	106	3770	140	3834	103	6721	45
3600	142	3771	140	3835	103	6722	45
3601	142	3772	140	3836	103	6723	45
3603	142	3774	140	3837	103	6724	45
3605	142	3776	140	3838	103	6725	45
3607	144	3778	140	3839	103	6726	45
3609	144	3800	102	3840	103	6727	45
3611	144	3801	103	4754	88	6728	45
3613	144	3802	103	4756	88	6729	45
3614	144	3803	103	4760	86	6730	45
3615	144	3804	103	4761	86	6731	45
3617	144	3805	103	4762	86	6732	45
3703	108	3806	103	4788	92	6733	45
3701	108	3807	103	4798	92	6734	45
3703	108	3808	103	4809	102	6735	45
3705	108	3809	103	4819	102	6736	45
3707	108	3810	103	4823	102	6737	45
3709	108	3811	103	4942	158	6738	45
3711	108	3812	103	4943	158	6739	45
3715	108	3813	103	4944	158	6740	45
3717	108	3814	103	5048	20	6741	45
3719	108	3815	103	5209	158	6742	45
3732	112	3816	103	6217	134	6743	45

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX (CONT)

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
6744	45						
6745	45						
6746	45						
6747	45						
6748	45						
6749	45						
6750	45						
6751	45						
6752	45						
6753	45						
6754	45						
6755	45						
6756	45						
6873	16						
6874	18						
6941	18						
6942	18						
7001	160						
7002	160						
7003	160						
7004	160						
7005	160						
7301	20						
7302	20						
7629	160						
7630	160						

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

CONTENTS

	Page
Abrasion Resistance	30
Additional Requirements	160
Adhesion	34
Aperture Cards Required	18
Appearance	22
Applicable Documents	160
Base Document	16
Breaking Strength	40
Brittle Point	42
Chemical Composition	42
City, State, Zip	16
Class	20
Classification	20
Coefficient of Linear Expansion	46
Color	22
Company Name/Command	16
Composition	20
Compression Set	48
Compression Strength	52
Contract Number/Office Symbol	16
Control Source	16
Control Specification	18
Corrosion	54
Curing	56
Date	16
Density/Specific Gravity	62
Design and Construction	22
Dielectric Constant	62
Dielectric Strength	66
Dissipation Factor	72
Drying	76
Elongation	78
Flammability	82
Format	16
Fungus	86
Government Design Activity FSCM	16

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX (CONT)

	Page
Hardness	88
Humidity	92
Hydrolytic Stability	96
Immersion	102
Insulation Resistance	108
K Factor	112
Materials	20
Mixing Ratio	24
Nomenclature	160
Nonvolatile Content	114
Notes	160
Oil and Solvent Resistance	116
Ozone Resistance	118
Packaging	160
Part Marking	160
Part Number	18
Part Number Cross-Reference	160
Particle Size	22
Peel Strength	120
Phone Number	16
Porosity	122
Pot Life	124
Quality Assurance Provisions	160
Requester FSCM	16
Requester's Name	16
Revision of AEDPS Document (Number)	18
Rise Time	22
Scope	18
Shear Strength	124
Shelf/Storage Life	126
Shrinkage	130
Solids Content	22
Source Table	18
Storage Conditions	158
Street/Building	18

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

INDEX (CONT)

	Page
Superseded Document	160
System Application	16
Tabulated Characteristics	20
Tack-Free Time	24
Tear Resistance	132
Temperature, High	134
Temperature, Low	138
Temperature Rating	20
Tensile Strength	142
Test Specimen Preparation	24
Toxicity	24
Type	20
Ultimate Elongation	144
Units of Measure	18
Viscosity	146
Volume Resistivity	154

*U.S. GOVERNMENT PRINTING OFFICE: 1991--504-034/50111

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

The digital copy of DOD-STD-35-116 (MI), dated 07 Jul 1978 does not include the foldout pages for the Specification Requirement Sheet (SRS). Please call ASSIST SERVICE DESK at 215-737-8000 for copies of these pages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

The digital copy of DOD-STD-35-116 (MI), dated 07 Jul 1978 does not include the foldout pages for the Specification Requirement Sheet (SRS). Please call ASSIST SERVICE DESK at 215-737-8000 for copies of these pages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
DOD-STD-35-116	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:24Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander,
U.S. Army Missile R & D Command
ATTN: DRDMI-ESD
Redstone Arsenal, Alabama 35809

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:24Z
Check the source to verify that this is the current version before use.