This document has been approved for public release and sale; its distribution is unlimited

MILITARY STANDARD

COMMON LONG HAUL AND TACTICAL

COMMUNICATION SYSTEM TECHNICAL STANDARDS

TO ALL HOLDERS OF MIL-STD-188-100

1. THE FOLLOWING PAGES OF MIL-STD-188-100 HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
xviii	16 July 1975	xviii	15 November 1972
159	16 July 1975	159	15 November 1972
160	16 July 1975	160	15 November 1972

2. THE FOLLOWING PAGES ARE TO BE ADDED:

NEW PAGES	DATE
161 - 186	16 July 1975

3. Holders of MIL-STD-188-100 will verify that page changes and additions indicated above have been entered. Pages 159 through 186 are to be inserted after Appendix F. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - EL
Navy - EC
Air Force - 17

Preparing Activity:
Army - SC
(Project SLHC-0041-2)

Review Activities:
Army - SC, EL, CE, ME
Navy - AS, OS, YD, MC, CG, SH
Air Force - 1, 11, 13, 71, 80, 89

User Activities:
Army - SC, EL
Navy - MC, YD, SH
Air Force

Other Interest:
JCS - J6
NSA - NS
TRI-TAC

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (Continued)

Paragraph		Page
5.8.3	Line Relay Characteristics	157
5.8.3.1	Electromechanical Polar Relays	157
5.8.3.1.1	Side Stable	157
5.8.3.1.2	Operating Differential	157
5.8.3.1.3	Distortion	157
5.8.3.1.4	Winding Current	157
5.8.3.1.5	Winding DC Resistance	157
5.8.3.1.6	Winding Reactance	157
5.8.3.1.7	Contact Material	157
5.8.3.1.8	International Octal Base Pin Connections	157
5.8.3.2	Electronic Polar Relays	158
5.8.3.2.1	Side Stable	158
5.8.3.2.2	Operating Differential	158
5.8.3.2.3	Modulation Rates	158
5.8.3.2.4	Distortion	158
5.8.3.2.5	Winding Current	158
5.8.3.2.6	Winding DC Resistance	158
5.8.3.2.7	Winding Reactance	158
5.8.3.2.8	Output Characteristics	158
5.8.3.2.9	Contacts	158
5.8.3.2.10	International Octal Base Pin Connections	158
5.8.4	Optical Character Recognition Equipment	158
	Index	159

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

INDEX

A PAGE

ABSOLUTE ENVELOPE DELAY, DEFINITION E-2
ACKNOWLEDGE (ACK) B-5
ACOUSTICAL/ELECTRICAL CONVERSION, TELEPHONE 140
  Four-Wire Instrument 143
  Two-Wire Instrument 140
ACTIVITY FACTOR 63, 75
ADMINISTRATION TRAFFIC 9
AMERICAN STANDARD CODE FOR INFORMATION INTERCHANGE . . . 24, B-1ff
AMPLIFICATION 10
AMPLITUDE HITS 45, 48
AMPLITUDE MODULATION 144, 147, A-2, A-4
AMPLITUDE VS. FREQUENCY CHARACTERISTIC (See Also Insertion Loss vs. Frequency Characteristic)
  Four-Wire Telephone Instrument 143
  Two-Wire Telephone Instrument 140
ANALOG SERVICE 10ff
  Facsimile 21
  Quasi-Analog 10
  Voice-Data Channels
    Nominal 3-kHz Bandwidth 58
    Nominal 4-kHz Bandwidth 61
    Nominal 48-kHz FDM Group Bandwidth 67
ANALOG SIGNALS 10ff, 139
APPROXIMATE ERROR 89
ARMATURE, ELECTROMECHANICAL RELAY 158
ASCII 22ff, B-1ff
  Dualcase, OCRE C-2
  Monocase, OCRE B-7ff, C-2
ASYNCHRONOUS DATA COMMUNICATION B-8
ATTENUATION, CROSSTALK D-23
ATTENUATOR
  Calibrated D-6
  Switched D-3
  Variable D-16
AUDIO FREQUENCY DISPLACEMENT 10
AUTODIN 44, 68, 107, B-9, B-15
AUTOMATIC-REQUEST-REPEAT (ARQ) 44
AUTOVON 53, 68, 107, 130

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

B

PAGE

BACKSPACE (BS) B-5
BALANCED LOW LEVEL DIGITAL INTERFACE 30ff, 35
BANDWIDTH, CONDITIONED VOICE 48ff
BANDWIDTH, NECESSARY A-4
BASIC NOISE D-10
BAUD 22ff
BEL B-5
BENCHMARK, OCRE C-4
BETWEEN-CIRCUIT CROSSTALK D-23
BINARY DECODER 138
BINARY ENCODER 135
BINARY SYNCHRONOUS SIGNAL SYSTEMS 22
BIT SEQUENCE, STANDARD, ASCII, FIPS B-9
BIT SEQUENCING, FIPS B-9
BIT STEPPED CONTROL 156
BIT SYNCHRONOUS 11, 34, 156
BIT TRANSMISSION, OCRE C-1
BIT-BY-BIT ASYNCHRONOUS 35
BIT-TO-CHANNEL RELATIONSHIP, STANDARD B-10
BREAK PERIOD 131
BUFFER STORAGE C-1

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:27Z
Check the source to verify that this is the current version before use.

C

PAGE

CABLE 13, 107, 141, D-23
  Coaxial 25
CANCEL (CAN) B-6
CAPACITANCE, SHUNT 28
CARBON TISSUE, FACSIMILE 149
CARRIAGE RETURN (CR) B-5
CARRIER LEAK 75
CARRIER OSCILLATOR D-7
CENTER-ZERO DECIBELMETER D-3
CHANNEL CHARACTERISTICS 58ff, 98
  Nominal 3-kHz Voice Bandwidth 58ff
  Nominal 4-kHz Voice Bandwidth 61ff
  Nominal 48-kHz Voice Bandwidth 67ff
CHANNEL
  Description 51ff
  Multiplexing
    FDM (Group-Supermastergroup) 11
    TDM 11
  Nominal 3-kHz Voice Bandwidth Channel 58ff
  Nominal 4-kHz Voice Bandwidth Channel 61ff
  Nominal 48-kHz FDM Group Bandwidth Channel 67ff
    Data Service 49
CHARACTER
  Interval Synchronous 35
  Parity B-9
  Parity Bit B-7ff, B-10
  Reading Rate, OCRE C-1
  Recognition, Optical 158
  Regenerator B-8
  Representation B-1
  Set Capabilities, OCRE C-2
  Stepped Control by Character 156
  Structure and Parity Sense
    Parallel-by-Bit Communication B-9
    Serial-by-Bit Communication B-7
  Structure, Standard Character B-10
CIRCUIT 51
  Data Grade (Conditioned Voice Bandwidth Circuits) . . . 48
  Full-Duplex 44
  Hybrid 17, 88, 91
  Neutral 32
  Polar 32
  Voice Grade (Facsimile) 21

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

PAGE

CIRCUIT NOISE AND SINGLE TONE INTERFERENCE,
TEST DESCRIPTION D-10
CIRCUIT, REFERENCE 99
CIRCUITRY, EQUIVALENT 158
CLOCK: EQUIPMENT, MASTER, STATION 34
Transmission Modes 34
Bit Synchronous 11, 34
Bit-by-Bit Asynchronous 35
Facsimile Meteorological Receiver 146
Facsimile Meteorological Receiver (Large Format) . 149
Facsimile Meteorological Receiver (Small Format) . 151
Gated Clock 35, 42ff
Paper Tape 156
Slewed Clock 35
Character Interval Synchronous 35
CLOCK CHARACTERISTICS 35ff
CLOCK/DATA PHASE RELATIONSHIP 36ff
Arrangement, Standard 41
CODE FOR INFORMATION EXCHANGE C-1
CODE FOR INFORMATION INTERCHANGE B-1ff
CODE, INTERIM 25, 151
CODED CHARACTER SET, STANDARD B-1
CODED SUBSETS B-10ff
CODER LEVEL 92
COINCIDENT SELECTION, PAPER TAPE READERS 152
COMMON CONTROL SYSTEM 131
COMMUNICATION CONTROL (CC) B-4
COMMUNICATION SYSTEMS 9
Configuration 15
Long Haul 9
Tactical 9, 15
COMPANDOR 90
CONDITIONING 56, 68
CONTACTS, ELECTROMECHANICAL RELAY 158
CONTACTS, PROTECTION OF 33
CONTROL CHARACTERS, OCRE B-4ff
CONTROL AND SUPERVISION, TELEPHONE 141
CONVERSION TECHNIQUES, ANALOG TO DIGITAL 11
CONVERTER, CABLE INTERFACE 89
CROSSBAR SYSTEM 131
CROSSTALK
Low Level Digital Interface 25
TDM/PCM Reference Voice Bandwidth Link,
Long Haul/Tactical 98
Voice Service 17
CROSSTALK, TEST DESCRIPTION D-22ff

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

D

PAGE

DATA COMMUNICATION
  Asynchronous B-8
  Conditioning, Voice Circuit 56
  Loading, Quasi-Analog 75
  Synchronous B-7
DATA GRADE CIRCUIT 48
DATA LEVEL, QUASI-ANALOG 64
DATA LINK ESCAPE (DLE) B-6
DATA REFERENCE TERMINALS AND CIRCUITS 51
DATA SERVICE
  Digital Parameters 21ff
  Quasi-Analog Parameters 48ff
    Nominal 4-kHz Voice Bandwidth Channel 61, 64
    Nominal 48-kHz FDM Group Bandwidth Channel 49, 67
    Unconditioned Voice Bandwidth Circuits 45
    Voice Frequency Carrier Telegraph 132
DEAD SECTOR
  Receiver, Meteorological Facsimile (Large Format) . . 148
  Receiver, Meteorological Facsimile (Small Format) . . 150
  Transmitter, Meteorological Facsimile 145
DECODER, BINARY 138
DELETE (DEL) B-7
DEVICE CONTROLS (DC1-DC4) B-6
DIBIT 135
DIFFERENTIAL PHASE SHIFT KEYING (150 b/s - 9,600 b/s) . . 134ff
DIFFERENTIAL PCM 12
DIGITAL SERVICE
  Binary System 10, 21ff
  Channel Parameters 68
  Clock Characteristics 35ff
  Clock/Data Phase Relationship 36ff
  End Instruments 151
  Error Rates 44
  High Level Interface 31
  Interface, DC 51
  Loop, Single 53, 58
  Low Level Interface, Balanced 25, 30
  Low Level Interface, Unbalanced 25, 27
  Minimum Interdigital Period 131
  Modem Location 53
  Modem Subsystem 134
  Modulation Rate 23
  Monitoring 44
  Parameters for Signals 10, 21
  Pulse Code Modulation 12

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:27Z
Check the source to verify that this is the current version before use.

DIGITAL SERVICE (con.) PAGE

Quaternary System 10
Signaling Rate 23
Single TDM/PCM Reference Voice Bandwidth Characteristic 88
DIMENSIONAL FIDELITY, FACSIMILE 145
DIMENSIONAL STABILITY, FACSIMILE 148
DIRECT CONTROL, CLOCK 36
DISPLAY
Analog D-2
Comparison Digital D-3
Direct-Reading Digital D-3
Null Digital D-3
Scale and Pointer D-2
Spectrum Analyzer CRT D-12
DISTORTION, BIAS, CYCLIC, CHARACTERISTIC, FORTUITOUS . . 43
DISTORTION, DELAY, DEFINITION E-1
DISTORTION, ENVELOPE DELAY
Definition E-3
Conditioned Voice Bandwidth Circuits, Data 49
Facsimile Service 21
Loop, Single, Analog Service 55
Loop, Single, Data Service over Conditioned Voice Bandwidth Circuit 58
Loop, Single, Data Service over Unconditioned Voice Bandwidth Circuit 56
Nominal 3-kHz Voice Bandwidth Channel 61
Nominal 4-kHz Voice Bandwidth Channel 65
Nominal 48-kHz FDM Group Bandwidth Channel 68
Single FDM Reference Modulation Bandwidth Link 86
Single TDM/PCM Reference Voice Bandwidth Link 94
Transfer Characteristics of Reference Links in Tandem. 99
Unconditioned Voice Bandwidth Circuits 46
Voice Service 17
DISTORTION, ENVELOPE DELAY, TEST DESCRIPTION D-7
DISTORTION, GROSS START-STOP 155, B-9
DISTORTION, HARMONIC
Conditioned Voice Bandwidth Circuits 49
Long Haul TDM/PCM Reference Voice Bandwidth Link . . . 97
Nominal 3-kHz Voice Bandwidth Channel 61
Nominal 4-kHz Voice Bandwidth Channel 65
Standard Test Signal 62
Tactical TDM/PCM Reference Voice Bandwidth Link . . . 97
Telephone Instrument, Four-Wire 144
Telephone Instrument, Two-Wire 143
Unconditioned Voice Bandwidth Circuits 46

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

PAGE

DISTORTION, HARMONIC, TEST DESCRIPTION D-16
DISTORTION, INTERMODULATION
  Conditioned Voice Bandwidth Circuits 49
  Long Haul TDM/PCM Reference Voice Bandwidth Link . . . 97
  Nominal 3-kHz Voice Bandwidth Channel 61
  Nominal 4-kHz Voice Bandwidth Channel 65
  Tactical TDM/PCM Reference Voice Bandwidth Link . . . 97
  Unconditioned Voice Bandwidth Circuits 46
DISTORTION, ISOCHRONOUS 135, 138
DISTORTION, LINE RELAY
  Relays, Electromechanical Polar 157
  Relays, Electronic Polar 158
  Voice Frequency Carrier Telegraph 133
DISTORTION, NON-LINEAR PCM 91
DISTORTION, OUTPUT 155
DISTORTION, SIGNAL A-4
DISTORTION, START/STOP 155, B-9
DISTORTION, TELETYPEWRITER TRANSMITTER 155ff
DRIVER, LOW LEVEL DIGITAL INTERFACE 25, 27ff
  Balanced 30ff
  Unbalanced 27ff
DROPOUTS 45
  Conditioned Voice Bandwidth Circuits 48
  Pulse Modulation Transmission 12
  Unconditioned Voice Bandwidth Circuits 45
DUALCASE ASCII, OCRE C-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

E	PAGE
EARTH RETURN	44
EBCDIC CARD CODE	B-24
ECHO	17, D-27
ELECTROMECHANICAL POLAR RELAY	157
ELECTROMECHANICAL RECEIVING DEVICE	155
ELECTRONIC-INPUT RECEIVING DEVICE	155
ELECTRONIC POLAR RELAY	158
EMISSIONS	
Classifications	A-1
Examples of	A-2ff
ENCODER, BINARY	135
END INSTRUMENTS, ANALOG	15, 139
Facsimile, General Purpose	151
Facsimile, Meteorological	144
Telephone, Four-Wire	143
Telephone, Two-Wire	140
END INSTRUMENTS, DIGITAL	15, 151ff
END OF MEDIUM (EM)	B-6
END OF TEXT (ETX)	B-5
END OF TRANSMISSION (EOT)	B-5
END OF TRANSMISSION BLOCK (ETB)	B-6
ENQUIRY (ENQ)	B-5
EQUALIZATION EQUIPMENT	58
ERASE SYMBOL, OCRE	C-5
ERROR	
Approximation	89
Calibration	D-2
Equipment	D-2
Human	D-2
Measurement	D-1
ERROR RATES, DIGITAL	44
ESCAPE (ESC)	B-6
EXTRANEOUS INK AREAS, OCRE	C-3

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

F PAGE

FACSIMILE EQUIPMENT, GENERAL PURPOSE 151
FACSIMILE EQUIPMENT, METEOROLOGICAL
  Receiver, Large Format 147
  Receiver, Small Format 149
  Transmitter 144
FACSIMILE SERVICE 21ff, 45, 55, 98, A-2ff, A-4
FADING 13
FALL TIME 27
FEDERAL INFORMATION PROCESSING STANDARDS (FIPS) 24, B-1ff
FONT C-2
FORM FEED (FF) B-5
FORMAT EFFECTOR (FE) B-4
FOUR-WIRE INSTRUMENTS 143ff
FRAME BIT 91
  Voice Frequency Carrier Telegraph 132
  Voice Frequency Test Methods D-4
FRAME SYNCHRONIZATION 91
FREQUENCY
  Amplitude vs. Frequency Characteristics 140, 143
  Center Frequency 132
  Counter D-20
  Displacement 21
  FDM Subsystems 70, 132
  Filter Attenuator 53
  Insertion Loss (See Insertion Loss vs. Frequency Characteristic) D-6
  Instantaneous Frequency A-4
  Long Term Stability 135
  Mark Frequency 133
  Modulation 147
  Selective Voltmeter (FSVM) D-10
  Shift Keying Frequency Modulation 44, 132, 144, A-2
  Single FDM Reference Modulation Links 70
  Single Tone Interference D-10
  Space Frequency 133
  Tolerance 133
  Translation, Test Description D-20
  Variable Carrier Frequency D-7
FREQUENCY DISPLACEMENT
  Conditioned Voice Bandwidth Circuits 49
  Facsimile Service 21
  Nominal 3-kHz Voice Bandwidth Channel 61
  Nominal 4-kHz Voice Bandwidth Channel 65

Source: https://assist.dla.mil -- Downloaded: 202640-26T07:27Z
Check the source to verify that this is the current version before use.

FREQUENCY DISPLACEMENT (con.) PAGE

Unconditioned Voice Bandwidth Circuits 48
Voice Grade Circuits 21
FREQUENCY DIVISION MULTIPLEX SUBSYSTEMS 132
Characteristics, Single FDM Reference
Modulation Links 70
Frequency Translation D-20ff
Harmonic Distortion D-16
Noise Power 59, 64, 99ff
Voice Frequency Carrier Telegraph 132
3-kHz (Wideband, HF Radio) 132
4-kHz 132
FREQUENCY TRANSLATION, TEST DESCRIPTION D-20

G

GAUSSIAN (NORMAL) DISTRIBUTION, SPEECH VOLUME 16
GRAPHIC CHARACTERS B-7
GRILLE, TONE RINGER 143
GROUP, FDM 11, 67ff
GROUP DISTRIBUTION FRAME (GDF) 67ff
GROUP PILOT, STANDARD 67

H

HALFTONE CHARACTERISTIC 146
HARMONIC DISTORTION (See Distortion, Harmonic)
HIGH LEVEL DIGITAL INTERFACE 31ff
HORIZONTAL TABULATION (HT) B-5
HUM, LOW-FREQUENCY D-10
HYPOTHETICAL TACTICAL LESS MANEUVERABLE REFERENCE
SYSTEM, 1,000 NAUTICAL MILES 15

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

I PAGE

IMPEDANCE
Loop, Single, Analog Service 55
Loop, Single, Data Service over Conditioned Voice Bandwidth Circuits 58
Loop, Single, Data Service over Unconditioned Voice Bandwidth Circuits 56
Telephone Instrument, Four-Wire 143
Telephone Instrument, Two-Wire 140
Voice 17
IMPEDANCE BRIDGE D-24
IMPEDANCE, HIGH BRIDGING D-14
IMPEDANCE MATCHING
Error D-1
Transformer D-17
IMPEDANCE, TEST DESCRIPTION D-24
IMPULSE COUNTER D-14
INDEX OF COOPERATION
Receiver, Meteorological Facsimile (Large Format) . . 148
Receiver, Meteorological Facsimile (Small Format) . . 150
Transmitter, Meteorological Facsimile 145
INFORMATION SEPARATOR (IS) B-4
INSERTION LOSS, TEST DESCRIPTION D-4ff
INSERTION LOSS VS. FREQUENCY CHARACTERISTIC (See Also Amplitude vs. Frequency Characteristic)
Conditioned Voice Bandwidth Circuits 49
Facsimile Service 21
Loop, Single, Analog Service 55
Loop, Single, Data Service over Conditioned Voice Bandwidth Circuit 58
Loop, Single, Data Service over Unconditioned Voice Bandwidth Circuit 56
Metallic Lines 13
Nominal 3-kHz Voice Bandwidth Channel 59
Nominal 4-kHz Voice Bandwidth Channel 65
Nominal 48-kHz FDM Group Bandwidth Channel 68
Single FDM Reference Modulation Link 82
Single TDM/PCM Reference Voice Bandwidth Link 94
Transfer Characteristics of Reference Links in Tandem 99
Unconditioned Voice Bandwidth Circuits 46
Voice Service 17
INTERCHARACTER INTERVAL B-8
INTERDIGITAL PERIOD, MINIMUM 131
INTERFACE 111ff
Clock/Digital 25

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

INTERFACE (con.) PAGE

Low Level Digital 25ff, 151
Reference Circuits 111ff
INTERFERENCE, SINGLE TONE
Conditioned Voice Bandwidth Circuits, Data Service . . 49
Facsimile Service 21
Nominal 3-kHz Voice Bandwidth Channel 61
Nominal 4-kHz Voice Bandwidth Channel 65
Unconditioned Voice Bandwidth Circuits, Data Service . 48
Voice Service 17
INTERNATIONAL OCTAL BASE PIN CONNECTION
Relays, Electromechanical Polar 157
Relays, Electronic Polar 158
INTERNATIONAL TELEGRAPH ALPHABET (ITA) B-24

K

KEYBOARD ARRANGEMENTS, TELEGRAPH B-24
KEYBOARD, TELETYPEWRITER 152

L

LACING, PUNCHED CARDS B-15
LEVEL ALIGNMENT 62
LEVEL-LENS INSTRUMENT D-3
LEVEL MEASURING SET D-16ff
LEVEL REGULATION, AUTOMATIC 141
LINE ADVANCE
Receiver, Meteorological Facsimile (Large Format) . . 148
Receiver, Meteorological Facsimile (Small Format) . . 150
Transmitter, Meteorological Facsimile 145
LINE FEED (LF) 156, B-5
LINE RELAY CHARACTERISTICS
Electromechanical Polar 157
Electronic Polar 158
LINK 12, 51, 62ff, 68, 88
Satellite Transmission 88, 91, 97

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

LINK (con.) PAGE

Single FDM Reference Modulation 70
Envelope Delay Distortion 86
Input/Output Impedances 81
Insertion Loss vs. Frequency Characteristic 82ff
Loading 74
Net Loss Variation 86
Noise 77ff
Test Signal Levels, Standard 77
Type I 70
Type II 70
Single TDM/PCM Reference Voice Bandwidth Link 88
Crosstalk 98
Envelope Delay Distortion 94
Input/Output Impedances 93
Input/Output Linearity 93
Insertion Loss vs. Frequency Characteristic 94
Intermodulation Distortion 97
Multiplex Signal Characteristic 90ff
Net Loss Variation 98
Noise 92
Equivalent PCM 93
Idle Channel 92
Test Signal-to-Quantizing Noise Ratio 92
Test Signal Frequency, Standard 91
Test Signal Levels, Standard 91
Total Harmonic Distortion 97
Submarine Cable Links 58, 70
Transfer Characteristics of Reference Links in Tandem 98
LOADING
Coils 56
Data/Voice 74ff
LOGICAL AND SIGNAL SENSE FOR BINARY SIGNALS 33
LONG HAUL COMMUNICATIONS 15
LONG HAUL/TACTICAL SYSTEMS 9
LONG TERM FREQUENCY STABILITY 135
LONGITUDINAL BALANCE, TEST DESCRIPTION D-30
LONGITUDINAL CURRENTS 59, 65ff, 81, 93, 133ff, 148, D-30
LOOP CHARACTERISTICS 48ff, 51
Analog 53
Digital 53, 98, 107ff, 128ff

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

PAGE

LOOP LOSS 21, 119ff
LOOP LOSS PADS 55
LOOP, SINGLE, FOR ANALOG SERVICE 53ff
LOOP, SINGLE FOR DATA SERVICE OVER CONDITIONED
VOICE BANDWIDTH CIRCUIT 56ff
LOOP, SINGLE, FOR DATA SERVICE OVER UNCONDITIONED
VOICE BANDWIDTH CIRCUIT 56
LOOP, SINGLE, FOR DATA SERVICE OVER NOMINAL 48-KHZ
FDM GROUP BANDWIDTH CIRCUITS 58
LOOP, SINGLE FOR DIGITAL SERVICE 58
LOOP, UNPROTECTED 56
LOW LEVEL DIGITAL INTERFACE 25

M

MARKING
  Element B-8
  Frequency 133
  Stylus 150
  Voltage 27ff
MASTER CLOCK 34
MASTERGROUP 11
MATCHING/ISOLATION TRANSFORMER D-27
MEASUREMENT
  Comparison D-6
  Direct Reading D-5
MEASUREMENT ACCURACY D-1ff
MEASURING APPARATUS D-4ff
MESSAGE COMPONENT SYMBOLIZATION, OCRE C-4
METALLIC
  Circuit 45, 59, 64
  Circuit Current D-30
  Lines 13, 25
METEOROLOGICAL FACSIMILE EQUIPMENT (See Facsimile)
MICROPHONE POWER, TELEPHONE 141
MICROWAVE RADIO 13
MODEM 22, 25, 45ff, 134ff

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

PAGE

MODULATION A-2ff
Amplitude 144, 147, A-2, A-4
Companding 90
Delta Modulation 12
Digital Data Modem Subsystem 134
Distortion, Intermodulation 97
Distortion, Non-Linear PCM 91
Frame Synchronization (PCM) 91
Frequency 147
Frequency Shift Modulation
Meteorological Facsimile Equipment 144
VFCT 132
Modem 22, 25, 45ff, 134ff
Modulation Rate Accuracy 155
Modulation Rate, OCRE C-1
Modulation Rate, Standard Clock 35
Multilevel (M-ary) 22, 48
Noise, Equivalent PCM 90
Pulse Amplitude 11, 88ff
Pulse Code 12, 62, 88ff, 98, D-14
Pulse Duration 11
Pulse Position 12
Signaling Rates 23
Single FDM Reference Modulation Link 70
Single TDM/PCM Reference Voice Bandwidth 88
TDM/PCM Subsystems 134
MODULO-2 ADDER 135, 138
MONITORING, DIGITAL DATA 44
MULTIPATH EFFECTS, DELAY 10
MULTIPLEXING 59, 70, 100ff, 132ff, 139
Frequency Division (FDM) 11
Noise 77ff
Pulse Transmission 11
Space Division (SDM) 11
Time Division (TDM) 11, 88ff, 98ff

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

N

PAGE

NEAR-END CROSSTALK D-22
NEGATIVE ACKNOWLEDGE (NAK) B-6
NET LOSS 130
NET LOSS VARIATION
  Conditioned Voice Bandwidth Circuits 49
  Facsimile Service 21
  Loop, Single, Analog Service 56
  Loop, Single, Data Service over Conditioned
  Voice Bandwidth Circuit 58
  Loop, Single, Data Service over Unconditioned
  Voice Bandwidth Circuit 56
  Nominal 3-kHz Voice Bandwidth Channel 61
  Nominal 4-kHz Voice Bandwidth Channel 65
  Nominal 48-kHz Voice Bandwidth Channel 68
  Single FDM Reference Modulation Link 86
  Single TDM/PCM Reference Voice Bandwidth Link 98
  Unconditioned Voice Bandwidth Circuits 48
  Voice Service 21
NETWORK, COMMUNICATION 9
NEW LINE (NL) B-5
NODE 51
NOISE
  All Year Median 98
  Basic D-10
  Circuit 15, 55, 67
  Equivalent PCM 90ff
  FDM Connection 100
  Generator 90
  Idle Channel (PCM) 89, 92
  Impulse 10, 13, 45,
  D-14
  Longitudinal 31
  Multiplex 77ff
  Nonimpulse Circuit 45, 59, 64
  Proration (Allocation) 99
  Quantizing 89
  Thermal 10, 89, 92,
  D-14
  Uniform Spectrum Random D-23
  Worst Hour Median 98
NOMINAL 3-KHZ VOICE BANDWIDTH CHANNEL 58
  Channel Input/Output Impedances 59
  Channel Input Levels 59
  Channel Output Levels 59
  Envelope Delay Distortion 61

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

NOMINAL 3-KHZ VOICE BANDWIDTH CHANNEL (con.) PAGE

Frequency Displacement 61
Insertion Loss vs. Frequency Characteristic 59
Intermodulation Distortion 61
Net Loss Variation 61
Signal Discontinuities 61
Single Tone Interference 61
Submarine Cable Links 58
Total Harmonic Distortion 61
NOMINAL 4-KHZ VOICE BANDWIDTH CHANNEL 61
Channel Input/Output Impedances 65
Channel Input Levels 61ff
Channel Output Levels 64
Envelope Delay Distortion 65
Frequency Displacement 65
Insertion Loss vs. Frequency Characteristic 65
Intermodulation Distortion 65
Net Loss Variation 65
Signal Discontinuities 65
Single Tone Interference 65
Total Harmonic Distortion 65
NOMINAL 48-KHZ FDM GROUP BANDWIDTH CHANNEL 67
Channel Input/Output Impedances 67
Channel Input Levels 67
Channel Output Levels 67
Data Service 49
Envelope Delay Distortion 68
Group Pilot, Standard 67
Impulse Noise 68
Insertion Loss vs. Frequency Characteristic 68
Net Loss Variation 68
NONLINEARITY D-16
NONREACTIVE SERIES, INSERTION 44
NONREACTIVE TAP 44
NULL B-4
NYQUIST RATE 11

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

O

PAGE

OFF-SET ZERO INSTRUMENT D-3
OPERATING DIFFERENTIAL
  Relay, Electromechanical Polar 157
  Relay, Electronic Polar 158
OPTICAL CHARACTER RECOGNITION EQUIPMENT (OCRE) 151, C-1ff
  Benchmark C-4
  Bit Transmission C-1
  Character Reading Rate C-1
  Character Set Capabilities C-2
  Dualcase ASCII C-2
  Erase Symbol C-5
  Extraneous Ink Areas C-3
  Font C-2
  Message Component Symbolization C-4
  Modulation Rate C-1
  Monocase ASCII C-2
  Multiple Character Set C-2
  Off-line C-1
  On-line C-1
  Orientation Symbol C-4
  Paper Specifications C-4
  Parity C-1
  Print Contrast Signal (PCS) C-3
  Print Quality C-3
  Scanning Rate C-1
  Signaling, Low Level C-1
  Single Character Set C-2
  Stroke Width Variation C-3
  Typewriters C-3
OSCILLATOR, STABLE . . . . . D-2(
OVERSEAS AUTOVON NETWORK SWITCHING PLAN 107

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

P

PAGE

PAPER FEED 152
PAPER LINE FEED OPERATION 155
PAPER SPECIFICATIONS, OCRE C-4
PAPER TAPE 156
PAPER TAPE READER 152
PARALLEL-BY-BIT B-9
PARITY B-9
  Character B-9, B-10
  Character Bit B-7
  OCRE C-1
PERIOD
  Clock 36
  Minimum Interdigital 131
PHASE
  Angle D-21
  Comparator D-7
  Delay, Definition E-1
  Flux Reversal 34
  Hits 45, 48
  Jitter Meter D-21
  Shift Line Signal 135
  Shifter D-8
PHASE JITTER, TEST DESCRIPTION D-20
PHASE MODULATION D-21
PHASE-SHIFT CHARACTERISTIC, NONLINEAR E-1
PHASING SIGNAL 146
PHOTOSENSITIVE TECHNIQUE 152
PHOTO-SURFACE RMA S-4 144
PILOT, STANDARD GROUP 67
PRESSURE SENSITIVE RECORDING TECHNIQUE 148
PRINT CONTRAST SIGNAL, OCRE C-3
PRINT QUALITY, OCRE C-3
PRINTING EQUIPMENT, PAGE 152
PRINTING SUBSETS B-11ff
PROPAGATION 139, D-26
PULSE DURATION A-4
PULSE MODULATION A-3, A-7
  Amplitude 11, 88ff
  Code 12, 62, 88ff, 98, D-14
  Duration 11
  Position 12
PULSE TRAIN, INTERLEAVED 11
PUNCH, PAPER TAPE 152

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

PAGE

PUNCHED CARD CODE, STANDARD B-15

Q

QUADRIPOLE D-6
QUANTIZATION 12, 89
QUASI-ANALOG SERVICE 10, 15, 22, 45ff, 48ff, 51, 61, 67, 75

R

RADIO SUBSYSTEMS
  Below HF (MF, LF, VLF, ILF, ELF) 13
  HF 13, 139
  Relay Subsystems 13
    LOS Radio Relay 70, 139
    Satellite Relay 139
    Submarine Cable 70
    Tropospheric Scatter 139
RECEIVED NOISE POWER 17
RECEIVER, METEOROLOGICAL FACSIMILE (LARGE FORMAT) . . . 147ff
RECEIVER, METEOROLOGICAL FACSIMILE (SMALL FORMAT) . . . 149
RECEIVING DEVICES, DISTORTION TOLERANCE
  Electromechanical 155
  Electronic-Input 155
RECORDING ON MAGNETIC TAPE 34
  Non Return to Zero 34
  Phase Encoded 34
RECORDING METEOROLOGICAL FACSIMILE 148ff
RECORDING SPOT SIZE, FACSIMILE 150
RECTIFIER D-14
REFERENCE CARRIER D-9
REFERENCE CIRCUIT EXAMPLES 99
  AUTODIN Long Haul/Tactical Connection 107
  AUTOVON Long Haul/Tactical Connection w/AUTOVON
  Four-Wire Instrument in Tactical Area 107

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

REFERENCE CIRCUIT EXAMPLES (con.) PAGE

AUTOVON Long Haul/Tactical Connection w/Two-Wire Switches at Both Terminations 107
Long Haul/Tactical Highly Maneuverable FDM Connection 103
Long Haul/Tactical Highly Maneuverable FDM-TDM/PCM Connection 105
Long Haul/Tactical Less Maneuverable FDM Connection . 100
Long Haul/Tactical Less Maneuverable FDM-TDM/PCM Connection 100
Noise Proration 99
REFERENCE MODULATION LINKS 68
Single FDM Reference Modulation Links 70ff
Single TDM/PCM Reference Voice Bandwidth Link 88ff
REGENERATION 10ff, 45, 49ff, 67ff, 89, 98, 138
REGULATION, AUTOMATIC LEVEL 141
REJECTION FILTER D-17
RELATIVE ENVELOPE DELAY, DEFINITION E-2
RELAY, ELECTROMECHANICAL POLAR 157
RELAY, ELECTRONIC POLAR 158
RELAY, MERCURY-WETTED MECHANICAL 27
RELAY, RADIO TRANSMISSION
Communication Satellite 139
Line of Sight (LOS) 70, 139
Submarine Cable 70
Tropospheric Scatter Radio 70
RESISTOR, CHANNEL TERMINATING D-23
RETURN LOSS, TEST DESCRIPTION D-26
RINGING, FOUR-WIRE TELEPHONE 143
RINGING, TWO-WIRE TELEPHONE 141
RISE TIME 27
ROOT-SUM-SQUARE LAW 99

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

S

PAGE

SAMPLING, CENTER 41
SATELLITE TRANSMISSION LINKS 88ff, 91, 97

SCANNER, FACSIMILE
  Continuous (Flat Bed) 144
  Drum 144
SCANNING, METEOROLOGICAL FACSIMILE 145
SCANNING RATE, OCRE C-1
SELECTIVE LEVEL MEASURING SET D-16ff
SEPARATORS (CONTROL CHARACTERS), OCRE B-6
SEQUENTIAL SELECTION, PAPER TAPE READERS 152
SERIAL 22, 135
SERIAL-BY-BIT B-7
SHIFT IN (SI) B-6
SHIFT OUT (SO) B-6
SHIFT REGISTER, TWO-BIT 135
SIDETONE COUPLING LOSS 140
SIGNAL/CROSSTALK RATIO D-23
SIGNAL/DISCONTINUITIES 12
  Conditioned Voice Bandwidth Circuits 49
  Nominal 3-kHz Voice Bandwidth Channel 61
  Nominal 4-kHz Voice Bandwidth Channel 65
  Unconditioned Voice Bandwidth Circuits 46
SIGNAL ELEMENT 10
SIGNAL, ISOCHRONOUS 22
SIGNALING
  Binary DC 21ff
  Dial Pulse, Low, High Speed 131
  Dual Tone Multifrequency (DTMF) 130
  Low Level C-1
  Neutral 44
  Polar 44
SIGNAL MODE (Analog, Digital, Quasi-Analog) 10
SIGNAL PATHS, DIGITAL DATA 44
SIGNAL, PRECEDENCE 130
SIGNAL, SYNCHRONOUS DIFFERENTIALLY COHERENT
QUATERNARY PHASE SHIFT KEYED 135
SINGING D-27
SINGLE FDM REFERENCE MODULATION LINK 70
  Envelope Delay Distortion 86
  Insertion Loss vs. Frequency Characteristic 82
  Link Input/Output Impedances 81
  Loading, Data Quasi-Analog 75
  Loading, Voice, Analog 74
  Net Loss Variation 86
  Noise, Multiplex-Group Bandwidth 80

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

SINGLE FDM REFERENCE MODULATION LINK (con.) PAGE

Noise, Multiplex-Voice Bandwidth 77
Noise, Transmission Media 80
Type I 70
Type II 70
SINGLE TDM/PCM REFERENCE VOICE BANDWIDTH LINK 88
Compandor Characteristics 90
Crosstalk 98
Envelope Delay Distortion 94
Frame Synchronization 91
Insertion Loss vs. Frequency Characteristic 94
Intermodulation Distortion 97
Link Input/Output Impedances 93
Link Input/Output Linearity 93
Multiplex Signal Characteristics 90
Net Loss Variation 98
Noise
Equivalent PCM 90, 93, 105
Idle Channel 92
Quantizing 90
Test Signal-to-Quantizing Noise Ratio 92
Thermal 90
SINGLE TONE INTERFERENCE (See Interference)
SINK 25ff, 36
SOLID STATE 158
SOURCE 25ff, 36
SPACE (SP) B-7
SPACING ELEMENT B-8
SPECTRAL SENSITIVITY 144
STANDARD CODE FOR INFORMATION INTERCHANGE 24, B-1ff
START OF HEADING (SOH) B-4
START OF TEXT (STX) B-5
START-STOP SYSTEMS 22, 151
STEP-BY-STEP SYSTEM 131
STRAY COUPLING D-24
SUBSCRIBER LINES 130
SUBSTITUTE (SUB) B-6
SUBSYSTEM STANDARDS AND DESIGN OBJECTIVES 132
SUMMATION METHODS 58, 61, 65, 98ff, 128
SUPERGROUP 11, 67ff
SUPERMASTERGROUP 11

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

T

PAGE

TACTICAL/LONG HAUL SYSTEMS 9, 15
TALKER VOLUME DISTRIBUTION 16
TDM/PCM SUBSYSTEMS 88ff, 98ff, 134, D-20
TECHNICAL CONTROL FACILITY (TCF) 53, 74, 100, 119
TELEGRAPH KEYBOARD ARRANGEMENTS B-24
TELEGRAPHY A-2ff, A-4ff
TELEPHONE INSTRUMENTS, FOUR-WIRE 143ff
TELEPHONE INSTRUMENTS, TWO-WIRE 140ff
TELEPHONY A-2ff, D-30
TELETYPEWRITER CODED CHARACTER SET, FIVE UNIT B-15
TELETYPEWRITER EQUIPMENT, PERFORMANCE CHARACTERISTICS . 155ff
TELETYPEWRITER EQUIPMENT, RECORDING MEDIA 156
TELEVISION A-2ff
TERMINATING IMPEDANCE D-14
TERMINATOR 27ff
TEST METHODS D-1ff
TEST SIGNAL, STANDARD (Nominal 4-kHz Voice Bandwidth Channel) 62
TEST SIGNAL, STANDARD (TDM/PCM Reference Voice Bandwidth Link) 91
TEST TONE, MONITORING 63
TEST TONE, STANDARD 62, 111
THERMAL NOISE 10, 89, 92, D-14
THRESHOLD DETECTOR D-14
THROUGHPUT 44
TIME DELAY E-1
TIME DIVISION MULTIPLEXING 11, 88ff, 98ff
TONES, SINGLE FREQUENCY D-10
TRAFFIC TYPES 9
TRANSFER TISSUE 148
TRANSFORMER
  Center-Tapped D-31
  Hybrid 53ff, D-29
  Impedance Matching D-17
  Matching/Isolation D-27
TRANSIENTS 13, 158, D-14, D-30
TRANSMISSION
  Cable 36
  Circuits 51, 53
  Media 12

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

TRANSMISSION (con.) PAGE

Modes, Clock Timing 34ff
Wideband 82
TRANSMISSION LEVEL POINT (TLP) 45, 55ff, 77, 92ff, 111ff
TRANSMITTER, METEOROLOGICAL FACSIMILE 144ff
TRUNK 51, 55, 99, 130
TWO-TERMINAL PAIR NETWORK D-4
TWO-WIRE INSTRUMENTS 140ff
TYPEWRITERS, OCRE C-3

U

UNBALANCED LOW LEVEL DIGITAL INTERFACE 27ff, 35
UNCONDITIONED VOICE BANDWIDTH CIRCUITS 45ff
USER-TO-USER CHARACTERISTICS BASED ON HYPOTHETICAL REFERENCE CIRCUIT EXAMPLES 107
Calculation of Hypothetical Envelope Delay Distortion 128
Calculation of Hypothetical Insertion Loss vs. Frequency Characteristic 128
Calculation of Hypothetical Net Loss Variation 129
Calculation of Hypothetical Noise Power 119
Long Haul/Tactical Highly Maneuverable Four-Wire Reference Circuit 111
Long Haul/Tactical Highly Maneuverable Two-Wire Reference Circuit 112
Long Haul/Tactical Less Maneuverable Four-Wire Reference Circuit 112
Long Haul/Tactical Less Maneuverable Two-Wire Reference Circuit 119
Tactical Less Maneuverable/Tactical Highly Maneuverable Four-Wire Reference Circuit 119
Tactical Less Maneuverable/Tactical Highly Maneuverable Two-Wire Reference Circuit 119

Source: https://assist.dla.mil -- Downloaded: 202610-26T07:27Z
Check the source to verify that this is the current version before use.

V

PAGE

VARIABLE CARRIER FREQUENCY D-7
VERTICAL TABULATION (VT) B-5
VESTIGIAL SIDEBAND TRANSMISSION 147
VOICE CHANNEL 75, D-22
  Net Loss Design 130
  Network Standards 129
  Nominal 3-kHz Bandwidth 58
  Nominal 4-kHz Bandwidth 61
  Nominal 48-kHz FDM Group 67
VOICE CIRCUIT FOR DATA SERVICE
  Conditioned 48
  Unconditioned 45
VOICE/EAR SUBJECTIVE TEST D-24
VOICE FREQUENCY CARRIER TELEGRAPH (VFCT) 132
VOICE FREQUENCY TEST METHODS D-4
  Circuit Noise and Single Tone Interference D-10
  Crosstalk D-22
  Envelope Delay Distortion D-7
  Frequency Translation D-20
  Harmonic Distortion D-16
  Impedance D-24
  Impulse Noise D-14
  Insertion Loss D-4
  Longitudinal Balance D-30
  Phase Jitter D-20
  Return Loss D-26
VOICE SERVICE 16, 55, 63, 70ff, 88ff, 98
  Crosstalk 17
  Echo 17
  Envelope Delay Distortion 17
  Frequency Displacement 21
  Insertion Loss vs. Frequency Characteristic 17
  Net Loss Variation 17
  Nominal 3-kHz Voice Bandwidth Channel 58ff
  Nominal 4-kHz Voice Bandwidth Channel 61ff
  Nominal 48-kHz FDM Group Bandwidth Channel 67ff
  Received Noise Power 17
  Single Tone Interference 17
  Speech Volume 16
VOLTAGE
  Marking 27ff
  Spacing 27ff
  Transient 30

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

PAGE

VOLTMETER
  Frequency Selective (FSVM) D-10
  True RMS D-10
VOLUME UNITS (VU) 16, 112

W

WAVE SHAPE 27, 32
WEIGHTING
  C-Message 92, 98, D-10ff
  F1A 98, D-10ff
  Flat 93
  Psophometric D-10ff
WHO ARE YOU (WRU) B-5
WIDEBAND TRANSMISSION 82, 132
WINDING CURRENT
  Relays, Electromechanical Polar 157
  Relays, Electronic Polar 158
WINDING DC RESISTANCE
  Relays, Electromechanical Polar 157
  Relays, Electronic Polar 158
WINDING REACTANCE, ELECTRONIC POLAR RELAY 158
WIRE TRANSMISSION SUBSYSTEMS 139

Z

ZERO LOSS CHANNEL 64

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 17

Review Activities:
Army - SC, EL
Navy - AS, OS, YD, MC, CG, SH
Air Force - 1, 11, 13, 71, 80, 89

User Activities:
Army - SC, EL
Navy - MC, YD, SH
Air Force

Preparing Activity:
DCA - DC
Army - EL

Other Interests:
JCS - J6
NSA - NS
TRI-TAC

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T07:27Z
Check the source to verify that this is the current version before use.