MIL-B-10746D
20 July 1970
SUPERSEDING
MIL-B-0010746C(MU)
11 September 1964, and
MIL-B-10746B
7 December 1955

MILITARY SPECIFICATION

BOMB, SMOKE, 100-LB; AN-M47A4, WP FILLING

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the WP loading and assembly of the AN-M47A4 100-lb smoke and incendiary bombs without fuzing components.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL14-5-883 - Bomb, Smoke, 100-lb., AN-M47A4 (W/O Burster, Fuze, Wire).

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1325

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:23Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL14-5-883 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the item shall conform to the specifications and drawings listed on Drawing DL14-5-883.

3.2 Cleaning before filling. All bombs shall be cleaned prior to filling.

3.3 Filling. When examined in accordance with 4.2.4, a 3 to 5 percent void of total volume shall exist above the surface of the water over the WP. The bomb shall be in the filling-end-up position, and the WP at a temperature of 130° ± 10° F (see 6.2). The depth of water on the surface of the WP shall not exceed 1/4 inch.

3.4 Cleaning after closing. The exterior surface of the bomb and the interior of the burster casing shall be cleaned thoroughly to remove any grease, oil, agent, or other contamination.

3.5 Leakage. The bomb shall not leak when maintained at a temperature of 207° to 212° F for a minimum period of 15 minutes and tested in accordance with 4.2.4.3. Alternate method: The bomb shall not leak when maintained at a temperature of 160° ± 5° F for a minimum period of 8 hours, and tested in accordance with 4.2.4.3.

3.6 Workmanship. The bomb assembly shall be free from contamination (foreign matter) and damage which could impair its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:23Z
Check the source to verify that this is the current version before use.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1, 3.2, and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in any one interfix number of bombs, no more than one interfix number from one manufacturer of the following components is permitted:

(a) Bomb body.
(b) Burster well.
(c) WP.

4.2.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure.

4.2.3.1 For examination. Sample bombs and the preparation for delivery shall be examined in accordance with the classification of defects and MIL-STD-105.

4.2.3.2 For critical defects. Each bomb shall be inspected for critical characteristics listed in the classification of defects.

4.2.3.3 Classification of defects.

(a) Bomb, Smoke, AN-M47A4 (W/O Burster, Fuze and Wire) (Dwg C14-5-883).

Categories	Defects	Acceptance standards
Critical:		
1	Leakage	4.2.4.3
2	Agent contamination	4.2.4.2
Major:	AQL 1.0 percent defective	
101	Component missing	
102	Component incorrectly assembled	
103	Filling height excessive	
104	Excessive water	4.2.4.1
105	Marking incorrect	
106	Workmanship (3.6)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:23Z
Check the source to verify that this is the current version before use.

4.2.3.3 Classification of defects (continued).

(a) Bomb, Smoke, AN-M47A4 (W/O Burster, Fuze and Wire) (Dwg C14-5-883) (continued).

Categories	Defects	Acceptance standards
Minor:	AQL 2.5 percent defective	
201	Marking illegible	
202	Grease missing (threads)	

(b) Preparation for delivery.

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Loose pack
102	Closure incorrect
103	Strapping loose

4.2.4 Tests.

4.2.4.1 Filling, WP. The depth of water shall be determined radiographically with the bomb oriented in a nose-up position.

4.2.4.2 Decontamination. Decontamination shall be determined by a method approved by the Government.

4.2.4.3 Leakage. The bomb shall be placed in an oven in a vertical filling-end-up position or laid horizontally for the 207° to 212° F method. For the alternate 160° ± 5° F method, the bomb shall be placed in a filling-end-down position or laid horizontally. It shall be maintained at the specified temperature for the required period of time.

5. PREPARATION FOR DELIVERY

5.1 Packing level A. The bombs shall be packed in accordance with Drawing D14-17-270.

5.2 Marking. In addition to any special marking in conjunction with information furnished in the contract or order, boxes shall be marked in accordance with Drawing D14-5-2826.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:23Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified in the contract or order (mandatory for level A shipment) the bombs, packed in accordance with 5.1, shall be palletized and the pallet load marked in accordance with Drawing D14-5-2827.

6. NOTES

6.1 Ordering data. Procurement documents should specify the title, number, and date of this specification.

6.2 Precaution. Because of the hazardous nature of filling munitions with chemical agents, filling installations are advised to take all necessary precautions to protect personnel from injury while filling bombs.

6.3 Component specifications. The following specifications reflect the components required for the completion of the AN-M47A4, Bomb:

MIL-C-215	-	Chemical Agent, White Phosphorus (WP)
MIL-B-0013393	-	Bomb, Incendiary or Smoke, AN-M47A4, 100-Pound Inert Components
MIL-A-10982	-	Arming Wire Assemblies
MIL-B-11007E	-	Burster, Bomb, AN-M20

Custodians:

Army - MU
Air Force - 70

Preparing activity:

Army - MU(EA)

Project No. 1325-0147

Review activities:

Air Force - 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:23Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:23Z
Check the source to verify that this is the current version before use.