11 March 1976

MILITARY SPECIFICATION

FUEL, COMPRESSED, TRIOXANE, RATION HEATING

This amendment forms a part of Military Specification MIL-F-10805D, dated 20 September 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 8

4.3.2 Delete and substitute new paragraph:

"4.3.2 Testing of the end item. The end item bar shall be tested for the characteristics listed in Table II. The lot size for sampling purposes shall be the number of bars of the same type from a single manufacturer's batch, and shall be expressed in units of one bar each. The sample unit for all tests except water leakage shall be 14 bars, and the sample size (inspection level) shall be 3. There shall be no evidence of failure of any characteristic to meet the sample unit requirement. The sample unit for the water leakage test shall be one (1) bar; the inspection level (sample size) shall be level I, and the acceptable quality level (AQL) expressed in defects per 100 units shall be 0.65. A batch is defined as the amount of product made from the same materials at the same time and under the same conditions."

Custodians:

Army - GL
Air Force - 68

Review activity:

Army - MD

User activities:

Navy - YD, MC

Preparing activity:

Army - GL

Project No. 9110-0011

FSC 9110

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:26Z
Check the source to verify that this is the current version before use.