MIL-U-10815H
25 February 1988
SUPERSEDING
MIL-U-10815G
15 June 1971

MILITARY SPECIFICATION

UTENSILS, COOKING, CORROSION-RESISTING STEEL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE


1.1 Scope. This specificaton covers corrosion-resisting steel cooking utensils.

1.2 Classification. The cooking utensils shall be of the following types and sizes as specified (see 6.2):

Type I - Fork, food preparation, 2-tine
Type II - Spoon, food service, basting
Type IV - Food turner
Type V - Skimmer, kitchen (size 1 only)

Size 1 - 15 inches long
Size 2 - 21 inches long

1.3 Part identification number. The part identification number shall consist of the document number, type and size as follows:



Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7330 & 7340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

PPP-B-566 - Boxes, Folding, Paperboard
PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-B-676 - Boxes, Set Up

STANDARDS

MILITARY

MIL-STD-105 - Sampling Pocedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property
MIL-STD-147 - Palletized Unit Loads

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

2-9-39 - Utensils, Cooking

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167-87 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

Basic Criteria C-2 - Special Equipment and Devices

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Arbor, MI 48106.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3)

3.2 Codes and Standards. The utensils shall comply with the applicable requirements of National Sanitation Foundation (NSF) Basic Criteria C-2 (see 4.4.7 and 4.4.7.1).

3.3 Materials. Stainless and Heat-resisting steel sheets and strips shall conform to any type in the 300 series of ASTM A167-87 (see 6.4)

3.4 Construction. Utensils covered by this specification shall be constructed of the material specified in 3.3 and shall conform to the requirements specified herein and as shown on Drawing 2-9-39. Either method of handle construction for the utensils as illustrated on Drawing 2-9-39 is acceptable. The hole in the handle may be oblong provided the hole does not reduce the total net cross-sectional width of the handle to less than 13/32 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

3.4.1 Fork and spoon. The fork and spoon shall be of one- or two-piece construction provided the two-piece construction consists of a butt or flash weld only. When butt welding is used, the weld shall be located not less than 1/2 inch from the end of the handle adjacent to the body.

3.4.2 Skimmer and food turner. The food turner and the skimmer shall be of one- or two-piece construction provided the two-piece construction consists of a butt weld in the handle portion or a lap or spot welded joint at the handle to the body portion of the utensil. Butt welding shall be as specified in 3.4.1. When a fillet welded lap joint is used, the handle shall lap over the body not less than 1/2 inch and the two pieces shall be secured by fillet welding using corrosion-resistant filler material and ground smooth, or may be spot welded to the body with a minimum of three spot welds, provided the spot weld joint area is sealed all around the edge as specified in 3.5.

3.5 Welding. All surfaces to be welded shall be clean. Welding shall be accomplished to prevent the occurrence of burn holes, fractures, undercuts, weld metal or base metal cracks, incomplete fusion, and slag inclusion. Welds shall be sound and smooth and shall be completely sealed with corrosion-resisting weld material or solder to eliminate pockets where food could accumulate. After finishing there shall be no grind marks, discoloration, and cracks or crevices that could collect dirt or food particles. All scale or flux deposits shall be removed from the finished welds.

3.6 Deflection. When tested as specified in 4.5.1, the utensils shall have no more than 1/8 inch permanent set for the 15-inch utensils and no more than 1/4 inch permanent set for the 21-inch utensils.

3.7 Finish. Utensils shall have a 2B or smoother finish, except for Navy use (see 6.2) utensils shall have a No. 4 or smoother finish. All rough and sharp edges shall be removed from the utensils. The finished surfaces shall be free from discoloration, rust, pits, and stains.

3.8 Marking for identification. The letters "U.S." and the manufacturer's name, trade name, or trademark of such known character as to be easily identifiable with said manufacturer shall be applied to the upper portion of the handle in accordance with MIL-STD-130, and in the size and location shown on Drawing 2-9-39. When marking is applied by stamping, the surface opposite these stampmarks shall not be penetrated or uneven.

3.9 Workmanship. The finished utensils shall be clean and shall not contain any burrs, slivers, sharp edges, or rough die, tool, gouge or grind marks. The finished item shall not be fractured, buckled, dented, bent, punctured, malformed, or otherwise damaged. The utensils shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3 and tested for the characteristics specified in 4.4.4. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of utensils. The sample unit shall be one utensil. The inspection level shall be II and the acceptable quality level (AQL) expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Finish	Not a No. 2B or smoother finish (where applicable).	X	
	Not a No. 4 or smoother finish (where applicable).	X	
	Evidence of discoloration, rust, pits, or stains.	X	
Construction and workmanship (applicable to all components and assemblies)	Any burrs, slivers, sharp edges or scratches; rough die, tool, gouge, or grind marks.	X	
	Fractured, buckled, bent, dented, punctured, malformed, or otherwise damaged.	X	
	Any cracks or crevices deep enough to hold food particles.	X	
Welding	Weld not as specified (in two-piece construction) or not fused.	X	
	Any evidence of burn holes, under cuts, weld metal or base metal cracks, incomplete fusion, or slag inclusion.	X	
	Weld (where required) not sound, smooth and doesn't blend with the contour of the handle.	X	
	Spot weld (where required) missing, broken, burned through, or flashes.	X	
Identification marking	Missing, incomplete, illegible, not in proper location.		X
	Surface opposite marking shows penetration or uneveness (when stamped).		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

4.4.3 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings and, when applicable, the total cross-sectional width requirement of 3.4. Any dimensions not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of utensils. The sample unit shall be one utensil. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 End item testing. The utensils shall be tested as specified in 4.5.1. The lot size shall be expressed in units of utensils. The sample unit shall be one utensil. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling. Bulged or distorted container.
Content	Number per container is more or less than required.

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum Load Limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.4.7 Code and standard compliance. Certifications, certified test reports, or listing marks for codes and standards, as applicable, submitted in accordance with 3.2, shall be examined and validated as proof of compliance. Prior to Government approval of the first shipment, the contractor shall submit to the contracting officer or his authorized representative for approval, certification that the dispensers he proposes to furnish meet the applicable requirements of NSF as follows:

4.4.7.1 National Sanitation Foundation (NSF). Acceptable evidence of meeting the applicable requirements of the National Sanitation Foundation standards specified in 3.2 shall be one of the following.

a. A listing in the current edition of the National Sanitation Foundation "Listing of Food Service Equipment", and display of the NSF seal on the finished unit.

b. A certification for the unit issued by NSF under their special onetime contract evaluation/certification service.

c. A certified test report acceptable to the contracting officer with the advice of the Army Surgeon General, from an independent testing laboratory, indicating that the unit has been tested and conforms to the specified NSF standards.

4.5 Methods of inspection.

4.5.1 Deflection test. The utensil shall be tested by securely attaching the body of the utensil on a base so that the handle is positioned horizontally with the hook pointed downward. No part of the handle shall be supported by the base. A point on the handle immediately adjacent to the hole shall be carefully located dimensionally with respect to some fixed reference point directly above or below the point on the handle for 15-inch utensil and 8-1/2 inches for 21-inch utensil measured from the extreme hook end of the handle. An 18-pound weight shall be applied to the handle at a location 3-1/2 inches for size 1 utensils or 8-1/2 inches for size 2 utensils from the extreme hook end of the handle. The load shall be held for not less than 1/2 minute before being

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

released. The load shall be applied and released three times. At the completion of the three separate loadings, the dimensions from the previously located point on the handle to the fixed reference point shall be remeasured. The difference between the measurement taken before and after the consecutive loadings (permanent set) shall be determined for conformance with 3.6. Any nonconformance shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Six or twelve utensils of one type only, shall be unit packed in the most compact manner in a snug-fitting folding paperboard, or setup paperboard box, or fiberboard box conforming to variety 1, style II, type D, class a or style VIII, type G, class i of PPP-B-566; type I, variety 1, class c, style 4 of PPP-B-676; or style RSC (end-opening), type CF, variety SW, or type SF, class domestic of PPP-B-636, respectively. Tissue paper shall be used to immobilize the utensils within each box during transit. Closure shall be in accordance with the appendix of the applicable box specification.

5.1.2 Commercial. Utensils shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2)

5.2.1 Level A Packing. Seventy-two utensils of one type only, preserved as specified in 5.1, shall be packed in the most compact manner in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B packing. Seventy-two utensils of one type only, preserved as specified in 5.1, shall be packed in the most compact manner in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.3 Commercial. Utensils preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified (see 6.2), utensils, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The utensils are for use with field food service equipment.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Type and size of utensil required (see 1.2).
d. When a No. 4 finish is required for Navy (see 3.7).
e. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).
f. When weather-resistant fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Food preparation
Food service
Utensils, cooking

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review Activities:

Army - MD, TS
Navy - MC
Air Force - 84
GSA - FSS

User Activity:

Navy - CG

Preparing Activity:

Army - GL

Project No. 7330-0575

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development & Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-U-10815H	Utensils, Cooking, Corrosion-Resisting Steel

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:27Z
Check the source to verify that this is the current version before use.