MIL-I-11132 / 3D
30 June 1987
SUPERSEDING
MIL-I-0011132 / 3C(IH)
13 August 1979

MILITARY SPECIFICATION SHEET

INSIGNIA, BRANCH OF SERVICE; ROTC, BASIC COURSE, SR. DIV, AND CORPS, JR. DIV., ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-I-11132.



DASH NOS.
-1: REGULAR
-2: SUBDUED

MATERIAL: RED BRASS OR ZINC ALUMINUM (SUBDUED ONLY)

DIMENSIONS (INCHES):
DISC:
DIAMETER: 1 ± 1/64
THICKNESS AT CENTER: .040 ± .005
EMBOSSED DEVICE:
HEIGHT (OVERALL): 3/4 (REF)
WIDTH (OVERALL): 7/16 (REF)
THICKNESS (THICKEST POINT): .080 ± .005

FINISH:
-1: DISC: MIRROR-LIKE POLISHED
DEVICE: POLISHED (SEE NOTES 1 AND 2)
-2: DULL, FLAT BLACK ENAMEL (SEE NOTES 3 AND 4)

NOTES:
1. PRONGS SHALL BE MADE FROM ANY TYPE HARD DRAWN BRASS.
2. ASSEMBLY DETAILS AND DETAILS OF THE ATTACHING DEVICE ARE SPECIFIED ON FIGURE 1.
3. SUBDUED DIE CAST INSIGNIA FOR DASH NO. 2 MAY BE CONSTRUCTED IN ONE PIECE ONLY.
4. THE PRONGS FOR SUBDUED INSIGNIA FOR DASH NO. 2 SHALL BE POSITIONED 5/8 INCH ON HORIZONTAL CENTER, EQUIDISTANT FROM THE EDGE OF THE DISC.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455 - 0227)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:09Z
Check the source to verify that this is the current version before use.