NOT MEASUREMENT SENSITIVE

MIL-DTL-11132/5F
6 June 1997
SUPERSEDING
MIL-I-11132/5E
17 January 1995

DETAIL SPECIFICATION SHEET

INSIGNIA, GARRISON CAP, JUNIOR DIVISION AND BASIC COURSE, SENIOR DIVISION, ROTC AND INSIGNIA, SERVICE CAP, BASIC COURSE, SENIOR DIVISION, ROTC, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11132 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
- -1: Insignia, Garrison Cap, Junior Division & Basic Course, Senior Division, ROTC, Army
- -2: Insignia, Service Cap, Basic Course, Senior Division, ROTC, Army

MATERIAL: Red Brass or Zinc Aluminum

FINISH: Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 3.

DIMENSIONS:
- HEIGHT (Overall): 1-3/16 inches (3.02 cm) (REF)
- WIDTH (Overall): 1-3/4 inch (4.45 cm) (REF)
- THICKNESS (Letter "R"): 0.070 inch ± 0.005 inch (0.178 cm ± 0.12 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:10Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. With the exception of the attaching device and the dapping requirements, Dash No. -1 and Dash No. -2 are identical.

3. Piercing shall be as indicated.

4. Prongs shall be made from any type hard drawn brass.

5. Dash No. -2 insignia shall be dapped in the horizontal direction through a radius of 4 inches ± 1/2 inch (10.16 cm ± 1.27 cm).

6. Attaching device for Dash No. -1 shall be prong and catch type. The prongs shall be located on the intersections of a horizontal line 11/16 inch ± 1/32 inch (1.75 cm ± 0.08 cm) above the base of the insignia and the center of the wreath. Attaching device for Dash No. -2 shall consist of registration prongs and a screw post and thumb nut. The prongs shall be located at the intersections of a horizontal line 11/16 inch ± 1/32 inch (1.75 cm ± 0.08 cm) above the base of the insignia and the center of the wreath. The post shall be located on the vertical center line of the insignia at the center of the bar connecting the letters "ROTC". A mock forcer may be used to bring up the lettering.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0894)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:10Z
Check the source to verify that this is the current version before use.