INCH-POUND

MIL-DTL-11132/5H
16 October 2001
SUPERSEDING
MIL-DTL-11132/5G
1 May 2001

DETAIL SPECIFICATION SHEET

INSIGNIA, GARRISON CAP, JUNIOR DIVISION AND BASIC COURSE, SENIOR DIVISION, ROTC AND INSIGNIA, SERVICE CAP, BASIC COURSE, SENIOR DIVISION, ROTC, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11132 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



DASH NO.
- -1: Insignia, Garrison Cap, Junior Division and Basic Course, Senior Division, ROTC, Army
- -2: Insignia, Service Cap, Basic Course, Senior Division, ROTC, Army

MATERIAL: Red Brass

FINISH: Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 3.

DIMENSIONS:

HEIGHT (overall): 1-3/16 inches (REF)
WIDTH (overall): 1-3/4 inch (REF)
THICKNESS (at the letter "R"): 0.070 inch ± 0.005 inch

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:10Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. With the exception of the attaching device and the dapping requirements, -1 and -2 are identical:

a. Attaching device for -1 shall be prong with clutch type. Two prongs shall be located on the intersections of a horizontal line 11/16 inch ± 1/32 inch above the base of the insignia and the center of each side of the wreath.

b. Attaching device for -2 shall consist of registration prongs and a screw post and thumb nut. Two prongs shall be located as above. The post shall be located on the vertical center line of the insignia at the center of the bar connecting the letters "ROTC."

c. -2 insignia shall be dapped in the horizontal direction through a radius of 4 inches ± 1/2 inch.

4. A mock forcer may be used to bring up the lettering.

5. At the option of the manufacturer, -1 may be die cast in zinc aluminum.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0064/005)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:10Z
Check the source to verify that this is the current version before use.