NOT MEASUREMENT SENSITIVE

MIL-I-11132/6G
19 October 1990
SUPERSEDING
MIL-I-11132/6F
3 April 1987

MILITARY SPECIFICATION SHEET

INSIGNIA, SERVICE AND GARRISON CAP, ROTC, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-11132.



DASH NO. 1 & 3



DASH NO. 2

MATERIAL: Red brass or nickel silver

DIMENSIONS:
- HEIGHT (Overall):
  - -1: 1-7/32 inches (3.10 cm) (REF)
  - -2: 1-5/16 inches (3.33 cm) (REF)
  - -3: 2-1/2 inches (6.35 cm) (REF)
- WIDTH (Overall):
  - -1: 23/32 inch (1.83 cm) (REF)
  - -2: 31.32 inch (2.46 cm) (REF)
  - -3: 1-1/2 inches (3.81 cm) (REF)
- THICKNESS:
  - -1,-2: .100 inch ± .005 inch (0.254 cm ± 0.012 cm) (Thickest point of shield)
  - -3: .065 inch ± .005 inch (0.165 cm ± 0.012 cm) (At edge)

DASH NO:
- -1: Garrison Cap, Basic Course
- -2: Garrison Cap, Advance Course
- -3: Service Cap, JROTC

FINISH: Nickel plated (red brass only), silver plated, oxidized, relieved, matte finish

NOTES:
1. The attaching device for Dash No. 1 and 2 shall be prong and clutch type. The prongs shall be located on the vertical centerline, 7/8 inch ± 1/32 inch (2.22 cm ± 0.08 cm) apart with the bottom prong 7/32 inch ± 1/32 inch (0.56 cm ± 0.08 cm) above the bottom of the insignia.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:10Z
Check the source to verify that this is the current version before use.

2. The attaching device for Dash No. 3 shall be a screw post, thumb nut, and registration prong. The screw post shall be located on the vertical centerline 1-5/16 inches ± 1/32 inches (3.33 cm ± 0.08 cm) above the base of the insignia. The registration prong shall be located on the vertical centerline 3/16 inch ± 1/32 inch (0.48 cm ± 0.08 cm) below the top of the insignia.
3. A mock forcer may be used for Dash No. 3 to bring up the design provided the forced area maintains a minimum thickness of .045 inch (0.114 cm).

Custodian:
Army - IH
Air Force - 11

Review activities:
Air Force 82,99
DLA - CT

User activity:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455-F551)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:10Z
Check the source to verify that this is the current version before use.