METRIC

A-A-59624C
22 February 2011
SUPERSEDING
A-A-59624B
27 May 2009

COMMERCIAL ITEM DESCRIPTION

BEARING, BALL, ANNULAR, SINGLE ROW, ANGULAR CONTACT, CONTACT ANGLE 11° THROUGH 22°, DIMENSION SERIES 10

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers metric, single row, angular contact, annular ball bearings for general-purpose use. These bearings are not intended for use in critical aeronautical or critical special precision applications.

2. CLASSIFICATION. The ball bearings shall be classified by the class, sizes, cage materials, shield and seal configurations, precision tolerances, lubricant and preservative requirements, and duplex mounting configurations listed below:

Class 4 - dimension series 10

Sizes - bearing dimensions (see table I)

Cage materials (see table II)

Shield and seal configurations (see table III)

Precision tolerances (see table IV)

Lubricant and preservative requirements (see table V)

Duplex mounting configurations (see table VI)

3. SALIENT CHARACTERISTICS

3.1 Bearing boundary dimensions shall conform to the requirements specified in table I for each of the coded bearing sizes. The listed dimensions conform to the requirements specified for the

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: STDZNMGT@dla.mil or Defense Logistics Agency Aviation VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

listed bearing sizes from dimension series 10 in the American Bearing Manufacturers Association (ABMA) Standard 20, "Radial Bearings of Ball, Cylindrical Roller, and Spherical Roller Types, Metric Design". The bearing size shall be as specified in the acquisition order (see 7.3(b)). For unlisted bearing sizes, the dimensional and dynamic load rating requirements should also be specified in the acquisition order.

TABLE I. Dimensional requirements (ABMA series 10).

Bearing size code	Bore diameter (mm)	Outside diameter (mm)	Width (mm)	Chamfer r/min. (mm)	Minimum shaft shoulder diameter [1] (mm)	Dynamic load rating, (minimum) (lbs.)
00	10	26	8	0.3	12.5	795
01	12	28	8	0.3	14.5	870
02	15	32	9	0.3	17.5	940
03	17	35	10	0.3	19.5	1,320
04	20	42	12	0.6	25	1,680
05	25	47	12	0.6	30	1,865
06	30	55	13	1.0	36	2,410
07	35	62	14	1.0	41	2,910
08	40	68	15	1.0	46	3,000
09	45	75	16	1.0	51	3,715
10	50	80	16	1.0	56	3,820
11	55	90	18	1.1	62	5,205
12	60	95	18	1.1	67	5,350
13	65	100	18	1.1	72	5,480
14	70	110	20	1.1	77	6,470
15	75	115	20	1.1	82	6,610
16	80	125	22	1.1	87	8,500
17	85	130	22	1.1	92	8,690
18	90	140	24	1.5	98.5	10,515
19	95	145	24	1.5	103.5	12,450
20	100	150	24	1.5	108.5	10,990
21	105	160	26	2.0	115	13,020
22	110	170	28	2.0	120	15,100
24	120	180	28	2.0	130	15,370
26	130	200	33	2.0	140	21,055
28	140	210	33	2.0	150	20,815
30	150	225	35	2.1	162	23,810
32	160	240	38	2.1	172	26,980
34	170	260	42	2.1	182	32,310
36	180	280	46	2.1	192	36,035

[1] Listed for reference purposes only. Shoulder height shall be determined to provide sufficient clearance for the direct application of bearing removal force against the bearing inner ring. If the required minimum clearance is not available, an alternative non-destructive bearing removal capability shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

3.2 Materials.

3.2.1 Rings. The bearing ring material shall be chromium-alloy steel 52100 (UNS G52986) as specified in ASTM International (ASTM) A295/A295M, "Standard Specification for High-Carbon Anti-Friction Bearing Steel". The finished rings shall not exceed the associated billet material inclusion rating also specified in ASTM A295/A295M. Ring hardness shall be at least 58 HRC as defined in ASTM E18, "Standard Test Methods for Rockwell Hardness of Metallic Materials". The grain size of the ring material shall be determined in accordance with ASTM E112, "Standard Methods for Determining Average Grain Size".

3.2.2 Balls. The bearing ball material shall be chromium-alloy steel 52100 (UNS G52986) as specified in ASTM A295/A295M. The finished balls shall not exceed the associated billet material inclusion rating, which is also specified in ASTM A295/A295M. Balls shall be through-hardened no less than 60 HRC and no more than 67 HRC as defined in ASTM E18. The grain size of the ball material shall be determined in accordance with ASTM E112.

3.2.3 Cage. The bearing cage material shall be impervious to deterioration from any lubricant, preservative, solvent, or other chemical substance expected to contact the bearing during normal use or storage. Similarly, the material shall not cause any chemical deterioration of any other bearing component. Metallic cage materials shall operate from -40 °F to 250 °F (-40 °C to 121 °C). Non-metallic cage materials shall operate from -20 °F to 250 °F (-30 °C to 121 °C). Unless otherwise specified in the acquisition order, the cage material shall be one of the optional coded types listed in table II (see 7.3(c)).

TABLE II. Cage materials.

Code [1]	Material type
J	Pressed steel
M	Machined bronze or brass
P	Molded plastic (nylon 6/6 or equal)
T	Machined non-metallic (phenolic)
Y	Pressed brass
X	Other (specify in acquisition order)

[1] No significant changes from FF-B-171/20.

3.2.4 Shields and seals. Unless otherwise specified in the acquisition order, the shield and seal configuration for the bearing shall be one of the coded options listed in table III (see 7.3(d)). The acquisition order shall state which side of the outer ring (heavy shoulder or counterbore side) the shield or seal is to be located (see 7.3(e)).

TABLE III. Shield and seal configurations.

Code [1]	Configuration option
A	Open
X	Other (specify in acquisition order)

[1] No significant changes from FF-B-171/20.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

3.2.4.1 If a single shield or seal is required, the shield or seal material shall be as recommended by the manufacturer, unless otherwise specified in the acquisition order (see 7.3(f)). The material shall be impervious to deterioration from any lubricant, preservative, solvent, or other chemical substance expected to contact the bearing during normal use or storage. Similarly, the material shall not cause any chemical deterioration of any other bearing component. The shield or seal material shall remain functionally effective at a minimum temperature range of -20 °F to 250 °F (-30 °C to 121 °C) for non-metallic and -40 °F to 250 °F (-40 °C to 121 °C) for metallic materials.

3.3 Precision tolerance. The bearing precision tolerance level shall conform to Annular Bearing Engineers Committee (ABEC) class ABEC-1, ABEC-3, ABEC-5, or ABEC-7 as defined in ABMA Standard 20. The tolerance class shall be one of the coded options listed in table IV (see 7.3(g)).

TABLE IV. Precision tolerance requirements.

Code	Tolerance class
B	ABEC-1
F	ABEC-3
K	ABEC-5
P	ABEC-7

3.3.1 Bearing precision tolerance levels and internal clearances may be affected by the addition of shields and/or seals. Manufacturers/suppliers should be consulted for availability of desired precision tolerances when shields and/or seals are required.

3.4 Lubrication and preservation requirements. Unless otherwise specified in the acquisition order, the bearing lubricant or preservative requirement shall be as selected from the approved coded options listed in table V (see 7.3(h)). When grease fill is required, the bearing void (the airspace between the inner and outer rings of the assembled bearing) shall be 25 to 50 percent filled. Bearing preservative shall be in accordance with MIL-DTL-197, "Packaging of Bearings, Associated Parts and Subassemblies".

TABLE V. Lubricant and preservative requirements.

Code	Lubricant or preservative compound
B	Grease in accordance with MIL-PRF-81322
E	Grease in accordance with DOD-G-24508
H	Grease in accordance with MIL-PRF-23827
L	Grease with SRI-2 or qualified equivalent
S	No fill
T	Preservation compound in accordance with MIL-DTL-197
X	Other (specify in the acquisition order)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

3.5 Duplex mounting. When required, the adjoining faces of bearings used in duplex applications shall be match ground and marked for proper mounting. The duplex mounting configuration shall be one of the coded options listed in table VI. If required, the duplex mounting configuration shall be specified in the acquisition order (see 7.3(i)).

TABLE VI. Duplex mounting.

Code	Configuration option
F	Face to face
B	Back to back
T	Tandem
U	Universal (F, B, or T)

3.6 Preload. Preload requirements shall be listed in the acquisition order (see 7.3(j)).

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Foreign acquisition restrictions. Unless otherwise indicated in the solicitation and resulting contract, the foreign acquisition restrictions in Section 252.225, Clause 252.225.7016 of the Defense Federal Acquisition Regulation Supplement (DFARS) apply to products described by this CID.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

5.2 Market acceptability. The products offered must have been previously sold either to the government or on the commercial market.


6. PACKAGING

6.1 Preservation, packaging, and marking. Unless otherwise specified in the acquisition order, the bearings supplied shall be preserved, packaged, and marked in accordance with MIL-DTL-197 (see 7.3(k)).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

7. NOTES

7.1 Part or identification number (PIN). The following PIN procedure is for government purposes and does not constitute a requirement for the contractor.



AA59624 - 4 08 J C B B U indicates: boundary dimension series 10; bore diameter 40 mm, outside diameter 80 mm, width 18 mm; pressed steel cage; open, no shield or seal; ABEC-1 tolerance class, normal radial internal clearance; filled with grease in accordance with MIL-PRF-81322; universal duplex mounting.

7.2 Sources of documents.

7.2.1 DFARS and FAR. Copies of DFARS and FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of DFARS may be obtained from http://www.acq.osd.mil/dpap/dars/dfarspgi/current/index.html. Electronic copies of FAR may be obtained from https://www.acquisition.gov/far/.

7.2.2 Military specifications. Copies of military specifications may be obtained from Standardization Documents Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. Electronic copies may be obtained from https://assist.daps.dla.mil/.

7.2.3 ABMA standards. Copies of ABMA standards may be obtained from the American Bearing Manufacturers Association, 2025 M Street NW, Suite 800, Washington, DC 20036. Electronic copies may be obtained from http://www.abma-dc.org/.

7.2.4 ASTM standards. Copies of ASTM standards may be obtained from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959. Electronic copies may be obtained from http://www.astm.org/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

7.3 Ordering data. The acquisition order should specify the following:

a. CID document number, revision, and CID PIN.
b. Bearing size (with dimension/load requirements if size is unlisted), if different (see 3.1).
c. Cage material type (see 3.2.3).
d. Shield and seal configuration (see 3.2.4).
e. Location of shield or seal (see 3.2.4).
f. Shield or seal material (see 3.2.4.1).
g. Precision tolerance requirement (see 3.3).
h. Lubricant and preservative requirements (see 3.4).
i. Duplex mounting configuration, if required (see 3.5).
j. Preload requirement, if required (see 3.6).
k. Preservation, packaging, and marking requirements (see 6.1).

7.4 Codes cross-reference. Tables VII, VIII, and IX contain cross-reference data for the PIN information as listed in FF-B-171/20 and this CID.

7.4.1 Bearing class designations. The CIDs replacing 33 of 37 associated specification sheets of FF-B-171 have been assigned class codes corresponding to ABMA dimension series. Table VII lists the FF-B-171 specification sheets, the corresponding dimension series, the CID class codes, and the replacement CIDs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

TABLE VII. Federal specification to CID cross-reference.

FF-B-171 specification sheets	ABMA dimension series	CID class codes	Replacement CID numbers
1	02, 03, 10	1, 2, 4	A-A-59581
2	19	5	A-A-59582
3	10	4	A-A-59583
4	02	1	A-A-59584
5	03	2	A-A-59585
6	04	3	A-A-59586
7	02	1	A-A-59587
8	03	2	A-A-59589
9	32	8	A-A-59595
10	33	9	A-A-59596
11	02	1	A-A-59597
12	03	2	A-A-59598
13	22	6	A-A-59599
14	23	7	A-A-59600
15	19	-	Canceled
16	10	-	Canceled
17	02	-	Canceled
18	03	-	Canceled
19	19	5	A-A-59623
20	10	4	A-A-59624
21	02	1	A-A-59625
22	03	2	A-A-59626
23	04	3	A-A-59627
24	10	4	A-A-59628
25	02	1	A-A-59629
26	03	2	A-A-59630
27	04	3	A-A-59631
28	10	4	A-A-59632
29	02	1	A-A-59633
30	03	2	A-A-59634
31	04	3	A-A-59635
32	32	8	A-A-59636
33	33	9	A-A-59637
34	32	8	A-A-59638
35	33	9	A-A-59639
36	32	8	A-A-59640
37	33	9	A-A-59641

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

TABLE VIII. Radial internal clearance and ABEC tolerance codes.

FF-B-171/20 codes			A-A-59624C codes	
Radial internal clearance		Tolerance Class	Code	Tolerance class
1	Symbol 2	ABEC-1	B	ABEC-1
2	Symbol 0			
3	Symbol 3			
4	Symbol 4			
			F	ABEC-3
5	Symbol 2	ABEC-5	K	ABEC-5
6	Symbol 0			
7	Symbol 3			
8	Symbol 4			
			P	ABEC-7

TABLE IX. Lubricant and preservative requirements codes.

FF-B-171/20 codes		A-A-59624C codes	
Code	Lubricant or preservative	Code	Lubricant or preservative
A	Grease IAW MIL-PRF-81322	B	Grease IAW MIL-PRF-81322
B	Grease IAW DOD-G-24508	E	Grease IAW DOD-G-24508
C	Grease IAW MIL-PRF-23827	H	Grease IAW MIL-PRF-23827
D	Grease with SRI-2 or equivalent	L	Grease with SRI-2 or qualified equivalent
E	Preservation compound IAW MIL-DTL-197	T	Preservation compound IAW MIL-DTL-197
		S	No fill
		X	Other (specify in the acquisition order)

7.5 Subject term (key word) listing.

ABEC
cage
precision tolerance
rings

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - OS
Air Force - 99
DLA - GS

Review Activities:
Army - GL, MI
Air Force - 11, 84

CIVIL AGENCY
COORDINATING ACTIVITY:

GSA - FAS

Preparing Activity:
DLA - GS4

(Project 3110-2011-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at https://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:21Z
Check the source to verify that this is the current version before use.