NOTICE: This list may be made available to prospective bidders or suppliers who require the list in furnishing supplies or services to the Military Departments. Reproduction or use of the list in whole or in part for other purposes is prohibited, and violation will be cause for removal from this list.

QPL-5591-3
17 November 1958
Superseding
QPL-5591-2
31 March 1954

MILITARY QUALIFIED PRODUCTS LIST OF PRODUCTS QUALIFIED UNDER MILITARY SPECIFICATION

MIL-F-5591

FASTENERS; Panel

All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. Revisions of this list will be issued as necessary. The listing of a product does not release the manufacturer from compliance with the specification requirements.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.

GOVERNMENT DESIGNATION				MANUFACTURER'S DESIGNATION				TEST OR	MANUFACTURER'S
				Receptacle					
Style	Size	Class	Type	Plain Rivet Hole	Dimpled Rivet Hole	Stud 1/	Crosspin	Stud Retaining Ring or Washer	QUALIFICATION REFERENCE	NAME AND ADDRESS
1	2	A	I	RF3-1/2		F3-1/2T-X	GH3-1/2		AMC Report	
1	2	B	I	R3-1/2		F3-1/2T-X	GH3-1/2		No. MCREXA7-	
1	2	A	II	RF3-1/2		A3-1/2T-X	GH3-1/2		45320-5-4	
1	2	B	II	R3-1/2		A3-1/2T-X	GH3-1/2		23 June 48	
1	2	A	III	RF3-1/2		A#3-1/2T-X	GH3-1/2			
1	2	B	III	R3-1/2		A#3-1/2T-X	GH3-1/2			
1	5	A	I	RF5		F5T-X	GH5			
1	5	B	I	R5		F5T-X	GH5		AMC Report	
1	5	A	II	RF5		A5T-X	GH5		No. TSEAC11-	Dzus Fastener
1	5	B	II	R5		A5T-X	GH5		45320-5-1	Company, Inc.
1	5	A	III	RF5		A#5T-X	GH5		26 Sep 47	Babylon, New York
1	5	B	III	R5		A#5T-X	GH5			"Supersonic" Fasteners
1	7	A	I	RF6		F6T-X	GH6		AMC Report	
1	7	B	I	R6		F6T-X	GH6		No. TSEAC11-	
1	7	A	II	RF6		A6T-X	GH6		45320-5-2	
1	7	B	II	R6		A6T-X	GH6		24 Nov 47	
1	7	A	III	RF6		A#6T-X	GH6			
1	7	B	III	R6		A#6T-X	GH6			
1	5	B	I		5-295	5-F-X	GOS-5-93		AMC Report	Lion Fastener Company,
1	5	B	II		5-295	5-0-X	GOS-5-93		No. MCREXA7-	Inc. Honeoye Falls,
1	5	B	III		5-295	5-#-X	GOS-5-93		45320-5-7	New York, Subsidiary of
									24 Aug 48	South Chester Corporation
1	5	A	I	R2000-Z-NC	H2000-Z-C	S2000-X-F	L-2000		AMC Report	
1	5	A	II	R2000-Z-NC	R2000-Z-C	S2000-X-R	L-2000		No. MCREXA7-	
1	5	A	III	R2000-Z-NC	R2000-Z-C	S2000-X-#	L-2000		45320-5-6	Zahodiakin-Scovill
1	5	B	I	R2000-NZ-NC	R2000-NZ-C	S2000-X-F	L-2000		23 July 49	Fasteners
1	5	B	II	R2000-NZ-NC	R2000-NZ-C	S2000-X-R	L-2000			Manufactured by
1	5	B	III	R2000-NZ-NC	R2000-NZ-C	S2000-X-#	L-2000			Scovill Mfg.
1	7	A	I	R4000-Z-NC	R4000-Z-C	S4000-X-F	L-4000		AMC Report	Company
1	7	A	II	R4000-Z-NC	R4000-Z-C	S4000-X-R	L-4000		No. MCREXA7-	Waterbury
1	7	A	III	R4000-Z-NC	R4000-Z-C	S4000-X-#	L-4000		45320-5-6	Connecticut
1	7	B	I	R4000-NZ-NC	R4000-NZ-C	S4000-X-F	L-4000		23 July 49	
1	7	B	II	R4000-NZ-NC	R4000-NZ-C	S4000-X-R	L-4000			
1	7	B	III	R4000-NZ-NC	R4000-NZ-C	S4000-X-#	L-4000			
5	7S	A	I	R3000-Z-NC	R3000-Z-C	S3000-F-X	L-3000	Scovill Mfg. Report No. D-81488		Scovill Manufacturing Co. 99 Mill Street Waterbury 20, Connecticut

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.

GOVERNMENT DESIGNATION				MANUFACTURER'S DESIGNATION						
				Receptacle				Stud Retaining		TEST OR QUALIFICATION REFERENCE	MANUFACTURER'S NAME AND ADDRESS
Style	Size	Class	Type	Plain Rivet Hole	Dimpled Rivet Hole	Stud 1/	Crosspin	Ring or Washer	Grommet		
3	7L	A	I	244-22	244-22D	4002-X		R4G	4002-G 4002-H		
3	7S	A	I	244-16	244-16D	4002-X		R4G	4002-G 4002-H		
3	7L	A	II	244-22	244-22D	4002-X		R4G	4002-N 4002-P		
3	7S	A	II	244-16	244-16D	4002-X		R4G	4002-N 4002-P	WADC Report No. WCLS53-74 18 Dec 53	Camloc Fastener Corp. 22 Spring Valley Road Paramus, New Jersey
3	7L	A	III	244-22	244-22D	4002-Xd		R4G	4002-N 4002-P		
3	7S	A	III	244-16	244-16D	4002-Xd		R4G	4002-N 4002-P		
3	7	B	I	214-16	214-16D	4002-X		R4G	4002-G 4002-H		
3	7	B	II	214-16	214-16D	4002-X		R4G	4002-N 4002-P		
3	7	B	III	214-16	214-16D	4002-Xd		R4G	4002-N 4002-P		
3	2	B	I	212-12	212-12D	2700-X		2700-Sd	2/		
3	2	B	II	212-12	212-12D	2600-X		2600-Sd	2/		
3	2	B	III	212-12	212-12D	2600-Xd		2600-Sd	2/		
1	5	B	I	98-5-MSP	98-5-MS	98-FS-5-X	98-5-CP			AMC Report No. MCREXA7-45320-6-1 28 Feb 51	Illinois Tool Works, Fastex Division, 195 Algonquin Road, Des Plaines, Illinois (formerly manufactured by Shakeproof Inc.)
1	5	B	II	98-5-MSP	98-5-MS	98-OS-5-X	98-5-CP				
1	5	B	III	98-5-MSP	98-5-MS	98-Od-5-X	98-5-CP				
1	7	B	I	98-7-MSP	98-7-MS	98-FS-7-X	98-7-CP			AMC Report No. MCREXA7-45320-5-10 30 Aug 49	
1	7	B	II	98-7-MSP	98-7-MS	98-OS-7-X	98-7-CP				
1	7	B	III	98-7-MSP	98-7-MS	98-Od-7-X	98-7-CP				
1	2	B	I	99871-P098	99871-C098	98264-X	99765			AMC Report No. MCREXA7-45320-5-9 25 Aug 49	Townsend Mills Subsidiary of United-Carr Fastener Corp. 1977 First Ave. San Leandro, California "Airlon" Fasteners
1	5	B	I	99833-P130	99833-C130	98265-X	99836				
1	7	B	I	99797-P130	99797-C130	98266-X	99799				

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.

GOVERNMENT DESIGNATION				MANUFACTURER'S DESIGNATION							TEST OR QUALIFICATION REFERENCE	MANUFACTURER'S NAME AND ADDRESS
				Receptacle				Stud Retaining Ring or Washer				
Style	Size	Class	Type	Plain Rivet Hole	Dimpled Rivet Hole	Stud 1/	Crosspin		Grommets	Spring		
3	7L	A	I	HS-AN3-13P	HS-AN3-13D	HS-AN3-3-X	HS-AN3-4	HS-AN3-6	HS-AN3-2FG HS-AN3-2FH	HS-AN3-5 HS-AN3-5R	Reports from International Testing Laboratories, Inc. dated 8 Dec. 54 2 Nov. 56 and 2 Jan. 57	
3	7S	A	I	HS-AN3-10P	HS-AN3-10D	HS-AN3-3-X	HS-AN3-4	HS-AN3-6	HS-AN3-2FG HS-AN3-2FH	HS-AN3-5 HS-AN3-5R		
3	7L	A	II	HS-AN3-13P	HS-AN3-13D	HS-AN3-3-X	HS-AN3-4	HS-AN3-6	HS-AN3-2RN HS-AN3-2RO	HS-AN3-5 HS-AN3-5R		
3	7S	A	II	HS-AN3-10P	HS-AN3-10D	HS-AN3-3-X	HS-AN3-4	HS-AN3-6	HS-AN3-2RN HS-AN3-2RO	HS-AN3-5 HS-AN3-5R		
3	7L	A	III	HS-AN3-13P	HS-AN3-13D	HS-AN3-3-X-4	HS-AN3-4	HS-AN3-6	HS-AN3-2RN HS-AN3-2RO	HS-AN3-5 HS-AN3-5R		V. P. Zahodiakin Aircraft, Ltd. Summit New Jersey
3	7S	A	III	HS-AN3-10P	HS-AN3-10D	HS-AN3-3-X-4	HS-AN3-4	HS-AN3-6	HS-AN3-2RN HS-AN3-2RO	HS-AN3-5 HS-AN3-5R		
3	7	B	I	HS-AN3-1000P	HS-AN3-1000D	HS-AN3-3-X	HS-AN3-4	HS-AN3-6	HS-AN3-2FG HS-AN3-2FH	HS-AN3-5 HS-AN3-5R		
3	7	B	II	HS-AN3-1000P	HS-AN3-1000D	HS-AN3-3-X	HS-AN3-4	HS-AN3-6	HS-AN3-2RN HS-AN3-2RO	HS-AN3-5 HS-AN3-5R		
3	7	B	III	HS-AN3-1000P	HS-AN3-1000D	HS-AN3-3-X-4	HS-AN3-4	HS-AN3-6	HS-AN3-2RN HS-AN3-2RO	HS-AN3-5 HS-AN3-5R		
3	2	B	I	S2-750P	S2-750D	S2-3F-X	S2-4	S2-6	S2-2F	S2-5F	Report from International Testing Laboratories, Inc. dated 24 Oct 57	
3	2	B	II	S2-750P	S2-750D	S2-3R-X	S2-4	S2-6	S2-2R	S2-5R		
3	2	B	III	S2-750P	S2-750D	S2-3R-X-4	S2-4	S2-6	S2-2R	S2-5R		
1	7	A	I	7-81-1	7-81-1-D	7-2-1-X		5-8-1 or 5-8-3		5-4-2		
1	7	A	II	7-81-1	7-81-1-D	7-2-2-X		5-8-1 or 5-8-3		5-4-2	WADC Report Nr. WCLS 54-50 2 Apr 54	Pachmayr Corporation 2222 S. Figueroa Los Angeles 7 California
1	7	B	I	7-81-2	7-81-2-D	7-2-1-X		5-8-1 or 5-8-3		5-4-2		
1	7	B	II	7-81-2	7-81-2-D	7-2-2-X		5-8-1 or 5-8-3		5-4-2		
3	7L	A	I	7-81-1	7-81-1-D	5-82-5-X		5-8-2				
3	7S	A	I	5-81-1	5-81-1-D	5-82-5-X		5-8-2				
3	7	B	I	5-81-2	5-81-2-D	5-82-5-X		5-8-2				
1	5	A	I	9531-9		9537-10					WADC Report Nr. WCNSJ1-45329-6-3 31 Mar 52	Pachmayr Gun Works 1220 S. Grand Ave. Los Angeles 15 California

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.

The X in the part number covers the grip length designations of the studs as follows:

(a) Dzus Fasteners. X ranges from 2 to 12, 3 to 18, and 6 to 25 for the size 2, 5, and 7 studs, respectively. The grip lengths are in 0.010 inch increments and the dash number indicates the maximum grip in hundredths of an inch. For example, F5T-8 indicates a flush head size 5 stud with a grip range of 0.071 to 0.080 inch total application thickness.

(b) Lion Fasteners. X = 60, 80, 100, 120.... to 1000 in increments of 20 indicating the nominal grip length of the stud in thousandths of an inch. The grip lengths are in 0.020 inch increments. For example, 5-F-120 indicates a size 5 flush head fastener with a grip range of 0.110 to 0.129 inch total application thickness.

(c) Zahodiskin-Scovill Fasteners. X = 5 thru 18 for size 5 fasteners and 6 thru 25 for size 7 fasteners. The grip lengths are in 0.010 inch increments and the dash number indicates the maximum grip in hundredths of an inch. For example, S2000-11-F indicates a size 5 flush head stud with a grip range of 0.101 to 0.110 inch total application thickness.

(d) Scovill Style 3, Size 7S, Class A, Type I, Fastener. X = 1 through 25 covering the grip range from 0.051 to 0.771 inch total application thickness in increments of 0.030 inch. For example, S3000-F-2 indicates a style 3, Class A, Type I Size 7S stud with a grip range of 0.081 to 0.110 inch total application thickness.

(e) Camloc Style 3, Size 7, Class A, Type I, and Class B, Types II and III Fasteners. X = 2, 3, 4, 5, etc, to 25 covering the grip range from 0.051 to 0.770 inch total application thickness in increments of 0.030 inch. For example, 4002-3 indicates a style 3, class A, type I, size 7L or 7S stud with a grip range of 0.081 to 0.110 inch total application thickness.

(f) Camloc Style 3, Size 7, Class A, Types II and III Fasteners. X = 3, 4, 5, 6, etc, to 25 covering the grip range from 0.051 to 0.740 inch total application thickness in increments of 0.030 inch. For example, 4002-3 indicates a style 3, class A, type II or III, size 7L or 7S stud with a grip range of 0.051 to 0.080 inch total application thickness.

(g) Camloc Style 3, Size 7, Class B, Type I Fasteners. X = 1, 2, 3, 4, etc, to 25 covering the grip range from 0.051 to 0.800 inch total thickness in increments of 0.030 inch. For example, 4002-3 indicates a style 3, class B, type 1, size 7 stud with a grip range of 0.111 to 0.140 inch total application thickness.

(h) Camloc Style 3, Size 2, Class B, Types I, II, and III Fasteners. X = 1, 2, 3, 4, etc, to 15 covering the grip range from 0.030 to 0.480 inch total application thickness in increments of 0.030 inch. For example, 2700-3 indicates a style 3, class B, size 2, type I stud with a grip range of 0.091 to 0.120 inch total application thickness.

(i) Shakeproof Fasteners. X = 03, 04, 05, etc, to 65 covering a grip range from 0.021 to 0.650 inch total application thickness in increments of 0.010 inch. The dash number indicates the maximum grip of the stud. For example, 98-FS-5-16 indicates a flush head size 5 stud with a grip range of 0.151 to 0.160 inch.

(j) United-Carr Size 5 and 7 Fasteners. X = 1-.040, 1-.050....1-.150, 2-.160....2-.250, 3-.260....3-.350, 4-.360.... 4-.450 etc, to 12-1.250 covering the grip range from 0.031 to 1.250 inches total application thickness in increments of 0.010 inch. The last dash number indicates the maximum grip of the stud in question.

(k) United-Carr Size 2 Fasteners. X = 1-.040, 1-.050....1-.100, 2-.110....2-.250, 3-.260....3-.400, 4-.410....4-.550, 5-.560 ....5-.700 to 8-1.150 covering the grip range from 0.031 inch total application thickness to 1.150 inches total application thickness in increments of 0.010 inch. The last dash number indicates the maximum grip of the stud in question.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.

(l) Zahodiakin Style 3, Size 7L or 7S, Class A, Type I Fasteners. X = 2, 3, 4, 5, etc. to 25 covering the grip range from 0.081 to 0.800 inch total application thickness in increments of 0.030 inch. For example, HS-AN3-3-2 indicates a style 3, Class A, Type I, size 7L or 7S stud with a grip range of 0.081 to 0.110 inch total application thickness.

(m) Zahodiakin Style 3, Size 7L or 7S, Class A, Types II and III Fasteners. X = 3, 4, 5, 6, etc. to 26 covering the grip range from 0.081 to 0.800 inch total application thickness in increments of 0.030 inch. For example, HS-AN3-3-3 indicates a style 3, Class A Type II, size 7L or 7S stud with a grip range of 0.081 to 0.110 inch total application thickness.

(n) Zahodiakin Style 3, Size 7, Class B, Type I Fasteners. X = 1, 2, 3, 4, etc. to 24 covering the grip range from 0.081 to 0.800 inch, total thickness in increments of 0.030 inch. For example, HS-AN3-3-3 indicates a style 3, Class B, Type I, size 7 stud with a grip range of 0.141 to 0.170 inch total application thickness.

(o) Zahodiakin Style 3, Size 7, Class B, Types II and III Fasteners. X = 2, 3, 4, 5, etc. to 25 covering the grip range from 0.081 to 0.800 total application thickness in increments of 0.030 inch. For example, HS-AN3-3-2 indicates a style 3, Class B, Type II, size 7 stud with a grip range of 0.081 to 0.110 inch total application thickness.

(p) Zahodiakin Style 3, Size 2, Class B, Types I, II and III Fasteners. X = 1, 2, 3, 4, etc. to 15. When X = 1, the fastener has a grip range of .030 to .060 inch total application thickness. When X = 2, 3, 4, 5, etc. to 15, the fasteners cover a grip range from .061 to .480 inch total application thickness in increments of .030 inch. For example, 32-3F-2 indicates a Style 3, Size 2, Class B, Type I stud with a grip range of .061 to .090 inch total application thickness.

(q) Pechmayr Style 1, Size 7, Classes A and B, Types I and II Fasteners. X = D, F, H, J, etc. to T. When X = D, the fastener has a grip range of 0.040 to 0.430 inch total application thickness. When X = F, H, J, L, etc. to T, the fastener covers a grip range from 0.431 to 2.430 inch total application thickness in increments of 0.250 inch. For example, 7-2-1-F indicates a Style 1, Size 7, Classes A and B, Type I stud with a grip range of 0.431 to 0.680 inch total application thickness.

(r) Pechmayr Style 3, Sizes 7L, 7S, and 7, Classes A and B, Type I Fasteners. X = C, E, G, I, etc. to S. When X = C, the fastener has a grip range of 0.040 to 0.320 inch total application thickness. When X = E, G, I, K, etc. to S, the fastener covers a grip range from 0.321 to 2.320 inch total application thickness in increments of 0.250 inch. For example, 5-82-5-I indicates a Style 3, Size 7L, 7S and 7, Classes A and B, Type I stud with a grip range of 0.321 to 0.570 inch total application thickness.

(s) Pechmayr Fasteners are universal in nature and are capable of covering a grip range of from 0 to 1/4 inch without adjustment or change.

2/ For the size 2 fasteners, the grommet is incorporated on the stud.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.