QPL-5591-3
AMENDMENT 2
9 MARCH 1960

SUPERSEDING
AMENDMENT 1
18 MAY 1959

MILITARY QUALIFIED PRODUCTS LIST
OF
PRODUCTS QUALIFIED UNDER MILITARY SPECIFICATION
MIL-F-5591

FASTENERS; PANEL

This amendment forms a part of QPL-5591-3, dated 17 Nov. 58.

Government designation				Manufacturer's designation				Test or qualification reference	Manufacturer's name and address
				Receptacle		Stud [1]	Crosspin		
Size	Style	Class	Type	Plain rivet hole	Dimpled rivet hole				
Page 4, add the following products:									
1	5	A	I	99947-P130	99947-C130	98265-X	99836	Triplett and	Monadnock Mills
1	5	A	II	99947-P130	99947-C130	98292-X	99836	Barton Inc.	Subsidiary of
1	5	A	III	99947-P130	99947-C130	W98292-X	99836	Report	United-Carr
1	2	A	I		99967-C098	98264-X	99785-2	Numbers	Fastener Corp.
1	2	A	II		99967-C098	98293-X	99785-2	5-9992	1977 First Ave.
1	2	A	III		99967-C098	W98293-X	99785-2	5-1516-A	San Leandro
								5-9992-A	California
								5-9486	"Airloc"
								5-1516-C	Fasteners
								5-9940	
								5-1516	
								5-9940-A	
								5-9485	
								5-1516-A	
								Dated	
								27 Jan 58	
								23 Dec 58	
								11 Feb 58	
								4 Oct 57	
								20 Jan 58	
								23 Dec 58	
								23 Dec 58	
								14 Feb 58	
								4 Oct 57	
								23 Dec 58	
								Respectively	

Notice: This list may be made available to prospective bidders or suppliers who require the list in furnishing supplies or services to the Military Departments. Reproduction or use of the list in whole or in part for other purposes is prohibited, and violation will be cause for removal from this list.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.

[1] The X in the part number covers the grip length designations as follows:

(a) United-Carr Style 1, Size 5 Class A, Type I Fasteners, x = 1—.040... 1—.150, 2—.160... 2—.250, 3—.260... 3—.350, 4—.360... 4—.450 etc. to 16—1.650 covering the grip range from 0.031 to 1.650 inches total application thickness in increments of 0.010 inch. The last dash number indicates the maximum grip of the stud in question. For example, 98265—1.040 indicates a style 1, size 5, class A, type I stud with a grip range of 0.031 to 0.040 inch total application thickness.

(b) United-Carr Style 1, Size 5, Class A, Type II Fasteners, x = 1—.040... 1—.150, 2—.160... 2—.250, 3—.260... 3—.350, 4—.360... 4—.450 etc. to 15—1.550 covering the range from 0.031 to 1.550 inches total application thickness in increments of 0.010 inch. The last dash number indicates the maximum grip of the stud in question. For example, 98292—1—.040 indicates a style 1, size 5, class A, type II stud with a grip range of 0.031 to 0.040 inch total application thickness.

(c) United-Carr Style 1, Size 5, Class A, Type III Fasteners, x = 1—.040... 1—.150, 2—.160... 2—.250, 3—.260... 3—.350, 4—.360... 4—.450 etc. to 14—1.450 covering the grip range from 0.031 to 1.450 inches total application thickness in increments of 0.010 inch. The last dash number indicates the maximum grip of the stud in question. For example, W98293—1—.040 indicates a style 5, class A, type III stud with a grip range of 0.031 to 0.040 inch total application thickness.

(d) United-Carr Style 1, Size 2, Class A, Types I and II Fasteners, x = 1—.040... 1—.100, 2—.110... 2—.250, 3—.260... 3—.400, 4—.410... 4—.550 etc. to 14—2.050 covering the grip range from 0.031 to 2.050 inches total application thickness in increments of 0.010 inch. The last dash number indicates the maximum grip of the stud in question. For example, 98264—1—.040 indicates a style 1, size 2, class A, type I stud with a grip range of 0.031 to 0.040 inch total application thickness.

(e) United-Carr Style 1, Size 2, Class A, Type III Fasteners, x = 1—.040... 1—.100, 2—.110... 2—.250, 3—.260... 3—.400, 4—.410... 4—.550 etc. to 8—1.150 covering the grip range from 0.031 to 1.150 inches total application thickness in increments of 0.010 inch. The last dash number indicates the maximum grip of the stud in question. For example, W98295—1.040 indicates a style 1, size 2, class A, type III stud with a grip range of 0.031 to 0.040 inch total application thickness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.

Page Four

Government designation				Manufacturer's designation							Test or qualification reference	Manufacturer's name and address
				Receptacle		Stud [1]	Crosspin	Stud retaining ring or washer	Grommets	Spring		
Style	Size	Class	Type	Plain rivet hole	Dimpled rivet hole							

Change address to read as follows:
Spiron, Inc.
315 Bowen Bldg.,
815 Fifteenth St. N.W.,
Washington, D. C.
(formerly V. F. Zahodiakin Aircraft Ltd.)

Page Six

In notes l, m, n. o, and p, change "Zahodiakin" to "Spiron".

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-603-118/2147

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:06Z
Check the source to verify that this is the current version before use.