METRIC

MIL-C-85623(AS)
AMENDMENT 1
12 August 1994

MILITARY SPECIFICATION

CARTRIDGE, 25 mm, TARGET PRACTICE,
PGU-23/U

This amendment forms a part of MIL-C-85623(AS), dated 11 August 1983, and is approved for use by the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Beneficial comments, lines 3, 4, and 5: Delete "Commanding Officer, Naval Air Engineering Center, Engineering Specification and Standards Department (ESSD), Code 93, Lakehurst, NJ 08733," and substitute "Commander, Naval Air Warfare Center Aircraft Division, Code SR3, Highway 547, Lakehurst, NJ 08733-5100,".

PAGE 4

4.4.1, line 3: Delete "744" and substitute "at least 500."

PAGE 6

Table I, 3/: Delete "tests" and substitute "tests (see 4.4.1.1)."

PAGE 8

4.5.3.3, under critical categories and defects 3: Add:

"4. Low propellant charge Weigh 100"

The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
11	11
12	12

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.

PAGE 15

Below 6. NOTES: Add:

"(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)"

6.2.2: Delete and substitute:

"6.2.2 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractural application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 227.405-70 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
5.3	DI-MISC-80043	Ammunition data cards	---

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423."

PAGE 16

6.3, first line: Delete "activity" and substitute "activity, with concurrence of the technical activity,".

Preparing activity:
Navy - AS

(Project 1305-0101)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued.

b. The lot shall be rejected if 4 or more cartridges fail to comply with the maximum requirement. If more than 1, but less than 4, cartridges fail to comply with the maximum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if 5 or more cartridges of the combined samples fail to comply with the maximum requirement.

3/Propellant contamination. The presence of foreign matter in the propellant of any of the test cartridges shall cause rejection of the lot (see 3.12 and 4.6.2).

4/Projectile torque. Failure of two or more of the sample cartridges to comply with the specified torque requirement shall cause rejection of the lot. If one cartridge of the sample fails to comply, a second sample of 20 cartridges shall be tested. The lot shall be rejected if two or more cartridges of the combined sample fail to comply with the applicable requirements.

5/Velocity. If the sample fails to comply with either or both requirements, a second sample of 40 cartridges shall be tested. The lot shall be rejected if the second sample fails to comply with the applicable requirements (see 4.6.4).

6/Pressure. If the sample fails to comply with the requirements, a second sample of 40 cartridges shall be tested. The lot shall be rejected if the second sample fails to comply with the applicable requirements.

7/Waterproofness. If the average velocity (wet) of the sample fails to comply with the applicable requirement, a second sample of 40 cartridges shall be tested. The lot shall be rejected if the average velocity (wet) differs by more than 30.5 mps from the average velocity (dry) specified in 3.6.

8/Accuracy. If the accuracy of the sample cartridges fails to meet the applicable requirement, a second sample of 80 cartridges shall be tested. The lot shall be rejected if the accuracy of the second sample fails to meet the applicable requirements.

9/Action time. If any sample cartridge fails to meet requirements for action time, the lot shall be rejected.

10/Function and casualty. The lot shall be rejected if any malfunction or firing casualty of Table III occurs in numbers equal to or greater than the applicable "Rej" number. Except as otherwise provided, if malfunctions or casualties occur in excess of the applicable "Acc" number, but less than the applicable "Rej" number, a second sample

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued.

of 300 cartridges shall be selected. The lot shall be rejected if, in the combined samples, malfunctions or casualties occur in numbers equal to or greater than the applicable "Rej" number.

11/Ammunition shall be conditioned at 18 to 24°C.

4.6 Test methods and procedures.

4.6.1 Projectile extraction. The method of test shall be as prescribed in AS12013566.

4.6.2 Propellant contamination. The propellant from each of the cartridges tested for projectile extraction shall be examined visually for contamination as prescribed in AS12013566, Section 12.

4.6.3 Projectile torque. Each cartridge of the test sample shall be marked across the rotating band onto the case neck. Torque, to the specified requirement, shall be applied slowly to the projectile. Movement of the projectile with respect to the cartridge case, detectable by misalignment in the scratch mark, shall be recorded.

4.6.4 Velocity, pressure, and waterproofness. The methods of test shall be as prescribed in AS12013566. Statistics necessary for testing of results against acceptance criteria shall be computed. A correction factor of 0.46 mps shall be applied to the recorded velocity at the measured range to obtain muzzle velocity. The method of computation shall be:

$$S = SQRT((SUM\ (X_i - X_{av})^2)/(n-1))$$

where

X_i = each individual value

X_{av} = arithmetic mean of the sample

n = number of units in sample

4.6.5 Accuracy. The method of test and measurement of targets shall be as prescribed in AS12013566. The specified range may be shortened to a minimum range of 100 meters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.