MILITARY SPECIFIATION

WATER TEST DEVICE, ANTI-EXPOSURE COVERALL

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the manufacture and inspection of a CWU-62/P anti-exposure coverall water test device.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	-	Identification Marking of U.S. Military Property.
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment.

2.1.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Air Systems Command, Washington, DC 20361, Attn: AIR-5311D, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

1370AS600 - Index, Water Test Device, CWU-62/P Anti-Exposure Coverall.
1370AS607 - Sleeve/Neck Clamp Assembly.

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified, a sample of the water test device shall be subjected to first article inspection (see 4.3 and 6.3).

3.2 Materials and components. The materials and components shall conform to the applicable specifications, standards and drawings as listed or required herein. Included with each device shall be 6 each, sleeve clamp assemblies (P/N 1370AS607-1) and 3 each, neck clamp assemblies (P/N 1370AS607-2) from drawing NA 1370AS607.

3.3 Design and construction. The design and construction of the water test device shall be in accordance with the drawings listed on Drawing 1370AS600.

3.4 Dimensions. The dimensions of each water test device, including each material and component, shall conform to the applicable drawings listed on Drawing 1370AS600.

3.5 Marking. Each water test device shall be marked with a permanent metal identification plate with the following information:

NSN
WATER TEST DEVICE, ANTI-EXPOSURE COVERALL
MIL-W-85635
SERIAL NUMBER
CONTRACT NUMBER
MANUFACTURERS NAME
115 VOLTS/60 HERTZ

3.6 Workmanship. The materials and components and the assembled water test device shall not be misaligned nor contain any sharp edge, crack, dent, nick, burr or sliver. The water test devices shall not contain any spot, stain, non-specified hole or abraded area. The water test devices shall be uniform in quality and shall be free from irregularities or defects which could adversely affect performance, reliability, or durability. The water test devices shall conform to the quality and grade of product established by this specification. The occurence of defects shall not exceed the acceptance criteria established herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection. First article inspection consists of examinations and tests performed on samples which are representative of the production item after award of a contract to determine that the production item conforms to the requirements of this specification (see 4.3).

b. Quality conformance inspection. Quality conformance inspection consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots with the requirements set forth in this specification (see 4.4).

4.3 First article inspection. The first article inspection shall consist of all the requirements of this specification.

4.3.1 First Article Samples. Unless otherwise specified, as soon as practicable, after the award of the contract or order, the manufacturer shall submit one water test device to an inspection laboratory designated by the government. The sample shall be representative of the construction, workmanship, components and materials to be used during production. When a manufacturer is in continuous production of these units from contract to contract, submission of further first article samples on a new contract may be waived at the discretion of the acquiring activity (see 6.2.1). Approval of the first article samples or the waiving of the first article inspection does not waive the requirements of submitting to the quality conformance inspection. The first article inspection samples shall be furnished to the Government as directed by the contracting officer (see 6.2.1).

4.3.1.1 Documentation. Upon completion of the first article inspection, all the applicable inspection reports and when applicable, recommendations and comments pertinent for use in monitoring production will be forwarded to the cognizant Government activity. The water test device will be returned to the manufacturer for use in monitoring production.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of all the requirements of this specification. The sampling, inspection levels and acceptance criteria shall conform to MIL-STD-105.

4.4.1 Sampling.

Source: https://assist.dla.mil -- Downloaded: 202640-23T11:13Z
Check the source to verify that this is the currentversion before use.

4.4.1.1 Inspection lot.

4.4.1.1.1 Water test devices. An inspection lot size shall be expressed in units of one water test device made under essentially the same conditions and from the same materials and components. The sample unit shall be one water test device.

4.4.1.2 Sampling for examination of the water test devices and packaging. The sample size, acceptance criteria, and examinations required for the water test devices and packaging shall be as specified in Table I.

4.5 Inspection methods.

4.5.1 Visual examination.

4.5.1.1 Water test devices. Every water test device shall be examined visually to determine conformance to this specification. The list of defects, Table II, shall be used to enumerate the defects found.

4.5.1.1.1 Dimensions. Each water test device, selected as a sample unit from the lot, shall be checked dimensionally to determine conformance to the dimensions specified in the applicable drawings listed in Drawing 1370AS600. The list of defects, Table III, shall be used to enumerate the defects found.

4.5.1.2 Packaging. Each of the fully prepared shipping containers, containing water test devices, selected as a sample unit from the lot, shall be examined to determine that the packaging, packing and marking conform to this specification. The list of defects, Table III, shall be used to enumerate the defects found.

5. PACKAGING

5.1 Packaging/preservation, packing and marking. The packaging/preservation, packing and marking shall conform to the Statement of Work (see 6.2.1).

6. NOTES

6.1 Intended use. The water test device described in this specification is intended to be used to determine whether ther is permeation of water through the CWU-62/P anti-exposure coverall cloth or seam construction.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Type, Government part number and quantity desired.

c. Whether first article inspection is waived (see 4.3.1).

Source: https://assist.dla.mil -- Downloaded: 202610-23T11:13Z
Check the source to verify that this is the currentversion before use.

d. Name and address of the first article inspection laboratory and the Government activity responsible for conducting the inspection program (see 4.3.1).

e. Selection of applicable levels of packaging/preservation and packing (see 5.1).

f. Items of data required (see 6.2.2).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph no.	Data requirements	Applicable DID no.
4.3.19	First article inspection reports	DI-T-5329

(Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and forms Center or as directed by the contracting officer.)

6.3 First article. When first article inspection is required, the water test devices will be tested and should be a preproduction item. The first article should consist of the samples specified in 4.3.1. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, test and approval of the first article.

Preparing activity:
Navy - AS

(Project 6635-N123)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.

TABLE I. Sample size, acceptance criteria and examinations of the water test devices and packaging.

Inspection	Sample size	Acceptance criteria
Visual examination	Every water test device	Reject any defective unit
Dimensional check	Inspection Level S-2	An acceptable quality level of 6.5 defects per 100 units
Packaging	Inspection Level S-2	An acceptable quality level of 2.5 defects per 100 units

TABLE II. List of defects for the visual examination of the water test devices.

1. Material imperfections - foreign matter embedded.
2. Surface - unclean, rough, misaligned, or containing any crack, nick, dent burr, sharp edge, sliver, abraded area, non specified hole, spot or stain, or other flaws.
3. Any component missing, malformed, fractured or otherwise damaged.
4. Any component loose or otherwise not securely retained.
5. Incorrect assembling or improper positioning of any component.
6. Any malfunctioning part such as lights, pump, switches or part that works with difficulty.
7. Faulty workmanship or other irregularities.
8. Marking - missing, insufficient, incorrect, illegible or not permanent.
9. Color not as specified.

TABLE III. List of dimensional defects for the assembled water test device.

Examine	Defect
Measure the water test device and all the visible materials and components.	Any measurement deviating from the dimensions and tolerances specified on the applicable drawings shall be enumerated as a dimensional defect.

Source: https://assist.dla.mil -- Downloaded: 202640-23T11:13Z
Check the source to verify that this is the current version before use.

TABLE IV. List of defects for packaging.

Item	Defects
Exterior and interior markings	Missing, incorrect, incomplete, illegible, of improper size, location, sequence or method of application; markings not the same on the interior and exterior containers.
Packaging and packing materials	Any non-conforming component; any component missing, damaged or otherwise defective.
Workmanship	Inadequate application of the components such as incomplete closure of the unit package, intermediate package, container flaps, loose strappings, etc.; bulging or distortion of any container.
Exterior and interior weight or content	Number per container is more or less than required; gross or net weight exceeds the requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-W-85635(AS)	WATER TEST DEVICE, ANTI-EXPOSURE COVERALL

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T11:13Z
Check the source to verify that this is the current version before use.