MILITARY SPECIFICATION SHEET

WINCH, DRUM, POWER OPERATED (SADDLE WINCH TYPES 5.0-S-1D AND 5.0-S-2D)

The complete requirements for procuring the winches described herein shall consist of this document and the issue in effect of MIL-W-17265.

1. SCOPE

1.1 Scope. - This specification covers the detail requirements for saddle winches.

1.2 Classification. - Winches shall be classified in accordance with the following types as specified (see 6.1).

Type 5.0-S-1D - Single drum saddle winches rated 5000 pounds at 330 feet per minute.

Type 5.0-S-2D - Double drum saddle winches rated 5000 pounds at 330 feet per minute.

2. APPLICABLE DOCUMENTS

2.1 The following specifications of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS
MILITARY

MIL-W-17265 - Winch, Drum, Power Operated

(Copies of specifications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Drums. - Each drum for winch types 5.0-S-1D and 5.0-S-2D shall be designed for the following:

(a) Stowage capacity for 600 feet of 3/4 inch wire rope. The breaking strength of the wire rope is 48,600 pounds.

FSC 3950

Source: https://assist.dla.mil -- Downloaded: 202640-18T09:54Z
Check the source to verify that this is the current version before use.

(b) Barrel diameter of 24 inches, plus or minus 1/2 inch.

(c) Distance between flanges shall be 15 inches, plus or minus 1/2 inch.

3.2 Gypsy heads. - Winch types 5.0-S-1D and 5.0-S-2D shall be provided with one gypsy head.

3.3 Wire rope lead. - The wire rope shall lead from top of the winch drum on winch types 5.0-S-1D and 5.0-S-2D over the prime mover. The design shall be such that the wire rope may be led from the first layer of the drum over the prime mover at an angle of at least seven and one-half degrees below the horizontal.

3.4 Rated line pull and line speed. - Rated line pull and line speed for winch types 5.0-S-1D and 5.0-S-2D shall be as follows:

(a) Rated line pull - 5000 pounds on the average layer of the drum.
(b) Rated line speed - 300 feet per minute.

3.5 Duty. - Type 5.0-S-1D and 5.0-S-2D winches shall be designed to permit continuous operation for a period of six hours. A normal operating cycle will consist of 10 seconds at rated speed rated load; 20 seconds at idle; 10 seconds at half speed and rated load; and 20 seconds at idle shall be used during this six hour period.

3.5.1 Name plate ampere rating of the electric motor shall not be exceeded by more than twenty-five percent when the winch is being operated at rated load and rated speed (constant velocity), temperature rise shall not exceed name plate permissible temperature rise when the winch is operated at the duty cycle and period specified in 3.5.

3.5.2 Thermal overload shall be indicated by energizing a master panel indicator light through a thermal heating device (see Para 3.22.16.7, MIL-W-17265) in either the motor or the motor controller. The indicator light shall be per para 3.22.13.5, MIL-W-17265. The device shall not de-energize the motor.

3.6 Size and weight. - The winch shall be as compact and light as is consistent with adequate strength and rigidity. Weight and size shall not exceed the following:

(a) Type 5.0-S-1D Winch
  (1) Maximum weight - 10,500 pounds
  (2) Maximum width (across drums) with gypsy head installed - 80 inches
  (3) Maximum length (perpendicular to drum) - 104 inches
  (4) Maximum height - 60 inches

(b) Type 5.0-S-2D Winch
  (1) Maximum weight - 14,000 pounds
  (2) Maximum width (across drums) with gypsy head installed - 100 inches

Source: https://assist.dla.mil -- Downloaded: 202610-18T09:54Z
Check the source to verify that this is the current version before use.

(3) Maximum length
(perpendicular to drum) - 104 inches
(4) Maximum height - 60 inches

6. NOTES

6.1 The ordering data shall include the following:

(a) Title, number and date of this specification.

(b) Type of winch required (see 1.2).

Preparing activity:

NAVY - SH

(Project 3950-N077Sh

Source: https://assist.dla.mil -- Downloaded: 202610-18T09:54Z
Check the source to verify that this is the current version before use.