MILITARY SPECIFICATION

# WINCH, DRUM, POWER OPERATED (GENERAL WINCHES, TYPE 9.0-G-1D, AND TYPE 7.4-G-1D)

The complete requirements for procuring the winches described herein shall consist of this document and the issue in effect of MIL-W-17265.

## 1. SCOPE

1.1 Scope - This specification covers the detail requirements for hoisting winches.

1.2 Classification. Winches shall be classified in accordance with the following types as specified (see 6.1):

Type 9.0-G-1D - Single drum hoisting winches rated 9000 pounds at 180 feet per minute.
Type 7.4-G-1D - Single drum vanging and burtoning winches rated at 7400 pounds at 220 feet per minute.

## 2. APPLICABLE DOCUMENTS

2.1 The following document of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY
MIL-W-17265 - Winch, Drum, Power Operated.

(Copies of specifications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS

3.1 Drums. Each drum for winch types 9.0-G-1D and 7.4-G-1D shall be designed for the following:

(a) Stowage capacity for 600 feet of 3/4 inch wire rope. The breaking strength of the wire rope is 48,600 pounds.
(b) Barrel diameter of 24 inches, plus or minus 1/2 inch.
(c) Distance between flanges shall be 15 inches, plus or minus 1/2 inch.

3.2 Gypsy heads. Winch type 9.0-G-1D shall be provided with one gypsy head.

3.3 Wire rope lead. The wire rope shall lead from top of the winch drum on winch types 9.0-G-1D and 7.4-G-1D over the prime mover. The design shall be such that the wire rope may be led from the first layer of the drum over the prime mover at an angle of at least seven and one-half degrees below the horizontal.

3.4 Rated line pull and line speed. Rated line pull and line speed for the various winch types shall be as follows:

(a) Type 9.0-G-1D
  (1) Rated line pull—9000 pounds on the average layer of the drum.
  (2) Rated line speed—180 feet per minute.
(b) Type 7.4-G-1D
  (1) Rated line pull—7400 pounds on the average layer of the drum.
  (2) Rated line speed—220 feet per minute.



Source: https://assist.dla.mil -- Downloaded: 20261O-18T09:54Z
Check the source to verify that this is the current version before use.

3.5 Duty. The winch types specified in 1.2 shall be designed to permit continuous operation for a period of twelve hours. A normal operation cycle will consist of 12 seconds at rated speed rated load; 12 seconds at idle; 24 seconds at half-speed and rated load; and 12 seconds at idle.

3.5.1 Name plate ampere rating of the electric motor shall not be exceeded by more than twenty-five percent when the winch is being operated at rated load and rated speed (constant velocity). temperature rise shall not exceed name plate permissible temperature rise when the winch is operated at the duty cycle and period specified in 3.5.

3.6 Size and weight. The winch shall be as compact and light as is consistent with adequate strength and rigidity. Weight and size shall not exceed the following:

(a) Type 9.0-G-1D
  (1) Maximum weight - 10,500 pounds.
  (2) Maximum width (across drum) with gypsy head installed - 80 inches.
  (3) Maximum length (perpendicular to drum) - 104 inches.
  (4) Maximum height - 60 inches.

(b) Type 7.4-G-1D
  (1) Maximum weight - 10,000 pounds.
  (2) Maximum width (across drum) with shaft caps installed - 70 inches.
  (3) Maximum length (perpendicular to drum) - 104 inches.
  (4) Maximum height - 60 inches.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality conformance inspection. Quality conformance inspection shall be in accordance with MIL-W-17265.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-W-17265.

6. NOTES

6.1 Ordering data. Ordering data shall be as specified in section 6 of MIL-W-17265.

Preparing activity:
Navy - SH
(Project 3950-N0117)



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:54Z
Check the source to verify that this is the current version before use.