MILITARY SPECIFICATION

WINCH, DRUM, POWER OPERATED, (SADDLE WINCH, INDEPENDENTLY OPERATED DRUMS, TYPE 5.0-S-2ID)

1. SCOPE

1.1 Scope. This specification covers the detail requirements for type 5.0-S-2ID, double drum saddle winches with independently operated drums rated 5,000 pounds at 260 feet per minute.

2. APPLICABLE DOCUMENTS

2.1 The following specifications of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY
MIL-W-17265 - Winch, Drum, Power Operated.

(Copies of specifications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General requirements. Winch drum power operated, type 5.0-S-2ID shall be in accordance with MIL-W-17265, except as specified herein.

3.2 Construction. The double drum saddle winch shall consist of two separate winch units mounted on a single bedplate. Each unit shall be independently operated and shall have its own power unit, air-oil cooler and operating controls.

3.2.1 Drums. Each drum for winch type 5.0-S-2ID shall be designed for the following:

(a) Stowage capacity for 600 feet of 1/2-inch wire rope. The breaking strength of the wire rope is 25,200 pounds.
(b) Barrel diameter of 24-inches, plus or minus 1/2-inch.
(c) Distance between flanges shall be 10-inches, plus or minus 1/2-inch.

3.3 Gypsy heads. Winch type 5.0-S-2ID shall be provided with two gypsy heads, one mounted on the outboard side of each winch drum unit.

3.4 Wire rope lead. The wire rope shall lead from the top of each winch drum and over the prime mover on winch type 5.0-S-2ID. The design shall be such that the wire rope may be led from the first layer of each drum over its prime mover at an angle of at least seven and one-half degrees below the horizontal.

3.5 Rated line pull and line speed. Rated line pull and line speed for each drum of winch type 5.0-S-2ID shall be as follows:

(a) Rated line pull - 5000 pounds on the average layer of the drum.
(b) Rated line speed - 260 feet per minute.

3.6 Gearing. The gear drives provided shall have a service factor of 1.25.

3.7 Bedplate. A single bedplate shall be provided for the double drum saddle winch.

3.8 Hydraulic transmission bedplate. The bedplate for each hydraulic transmission package shall be designed so that each package can be readily installed and removed from the winch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T09:54Z
Check the source to verify that this is the current version before use.

3.9 Duty. The winch type specified in 1.2 shall be designed to permit continuous operation for a period of six hours. A normal operating cycle will consist of 10 seconds at rated speed and rated load; 20 seconds at idle; 10 seconds at half-speed and rated load; and 20 seconds at idle.

3.9.1 Name plate ampere rating of the electric motor shall not be exceeded by more than fifty percent when the winch is being operated at rated load and rated speed (constant velocity), temperature rise shall not exceed name plate permissible temperature rise when the winch is operated at the duty cycle and period specified in 3.9.

3.9.2 Thermal overload shall be indicated by energizing a master panel indicating light through a thermal heating device (see thermal requirements of MIL-W-17265) in either the motor or the controller. The indicator light shall be in accordance with the illumination requirements of MIL-W-17265. This device shall not de-energize the motor.

3.10 Control system. A separate control system shall be provided for the independent operation of each drum unit.

3.10.1 The winch control levers shall be designed so that they will allow one winch operator to operate each control or both simultaneously with one hand.

3.11 Size and weight. The winch shall be as compact and light as is consistent with adequate strength and rigidity. Weight and size shall not exceed the following:

(a) Type 5.0-S-2ID
  (1) Maximum weight - 17,000 pounds.
  (2) Maximum width (across drums) with gypsy heads installed - 140 inches.
  (3) Maximum length (perpendicular to drum) - 100 inches.
  (4) Maximum height - 60 inches.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality conformance inspection. Quality conformance inspection shall be in accordance with MIL-W-17265.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-W-17265.

6. NOTES

6.1 Ordering data. Ordering data shall be as specified in section 6 of MIL-W-17265.

Preparing activity:
Navy - SH
(Project 3950-N0119)

Source: https://assist.dla.mil -- Downloaded: 202610-18T09:54Z
Check the source to verify that this is the currentversion before use.