NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/14D
30 September 1996
SUPERSEDING
MIL-R-41819/14C
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, LETTER “W”

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Red Brass or Nickel Silver

DIMENSIONS:
HEIGHT: 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm)
WIDTH: 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm)
THICKNESS (At Thickest Point): 0.055 inch ± 0.005 inch (0.140 cm ± 0.012 cm)

FINISH: Nickel Plated (Red Brass only), Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

NOTES:
1. Ribbon attachment "W" shall be die cut.

2. The attaching device shall be two single post type prongs. The prongs shall be located on the reverse side of the ribbon attachment at the intersection of each outside leg of the "W" and the horizontal center line.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:50Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:50Z
Check the source to verify that this is the current version before use.