NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/20D
30 September 1996
SUPERSEDING
MIL-R-41819/20C
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, ADDITIONAL AWARDS, NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL:
-1: Red Brass or Nickel Silver
-2: Red Brass

DASH NO.
-1: 2ND AWARD, SILVER
-2: 3RD AWARD, GOLD

FINISH:
-1: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.
-2: Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:52Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT: 5/16 inch (0.79 cm) (REF)
WIDTH: 3/8 inch (0.95 cm) (REF)
THICKNESS (At Thickest Point: 0.063 inch $\pm$ 0.005 inch (0.160 cm + 0.012 cm - $\overline{0}$)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be a staple type prong. The prong shall be located on the vertical center line on the reverse side of the ribbon attachment.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:52Z
Check the source to verify that this is the current version before use.