INCH-POUND


MIL-DTL-41819/20E
11 February 2013
SUPERSEDING
MIL-DTL-41819/20D
30 September 1996


DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENTS, ADDITIONAL AWARDS, NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-R-41819.





DASH NO.
-1: 2ND Award, Silver
-2: 3rd Award, Gold

MATERIAL:
-1: Red Brass 85/15 (UNS Alloy No.C-230) or Nickel Silver 65/15 (UNS Alloy C-752)
-2: Red Brass 85/15 (UNS Alloy No.C-230)

FINISH:
-1: Nickel Plated (C-230 only) Silver Plated, Oxidized, Buffed Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 14.
-2: 24K Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:52Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT: 5/16 inch (REF)
WIDTH: 3/8 inch (REF)
THICKNESS (At thickest point): 0.063 ± 0.005 inch

ATTACHMENT DEVICE:
1. The attaching device shall be a staple type prong

2. The prong shall be located on the vertical center line on the reverse side of the ribbon attachment.

NOTES:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2013-119)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:52Z
Check the source to verify that this is the current version before use.