NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/7J
12 May 1997
SUPERSEDING
MIL-DTL-41819/7H
30 September 1996

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, STAR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.		USER
-1:	Bronze (3/16 inch) (0.48 cm), Single	A,N,AF,MC,CG
-2:	Silver (3/16 inch) (0.48 cm), Single	A,N,AF,MC,CG
-3:	Silver (5/16 inch) (0.79 cm), Single	A,N,AF,MC,CG
-4:	Gold (5/16 inch) (0.79 cm), Single	N,AF,MC,CG
-5:	Bronze (3/16 inch) (0.48 cm), Double	A,N,AF,MC,CG
-6:	Bronze (3/16 inch) (0.48 cm), Triple	A,N,AF,MC,CG
-7:	Bronze (3/16 inch) (0.48 cm), Quadruple	A,N,AF,MC,CG
-8:	Silver (3/16 inch) (0.48 cm), Double	A,N,AF,MC,CG
-9:	Silver (3/16 inch) (0.48 cm), Triple	A,N,AF,MC,CG
-10:	Silver (3/16 inch) (0.48 cm), Quadruple	A,N,AF,MC,CG
-11:	Gold (5/16 inch) (0.79 cm), Double	N, MC,CG
-12:	Gold (5/16 inch) (0.79 cm), Triple	N, MC,CG
-13:	Gold (5/16 inch) (0.79 cm), Quadruple	N, MC,CG
-14:	Bronze (5/16 inch) (0.79 cm), Single	AF

MATERIAL: Red brass or Gilding Metal

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:47Z
Check the source to verify that this is the current version before use.

FINISH:
-1, -5, -6, -7, 14: Copper Flash (Red Brass only), Oxidized, Relieved
-2, -3, -8 thru -10: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
-4, -11 thru -13: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall):
-1, -2, -5 thru -10: 3/16 inch (0.48 cm) REF
-3, -4, -11 thru -14: 5/16 inch (0.79 cm) REF
WIDTH (Overall):
-1, -2: 3/16 inch (0.48 cm) REF
-3, -4, -14: 5/16 inch (0.79 cm) REF
-5, -8: 13/32 inch (1.03 cm) REF
-6, -9: 5/8 inch (1.59 cm) REF
-7, -10: 13/16 inch (0.48 cm) REF
-11: 19/32 inch (1.51 cm) REF
-12: 15/16 inch (2.38 cm) REF
-13: 1-3/16 inch (3.02 cm) REF
THICKNESS:
-1, -2, -5 thru -10: 1/16 inch + 1/64 - 0 (0.16 cm + 0.04 cm - 0)
-3, -4, -11 thru -14: 5/64 inch + 1/64 - 0 (0.20 cm + 0.04 cm - 0)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be located as follows:

1 thru -4, -14: Staple type prong centered on the back of the star.
-5, -8, -11: One prong centered on the back of each star.
-6, -9, -12: One prong centered on the back of the first and second star beginning from the right when viewed from the reverse with one point of the star facing up.
-7, -10: One prong centered on the back of the first and third stars beginning from the right when viewed on the reverse side with one point of the star facing up.
-13: One prong centered on the back of each interior star.

3. Dash Numbers -5 through -13 are optional items and were developed for commercial sale.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45
Navy - NU
Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0891)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:47Z
Check the source to verify that this is the current version before use.