INCH-POUND

MIL-DTL-41819/7K
13 June 2003
SUPERSEDING
MIL-DTL-41819/7J
12 May 1997

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, STAR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-41819.

The various stars and star configurations addressed by this specification sheet are listed in the table below:

DASH NO.	TYPE STAR	CONFIGURATION	HEIGHT	OVERALL WIDTH (STAR POINT TO STAR POINT)	USER
-1	Bronze	Single	3/16"	3/16"	A, N, AF, MC, CG
-2	Silver (polished)	Single	3/16"	3/16"	A, N, AF, MC, CG
-3	Silver (polished)	Single	5/16"	5/16"	A, N, AF, MC, CG
-4	Gold (polished)	Single	5/16"	5/16"	N, AF, MC, CG
-5	Bronze	Double	3/16"	13/32"	A, N, AF, MC, CG
-6	Bronze	Triple	3/16"	5/8"	A, N, AF, MC, CG
-7	Bronze	Quadruple	3/16"	13/16"	A, N, AF, MC, CG
-8	Silver (polished)	Double	3/16"	13/32"	A, N, AF, MC, CG
-9	Silver (polished)	Triple	3/16"	5/8"	A, N, AF, MC, CG
-10	Silver (polished)	Quadruple	3/16"	13/16"	A, N, AF, MC, CG
-11	Gold (polished)	Double	5/16"	19/32"	N, MC, CG
-12	Gold (polished)	Triple	5/16"	29/32"	N, MC, CG
-13	Gold (polished)	Quadruple	5/16"	1-3/16"	N, MC, CG
-14	Bronze	Single	5/16"	5/16"	AF
-15	Silver (matte)	Single	5/16"	5/16"	A, N, AF, MC, CG
-16	Silver (matte)	Double	5/16"	19/32"	A, N, AF, MC, CG
-17	Silver (matte)	Triple	5/16	29/32"	A, N, AF, MC, CG
-18	Silver (matte)	Quadruple	5/16"	1-3/16"	A, N, AF, MC, CG
-19	Gold (matte)	Single	5/16"	5/16"	A, N, AF, MC, CG
-20	Gold (matte)	Double	5/16"	19/32"	A, N, AF, MC, CG
-21	Gold (matte)	Triple	5/16"	29/32"	A, N, AF, MC, CG
-22	Gold (matte)	Quadruple	5/16"	1-3/16"	A, N, AF, MC, CG

MATERIAL: Red Brass or Gilding Metal

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:47Z
Check the source to verify that this is the current version before use.

FINISH:

-1, -5, -6, -7, -14: Copper Flashed (Red Brass only), Oxidized, Relieved
-2, -3, -8, -9, -10: Nickel Plated, Mirror-like Polished, and shall match The Institute of Heraldry Metal Finish Chip Number 16
-4, -11, -12, -13: Gold Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 6.
-15 thru -18: Nickel Plated, Matte Finished, and shall match TIOH Metal Finish Chip Number 17.
-16 thru -22: Gold Plated, Matte Finished, and shall match TIOH Metal Finish Chip Number 7.

THICKNESS:

-1, -2, -5 thru -10 (3/16 inch stars): 1/16 inch ± 1/64 inch
-3, -4, -11 thru -22 (5/16 inch stars): 5/64 inch ± 1/64 inch

NOTES:

1. The height and width measurements (shown on the table on page 1) are REF and refer to measurements taken from the Government furnished hub or die.

2. Attaching device shall be of the type and at the location noted below:

-1 thru -4, -14, -15, -19: Staple type prong centered on the back of the star.
-5, -8, -11, -16, -20: One prong centered on the back of each star.
-6, -9, -12, -17, -21: One prong centered on the back of the first and second star beginning from the right when viewed from the reverse with one point of the star facing up.
-7, -10: One prong centered on the back of the first and third stars beginning from the right when viewed on the reverse side with one point of the star facing up.
-13, -18, -22: One prong centered on the back of each interior star.

3. -5 thru -13, -16 thru -18, and -20 thru -22 are optional items and were developed for commercial sale.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 11
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0124/001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:47Z
Check the source to verify that this is the current version before use.