MIL-A-9597B(USAF)
AMENDMENT 2

1 AUGUST 1978
SUPERSEDING
AMENDMENT 1
1 November 1966

MILITARY SPECIFICATION

ANTENNA AT-309 ( )/GPX

This amendment forms a part of Military Specification MIL-A-9597B(USAF) dated 10 October 1963.

PAGE 1

*2.1 SPECIFICATIONS

Under MILITARY:

Delete: "MIL-T-4807 Tests, Vibration and Shock Ground Electronic Equipment (Requirements For)"

Delete: "MIL-T-9107 Test Reports. Preparation of"

STANDARDS

Under Military:

add: "MIL-STD-831 Test Reports, Preparation of"

PAGE 4

3.5.4 - Delete and substitute:
"3.5.4 Vertical pattern. The vertical pattern shall have a 3DB beamwidth of 52 degrees ± 2 degrees at 1030 MHz and a 3DB beamwidth of at least 45 degrees at 1090 MHz. The main lobe of the vertical pattern shall be no more than 6DB below maximum at the elevation angle of +38 degrees for any frequency within the antenna band. The envelope of the vertical pattern shall be a smooth curve with no reversal in direction from the maximum radiation point to the points at least 20DB below maximum, at plus and minus elevation angles. Energy at the +90 degree elevation angle shall be at least 20DB below the main lobe maximum at 1030 MHz and 1090 MHz. Energy at elevation angles greater than - 90 degrees and + 135 degrees shall be at least 24DB below the maximum of the main beam across the band and at least 26DB below the maximum of the main beam at 1030 MHz.

PAGE 5

3.5.6, line 3, delete: "0.5DB" and substitute "1.0DB"

3.5.7, line 1, delete: "MI" and substitute "HN"

FSC 5895

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:01Z
Check the source to verify that this is the current version before use.

3.7, line 1, delete: "325" and substitute "350"

PAGE 6

*4.4.2, line 3, delete: "MIL-T-9107" and substitute "MIL-STD-831"

PAGE 9

*4.6.5, line 2, delete: "MIL-T-4807" and substitute "MIL-STD-810"

a. Vibration test: Delete "Method 1" and substitute "METHOD 514.2, Procedure X.

b. Delete "Bounce test" and substitute "Transit drop test" Delete "Method 2" and substitute "Method 516.2, Procedure II."

PAGE 10

Add a new para as follows:

*6.4 Reclaimed materials shall be utilized to the maximum extent possible as cited in MIL-STD-961 and MIL-STD-962 within the quality limits required by this document and to fulfill compliance with the Resource Conservation/ Recovery Act of 1976 (Public Law 94-580 dated 21 Oct 76).

NOTE: The margins of this amendment are marked with an asterick to indicate where change from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99

(Project 5895 - F268)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:01Z
Check the source to verify that this is the current version before use.