INCH-POUND
MIL-DTL-9814C (USAF)
5 June 1996
SUPERSEDING
MIL-S-9814B (USAF)
26 July 1993

DETAIL SPECIFICATION

STAND, CABLE REWIND, REVERSIBLE, THU-4/E

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for a reversible cable rewind stand, designated THU-4/E.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 or 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the applicable issues are those cited in the solicitation.

DRAWINGS

AIR FORCE

61J10905 Stand, Cable Rewind, Reversible THU-4/E

(Copies of drawings are available from the Ogden Air Logistics Center, OO-ALC\TIEDD, 6032 Fir Avenue, Hill AFB, Utah 84056-5609.)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Ogden ALC/LIRF, 6041 Gum Lane, Hill Air Force Base, Utah 84056-5826, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:05Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. A conflict between this document and its related associated specifications or specification sheets should be brought to the attention of the issuer of the solicitation.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Design. The rewind stand shall conform to Drawing 61J10905.

3.3 Performance characteristics.

3.3.1 Cable Transfer. The rewind stand shall be capable of transferring cable from the contractor shipping spool to the cable spool , Federal Stock Number 6920-00-125-5284, which is removable from the RMU-10/A tow reel pod, a component of the A/A37U-15 tow target system. The rewind stand shall be capable of transferring 2200 feet of cable in 30 minutes.

3.3.2 Reverse winding. The rewind stand shall be capable of transferring cable from the RMU-10/A spool back to the contractor shipping spool.

3.3.3 Cable tension. Cable shall be wound on the RMU-10/A spool under controlled tension of 50 ± 15 pounds.

3.3.4 Cable counter. A means shall be provided to visually indicate, to four digits, with the least significant digit being units, the number of feet of cable that has been wound onto, or unwound from, the rewind stand. The device shall be manually resettable.

3.4 Supportability. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable.

3.5 Identification. Equipment, assemblies, containers, and parts shall be marked for identification.

3.6 Safety. The rewind stand shall be functional without sharp edges, burrs, or protrusions that might injure personnel who come into contact with the rewind stand.

3.7 Workmanship. The cable rewind stand, including all parts and equipment, shall be constructed in accordance with commonly accepted industrial workmanship standards.

3.8 Government-furnished property. When specified in the contract or purchase order (see 6.2), the Government will furnish the following to the contractor upon request, for use in fabrication of the rewind stand system:

ITEM NO.	STOCK NO.	PART NO.	ITEM DESCRIPTION	QUANTITY
1	4010-00-202-2087	MIL-S-5765	Strand Armored Tow Cable (11/64 inch)	1 10,000 ft reel
2	6920-00-125-5284	29-0429-1	Cable Spool	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:05Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)

b. Conformance inspection (see 4.3)

4.2 First article inspection.

4.2.1 First article inspection sample. The first article test sample shall be the first production item.

4.2.2 First article inspection requirements. First article inspection shall consist of all examinations and tests described in 4.4.

4.3 Conformance inspection. Each rewind stand shall be subjected to the individual examinations and tests as described in 4.4.

4.4 Methods of inspection.

4.4.1 Examination. Each target system shall be examined for compliance with the requirements specified in 3.2, 3.5, and 3.6. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirement, or presence of one or more defects preventing, or lessening, maximum efficiency, shall constitute cause for rejection.

4.4.2 Cable transfer test. Each rewind stand shall be operated to determine compliance with 3.3.1 and 3.3.2. Using a 10,000 foot supply reel of 11/64-inch diameter cable and a RMU-10/A tow reel pod spool, the rewind stand shall be used to transfer 2200 feet of cable in 30 minutes from the supply spool to the RMU-10/A spool and back again to the supply spool. This operation shall be accomplished five times to verify compliance with 3.3.1 and 3.3.2.

4.4.3 Cable tension test. The cable tension during winding on to the RMU-10/A spool shall be measured to determine compliance with 3.3.3.

4.4.4 Cable counter test. The cable counter shall be visually observed during all cable winding testing to determine compliance with 3.3.4.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point packaging activity within the Military Department or Defense Agency. Packaging data retrieval is available from the managing Military Department or Defense Agency automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature which may be helpful, but is not mandatory.)

6.1 Intended use. The rewind stand is intended for use as ground support equipment for the RMU-10/A tow reel pod, a component of the A/A37U-15 gunnery tow target system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:05Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2).

c. Packaging requirements (see 5.1).

d. When first article is required (see 3.1).

6.3 Government-furnished property. The contracting officer should arrange to furnish the property listed in 3.7.

6.4 Subject term (key word) listing.

Cable
Rewind

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 70

Project NR 6920-0143

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-DTL-9814C	2. DOCUMENT DATE (YYMMDD) 960605

3. DOCUMENT TITLE

STAND, CABLE REWIND, REVERSIBLE THU-4/E

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. Organization	
c. ADDRESS *(Include zip code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME **Pete Schwager, LIRBA**	b. TELEPHONE *(Include Area Code)* (1) Commercial **(801) 777-5603** (2) DSN **458-5603**
c. ADDRESS *(Include Zip Code)* ***6041 Gum Lane*** ***Hill Air Force Base, Utah*** ***84056-5826***	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 DSN 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:05Z
Check the source to verify that this is the current version before use.