The documentation and process conversion measures necessary to comply with this document shall be completed by 27 October 2007.

INCH-POUND

MIL-PRF-19500/511G
27 July 2007
SUPERSEDING
MIL-PRF-19500/511F
8 April 2005

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, PNP, SILICON, SWITCHING
TYPE 2N4261, 2N4261UB, 2N4261UBC JAN, JANTX, JANTXV AND JANS, JANHC AND JANKC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for PNP silicon, switching transistors. Four levels of product assurance are provided for each encapsulated device type. Two levels for unencapsulated die as specified in MIL-PRF-19500.

* 1.2 Physical dimensions. See figure 1 (TO-72), figure 2 and 3 (UB and UBC) and figure 4 (JANHC, JANKC).

1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C.

P_T T_A = +25°C (1)	$R_{\theta JA}$	V_{CBO}	V_{CEO}	V_{EBO}	I_C	T_J	T_J and T_{STG}
mW	°C/mW	V dc	V dc	V dc	mA dc	°C	°C
200	0.860	15	15	4.5	30	200	-65 to +200

(1) Derate linearly 1.14 mW/°C above T_A = +25°C.

1.4 Primary electrical characteristics. Unless otherwise specified, T_A = +25°C.

	h_{FE1} (1)	h_{FE2} (1)	h_{FE3} (1)	$\|h_{fe2}\|$	$r_b' C_c$	Switching	
	V_{CE} = 1.0 V dc I_C = 1 mA dc	V_{CE} = 1.0 V dc I_C = 10 mA dc	V_{CE} = 1.0 V dc I_C = 30 mA dc	V_{CE} = 10 V dc I_C = 10 mA dc f = 100 MHz	V_{CE} = 4.0 V dc I_C = 5 mA dc f = 31.8 MHz	t_{on}	t_{off}
					ps	ns	ns
Min	25	30	20	20			
Max		150			60	2.5	3.5

See note on next page.

Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dscc.dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics at T_A = +25°C, unless otherwise specified - Continued.

	$V_{CE(sat)1}$ I_C = 1 mA dc I_B = 0.1 mA dc	$V_{CE(sat)2}$ I_C = 10 mA dc I_B = 1.0 mA dc	V_{BE1} I_C = 1 mA dc V_{CE} = 1 V dc	V_{BE2} I_C = 10 mA dc V_{CE} = 1 V dc	C_{obo} V_{CB} = 4 V dc I_E = 0 100 kHz ≤ f ≤ 1 MHz
	V dc	V dc	V dc	V dc	PF
Min					
Max	0.15	0.35	0.8	1.0	2.5

(1) Pulsed (see 4.5.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.


3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.


Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.178	.195	4.52	4.95	5
CH	.170	.210	4.32	5.33	
HD	.209	.230	5.31	5.84	5
LC	.100 TP		2.54 TP		7, 8
LD	.016	.021	.406	.533	7, 8
LL	.500	.750	12.70	19.05	7, 8
LU	.016	.019	.41	.48	
L_1		.050		1.27	
L_2	.250		6.35		
P	.100		2.54		
Q		.040		1.02	5
TL	.028	.048	.71	1.22	
TW	.036	.046	.91	1.17	
r		.007		.18	
α	45° TP				



NOTES:
1. Dimension are in inches.
2. Millimeters are given for general information only.
3. Beyond r (radius) maximum, TH shall be held for a minimum length of .011 (0.28 mm).
4. Dimension TL measured from maximum HD.
5. Body contour optional within zone defined by HD, CD, and Q.
6. Leads at gauge plane .054 +.001 -.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within .007 inch (0.18mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC.
7. Dimension LU applies between L_1 and L_2. Dimension LD applies between L_2 and LL minimum. Diameter is uncontrolled in L_1 and beyond LL minimum.
8. All four leads.
9. Dimension r (radius) applies to both inside corners of tab.
10. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.
11. Lead 1 = emitter, lead 2 = base, lead 3 = collector, lead 4 = case (electrically connected).

FIGURE 1. Physical dimensions for 2N4261 (TO-72).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.




Ltr.	Dimensions				Note	Ltr.	Dimensions				Note
	Inches		Millimeters				Inches		Millimeters		
	Min	Max	Min	Max			Min	Max	Min	Max	
BH	.046	.056	1.17	1.42		LS1	.035	.040	0.89	1.02	
BL	.115	.128	2.92	3.25		LS2	.071	.079	1.80	2.01	
BW	.085	.108	2.16	2.74		LW	.016	.024	0.41	0.61	
CL		.128		3.25		r		.008		0.20	
CW		.108		2.74		r1		.012		0.31	
LL1	.022	.038	0.56	0.96		r2		.022		0.56	
LL2	.017	.035	0.43	0.89							

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Pad 1 = Base, Pad 2 = Emitter, Pad 3 = Collector, Pad 4 = Shielding connected to the lid.
4. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

FIGURE 2. Physical dimensions for 2N4261UB, surface mount.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Note
	Inches		Millimeters		
	Min	Max	Min	Max	
BH	.046	.071	1.17	1.80	
BL	.115	.128	2.92	3.25	
BW	.085	.108	2.16	2.74	
CL		.128		3.25	
CW		.108		2.74	
LL1	.022	.038	0.56	0.96	
LL2	.017	.035	0.43	0.89	

Symbol	Dimensions				Note
	Inches		Millimeters		
	Min	Max	Min	Max	
LS_1	.036	.040	0.91	1.02	
LS_2	.071	.079	1.81	2.01	
LW	.016	.024	0.41	0.61	
r		.008		.203	
r1		.012		.305	
r2		.022		.559	

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Hatched areas on package denote metallized areas
4. Pad 1 = Base, Pad 2 = Emitter, Pad 3 = Collector, Pad 4 = connected to the lid braze ring.
5. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

* FIGURE 3. Physical dimensions, surface mount (UBC version, ceramic lid).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.



NOTES:
1. Die size ..... .016 x .016 inch (0.406 mm x 0.406mm).
2. Die thickness..... .008 ±.0016 inch (0.203 mm ±0.041mm).
3. Base pad ..... .0021 x.0021 inch (0.053 mm x 0.053 mm).
4. Back metal ..... Gold, 6,500 ±1,950 Ang.
5. Backside..... Collector
6. Emitter pad..... .0021 x.0021 inch (0.053 mm x 0.053 mm).
7. Top metal ..... Aluminum, 14,500 ±2,500 Ang.
8. Back side..... Collector.
9. Glassivation..... SiO2, 7,500 ±1,500 Ang.

FIGURE 4. JANHC and JANKC (A-version) die dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

* 3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-19500 and as follows:

g_s ..... Noise source conductance.
P_o..... Oscillator, power output.
R_{BE} ..... External resistance, base to emitter.
UB and UBC..... Surface mount case outlines (see figures 2 and 3).

* 3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and figure 1 (TO-72), figure 2 and 3 (UB and UBC), and figure 4 (JANHC and JANKC) herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the contract or purchase order (see 6.2).

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.6 Electrical test requirements. The electrical test requirements shall be as specified in table I.

* 3.7 Marking. Marking shall be in accordance with MIL-PRF-19500. At the option of the manufacturer, marking may be omitted from the body of the UB and UBC package, but shall be retained on the initial container.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4.VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table I).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 JANHC and JANKC qualification. JANHC and JANKC qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.2 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

* 4.2.2.1 Group E thermal response. With extremely small junction devices such as this one, a true thermal impedance cannot be measured, only calculated. While “thermal response” has been substituted for “thermal impedance” herein, the terms, units and procedure as essentially unchanged. Each supplier shall submit a thermal response ($Z_{\theta JX}$) histogram of the entire qualification lot. The histogram data shall be taken prior to the removal of devices that are atypical for thermal response. Thermal response curves (from $Z_{\theta JX}$ test pulse time to $R_{\theta JX}$ minimum steady-state time) of the best device in the qual lot and the worst device in the qual lot (that meets the supplier proposed screening limit), or from the thermal grouping, shall be submitted. The optimal test conditions and proposed initial thermal response screening limit shall be provided in the qualification report. Data indicating how the optimal test conditions were derived for $Z_{\theta JX}$ shall also be submitted. The proposed maximum thermal response $Z_{\theta JX}$ screening limit shall be submitted. The qualifying activity may approve a different $Z_{\theta JX}$ limit for conformance inspection end-point measurements as applicable**.** Equivalent data, procedures, or statistical process control plans may be used for part, or all, of the above requirements. The approved thermal response conditions and limit for $Z_{\theta JX}$ shall be used by the supplier in screening and table I, subgroup 2. The approved thermal resistance conditions for $R_{\theta JX}$ shall be used by the supplier for conformance inspection. For product families with similar thermal characteristics based on the same physical and thermal die, package, and construction combination (thermal grouping), the supplier may use the same thermal response curves.

* 4.3 Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500)	Measurements	
	JANS	JANTX, JANTXV levels
3c	Thermal impedance, method 3131 of MIL-STD-750 (see 4.3.2).	Thermal impedance, method 3131 of MIL-STD-750 (see 4.3.2).
9	I_{CEX2} and h_{FE2}	Not applicable
11	I_{CEX2} and h_{FE2}; ΔI_{CEX2} = 100 percent of initial value or 1 nA dc, whichever is greater. Δh_{FE2} = ±15 percent of initial value.	I_{CEX2} and h_{FE2}
12	See 4.3.3.	See 4.3.3, 80 hours min.
13	Subgroup 2 and 3 of table I herein; ΔI_{CEX2} = 100 percent of initial value or 1 nA dc, whichever is greater. Δh_{FE2} = ±25 percent of initial value.	Subgroup 2 of table I herein; ΔI_{CEX2} = 100 percent of initial value or 2 nA dc, whichever is greater. Δh_{FE2} = ±25 percent of initial value.

(1) Shall be performed anytime after temperature cycling, screen 3a; and does not need to be repeated in screening requirements.

* 4.3.1 Screening (JANHC and JANKC). Screening of JANHC and JANKC die shall be in accordance with MIL-PRF-19500, "Discrete Semiconductor Die/Chip Lot Acceptance". Burn-in duration for the JANKC level follows JANS requirements; the JANHC follows JANTX requirements.

* 4.3.2 Thermal impedance (ΔV_{BE} measurements). The ΔV_{BE} measurements shall be performed in accordance with method 3131 of MIL-STD-750 using the guidelines in that method for determining V_H, V_{CE}, I_M, I_H, t_H, and t_{MD}. The ΔV_{BE} limit used in screen 3c and table I, subgroup 2 shall be set statistically by the supplier over several die lots and submitted to the qualifying activity for approval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

* 4.3.3 Power burn-in conditions. Power burn-in conditions are as follows: T_A = room ambient in accordance with the general requirements of MIL-STD-750 (see 4.5). V_{CB} = 10 V dc, P_T = 200 mW.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500, and table I herein. Electrical measurements (end-points) shall be in accordance with table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-VIa (JANS) of MIL-PRF-19500 and 4.4.2.1. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2. See 4.4.2.2 for JAN, JANTX, and JANTXV group B testing. Electrical measurements (end-points) for JAN, JANTX, and JANTXV shall be after each step in 4.4.2.2 and shall be in accordance with table I, subgroup 2 herein.

4.4.2.1 Group B inspection, table E-VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
B4	1037	V_{CB} = 10 V dc, 2,000 cycles, $t_{ON} = t_{OFF}$ = 3 minutes, $P_{D(ON)} = P_D$ max rated per 1.3; $P_{D(OFF)}$ = 0.
B5	1027	V_{CB} = 10 V dc, t = 1,000 hours minimum. P_D = maximum rated P_T (see 1.3), T_J = +150°C minimum, in addition, adjust T_A to achieve T_J. n = 45, c = 0.

4.4.2.2 Group B inspection, (JAN, JANTX, and JANTXV). Separate samples may be used for each step. In the event of a lot failure, the resubmission requirements of MIL-PRF-19500 shall apply. In addition, all catastrophic failures during CI shall be analyzed to the extent possible to identify root cause and corrective action.

Step	Method	Condition
1	1026	Steady-state life: Test condition B, 1,000 hours minimum, V_{CB} = 10 V dc; power shall be applied and T_A adjusted to achieve T_J = +150°C minimum, using a minimum of P_D = 75 percent of maximum rated P_T as defined in 1.3. n = 45 devices, c = 0.
2	1048	Blocking life: T_A = +150°C, V_{CB} = 80 percent rated voltage, 48 hours minimum. n = 45 devices, c = 0.
3	1032	High-temperature life (non-operating), t = 340 hours, T_A = +200°C. n = 22, c = 0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

4.4.2.3 Group B sample selection. Samples selected from group B inspection shall meet all of the following requirements:

a. For JAN, JANTX, and JANTXV samples shall be selected randomly from a minimum of three wafers (or from each wafer in the lot) from each wafer lot. For JANS samples shall be selected from each inspection lot. See MIL-PRF-19500.

b. Shall be chosen from an inspection lot that has been submitted to and passed table I, subgroup 2 conformance inspection. When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for life test (subgroups B4 and B5 for JANS, and group B for JAN, JANTX, and JANTXV) may be pulled prior to the application of final lead finish.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

Subgroup	Method	Condition
C2	2036	Test condition E; (not applicable for UB devices).
C5	3131	See 1.3 $R_{\theta JA}$.
C6	1026	V_{CB} = 10 V dc; P_T = 200 mW, time = 1,000 hrs, adjust T_A to achieve T_J = +150°C minimum. Not applicable to JAN, JANTX, and JANTXV levels.

4.4.3.3 Group C sample selection. Samples for subgroups in group C shall be chosen at random from any inspection lot containing the intended package type and lead finish procured to the same specification which is submitted to and passes table I tests herein for conformance inspection. When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for C6 life test may be pulled prior to the application of final lead finish. Testing of a subgroup using a single device type enclosed in the intended package type shall be considered as complying with the requirements for that subgroup.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table E-IX of MIL-PRF-19500 and as specified herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Collector base time constant. This parameter may be determined by applying an RF signal voltage of 0.5 volt (rms) across the collector base terminals, and measuring the ac voltage drop (V_{eb}) with a high impedance RF voltmeter across the emitter base terminals. With f = 31.8 MHz used for the 0.5 volt signal, the following computation applies: $r_b' C_c$: (ps) = 10 x Veb (millivolts).

4.5.3 Base cutoff current. This parameter shall be measured using method 3041 of MIL-STD-750, bias condition A. The value of the base to emitter cutoff current shall be read on the current meter inserted in the base circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

	Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
		Method	Conditions		Min	Max	
	Subgroup 1 2/						
	Visual and mechanical examination 3/	2071	n = 45 devices, c = 0				
	Solderability 3/ 4/	2026	n = 15 leads, c = 0				
	Resistance to solvents 3/ 4/ 5/	1022	n = 15 devices, c = 0				
	Temp cycling 3/ 4/	1051	Test condition C, 25 cycles. n = 22 devices, c = 0				
	Hermetic seal 4/ Fine leak Gross leak	1071	n = 22 devices, c = 0 Test conditions G or H Test conditions C or D				
	Electrical measurements 4/		Table I, subgroup 2				
	Bond strength 3/ 4/	2037	Precondition T_A = +250°C at t = 24 hrs or T_A = +300°C at t = 2 hrs n = 11 wires, c = 0				
*	De-cap internal visual	2075	n = 4, c = 0				
	Subgroup 2						
*	Thermal impedance	3131	See 4.3.2	ΔV_{BE}			mV
	Collector to emitter breakdown voltage	3011	Bias condition D, I_C = 10 mA dc.	$V_{(BR)CEO}$	15		V dc
	Collector to base cutoff current	3036	Bias Condition D, V_{CBO}= 15 V.	I_{CBO}		10	µA dc
	Emitter-base cutoff current	3061	Bias condition D, V_{EB} = 4.5 V dc.	I_{EBO}		10	µA dc
	Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 0.4 V dc. V_{CE} = 10 V dc	I_{CEX1}		50	nA dc
	Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 2.0 V dc V_{CE} = 10 V dc	I_{CEX2}		5.0	nA dc
	Base cutoff current		V_{BE} = 2.0 V dc; V_{CE} = 10 V dc, see 4.5.3.	I_{BEX}		5.0	nA dc
	Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc; I_C = 1.0 mA dc; pulsed (see 4.5.1).	h_{FE1}	25		
	Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc; I_C = 10 mA dc; pulsed (see 4.5.1).	h_{FE2}	30	150	

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued.						
Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc; I_C = 30 mA dc; pulsed (see 4.5.1).	h_{FE3}	20		
Base to emitter voltage (non-saturated)	3066	Test condition B; V_{CE} = 1.0 V dc; I_C = 1.0 mA dc.	V_{BE1}		0.8	V dc
Base to emitter voltage (non-saturated)	3066	Test condition B; V_{CE} = 1.0 V dc; I_C = 10 mA dc.	V_{BE2}		1.0	V dc
Collector to emitter saturated voltage	3071	I_C = 1.0 mA dc; I_B = 0.1 mA dc.	$V_{CE(sat)1}$		0.15	V dc
Collector to emitter saturated voltage	3071	I_C = 10 mA dc; I_B = 1.0 mA dc; pulsed (see 4.5.1).	$V_{CE(sat)2}$		0.35	V dc
Subgroup 3						
High-temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3041	Bias condition A; V_{BE} = 2.0 V dc V_{CE} = 10 V dc.	I_{CEX3}		5.0	µA dc
Low-temperature operation :		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 1.0 V dc I_C = 10 mA dc; pulsed (see 4.5.1).	h_{FE4}	15		
Subgroup 4						
Magnitude of common emitter small-signal short-circuit forward- current transfer ratio	3306	V_{CE} = 4.0 V dc; I_C = 5.0 mA dc; f = 100 MHz.	$\|h_{fe1}\|$	15		
Magnitude of common emitter small-signal short-circuit forward- current transfer ratio	3306	V_{CE} = 10 V dc; I_C = 10 mA dc; f = 100 MHz.	$\|h_{fe2}\|$	20		
Open capacitance (open circuit)	3236	V_{CB} = 4.0 V dc; I_E = 0; 100 kHz ≤ f ≤ 1.0 MHz.	C_{obo}		2.5	pF
Input capacitance (output open circuit)	3240	V_{EB} = 0.5 V dc; I_C = 0; 100 kHz ≤ f ≤ 1.0 MHz.	C_{ibo}		2.5	pF
Collector-base time constant		V_{CE} = 4.0 V dc; I_C = 5.0 mA dc; f = 31.8 MHz; see 4.5.2 and figure 5.	$r_b'C_{c1}$		60	ps

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued.						
Collector-base time constant		V_{CE} = 4.0 V dc; I_C = 10 mA dc; f = 31.8 MHz; see 4.5.2 and figure 5.	$r_b'C_{c2}$		50	ps
Pulse response:	3251	Test condition B, except test circuit and pulse requirements in accordance with figure 6 herein.				
Turn-on time		V_{CC} = 17 V dc; I_C = 10 mA dc.	t_{on}		2.5	ns
Turn-off time		V_{CC} = 17 V dc; I_C = 10 mA dc.	t_{off}		3.5	ns
Subgroups 5, 6 and 7						
Not applicable						


1/ For sampling plan (unless otherwise specified) see MIL-PRF-19500.
2/ For resubmission of failed test in subgroup 1 of table I, double the sample size of the failed test or sequence of tests. A failure in table I, subgroup 1 shall not require retest of the entire subgroup. Only the failed test shall be rerun upon submission.
3/ Separate samples may be used.
4/ Not required for JANS devices.
5/ Not required for laser marked devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

* TABLE II. Group E inspection (all quality levels) for qualification or re-qualification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles.	
Hermetic seal Fine leak Gross leak	1071	 Test conditions G or H Test conditions C or D	
Electrical measurements		See table I, subgroup 2 and 4.5.3 herein.	
Subgroup 2			45 devices c = 0
Intermittent life	1037	V_{CB} = 10 V dc; 6,000 cycles, t_{ON} = t_{OFF} = 3 minutes, $P_{D(ON)}$ = P_D max rated per 1.3; $P_{D(OFF)}$ = 0.	
Electrical measurements		See table I, subgroup 2 and 4.5.3 herein.	
Subgroup 4			Sample size N/A
* Thermal impedance curves		See 4.2.2.1.	
Subgroup 5			
Not applicable			
Subgroup 6			3 devices
ESD	1020		
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.




Procedure:

1. Set signal generator to 31.8 MHz and connect to “in” connector on test jig.
2. Connect low voltage dc power supplies as shown. A 1 k ohm resistor should be placed in series with the emitter power supply to prevent damage to transistors being tested.
3. Place transistor to be tested in socket. Set collector supply for V_{CE} = 4.0 V dc, and emitter supply for I_C as specified.
4. Connect RF voltmeter with unterminated probe adapter to “CAL” connector on test jig. Adjust signal generator until RF voltage is 0.5 volts. (Note: Decade switching of voltmeter should be accurate from 1 mV to 3 volts. If not, input voltage may be set using voltage dividers, utilizing lower scales of the RF voltmeter. If this is done, the voltage dividers should be left in place when the voltmeter is removed, as they constitute a load on the input of the circuit.
5. Remove RF voltmeter from “CAL” connector to “OUT” connector. Meter will now read $r_b' C_c$ as follows:

Meter range full scale	$r_b' C_c$ range
0.003 volts	10 to 30 ps
0.01 volts	30 to 100 ps
0.03 volts	100 to 300 ps

FIGURE 5. Collector base time constant test circuit (an equivalent circuit may be used).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.



NOTES:
1. The input waveform is supplied by a pulse generator with the following characteristics: Z_{OUT} = 50 ohms; PW = 30 ns; duty cycle ≤ 2 percent.
2. Resistors shall be noninductive types.
3. The dc power supplies may require additional bypassing in order to minimize ringing.

FIGURE 6. Switching time test circuit and waveforms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

* (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

* 6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. Product assurance level and type designator.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil.

6.4. Suppliers of JANHC and JANKC die. The qualified JANHC and JANKC suppliers with the applicable letter version (example JANHCA2N4261) will be identified on the QML.

Die ordering information	
PIN	Manufacturer
	34156
2N4261	JANHCA2N4261, JANKCA2N4261

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2007-040)

Review activities:
Air Force - 19, 71, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T02:37Z
Check the source to verify that this is the current version before use.