The documentation and process conversion measures necessary to comply with this amendment shall be completed by 7 December 2000.

INCH-POUND

MIL-PRF19500/680
7 September 2000

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, DUAL SCHOTTKY CENTER TAP
POWER RECTIFIER, SURFACE MOUNTED,
TYPE 1N6842U3, JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

1. SCOPE

1.1. Scope. This specification covers the performance requirements for silicon, dual Schottky power rectifier in a surface mount package. Four levels of product assurance are provided for each device types as specified in MIL-PRF-19500.

1.2. Physical dimensions. See figure 1 (U3).

1.3. Maximum ratings.

Type	V_{RWM}	I_O (1) T_C= +100 °C	I_{FSM} T_C =+25 °C T_p = 8.3 ms	C_J at 5 V	T_{STG}	T_J
	V	A dc	A (pk)	pF	°C	°C
1N6842	60	10	200	400	-65 to +150	-65 to +150

(1) Derate linearly at 200 mA/°C from T_J=T_C=+100°C to +150°C.

1.4. Primary electrical characteristics. $R_{\theta JC}$ = 2.8ºC/W maximum on each leg.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. BOX 3990, Columbus, OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1. General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2. Government documents.

2.2.1. Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

DEPARTMENT OF DEFENSE

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Document Automation and Production Services (DAPS), Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.3. Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1. General. The requirements for aquiring the product described herein shall consist of this document and MIL-PRF-19500.


3.2. Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3. Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4. Interface and physical dimensions. The requirements and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 (SMD.5) herein. The US government preferred system of measurement is the metric SI system. However, since this item was originally designed using inch-pound units of measurement, in the event of conflict between the metric and inch-pound units, the inch-pound units shall take precedence.

3.4.1. Polarity. Polarity and terminal configuration shall be in accordance with figure 1 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	0.111	0.122	2.82	3.10
B	0.291	0.301	7.39	7.65
C	0.395	0.405	10.03	10.29
D	0.281	0.291	7.14	7.39
E	0.220	0.230	5.59	5.84
F	0.115	0.125	2.92	3.18
G	0.090	0.100	2.29	2.54
H	0.125	0.135	3.68	3.94
I	0.073 TYP.	-	1.85 TYP.	-
J	0.083 TYP.	-	2.11 TYP.	-
K	0.005 TYP.		0.13 TYP.	-
L	0.015 TYP.	-	0.38 TYP.	-

NOTES:
1. Dimensions are in inch-pound.
2. Millimeters equivalents are given for general information only.
3. Terminal 1 is common cathode.
4. Terminal 2 is anode 1.
5. Terminal 3 is anode 2.

SCHEMATIC




FIGURE 1. Physical dimensions and configuration (SMD.5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

3.5. Marking. Marking shall be in accordance with MIL-PRF-19500. At the option of the manufacturer, marking may be omitted from the body, but shall be retained on the initial container.

3.6. Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7. Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I and III herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1. Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4).

4.2. Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.1 Group E inspection. Group E inspection shall be in accordance with table II herein.

4.3. Screening (JANS, JANTX, and JANTXV levels only). Screening shall be in accordance with table IV of MIL-PRF-19500. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
(1) 3c	Method 3101 (see 4.3.2)	Method 3101 (see 4.3.2)
9 and 10	Not applicable	Not applicable
11	V_{F2} and I_{R1}	V_{F2} and I_{R1}
12	Condition A, see 4.3.1, t = 240 hours	Condition A, see 4.3.1, t = 48 hours
13	Subgroup 2 and 3 of table I herein; ΔV_{F2} = ± 50 mV, ΔI_{R1} = 100 percent of initial value or 25 µA, whichever is greater.	Subgroup 2 of table I herein; ΔV_{F2} = ± 50 mV, ΔI_{R1} = 100 percent of initial value or 25 µA, whichever is greater.

(1) Shall be performed anytime after screen 3.

4.3.1. Power burn-in conditions. Burn-in conditions are as follows: MIL-STD-750 method 1038, test condition A. T_j = +125°C minimum; V_R = 80 percent of rated V_{RWM} dc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

4.3.2. Thermal impedance ($Z_{\theta JX}$ measurements) The $Z_{\theta JX}$ measurements shall be performed in accordance with method 3101 of MIL-STD-750. The maximum limit and conditions for $Z_{\theta JX}$ in screening (table IV of MIL-PRF-19500) shall be derived by each vendor by means of process control of actual measurements which characterizes the die attach process. When three lot date codes have exhibited control, the data from these three lots will be used to establish a fixed screening limit (not exceed the group A limit). Once a fixed limit has been established, monitor all future sealing lots using a sample from each lot to be plotted on the applicable SPC chart.

4.3.2.1. Thermal impedance ($Z_{\theta JX}$ measurements) for initial qualification or requalification. The $Z_{\theta JX}$ measurements shall be performed in accordance with MIL-STD-750. Method 3101 (read and record date $Z_{\theta JX}$) derived conditions limits and thermal response curve shall be supplied to the qualifying activity on the qualification lot prior to qualification approval.

4.3.2.2 Thermal resistance. Thermal resistance shall be measured as follow in accordance with method 3101.

a. I_M……10 mA.

b. I_H……5 -15 A.

c. t_{MD}……100 µs maximum.

d. $R_{\theta JC}$……2.80°C/W.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.4.1. Group A inspection. Group A inspection shall be conducted in accordance with table V of MIL-PRF-19500, and table I herein. Electrical measurements (end-points) and delta requirements shall be in accordance with table I, subgroup 2 herein. The following test conditions shall be used for $Z_{\theta JX}$, group A inspection:

a. I_M measurement current ..... 10 mA

b. I_H forward heating current ..... 5-15 A

c. t_H heating time ..... 10 ms

d. t_{MD} measurement delay time ..... 100 µs maximum.

The maximum limit for $Z_{\theta JX}$ under these test conditions are $Z_{\theta JX}$ (max) = 2.7 °C/W.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

4.4.2. Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VIa (JANS) and table VIb (JANTX, and JANTXV) of MIL-PRF-19500, and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with table III herein.

4.4.2.1. Group B inspection, table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Conditions
B3	4066	I_{FSM} = 200 A each leg; 1 surge of 8.3 ms superimposed on I_O. Condition A, T_A = +25°C; V_R = 0; I_O = 10A continuous half-wave.
B4	1037	Condition for intermittent operation life for each diode is as follows: I_F or I_O = 1 A (minimum) ΔT_J = +85°C, +15°C, -5°C for 2,000 cycles minimum.
B5	1038	Condition for steady - state operation life (accelerated) is as follows: Conditions B, T_j = +150°C, T_A +100°C, 240 hrs.
B6		Limit for thermal resistance is 2.80ºC/W per side.

4.4.2.2. Group B inspection, table VIb (JANTX and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Conditions
B2	4066	I_{FSM} = 200 A each leg; 1 surge of 8.3 ms superimposed on I_O. Condition A, T_A = +25°C; V_R = 0; I_O = 10A continuous half-wave.
B3	1037	Condition for intermittent operation life for each diode are as follows: I_F or I_O = 1 A (minimum); ΔT_J = 85°C, +15°C, -5°C for 2,000 cycles minimum.
B5		Not applicable.

4.4.3. Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500, and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein. Delta requirements shall be in accordance with table III herein.

4.4.3.1. Group C inspection, table VII of MIL-PRF-19500.

Subgroup	Method	Conditions
C5	3101	Limit for thermal resistance is $R_{\theta JC}$ = 2.80°C/W maximum.
C6	1037	I_F or I_O = 1A (minimum).

4.5. Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1. Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection. 1/ 2/

Inspection	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical inspection	2071					
Subgroup 2						
Thermal impedance	3101	See 4.4.1	$Z_{\theta JX}$		2.70	°C/W
Forward voltage	4011					
		I_{FM} = 3 A (dc) pulsed (see 4.5.1)	V_{F1}		0.62	V dc
		I_{FM} =10 A (dc) pulsed (see 4.5.1)	V_{F2}		0.78	V dc
		I_{FM} =15 A (dc) pulsed (see 4.5.1)	V_{F3}		0.90	V dc
Reverse current leakage 1N6842	4016	DC method, pulsed (see 4.5.1.) V_R =60 V dc	I_{R1}		50	uA dc
Subgroup 3						
High temperature operation:		T_A = +100°C				
Reverse current leakage	4016	DC method, pulsed (see 4.5.1)				
1N6842		V_R =60 V dc	I_{R2}		10	mA dc
Forward voltage	4011	I_F = 10A pulsed (see 4.5.1)	V_{F4}		0.70	V dc
		I_F = 15A pulsed (see 4.5.1)	V_{F5}		0.80	V dc
Forward voltage	4011	T_A = -55°C				
		Pulsed (see 4.5.1) I_F = 10 A (dc)	V_{F6}		0.85	V dc
Subgroup 4						
Junction capacitance	4001	V_R = 5 V dc; f = 1 MHz, V_{SIG} = 50 mV (p-p) (max)	C_J		400	pF
Subgroup 5						
Insulation Resistance	1016	V_R = 600 V dc; From lid to bottom case. All terminals shorted.	I_{RES}		10	µA
Subgroup 6 and 7						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.
2/ All measurements are for each side.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) for qualification only.

Inspection	MIL-STD-750		Qualification Inspection
	Method	Conditions	
Subgroup 1			38 devices, c = 0
Thermal shock (temperature cycling)	1051	500 cycles. Condition G	
Hermetic seal	1071		
Electrical measurements		See table I, subgroup 2, and table III, steps 1 and 2.	
Subgroup 2			38 devices, c = 0
Steady-state blocking life	1038	t = 1,000 hours, T_j = +125°C; V_R = 80% of rated V_{RWM}	
Electrical measurements		See table I, subgroup 2, and table III, steps 1 and 2.	
Subgroup 3			
Not applicable			
Subgroup 4			5 devices, c = 0
Thermal resistance	3101	See 4.5.2, $R_{\theta JC}$ = 2.80°C/W	
Subgroup 5			5 devices, c = 0
Surge	4066	Condition A, T_A = +25°C I_{FSM} = 200 A each leg, 1 surge of 8.3 ms superimposed on I_O. V_R = 0; I_O = 10A half sine wave, continuous	
Electrical measurements		See table I, subgroup 2, and table III, steps 1 and 2.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

TABLEIII. Group B, C, and E, electrical end-point measurement 1/ 2/ 3/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Forward voltage	4011	I_F = 10 A (pk) pulsed (see 4.5.1)	ΔV_{F2}		±50	mV
2.	Reverse current leakage	4016	pulsed (see 4.5.1) DC method $V_R = V_{RWM}$	ΔI_{R1}		25 µA or 100 % of initial reading, which ever is greater.	
3.	Thermal impedance	3101	See 4.4.1	$Z_{\theta JX}$		2.70	°C/W

1/ The electrical measurements for table VIa (JANS) of MIL-PRF-19500 are as follows:
   a. Subgroup 3, see table III herein, steps 1 and 2.
   b. Subgroup 4, see table III herein, steps 1, 2, and 3.
   c. Subgroup5, see table III herein, steps 1, 2, and 3.

2/ The electrical measurements for table VIb (JANTX and JANTXV) of MIL-PRF-19500 are as follows:
   a. Subgroup 2, see table III herein, steps 1 and 2.
   b. Subgroup 3, see table III herein, steps 1, 2, and 3.

3/ The electrical measurements for table VII of MIL-PRF-19500 are as follows:
   a. Subgroup 2, see table III herein, steps 1 and 2 for all levels.
   b. Subgroup 6, see table III herein, steps 1, 2 and 3 for all levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1. Packaging. Packaging shall prevent mechanical damage of the devices during shipping and handling and shall not be detrimental to the device. When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Departments' or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1. Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2. Acquisition requirements. The acquisition requirements shall be as specified in MIL- PRF-19500.

6.3. Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers' List whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from: Defense Supply Center, Columbus, ATTN: DSCC-VQE, P.O. Box 3990, Columbus, OH 43216-5000.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA -CC

(Project 5961-2311)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-PRF-19500/680	2. DOCUMENT DATE 7 September 2000

3. **DOCUMENT TITLE**
SEMICONDUCTOR DEVICE, DIODE, SILICON, DUAL SCHOTTKY CENTER TAP POWER RECTIFIER, SURFACE MOUNTED, TYPE 1N6842U3, JAN, JANTX, JANTXV, AND JANS

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) COMMERCIAL DSN FAX EMAIL	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. Point of Contact Alan Barone	b. TELEPHONE Commercial 614-692-0510	DSN 850-0510	FAX 614-692-6939	EMAIL alan_barone@dscc.dla.mil
c. ADDRESS Defense Supply Center Columbus ATTN: DSCC-VAC P.O. Box 3990 Columbus, OH 43216-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman, Suite 2533 Fort Belvoir, VA 22060-6221 Telephone (703) 767-6888 DSN 427-6888			

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:44Z
Check the source to verify that this is the current version before use.