[INCH-POUND]
A-A-551A
October 12, 1993
SUPERSEDING
A-A-551
June 2, 1980

COMMERCIAL ITEM DESCRIPTION

DOUBLE BOILER

The General Services Administration has authorized the use of this commercial item description (CID) as a replacement for CID A-A-552 which has been canceled.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This commercial item description covers aluminum double boilers.

1.2 Classification. The double boilers shall be of the following sizes.

Size 1 - 4 quart inner pan (3.8 liters)
Size 2 - 6 quart inner pan (5.7 liters)
Size 3 - 11 quart inner pan (10.4 liters)

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of the invitation for bids or request for proposals unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor Street, Fort Worth, TX 76102.

DISTRIBUTION STATEMENT A : Approved for public release. Distribution is unlimited.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

Federal Standard:

FED-STD-376 - Preferred Metric Units For General Use By The Federal Government.

Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM Standard:

E 29 - Standard Practice For Using Significant Digits In Test Data To Determine Conformance With Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

NSF International:

Standard Number 2 - Food Service Equipment.
Annual Listing - Food Service Equipment and Related Products, Components and Materials.

Application for NSF International documents should be addressed to NSF International, 3475 Plymouth Road, P.O. Box 130140, Ann Arbor, MI 48113-0140.

3. SALIENT CHARACTERISTICS

3.1 Dimensions. The double boilers shall be in the following sizes as shown in Table I. All dimensions (except capacity) are listed in inches.

3.2 Construction.

3.2.1 Pans. The double boilers shall be made from a type 3000 series aluminum alloy. The body of the pans shall be formed seamless from a single piece of aluminum and conform to the dimensions in Table I. The inner pan shall securely nest within the outer pan for cooking purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

Table I - Dimensions

Size	Inner Pan Capacity 1/	Inner Pan Thickness	Outer Pan Capacity 1/	Outer Pan Thickness
1	4 quarts (3.8 l)	0.061 2/ (1.6 mm)	6 quarts (5.7 l)	0.061 2/ (1.6 mm)
2	6 quarts (5.7 l)	0.061 2/ (1.6 mm)	8 quarts (7.6 l)	0.061 2/ (1.6 mm)
3	11 quarts (10.4 l)	0.081 2/ (2.1 mm)	12 quarts (11.4 l)	0.081 3/ (2.1 mm)

Note: Thickness shall be measured at any point within the bottom of the pans except for an area to include the bottom corner radius and up to 1 inch (2.54 cm) from the tangent of this radius and the bottom. All thicknesses shall be minimums.

1/ - Capacity tolerance shall be + 15 percent, - 5 percent.
2/ - Minimum thickness for drawn pans. Spun pans shall have an initial minimum thickness of 0.081 inch (2.1 mm).
3/ - Minimum thickness for drawn pans. Spun pans shall have an initial minimum thickness of 0.100 inch (2.5 mm).

3.2.2 Pan handles. The pans shall have two loop handles located diametrically opposite each other. The handles shall be attached by rivets, spot welding or continuous welding. The pan handles shall be made from aluminum, nickel-chrome plated steel, stainless steel, or nickel plated steel. The diametrically opposed pan handles will be located in the upper 25% of the pan height. The size 1 double boiler may have a single long handle with a minimum thickness of 0.045 inch (1.1 mm) and minimum width of 1 inch (2.54 cm). The ends of the handle shall be formed to fit flush against the pan body.

3.2.3 Covers. The inner pan shall be provided with a cover. The cover for the inner pan shall be formed seamless from a piece of aluminum. The covers for the size 1, 2, and 3 pans shall have a minimum thickness of 0.064 inch (1.6 mm). The cover shall be provided with a strap handle or plastic knob attached in the center.

3.3 Marking. The pans shall be marked with the manufacturer's name, trade name, or trademark of such known character that the source of the pan may be readily determined.

3.4 NSF International compliance. Prior to approval of first shipment, the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the items offered meet the applicable requirements of NSF International Standard No. 2. Satisfactory evidence of this compliance may be any of the following:

Source: https://assist.dla.mil -- Downloaded: 20261O-26T08:08Z
Check the source to verify that this is the currentversion before use.

(1) A listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished item, or

(2) A certification issued by NSF International under this special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory, acceptable to the contracting officer and the medical authority of the service for which the items are being procured, indicating that the item has been tested and conforms to NSF International Standard No. 2. Acceptability of the testing laboratory by the medical authority shall be determined prior to initiation of procurement actions.

NSF International compliance will not be required for the size 1, 4-quart double boiler.

3.5 Workmanship. The double boilers shall be clean and free from any cracks, fractures, malforming, scale, pits and flux deposits. The double boilers shall have no sharp edges, slivers, burrs, deep scratches, tool marks, or other defects which might affect serviceability, durability, or appearance.

3.6 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.7 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The values stated in parentheses are for informational purposes only.

3.8 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document.

3.9 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor certification. The contractor shall certify that the double boiler meets the salient characteristics and the requirements of this commercial item description, and, except for any government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace, or is the same product that has been successfully been delivered to the government on a previous contract or purchase order. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the use of the contractor's own or any other facilities suitable for the performance of the inspection requirements specified herein shall be permitted, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.3 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.4 Lot formation. All double boilers of the same size from the same manufacturer offered for delivery at one time shall be considered a lot for purposes of inspection.

4.5 Sampling for visual and dimensional examination. A random sample of double boilers shall be selected from each lot in accordance with inspection level S-4, AQL 4.0 expressed in terms of defects per hundred units. The sample unit shall be one double boiler with cover. The sample double boilers (and covers) shall be visually and dimensionally examined for any defects listed in table II and the remainder of this commercial item description. All dimensions are absolute as defined in ASTM E 29.

4.6 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate and shipping containers (as applicable) for conformance with the preservation, packaging, packing, labeling, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, acceptable quality level (AQL) 6.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

TABLE II. Examination for defects

Examine	Defect
Finish	Area of corrosion, stained or discolored
Construction and Workmanship	Scratch or tool mark on interior surface, clearly noticeable 1/ Scratched, pitted, or tool mark on exterior surfaces Any sharp edge, sliver or burr Any part missing, or not specified size Any component fractured, split, bent, buckled, punctured or otherwise impaired Marking missing or illegible
Handles	Not securely attached

1/ - An unacceptable scratch is one that will catch a fingernail when run across it.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Size double boiler required (see 1.2)
c. The packaging, packing, and marking desired.

6.2 Part Numbering. Double boilers conforming with this commercial item description shall be identified by a part number configuration consisting of identification of a portion of the specification number and size. An example of the part number configuration is shown below. This part numbering system is intended for identification and cross-indexing of the item within the Federal cataloging system. Part numbers are not required to be placed on the product or container.

Part Numbering System for Commercial Item Description A-A-551

Example: AA551-1 (AA551-1) Example - Size 1, 4 quart double boiler
|
|---- Size (1, 2, or 3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.

6.3 National Stock Numbers (NSN's): The following is a list of NSN's assigned which correspond to this CID. The list may not be indicative of all possible NSN's associated with the CID.

Size	NSN	Nomenclature	P/N
1	7330-00-205-3154	Double Boiler	AA551-1
2	7330-00-984-4065	Double Boiler	AA551-2
3	7330-00-205-3155	Double Boiler	AA551-3

MILITARY INTERESTS:

Military Coordinating Activity:

Army - GL

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review Activities:

Army - MD, QM
Air Force - 84, 50

User Activities:

Navy - MC

Civil Agency Coordinating Activity:

VA - OSS

Preparing Activity:

GSA - FSS

(DoD Project 7330-0667)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.