MILITARY STANDARD

MIL-STD-1325-80
(NAVY)


17 JULY 1973
SUPERSEDING
WR-52/80
12 OCTOBER 1967

CARLOADING

PROJECTILE, 8 INCH MK 24, 25 & MODS
IN ADAPTER MK 74 MOD 0
FLEET ISSUE UNIT LOAD

UNIT LOAD DATA

UNIT LOAD DRAWING WR-54/124
WEIGHT. . . . . 2500 LBS
DIMENSIONS . . . . . 40 L x 36 1/4 W x 28 H
CUBE . . . . . 23.4 CU FT
DOT HAZARD CLASSIFICATION. . . . EXPLOSIVES A



INDEX

ITEM	PAGE
GENERAL NOTES	2
DODX CARLOAD	2, 3 & 4
50' 6" CARLOAD	6, 7 & 8

NOTES:

1. UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.
2. FOR CROSS REFERENCE TO ASSOCIATED PALLETIZING, TRUCK-LOADING AND CONTAINERLOADING MILITARY STANDARDS, REFER TO INDEX TO STANDARDS, MIL-STD-236 (NAVY)

AUTHORIZED AND RELEASED FOR GENERAL USE.

APPROVED BY BUREAU OF EXPLOSIVES

A. F. Grassmuck — MILITARY ASSISTANT — 3/23/73
SIGNATURE — DATE

M. S. Gray NWHL — 7/3/73
SIGNATURE — TECHNICAL DIRECTION AGENT (TDA) — DATE

J. E. Kelly — 7/3/73
SIGNATURE — (ORD) SYSCOM BY DIRECTION — DATE

ORIGINATOR L. R. Cairngis — 7/2/73
SIGNATURE

NAVAL WEAPONS HANDLING LABORATORY
N A D EARLE, NEW JERSEY

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:01Z
Check the source to verify that this is the current version before use.

GENERAL NOTES

1. FOR GENERAL INFORMATION CONCERNING ORDERING, INSPECTING, AND PREPARING CARS, AND FOR DUNNAGING MATERIALS, DESIGN, AND INSTALLATION OF DUNNAGE SEE THE GENERAL DOCUMENT MIL-STD-1325 (NAVY) "RAILCAR LOADING OF HAZARDOUS MATERIALS."
2. WHEN PLANNING SHIPMENTS ORDER THE MINIMUM NUMBER OF CARS OF THE CAPACITY REQUIRED FOR THE SHIPMENT. UTILITY LOADER CARS SHALL BE SERIES DODX 28000.
3. LOADING PLANS SHOWN ARE FOR DODX UTILITY LOADER CAR WITH 50 FT 6 INCHES INSIDE LENGTH, 107 3/4 INCHES INSIDE WIDTH BETWEEN RAILS (111 INCHES INSIDE WIDTH BETWEEN SIDE WALLS), AND COMMERCIAL BOXCARS WITH 50 FT 6 INCHES INSIDE LENGTH, 110 INCHES INSIDE WIDTH.
4. THE "LOAD LIMIT" OF A CAR MUST NOT BE EXCEEDED NOR SHOULD THE RAILCAR BE LOADED SO THAT MORE THAN ONE-HALF OF THE "LOAD LIMIT" IS CARRIED BY ONE SET OF TRUCKS.
5. IF END WALLS OF CARS ARE NOT SQUARE THEY MUST BE SQUARED OFF BEFORE STARTING TO LOAD CAR.
6. THE LOAD CONSISTS OF 8 INCH PROJECTILES MK 24, 25 & MODS UNITIZED IN ADAPTER MK 74 MOD 0 IN ACCORDANCE WITH WR-54/124.
7. THE UNIT LOADS ARE HANDLED AND LOADED WITH A SUITABLE FORK LIFT TRUCK.
8. UNLESS OTHERWISE SPECIFIED NAILING SHALL BE IN ACCORDANCE WITH MIL-STD-1325 (NAVY).
9. APPLICABLE MATERIAL SPECIFICATIONS:

   DUNNAGE LUMBER - FED. SPEC. MM-L-751


   NAILS - FED. SPEC. FF-N-105

   STRAPPING - FED. SPEC. QQ-S-781, TYPE I, HEAVY DUTY, CLASS A, DRY (UNLUBRICATED).


   SEALS - FED. SPEC. QQ-S-781, STYLE III, HEAVY DUTY.
10. AFTER BLOCKING AND BRACING HAS BEEN INSPECTED ATTACH SHIPPING DOCUMENTS INSIDE THE CAR IN AN ACCESSIBLE AREA, CLOSE AND SEAL BOXCAR DOORS, AND ATTACH APPLICABLE PLACARDS TO THE OUTSIDE OF CAR AS PRESCRIBED IN OP 2165 (VOL. 1).

50 FT 6 IN. BOXCAR, DODX

1. THE CARLOAD CONSISTS OF 42 UNIT LOADS WHICH MUST BE LOADED AND DUNNAGED IN ACCORDANCE WITH THIS PROCEDURAL DRAWING.
2. A DETAILED DESCRIPTION AND OPERATING INSTRUCTIONS FOR THE UTILITY LOADER ARE CONTAINED IN OP 1750.
3. TO PREVENT UNUSED "DF" EQUIPMENT FROM BECOMING DISLODGED DURING TRANSIT OF DODX CARS SECURE IT AT ANY LOCATION IN THE BOXCAR WHICH WILL NOT INTERFERE WITH UNLOADING.
4. WHEN LESS THAN CARLOAD (LCL) QUANTITIES ARE REQUIRED TO BE SHIPPED IN DODX BOXCARS THE SAME PROCEDURES AND METHODS OF BLOCKING ARE APPLICABLE. ANY BAYS OR PORTION THEREOF MAY BE USED PROVIDING THE WEIGHT DISTRIBUTION REQUIREMENTS OF THE AAR ARE COMPLIED WITH, SEE MIL-STD-1325 (NAVY). EACH CROSSMEMBER WILL BE USED IN SUCH A MANNER THAT IT WILL RETAIN NOT MORE THAN 2500 LBS OF THE LADING.




LOADING PLAN



ELEVATION

Source: https://assist.dla.mil -- Downloaded: 202610-24T00:01Z
Check the source to verify that this is the current version before use.




CARLOAD DATA

NUMBER OF UNIT LOADS	42
NUMBER OF CROSSMEMBERS REQ'D	42
LOAD WEIGHT	105,000 LBS
DUNNAGE WEIGHT	1,095 LBS
CARLOAD WEIGHT	106,095 LBS

PIECE NO.	DESCRIPTION	SIZE	NO. OF PIECES REQ'D	NAIL TO	NAILS NUMBER	NAILS SIZE
5	SLEEPER	2 x 4 x 40	6	4	2 PER FOOT	30d
4	SLEEPER	2 x 4 x 40	6	CAR FLOOR	2 PER FOOT	16d
3	CROSS BRACE	2 x 4 x TO SUIT	72	TOENAIL 2	2 PER JOINT	10d
2	SWAY BRACE HORIZONTAL	2 x 4 x 39 1/2	72	1	3 PER JOINT	10d
1	SWAY BRACE VERTICAL	2 x 4 x 56	36	SEE 2	-	-

LIST OF MATERIALS & NAILING DATA


Source: https://assist.dla.mil -- Downloaded: 202610-24T00:01Z
Check the source to verify that this is the current version before use.



SECTION A-A

SHOWING LOCATION OF WALL MEMBERS
USED FOR CROSSMEMBERS


*DOORWAY MEMBER LOCATIONS



"W" = DISTANCE BETWEEN UNIT LOADS ACROSS THE CAR.

DETAIL B

SWAY BRACE ASSEMBLY
9 REQUIRED



SECTION C-C


Source: https://assist.dla.mil -- Downloaded: 202610-24T00:01Z
Check the source to verify that this is the current version before use.

THIS PAGE INTENTIONALLY LEFT BLANK

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:01Z
Check the source to verify that this is the current version before use.


50 FT 6 IN. BOXCAR, COMMERCIAL

1. THE CARLOAD CONSISTS OF 42 UNIT LOADS WHICH MUST BE LOADED AND DUNNAGED IN ACCORDANCE WITH THIS PROCEDURAL DRAWING.
2. WHEN LESS THAN CARLOAD (LCL) QUANTITIES ARE REQUIRED TO BE SHIPPED IN COMMERCIAL BOXCARS AND A PARTIAL LAYER RESULTS, THE PARTIAL LAYER OF LADING SHALL BE BRACED BY MEANS OF END BRACING AND/OR PARTIAL LAYER BRACING CONSTRUCTED IN ACCORDANCE WITH WR-52/100. SELECT THE TYPE OF BRACE TO COMPLY WITH THE WEIGHT OF THE UNITS TO BE RETAINED.
3. THE LOADS AS SHOWN ARE BASED ON CARS WHICH HAVE 10 FT WIDE DOORWAY OPENINGS AND ARE EQUIPPED WITH CONVENTIONAL SLIDING TYPE DOORS. THE DEPICTED PROCEDURES AND METHODS OF BLOCKING ARE APPLICABLE TO BOXCARS EQUIPPED WITH CONVENTIONAL SLIDING TYPE DOORS OTHER THAN 10 FT WIDE PROVIDING THE LENGTH OF PIECE 7 IS ADJUSTED AS REQUIRED TO SUIT THE PARTICULAR DOORWAY OPENING.
4. THE DEPICTED PROCEDURES AND METHODS OF BLOCKING ARE ALSO APPLICABLE TO BOXCARS EQUIPPED WITH PLUG TYPE DOORS PROVIDING THE LENGTH OF PIECE 7 IS ADJUSTED AS REQUIRED TO SUIT THE PARTICULAR DOORWAY OPENING. DUNNAGE MATERIAL MUST NOT BE NAILED TO ANY PLUG DOOR, WHETHER MAIN OR AUXILIARY, EXCEPT WHEN THE CAR HAS A COMBINATION OF A CONVENTIONAL SLIDING TYPE DOOR AND A PLUG DOOR, AND AN ADEQUATE NAILING STRIP IS PROVIDED ON THE PLUG TYPE DOOR. IF LUMBER OF SUFFICIENT LENGTH TO SPAN PLUG DOORS IS NOT AVAILABLE, RANDOM LENGTH MATERIAL, DOUBLED AND SPLICED, BUT WITH JOINTS OF SPLICES OFFSET, MAY BE USED. STACKS WITH MORE THAN HALF OF THE UNIT LOAD IN THE DOORWAY AREA MUST BE UNITIZED WITH TWO LATERALLY APPLIED 1 1/4" STEEL STRAPS PER STACK, EACH TENSIONED AND SEALED WITH TWO DOUBLE CRIMPED SEALS. DOORWAY PROTECTION, PIECES 9 AND 10, IS NOT REQUIRED WHEN PLUG DOOR EQUIPPED BOXCARS ARE USED, EXCEPT WHEN CAR HAS A COMBINATION OF PLUG DOOR AND CONVENTIONAL SLIDING DOOR. THEN DOORWAY PROTECTION IS REQUIRED FOR THE CONVENTIONAL DOOR. SECURELY CLOSE DOORS AND WIRE TOGETHER WITH A STRONG FLEXIBLE STEEL WIRE INSERTED THROUGH THE HOLES IN THE DOOR LATCH ASSEMBLY ONE OR MORE TIMES AND THE WIRE ENDS TWISTED TOGETHER.



SECTION A-A

SHOWING LOCATION OF END WALL MEMBERS




LOADING PLAN

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:01Z
Check the source to verify that this is the current version before use.

CARLOAD DATA


NUMBER OF UNIT LOADS	42
LOAD WEIGHT	105,000 LBS
DUNNAGE WEIGHT	830 LBS
CARLOAD WEIGHT	105,830 LBS



PIECE NO.	DESCRIPTION	SIZE	NO. OF PIECES REQ'D	NAIL TO	NAILS NUMBER	NAILS SIZE
10	HORIZONTAL DOORWAY MEMBER	2 x 4 x DOOR WIDTH	4	9	2 PER JOINT	10d
9	VERTICAL DOORWAY MEMBER	2 x 3 x 48	4	DOOR POST	2 PER FOOT	20d
8	HOLD DOWN CLEAT	2 x 6 x 60	2	7	2 PER FOOT	10d
7	GATE HOLD DOWN	2 x 6 x 14 FT	2	CAR WALL	5 EACH END	10d
6	STRUT	2 x 6 x WEDGE FIT	36	3	3 PER JOINT	16d
5	CENTER GATE HORIZONTAL	2 x 4 x CAR WIDTH - 1	2	3	3 PER JOINT	10d
4	CENTER GATE STRUT CLEAT	2 x 4 x CAR WIDTH - 1	4	3	3 PER JOINT	10d
3	CENTER GATE VERTICAL	2 x 6 x 32	12	SEE 2	-	-
2	CENTER GATE HORIZONTAL	2 x 6 x CAR WIDTH - 1	4	3	3 PER JOINT	10d
1	END WALL MEMBER	2 x 6 x 48	12	CAR WALL	1 PER FOOT	10d

LIST OF MATERIALS & NAILING DATA


Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:01Z
Check the source to verify that this is the current version before use.



DETAIL B

CENTER GATE
2 REQUIRED

WHEN BOXCAR HAS STEEL DOOR POSTS DOORWAY PROTECTION AS PER MIL-STD-1325 (NAVY) PAGE 46, FIG. 21 IS REQUIRED.



DETAIL C

DOORWAY PROTECTION
2 REQUIRED

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:01Z
Check the source to verify that this is the current version before use.