NOT MEASUREMENT SENSITIVE

MIL-STD-1339D(SH)
11 June 2024

SUPERSEDING
MIL-STD-1339C(SH)
27 February 1990

DEPARTMENT OF DEFENSE STANDARD PRACTICE

FITTING OUT PROCEDURES - SHIPS

AMSC N/A AREA PSSS

Distribution Statement A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

FOREWORD

1. This standard is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

2. The purpose of this standard is to describe fitting out procedures and define fitting out responsibilities for new construction, conversion, and modernization shipbuilding programs. It is intended for inclusion in Naval Sea Systems Command (NAVSEA) shipbuilding contracts as appropriate.

3. Comments, suggestions, or questions on this document should be addressed to Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard, D.C. 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH PAGE
1. SCOPE 1
1.1 Scope 1
1.2 Applicability 1
1.2.1 Industrial work 1
1.2.2 Provisioning 1
1.2.3 Nuclear propulsion 1
2. APPLICABLE DOCUMENTS 1
2.1 General 1
2.2 Government documents 1
2.2.1 Other Government documents, drawings, and publications 1
2.3 Order of precedence 1
3. DEFINITIONS 2
3.1 Definitions 2
3.1.1 Allowance 2
3.1.2 Allowance appendix page (AAP) 2
3.1.3 Allowance appendix package (AAPG) 2
3.1.4 AEL 2
3.1.5 APL, hull, mechanical and electrical, ordnance, electronics APL 2
3.1.6 Authorized dental allowance list (ADAL) 2
3.1.7 Authorized medical allowance list (AMAL) 2
3.1.8 Binning 2
3.1.9 Commercial and Government entity (CAGE) 2
3.1.10 Component 2
3.1.11 Contractor-furnished material (CFM) 2
3.1.12 COSAL 2
3.1.13 Delivery 3
3.1.14 Equipment 3
3.1.15 Estimated delivery date (EDD) 3
3.1.16 Excess in depth 3
3.1.17 Excess in range 3
3.1.18 Expediting 3
3.1.19 Fitting out 3
3.1.20 Follow-up 3
3.1.21 Funding 3
3.1.22 General purpose electronic test equipment (GPETE) 3
3.1.23 Government-furnished material (GFM) 4

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

PARAGRAPH PAGE

3.1.24 Incremental stock number sequence list (ISNSL) 4
3.1.25 Loose hardware 4
3.1.26 Mockup 4
3.1.27 National stock number (NSN) 4
3.1.28 Naval supervising activity (NSA) 4
3.1.29 Navy item control number (NICN) 4
3.1.30 NAVSUP WSS 4
3.1.31 OSIs 4
3.1.32 Outfitting 4
3.1.33 Outfitting material 5
3.1.34 Outfitting requisition control and accounting system (ORCAS) 5
3.1.35 Part or reference number 5
3.1.36 Real time outfitting management information system (ROMIS) 5
3.1.37 Repair part or module 5
3.1.38 Shortage in depth 5
3.1.39 Shortage in range 5
3.1.40 Storage 5
3.1.41 SRIs 5
3.1.42 Stowage 5
3.1.43 Sub-category code (SCAT) 5
3.1.44 Supervisor of Shipbuilding, Conversion, and Repair (SUPSHIP) 5
3.1.45 Unit identification code (UIC) 5
3.2 Abbreviations and acronyms 5
4. GENERAL REQUIREMENTS 7
4.1 Outfitting operations 7
5. DETAILED REQUIREMENTS 7
5.1 Asset management 7
5.1.1 Asset records and files 8
5.1.1.1 Initialization of SRI and OSI records 8
5.1.1.2 Modification of SRI and OSI records 8
5.1.1.3 Initialization and modification of RAF records 9
5.1.2 Residual asset reporting 9
5.1.3 Residual asset application 9
5.1.3.1 Cancellation of RAF orders 9
5.1.4 Asset accounting and verification 10
5.1.5 SRI and OSI record reconciliation 10
5.2 Material processing 10
5.3 Processing procedures for COSAL SRI 10

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

PARAGRAPH PAGE

5.3.1 Processing of initial inventory 10
5.3.2 Ordering and funding 10
5.3.3 Receipt, inspection, and identification 10
5.3.4 Preliminary storage 11
5.3.5 Storeroom mockups 11
5.3.5.1 Random stowage 11
5.3.5.2 Special stowage 11
5.3.5.3 Segregated stowage 11
5.3.5.4 Uniquely configured items 12
5.3.5.5 Identical items 12
5.3.5.6 Storage criteria 12
5.3.5.7 MDS 12
5.3.5.8 Bins, racks, and bulk stowage 12
5.3.5.9 Over-pack 12
5.3.5.10 Location numbers 12
5.3.5.11 Bulkhead mounted repair parts 12
5.3.5.12 Containers 12
5.3.6 Binning 12
5.3.7 Loading 13
5.3.8 Expediting and follow-up 13
5.3.9 Shortage lists 13
5.3.10 Inventory accuracy 13
5.4 Issues of SRI 13
5.4.1 Supporting GFM 13
5.4.2 Supporting CFM 13
5.4.3 Government authorization required 13
5.5 Processing procedures for COSAL OSI 13
5.5.1 Processing of initial OSI inventory 14
5.5.2 Ordering and funding 14
5.5.3 Receipt, inspection, and identification 14
5.5.4 Segregating and storing 14
5.5.5 Loading or turnover 15
5.5.5.1 Category I OSIs 15
5.5.5.2 Category II OSIs 15
5.5.5.3 Inventory and loading of OSIs 15
5.5.6 Expediting and follow-up 15
5.5.7 Shortage lists 15
5.5.8 Inventory accuracy 15

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

PARAGRAPH PAGE
5.6 Processing and integration of allowance documents 16
5.6.1 COSAL and SRI and OSI record changes 16
5.7 Other significant allowance documents 16
5.7.1 SPETERL 17
5.7.1.1 Processing of SPETERL items 17
5.7.2 VLA, MET, and PHOTO support 17
5.7.3 Medical and dental allowance 17
5.7.3.1 Processing AMAL and ADAL items 17
5.7.4 Oceanographic allowance 17
5.7.4.1 Receipt and inspection 17
5.7.5 Library books 17
5.7.6 GUCL 17
5.7.7 Forms and publications (COSAL part III, section F) 17
5.7.7.1 Processing 17
5.8 Loose hardware 17
5.8.1 Processing loose hardware 17
6. NOTES 18
6.1 Intended use 18
6.2 Acquisition requirements 18
6.3 Subject term (key word) listing 18
6.4 Changes from previous issue 18
APPENDIX A 19
A.1. GENERAL 19
A.1.1 Scope 19
A.2 REFERENCED DOCUMENTS 19
A.3 DEFINITIONS 19
A.4 GENERAL REQUIREMENTS 19
A.4.1 Identification of information and data 19
A.4.1.1 Table A-I contents 19
A.4.1.2 Table A-II contents 19
A.5 DETAILED REQUIREMENTS 19
A.6 NOTES 19

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

LIST OF TABLES

TABLE PAGE
TABLE A-I. ISNSL reports and supply aids. 20
TABLE A-II. Data content and format of 1109 supply aids for COSAL and ISNSL. 22

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard covers fitting out procedures and responsibilities for new construction, conversion, and modernization ships.

1.2 Applicability. This standard applies to the end products of the fitting out process, which are items of material specified in the authorized allowance lists and stowed in their proper locations in the ship and, equally important, to standard documentation for locating each of these items.

1.2.1 Industrial work. This standard neither applies to nor is intended to affect the industrial work performed in the ship during the period of contract performance.

1.2.2 Provisioning. Provisioning is the process of determining and acquiring the range and quantity (depth) of spares and repair parts and support and test equipment required to operate and maintain an end item of material for an initial period of service, usually referring to first outfitting of a ship, unit, or system. For the purpose of this document, allowance refers to on-board repair parts (OBRP) allowances resulting from the provisioning process.

1.2.3 Nuclear propulsion. This standard does not apply to those NAVSEA nuclear propulsion equipment, components, spares, and repair parts that are included in the "Q" coordinated shipboard allowance list (COSAL), that is, the nuclear plant COSAL.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this standard. This section does not include documents cited in other sections of this standard or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this standard, whether or not they are listed.

2.2 Government documents.

2.2.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

NAVAL SEA SYSTEMS COMMAND (NAVSEA) INSTRUCTIONS

NAVSEAINST 4423.5 - Provisioning Policy

NAVSEA M-4423.1 - Provisioning and Allowance Procedures Manual

(Copies of these documents are available online at www.navsea.navy.mil.)

NAVAL SUPPLY SYSTEMS COMMAND PUBLICATIONS

NAVSUP P-485 - Volume I – Operational Forces Supply

NAVSUP P-488 - Coordinated Shipboard Allowance List Use and Maintenance Manual

(Copies of these documents are available online at https://my.navsup.navy.mil/.)

OPNAV INSTRUCTIONS

OPNAVINST 5400.44 - Navy Organization Change Manual

(Copies of this document are available online at https://www.secnav.navy.mil/doni/default.aspx.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

3. DEFINITIONS

3.1 Definitions. The following definitions are contained in this standard or are commonly used in conjunction with outfitting procedures for naval ships.

3.1.1 Allowance. Allowance is the Government authorization for carrying an item on the ship in a designated quantity.

3.1.2 Allowance appendix page (AAP). AAPs are the additional allowance documents not included in the loading COSAL. These documents serve the same purpose as allowance parts lists (APL) and allowance equipage lists (AEL).

3.1.3 Allowance appendix package (AAPG). An AAPG is the aggregate of allowance documents supporting requirements for equipment and components not included and not supported in the loading COSAL.

3.1.4 AEL. An AEL is a technical and supply document comprised of characteristics (description) and listings of special categories of non-installed allowance items of a durable nature, which should be on board for the ship to perform its mission (non-installed equipage, tools, peculiar, and common support and test equipment).

3.1.5 APL, hull, mechanical and electrical, ordnance, electronics APL. APLs list both the technical characteristics of a particular piece of equipment and its logistic and supply information. APLs also identify all maintenance significant repair parts associated with the equipment. Each repair part listed is expected to fail during normal operation and is a potential allowance item. See NAVSUP P-488 for more information.

3.1.6 Authorized dental allowance list (ADAL). ADAL is the allowance of dental equipment items and the minimum quantities of consumables that are to be maintained on board at all times.

3.1.7 Authorized medical allowance list (AMAL). AMAL is the allowance of medical equipment items and the minimum quantities of consumables that are to be maintained on board at all times.

3.1.8 Binning. Binning is the operation by which authorized allowance material is placed into designated shipboard stowage devices or shipboard stowage device replicas representing the ship's storeroom configuration in the warehouse receiving and holding area prior to loading.

3.1.9 Commercial and Government entity (CAGE). The CAGE code, a 5-digit number used to identify the item's manufacturer/supplier, is used in conjunction with the part number, item number, symbol, or trade name assigned by the manufacturer of the product. Care should be exercised in selecting the CAGE code because some major manufacturers have more than one code assigned. Codes often are assigned to separate divisions or affiliates as well as to the parent company. To verify CAGE codes, reference https://cage.dla.mil/.

3.1.10 Component. A component is an assembly or any combination of parts, sub-assemblies, and assemblies mounted together, normally capable of independent operation.

3.1.11 Contractor-furnished material (CFM). CFM is an item furnished by the contractor under the requirements of the contract for installation into the ship or for turnover to the Government for other use or disposition. It includes, but is not limited to, equipment, components, assemblies, parts, tools, supplies, and materials.

3.1.12 COSAL.

a. A COSAL is an authoritative document that lists:

(1) The equipment/components verified by the MBPS configuration data manager to be installed on a ship to perform its operational mission;

(2) The repair parts and special tools required for the operation, overhaul, and repair of equipment/components;

(3) Operating space items (OSI) and consumables necessary for the safety, care, and upkeep of the ship itself; and

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

(4) Aeronautical equipment managed by Naval Supply Systems Command Weapon Systems Support (NAVSUP WSS) Philadelphia.

b. The end items that are managed by the Naval Information Warfare Systems Command are also included. These items include, but are not limited to, the following:

(1) Aircraft launch and recovery equipment,

(2) Visual and optical landing aids,

(3) Ground support equipment, and

(4) Selected communications equipment.

c. COSAL provides both technical and supply information that makes it a product support document. It is a technical document to the extent that equipment/component/part nomenclatures, operating characteristics, TMs, etc., are described in APLs or AELs. It is a supply document because it lists the items required to achieve a maximum self-supporting capability for an extended period of time. Since the COSAL provides the ship with basic guidance for determining the items (and quantity of each item) that should be stocked by the supply department or held in the custody of other departments, it is essential that changes be incorporated promptly and properly upon receipt, and that corrective action be taken when it is determined that any part of the COSAL is inaccurate or incomplete. The COSAL does not cover information relative to other commodities/materials such as subsistence, recreational equipment, medical material, hydrographic charts, resale clothing, ship's store merchandise, bulk fuels and lubricants, ammunition, small arms, and weapons, which will continue to be published in unique lists prepared by the appropriate commodity/material managers. Refer to NAVSUP P-488 for additional details.

3.1.13 Delivery. Delivery is the transfer of possession of the ship to the Government in accordance with the contract. The time and place for delivery are designated in the contract.

3.1.14 Equipment. Equipment is the components and assemblies connected or associated to perform a specific function.

3.1.15 Estimated delivery date (EDD). As used in this standard, the EDD is the ship delivery date shown in the current NAVSEA monthly progress report for shipbuilding and conversion.

3.1.16 Excess in depth. An excess in depth exists when there is an on-hand quantity of an item greater than the allowed quantity.

3.1.17 Excess in range. An excess in range exists when there is an on-hand quantity of an item that is not on the allowance.

3.1.18 Expediting. Expediting is to accelerate availability of a specific item or order. It is generally interpreted to mean hastening availability by follow-up action.

3.1.19 Fitting out. Fitting out is the operation of placing all of the material specified in a ship's allowance list on board the ship. For the purposes of this standard, the functions normally associated with the term outfitting (for example, ordering, funding, expediting, follow-up, receipt, and inspection) are included in the definition of fitting out. As used herein, fitting out commences early in the construction period, continues during the designated fitting out availability, and does not end until the completion of the allowance requirements definition and the receipt by the ship of all initial allowance material. Fitting out is usually accomplished in two places: the shipbuilding yard and the fitting out activity. In some cases, the Chief of Naval Operations may designate the shipbuilding yard as the fitting out activity.

3.1.20 Follow-up. Follow-up is the use of procedures to follow a material acquisition closely and persistently and to stay knowledgeable on the status of the order.

3.1.21 Funding. Funding is defined as the reservation of money or other resources to pay for material ordered.

3.1.22 General purpose electronic test equipment (GPETE). GPETE is electronic test equipment capable of generating, modifying, or measuring a range of electronic functions to test two or more systems.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

3.1.23 Government-furnished material (GFM). GFM is material provided by the Government to a contractor or comparable Government production facility to be used with or in support of a product to be delivered to the Government or ordering activity, which may be consumed or expended in the performance of the contract. It includes, but is not limited to, equipment, components, assemblies, documentation, publications, parts, tools, supplies, and materials.

3.1.24 Incremental stock number sequence list (ISNSL). An ISNSL is a series of lists that contains the computed range and depth of storeroom items (SRI) or OSIs at a point during the ship's construction, conversion, or modernization based upon the installed equipment, component, or equipage population recorded at that time. The first ISNSLs reflect separate ranges and depths of SRI or OSI requirements for Government-furnished (GF) and contractor-furnished (CF) items and are accompanied by the necessary supply and processing aids. Subsequent ISNSLs reflect the net differences in range and depth (increase or decrease) from the previous ISNSLs. The final ISNSLs are produced concurrently with the ship's loading COSAL.

3.1.25 Loose hardware. Loose hardware is portable or semi-portable CF/GF OSIs that are required by the shipbuilding, conversion, or modernization contract, specification, drawing, or another authoritative source document. Loose hardware cannot be classified as belonging to or incorporated into an AEL of the general AEL material categories listed in NAVSUP P-488. Loose hardware then is an exception classification and will be assigned to categorized material only after it has been determined that no proper AEL classification is available or that it is excluded from AEL incorporation.

3.1.26 Mockup. Mockups are full-scale stowage models or replicas representing the shipboard stowage devices or spaces. Mockups represent shipboard stowage and storeroom configuration in capacity only and do not need to be an exact replica. Mockups accommodate the ship's actual stowage drawers or other devices when possible.

3.1.27 National stock number (NSN). An NSN is a 13-digit number assigned by the Defense Logistics Information Service, Battle Creek, Michigan, to identify an item of material in the supply distribution system of the U.S. It consists of a four-digit federal supply code (FSC) and a nine-digit national item identification number (NIIN). The NIIN consists of a two-digit national codification bureau (NCB) code plus seven digits, which, in conjunction with the NCB code, uniquely identifies each NSN item in the federal supply distribution system.

3.1.28 Naval supervising activity (NSA). The NSA is the Government activity responsible for administering the contract. As used herein, the term includes officers of the Government and civilian employees who may act as the Government's agents in connection with fitting out.

3.1.29 Navy item control number (NICN). NICNs are 13-character item identification numbers that are automatically assigned by the interactive computer aided provisioning system for permanent or temporary control of selected non-NSN items under their cognizance. An NICN consists of numeric characters in the first four positions; a two-position alpha code (NICN code) that identifies the type of NICN; and seven alphanumeric characters that, in conjunction with the NICN code, uniquely identify each NICN. NICNs can be permanent NICNs (also referred to as P-NICNs), which reside in the technical reference file and are generated at the request of the technical support authority during the provisioning process and should not be requisitioned.

3.1.30 NAVSUP WSS. NAVSUP WSS is the Navy inventory control point, which has program support responsibility for hull, mechanical, electrical, ordnance, and electronic equipment or components. NAVSUP WSS publishes the ship's COSALs and ISNSLs covering these categories.

3.1.31 OSIs. OSIs are any items that are used for the normal operation or maintenance of equipment in close proximity to the operating space in which it is most frequently used while performing the ship's mission. OSIs may consist of equipage, repair parts, spares, consumables, accessories, tools, or test equipment. OSI material is in the custody and management of the designated ship's department head. Positioning of OSI material is determined by the nature of the item such as weight, size, number of departments requiring use of the item, criticality, and anticipated frequency of use in each department and special stowage requirements. OSIs are predominately AELs.

3.1.32 Outfitting. Outfitting is a term that may be used interchangeably with "fitting out" for the purposes of this standard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

3.1.33 Outfitting material. Outfitting material is the term generally applied to those items of material required because of the defined allowances, specifications, and associated documentation of ships being constructed, converted, or modernized. The responsibility to provide such material may rest with the Government or the shipbuilding contractor.

3.1.34 Outfitting requisition control and accounting system (ORCAS). The ORCAS is an integrated financial and supply system that manages new ship construction outfitting and operational/availability outfitting. ORCAS was designed in the NAVSEA data environment, a system that consolidates multiple unclassified database architectures into a single data environment that houses the Navy's logistics, maintenance, modernization, and supply data.

3.1.35 Part or reference number. A part or reference number is an identifying number such as an equipment contractor's part number, an actual manufacturer's drawing or part number, a Government drawing or model number, or a reference designation and specification of a standard part, drawing, or type number.

3.1.36 Real time outfitting management information system (ROMIS). ROMIS provides a means to accurately define the ship configuration and to evaluate progress leading to achievement of specific supply readiness and logistics objectives at established milestones. Specifically, ROMIS is designed to improve accuracy of the ship's COSAL by providing early and precise configuration definition, improving allowance support available at the end of construction, and providing a central data bank for reporting progress and status information to activities responsible for managing and supporting the construction fitting out and availability-related activities.

3.1.37 Repair part or module. A repair part or module is any individual part, sub-assembly, or assembly required for maintenance or repair of an end item.

3.1.38 Shortage in depth. A shortage in depth exists when there is at least one of an allowed item on hand, but the on-hand quantity is less than the allowed quantity.

3.1.39 Shortage in range. A shortage in range exists when there is no on-hand quantity of an allowed item.

3.1.40 Storage. Storage is the placing and keeping of material in a warehouse or other designated facility. Storage is a continuation of the receiving and inspection operation and is preliminary to the loading operation.

3.1.41 SRIs. SRIs include allowed OBRPs, sub-assemblies, and units in support of equipment in a ship; backup quantities of consumable supplies not related to specific equipment; and backup quantities of forms, which are located in the ship's storerooms. However, for purposes of this standard, SRIs are limited to OBRPs, sub-assemblies, units in support of hull, mechanical, electrical, ordnance, and electronic materials in the ship, and any other items which may be specifically designated by the NSA. SRIs are predominately APLs.

3.1.42 Stowage. Stowage is the place, location, or device for storing an item in the ship.

3.1.43 Sub-category code (SCAT). A SCAT is a four-digit numeric code used to identify a range of measurement requirements by functional category.

3.1.44 Supervisor of Shipbuilding, Conversion, and Repair (SUPSHIP). SUPSHIPs are responsible for administering the Navy's new construction, nuclear repair, and modernization contracts that are accomplished in the private sector.

3.1.45 Unit identification code (UIC). A UIC is a six-character code with the last five positions representing the UIC of the ship as assigned by the comptroller of the Navy. OPNAVINST 5400.44 addresses the UIC issuance process.

3.2 Abbreviations and acronyms. The following acronyms are contained in this standard:

AAP – Allowance appendix page

AAPG – Allowance appendix package

ADAL – Authorized dental allowance list

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

AEL	–	Allowance equipage list
AMAL	–	Authorized medical allowance list
APL	–	Allowance parts list
CAGE	–	Commercial and Government entity
CDRL	–	Contract data requirements list
CF	–	Contractor-furnished
CFM	–	Contractor-furnished material
CNET	–	Navy Education and Training Command
COSAL	–	Coordinated shipboard allowance list
EDD	–	Estimated delivery date
FSC	–	Federal supply code
GF	–	Government-furnished
GFM	–	Government-furnished material
GPETE	–	General purpose electronic test equipment
GUCL	–	General use consumables list
IAD	–	Integrated allowance document
ISL	–	Integrated stock list
ISNSL	–	Incremental stock number sequence list
MBPS	–	Model based product support
MDS	–	Modular drawer stowage
MET	–	Meteorological
ML-N	–	Management list-Navy
NAVSUP WSS	–	Naval Supply Systems Command Weapon Systems Support
NCB	–	National codification bureau
NMLC	–	Naval Medical Logistics Command
NICN	–	Navy item control number
NIIN	–	National item identification number
NLL	–	Naval Logistics Library
Non-RFI	–	Not ready-for-issue
NSA	–	Naval supervising activity
NSN	–	National stock number
OBRP	–	On-board repair part
ORCAS	–	Outfitting requisition control and accounting system

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

OSI – Operating space item

PHOTO – Photographic

RAF – Residual assets file

RFI – Ready-for-issue

ROMIS – Real time outfitting management information system

SCAT – Sub-category code

SNSL – Stock number sequence list

SOEAPL – Summary of effective allowance parts/equipage list

SPETERL – Ships' portable electrical/electronic test equipment requirement list

SRI – Storeroom items

SUPSHIP – Supervisor of shipbuilding, conversion, and repair

VLA – Visual landing aid

4. GENERAL REQUIREMENTS

4.1 Outfitting operations. Asset management and material processing shall be performed and shall consist of the receipt, inspection, identification, preliminary storage, binning, and loading of all CF and GF outfitting material received prior to delivery of the ship to the Government. Both NAVSEAINST 4423.5 and NAVSEA M-4423.1 provide policy and procedures while defining the responsibilities of the provisioning process stakeholders. In the case of ships being converted or modernized, material processing includes the offloading and processing of offloaded material inventories. In the performance of asset management, the following automated files shall be maintained, as a minimum:

a. SRI record

b. OSI record

c. RAF

These files may be integrated, so long as the capability to separately identify the three categories of items is maintained. Outfitting procedures shall be established to be used in accomplishing the detailed requirements contained herein and describe them in an outfitting operations plan. Deliverable data identified on the CDRL shall be entered in ROMIS, or an equivalent tool. Refer to section 2 for additional details regarding general requirements for outfitting operations.

5. DETAILED REQUIREMENTS

5.1 Asset management. Records shall be maintained, and necessary controls shall be exercised to ensure the following goals are achieved upon delivery of the ship:

a. The SRI and OSI records identify every allowed item as defined in the ship's authorized allowance lists.

b. Only allowed items, or authorized substitutes, in allowed quantities are stowed in the ship's stowage devices and work centers.

c. SRI and OSI stowed in the ship, including substitutes, are identified exactly as they appear in the ship's defined allowances as reflected in the IAD and corresponding stock records.

d. Shortages are identified to a valid due-in purchase order or other acquisition document number.

e. Due-in document numbers can be related to meaningful and complete supply status.

f. Accurate records are available for all shortages.

g. The quantity and stowage location of all SRI stowed in the ship are accurately recorded on corresponding stock records.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

h. Due-in document numbers and quantities are accurately recorded on corresponding stock records.

i. All material on hand and on order, not required by the ship's authorized allowance lists, is accurately identified in the RAF.

5.1.1 Asset records and files. A baseline asset record shall be initialized and maintained for each SRI and OSI identified in the ship's authorized allowance lists. In addition, a residual asset record shall be initialized and maintained for each RFI GF and CF SRI and OSI for any on-hand or on-order quantity that exceeds the baseline asset record allowance requirement. The SRI and OSI records and the RAF shall interact to provide for automated application of residual assets to unfilled SRI and OSI allowance requirements. The SRI and OSI records shall have the capability to separately identify SRIs and OSIs by the type of ship's allowance list (e.g., COSAL), allowance list application (e.g., APL/AEL number), and acquisition responsibility (e.g., CF or GF).

5.1.1.1 Initialization of SRI and OSI records. SRI and OSI records shall be initialized using data provided by the Government. Using the ROMIS tool results in the development of Form 1109, herein referred to as 1109. The Government will provide an 1109 for each SRI and OSI allowance requirement identified in each ISNSL. Data contained in the 1109 is defined in table A-II of this standard. The Government may issue up to four ISNSLs for a ship. Upon publication of the first ISNSL, the Government will provide the following groups of ISNSL supply aids:

a. CF SRI-adds (ISNSL report IA-1A)

b. CF OSI-adds (ISNSL report IA-2A)

c. GF SRI-adds (ISNSL report IA-3A)

d. GF OSI-adds (ISNSL report IA-4A)

Upon receipt of the 1109, SRI and OSI records shall be initialized using the following criteria:

e. ISNSL reports IA-1A and IA-3A. Only one SRI record shall be initialized for a single NIIN or NICN. When the same NIIN or NICN appears in both the IA-1A and IA-3A group, the aggregate of the allowance quantity on each 1109 shall be used as the SRI allowance quantity. The CF and GF allowance quantities shall be separately identified within the SRI record, for they shall identify CF and GF material availability. The APL/AEL number contained in the 1109 shall be identified in each SRI record. When more than one APL/AEL number applies to a single NIIN or NICN, the letter "M" will appear in record position 47 of the 1109. The "M" will be perpetuated to the SRI record in lieu of the APL/AEL number. For each 1109 bearing "M" in record position 47, an 1109 trailer card identifying each APL/AEL number applicable to the NIIN or NICN will be provided. An SRI trailer file shall be initialized in which all APL/AEL numbers shall be entered. Trailer 1109s can be identified by the letter "T" in record position 47. For other SRI ISNSL reports, such as IA-13 and IA-15, CF- and GF-applied assets may be provided by the Government depending on program requirements.

f. ISNSL reports IA-2A and IA-4A. The OSI record is different from the SRI record in that each OSI NIIN or NICN allowance is unique to the AEL/APL application. One OSI record shall be initialized for each NIIN/NICN and its respective AEL/APL number (e.g., the same NIIN applicable to five different AEL/APL numbers requires five OSI records). Should the same NIIN/NICN and AEL/APL number appear in both an IA-2A and an IA-4A 1109, the aggregate of the allowance quantity on each 1109 shall be used as the OSI allowance quantity. The CF and GF allowance quantities shall be separately identified within the OSI record for the purpose of maintaining the status of CF and GF material availability. Other OSI ISNSL reports, such as IA-10A, GPETE 1109-OSI adds, and IA-12, -14, and -16 for CF, GF, and GPETE applied assets may be provided by the Government depending on program requirements. Additional data in each SRI and OSI record shall be included as required to identify and control due-in orders, receipts, on-hand quantity, temporary and permanent stowage locations, and issues applicable to each item. The capability of identifying and cross-referencing substitute items to the prime NIIN shall be provided. Cross-referencing includes those SRI and OSI NIINs selected by the Government to satisfy ISNSL allowance selection requirements identified in ISNSL Report IF-11. The Government will provide 1109s for selected items. Records for the selected items shall be initialized, maintaining cross-reference to the prime SRI and OSI record NIIN/NICN.

5.1.1.2 Modification of SRI and OSI records. SRI and OSI records shall be modified to reflect allowance quantity changes and deletions and stock number changes. Upon publication of the second and subsequent ISNSLs, the Government will provide the following ISNSL supply aids:

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

SRI Supply Aids:	OSI Supply Aids:
IA-1A, IA-1B, IA-3A, IA-3B	IA-2A, IA-2B, IA-4A, IA-4B

Descriptions of these and all other ISNSL reports and supply aids are contained in table A-I of this standard. Upon receipt of these supply aids, SRI and OSI allowance quantities shall be modified using the IA-1A through -4A 1109s to initialize new SRI and OSI allowance requirements or increase the allowance quantity on existing SRI and OSI records. IA-1B through -4B supply aids shall be used for decreasing or deleting allowance requirements on existing SRI and OSI records. An SRI and OSI history record shall be maintained and shall reflect all changes made to SRI and OSI allowances identified to the respective change document (e.g., ISNSL #2, ISNSL #3, and AAP). For stock number changes, the Government will provide ISNSL report IF-12B and IF-13B. Existing SRI and OSI records shall be updated to the new stock numbers identified in the IF-12B and IF-13B. Stock number changes shall be included in the SRI and OSI history record file to provide traceability of stock number changes. When an SRI and OSI record stock number is changed and the material is on hand, the material shall be marked with the new stock number.

5.1.1.3 Initialization and modification of RAF records. A residual asset record shall be initialized for all RFI CF and GF material on hand or on order with a quantity that exceeds the SRI or OSI allowance requirement. Only one RAF record shall be initialized for each NIIN, NICN, or part number and CAGE. The quantity on hand and stowage location or the quantity on order and the applicable acquisition document number shall be identified in each record. When a quantity on hand and a quantity on order exists, both quantities with the respective stowage location and acquisition document number shall be identified in the RAF record. Capability shall be provided to separately identify on-hand and on-order residual assets. Separate identification of CF and GF is not required for RAF records. The RAF shall have automated interaction with the SRI and OSI records to provide for: (1) automated application of residual assets to unfilled SRI and OSI allowance requirements and (2) initializing or modifying RAF records when SRI and OSI allowance quantity decreases or deletions occur. RAF records shall be initialized or modified, as the following conditions occur:

a. Inventory of RFI SRI and OSI are offloaded from ships to be converted or modernized.

b. SRI or OSI material is received with no SRI and OSI record application, including residual I and C spares.

c. Decreases or deletions of SRI and OSI allowance requirements that have material on hand or on order.

d. Updated stock number information is provided by the Government. Material shall be marked with the new stock number when this condition occurs.

5.1.2 Residual asset reporting. ROMIS, or an equivalent tool, shall be used to report residual assets to the Government for updating and, when consistent with program requirements, applying to ISNSL allowance requirements. In addition, all residual assets contained in the RAF shall be reported for review and disposition instructions by the Government. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool. Residual assets shall be disposed of as directed by the Government.

5.1.3 Residual asset application. Concurrent with the initialization or modification of SRI or OSI prescribed by 5.1.1.1 and 5.1.1.2, residual assets shall be applied to baseline allowance requirements. On-hand and on-order quantities of residual assets shall be applied to the allowance quantities required by SRI and OSI records with the corresponding NIIN or NICN. When the residual asset quantity is greater than the SRI and OSI allowance quantity, the residual asset quantity will be reduced by the amount applied to the SRI and OSI requirement, and the remaining balance will be retained in the RAF. Residual assets that have no corresponding NIIN or NICN in the SRI and OSI record shall be retained in the RAF. The quantities and stowage locations of all residual assets applied to an SRI and OSI record requirement shall be identified in the applicable SRI and OSI record.

5.1.3.1 Cancellation of RAF orders. Upon completion of the residual asset application prescribed by 5.1.3, ROMIS, or an equivalent tool, shall be used to identify residual assets on order that have no application to baseline requirements. Unapplied GF RAF orders shall be reported to the Government. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

5.1.4 Asset accounting and verification. Procedures shall be developed to verify that the baseline SRI and OSI allowance requirements have been satisfied by on-hand assets or that CF or GF orders have been established. The Government will provide the 1109 for GF orders. Upon completion of the residual asset application, as prescribed by 5.1.3, SRI and OSI allowance deficiencies shall be identified.

5.1.5 SRI and OSI record reconciliation. Concurrent with publication of the final ISNSL scheduled for the ship, the Government will produce the loading COSAL. The Government will provide ISNSL supply aids for the last ISNSL and an 1109 for the total SRI and OSI COSAL allowance. The SRI and OSI with ISNSL supply aids shall be updated as prescribed by 5.1.1.1 and 5.1.1.2. Upon completion of SRI and OSI record updating to reflect the final ISNSL, the SRI and OSI record shall be reconciled with the loading COSAL using the 1109 generated in ROMIS provided by the Government. Each COSAL SRI stock number and allowance quantity shall be compared with the corresponding SRI stock number and allowance quantity. SRI records for substitutes, selected items, and any AAPs shall not be used in the reconciliation process as they will not appear in the loading COSAL. An SRI record shall be initialized for any COSAL SRI NIIN or NICN that does not exist in the SRI record. Existing SRI allowance quantities shall be modified (as necessary) to reflect the loading COSAL allowance quantity in the SRI record. All differences between the SRI and OSI record and loading COSAL resulting from the SRI and OSI record reconciliation shall be reported. Deliverable data identified in the CDRL shall be entered in ROMIS, or an equivalent tool.

5.2 Material processing. The material processing consisting of the receipt, inspection, identification, preliminary stowage, binning, and loading of all CF and GF material received shall be performed at the premises prior to delivery of the ship to the Government. Material processing includes the offloading and processing of material inventories of ships being converted or modernized. The following paragraphs prescribe detailed material processing requirements as they apply to COSAL SRI, COSAL OSI, and other significant allowance documents.

5.3 Processing procedures for COSAL SRI. Material processing procedures for COSAL SRI are identified in 5.3.1 through 5.3.10 and 5.4. The only significant difference in fitting out new construction ships versus major conversion or modernization ships is that the latter have initial SRI inventories that shall be offloaded and processed. This offload procedure is specified in 5.3.1. For new construction, as well as major conversion and modernization, see 5.3.2 through 5.3.10 and 5.4.

5.3.1 Processing of initial inventory. All SRIs shall be offloaded from the ship as soon as practicable after the ship arrives at the facility. All items removed from the ship shall be inspected and inventoried. Those items determined to be in RFI condition shall be packaged and remarked (as necessary) and stored in preliminary storage locations. In remarking material, the same NSN or part number originally used to identify the item shall be used. In determining the RFI condition, shelf-life expiration dates shall be examined. Only those shelf-life items with shelf-life expiration dates later than the ship delivery date plus 6 months shall be considered as RFI. All RFI SRIs shall be recorded in the RAF as specified in 5.1.1.3. Non-RFI material shall be reported to the NSA. Deliverable data identified in the CDRL shall be entered in ROMIS, or an equivalent tool. Non-RFI material shall be disposed of as directed by the NSA.

5.3.2 Ordering and funding. SRIs shall be ordered and funded in support of CF equipment or components as prescribed by the contract specifications.

5.3.3 Receipt, inspection, and identification. All CF SRIs and all GF SRIs that are delivered to the premises prior to ship delivery or departure of the ship from the facility, whichever occurs last, shall be received, inspected, and identified. All items received shall be inspected for damage and shelf-life expiration. All receipts shall be verified against the packing lists, the shipping document and purchase order, or the Government requisition to ensure the NSN and quantity received match the NSN and quantity ordered. The following terms shall be used to identify receipt disparities:

Term:	Used when:
Wrong material	NSN on item received differs from NSN on shipping document
Substitute material	NSN on item received and related shipping document differs from NSN on purchase order or Government requisition
Missing material	Shipping document is received without material

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

Shipping shortage	Quantity of item received is less than quantity on shipping document
Partial receipt	Quantity of item received equals quantity on related shipping document but is less than quantity on purchase order or Government requisition
Overage	Quantity of item received is greater than quantity on purchase order or Government requisition

Expeditious action shall be taken to replace wrong, missing, or shortage material identified during the receipt process. All material received shall be recorded in the applicable SRI and OSI records or RAF records. SRI records shall be initialized for substitute items received. The SRI prime NIIN shall be coded with the letter "P", and the substitute item received shall be coded with the letter "S" and cross-referenced to the prime SRI and OSI record NIIN as specified in 5.1.1.1. All receipts shall be reported to the NSA. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool. CF material shall be packaged and identified with the NSN, nomenclature, unit of issue, and quantity per package as prescribed by the contract specifications. Any torn or mutilated packages received shall be repackaged (as necessary). Repackaged items shall be re-marked with the original identification data. Refer to NAVSUP P-485 for additional information.

5.3.4 Preliminary storage. After each package is clearly marked with the NSN, NICN, or part number shown in the records, all on-hand SRIs shall be placed in an appropriate storage location, and the item location data shall be entered into the records. The records shall clearly indicate for each location the identification and quantity of the items contained therein. Parts in their individual packages shall be stowed in racks, drawers, bins, lockers, and shelves, or other stowage spaces. Information concerning the location of SRIs in ROMIS, or an equivalent tool, shall be prepared. This information shall be available to the Government upon request. Refer to NAVSUP P-485 for additional details. During preliminary storage operations, parts not that do not meet requirements for rack, bin, shelf, or drawer stowage shall be stored as follows:

a. Bulk SRI. Parts designated for stowage in shipboard bulk storerooms shall be packed in containers designed to prevent damage caused by movement of heavy parts contained therein.

b. Bracket or bulkhead mounted repair parts. SRIs that will be located in operating spaces because of size, weight, and so forth, shall be packed in containers designed to be mounted or secured to prevent damage due to movement of parts contained therein. Containers and parts contained therein shall be capable of being secured against coming adrift due to the pitch and roll of the ship in a seaway.

5.3.5 Storeroom mockups. Prior to binning, the ship's storerooms and stowage spaces that will be used for the stowage of SRIs shall be ascertained. To facilitate the preparation of the spaces for loading, full-size mockups of the stowage shall be constructed to be used in the designated shipboard stowage spaces. The mockup shall represent the drawers, bins, racks, and bulk stowage areas necessary to bin the repair parts and consumable items. The mockup need not be an exact replica of the shipboard storeroom configuration; however, it shall accommodate the exact number and cubic dimensions of each type of stowage facility to be used aboard ship. The actual ship's stowage devices shall be utilized in the mockup where they are portable (for example, items that lend themselves to drawer stowage shall be binned in the drawers to be used aboard ship). Refer to NAVSUP P-485 for additional details.

5.3.5.1 Random stowage. Random stowage shall be utilized with the exception of items requiring special stowage, management control, or dedicated storage to support primary customers (for example, hazardous materials, shelf-life items, or aviation storeroom [electronics]). It is not necessary to segregate general stowage items according to commodity (electronics, hull, mechanical, electrical, ordnance, and consumables).

5.3.5.2 Special stowage. Items identified by the Government as requiring specialized stowage, such as flammable, hazardous, or classified items, shall be stowed in dedicated stowage areas included in the ship's design for such material.

5.3.5.3 Segregated stowage. Items requiring specialized management control but having no special stowage requirements, such as shelf-life items, part numbered items, local stock numbered items, NICNs, classified materials, and radioactive materials, shall have segregated storage within the compartment or storeroom used for stowage of other items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

5.3.5.4 Uniquely configured items. Items that, due to their size, shape, or weight, require specialized storage facilities, such as bar stock, pipe, angle iron, sheet metal, plywood, wire and rope reels, crated repair parts, canned aircraft engines, and so forth, shall be stowed to facilitate their storage and handling.

5.3.5.5 Identical items. Identical items shall be stowed in the same location. If space limitations require multiple locations of the same items, the locations shall be immediately adjacent.

5.3.5.6 Storage criteria. To the extent practicable, the following criteria shall be followed. The NSA will enforce these criteria, which are not applicable to MDS cabinets, and each ship's configuration will be considered a major decision factor. Each item to be stowed shall be placed in the smallest stowage device that will completely house the total allowance for the item. No more than 75 percent of the stowage capacity of each drawer or bin shall be utilized; 40 percent of the available bulk stowage areas shall be left vacant to allow for expansion of stocks and accessibility. Additionally, not more than 10 line items shall be stowed in a single type A or B drawer or bin compartment, and not more than 20 line items shall be stowed in a single rack compartment.

5.3.5.7 MDS. When MDS cabinets are used, each cabinet shall have a mix of different-sized drawers with the larger drawers located at the bottom. The drawer mix shall provide not more than nine drawers per cabinet. Ten percent of the MDS cabinets shall be left vacant for future growth in the range of SRIs. Stowage drawers shall have a 20 percent space allowance for depth shortages and to prevent damage to materials stowed therein when the drawer is opened.

5.3.5.8 Bins, racks, and bulk stowage. Items in bins, racks, and bulk stowage areas shall be stowed so that heavier items are stowed on the bottom and lighter items are stowed on the top. Bulk stowage of items that exceed 50 pounds and stowage of large bulky items shall be in the most accessible bulk storerooms convenient to installed materials handling equipment or hatches and accesses to the extent feasible.

5.3.5.9 Over-pack. An over-pack (wrapping covering multiple line items) shall not be applied. Where the quantity in the storage pack differs from the unit of issue, items shall be packaged and stowed according to the unit of issue as specified in the ML-N. Small nuts, bolts, washers, and similar items where the storage package contains all the same line items are excepted from this criterion.

5.3.5.10 Location numbers. Locations and devices used in the mockup shall be assigned identification numbers in accordance with the identification system to be used aboard ship. Shipboard stowage corresponding to those in the mockup and the shipboard stowage actually used in the mockup shall be assigned permanent location identification numbers.

5.3.5.11 Bulkhead mounted repair parts. Locations for bulkhead mounted repair parts shall be clearly marked with a placard affixed adjacent to the location. This placard shall identify the name and NSN or part number of the bulkhead mounted repair part, plus the applicable APL and equipment nomenclature. The placard and the necessary stowage aids shall be installed at delivery whether or not the repair part is on hand. Securing devices for bulkhead mounted repair parts shall conform to the shock requirements as specified (see 6.2).

5.3.5.12 Containers. Stowage containers (bulk and bulkhead mounted) shall be marked with permanent identifying symbols, as specified by the NSA. The symbols shall consist of numbers or letters, or both, from which the stowage location can be easily determined. This requirement is in addition to 5.3.5.11.

5.3.6 Binning. The SRI, as reconciled with the loading COSAL in accordance with 5.1.5, identifies the authorized range and depth of the ship's SRI allowances to be binned and loaded. Subsequent to receipt and reconciliation of the loading COSAL with the SRI, additional allowance data, based on AAP development, may be provided by the Government. The SRI shall be modified to reflect AAP allowance requirements using the procedures prescribed in 5.1.1.2. Prior to loading SRIs on board the ship, material shall be binned in the range and depth identified in the updated SRI, including substitutes and Government-selected items. The SRI shall be updated to identify the quantity and stowage location number of each item binned. A complete listing of binned SRIs shall be prepared prior to the time of loading. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

5.3.7 Loading. Upon completion of the binning operation, at a time to be approved by the NSA, 100 percent of the SRI received shall be loaded and stowed on board the ship for the ship's approved allowance lists as reflected by the 1109 data provided by the Government and recorded in the SRI. Loading shall be accomplished by transferring stowage devices with the contents intact from the stowage mockups to predetermined corresponding shipboard storeroom stowage or locations. Bin, rack, shelf, or bulk items shall be transferred in the same manner. All allowed SRI received at a time mutually agreed to by the Government based on the particular type of program and ship involved shall be loaded. Material received subsequent to loading shall be delivered at the earliest feasible time after receipt until ship delivery. The loading operation shall be closely coordinated with the NSA.

5.3.8 Expediting and follow-up. One hundred percent of the CF SRI shall be provided prior to delivery or departure of the ship. When shortages exist at this time, such shortages shall be expedited and followed up on until all items required by the contract have been delivered to the ship. The receipt of CF or GF SRI shall continue to be reported after delivery or departure of the ship. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

5.3.9 Shortage lists. Shortage lists shall be prepared for SRI allowance shortages. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

5.3.10 Inventory accuracy. Complete and accurate records shall reflect the location, quantity, and identification of each item are maintained during the preliminary storage and binning processes. Inventory accuracy shall be 100 percent. Errors falling within the following categories shall be considered inventory accuracy errors:

a. Materials in bin (location), no stock record.

b. Wrong NSN, part number (or other identification number) on material.

c. Stock record indicates wrong location, or multiple locations not posted.

d. Binned quantity less than allowed quantity, no due-in document or outstanding requisition number posted on stock record.

e. Incomplete cross-reference information on stock record in case of superseded NSN or substitute item.

f. Quantities in bin greater than quantity on hand on stock record.

5.4 Issues of SRI.

5.4.1 Supporting GFM. The NSA may authorize the issue of GF SRI for the test and checkout of GFM. The Government will order and fund replacements and will provide copies of requisitions. Records shall be adjusted accordingly.

5.4.2 Supporting CFM. The NSA may authorize the issue of GF SRI for the test and checkout of CFM. Issues of GF SRI will be restricted to emergency situations. Immediate action shall be taken to order and fund replacements. Records shall be adjusted accordingly.

5.4.3 Government authorization required. GF SRI shall not be issued without prior written authorization of the NSA.

5.5 Processing procedures for COSAL OSI. Material processing procedures for COSAL OSI are identified in 5.5.1 through 5.5.8. The only significant difference in fitting out new construction ships versus major conversion or modernization ships is that the latter have initial OSI inventories that shall be offloaded and processed. This offload procedure is specified in 5.5.1. New construction, as well as major conversions and modernizations, are specified in 5.5.2 through 5.5.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

5.5.1 Processing of initial OSI inventory. All portable and non-installed OSI defined by the Government shall be removed as soon as practicable after arrival of the ship at the facility. In some cases, when approved by the NSA, certain OSI (such as firefighting equipment and mooring lines) may be retained on the ship. These items shall be inventoried and screened, but their recorded location shall indicate the specific ship's compartment in which they are located. These items shall be re-inventoried and conditioned screened near the end of conversion or modernization to ensure they are still present and are still in RFI condition. All OSI offloaded to the facility shall be inspected and inventoried. Those items determined to be in RFI condition shall be packaged and re-marked (as necessary) and stored in preliminary storage locations. In re-marking material, the same NSN or part number originally used to identify the item shall be used. In determining RFI condition, shelf-life expiration dates on the material shall be examined. Only those shelf-life items with a shelf-life expiration date later than ship EDD plus 6 months shall be considered as RFI. All RFI OSI inventoried in the RAF shall be recorded as specified in 5.1.1.3. Non-RFI material shall be reported to the NSA. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool. Non-RFI material shall be disposed of as directed by the NSA.

5.5.2 Ordering and funding. All OSI shall be ordered and funded as prescribed by the contract specifications.

5.5.3 Receipt, inspection, and identification. All CF OSI and all GF OSI delivered to the premises shall be received, inspected, and identified prior to ship delivery or departure of the ship from the facility, whichever occurs last. All items received shall be inspected for damage and shelf-life expiration. All receipts shall be verified against packing lists or shipping documents and the purchase order or Government requisition to ensure the NSN and quantity received matches the NSN and quantity ordered. The following terms shall be used to identify receipt disparities:

Term:	Used when:
Wrong material	NSN on item received differs from NSN on shipping document
Substitute material	NSN on item received and related shipping document differs from NSN on purchase order or Government requisition
Missing material	Shipping document is received without material
Shipping shortage	Quantity of item received is less than quantity on shipping document
Partial receipt	Quantity of item received equals quantity on related shipping document but is less than quantity on purchase order or Government requisition
Overage	Quantity of item received is greater than quantity on purchase order or Government requisition

Expeditious action shall be taken to replace wrong, missing, or shortage CF material identified during the receipt process. All material received shall be recorded in the applicable SRI and OSI record or RAF records. OSI records shall be initialized for substitute items received. The OSI prime NIIN shall be coded with the letter "P", and the substitute item received shall be coded with the letter "S" and cross-referenced to the prime NIIN as specified in 5.1.1.1. ROMIS, or an equivalent tool, shall be used to report all receipts to the NSA. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool. All CF material shall be packaged and identified with the NSN, nomenclature, unit of issue, and quantity per package as prescribed by the contract specifications. Any torn or mutilated packages received shall be repackaged (as necessary). Re-packaged items shall be re-marked with the original identification data.

5.5.4 Segregating and storing. Space shall be provided for segregating and storing OSI by category or allowance list number as identified by the NSA. Upon completion of receipt, inspection, and identification of CF and GF OSIs, items shall be segregated and stored by allowance list number, shipboard compartment, or another category as pre-designated by the NSA. All material stored shall be readily located for shipboard stowage or turnover, as appropriate. Warehousing space or other facilities required for the processing and loading or turnover of OSIs shall be provided. Facilities shall include the capability to handle classified material and documents, drugs, and hazardous or radioactive material. Refer to NAVSUP P-485 for additional details.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

5.5.5 Loading or turnover. The loading of COSAL-related OSIs encompasses the transfer of custody of material from the entity responsible for outfitting to the Government. From a custodial transfer point of view, OSIs can be categorized as follows:

a. Category I: OSIs that shall be placed into stowage devices throughout the ship (for example, portable battle lanterns and fire extinguishers).

b. Category II: OSIs that are segregated by APL, AEL, or AAP, shipboard compartment, or user and loaded into designated shipboard spaces.

5.5.5.1 Category I OSIs. Category I OSIs pose the greatest problem relative to custodial transfer and shall be held to an absolute minimum after considering safety and operational necessities.

5.5.5.2 Category II OSIs. Category II OSIs, in most instances, require very little additional processing to achieve its final distribution to the ultimate user. OSIs in this category are normally packaged in sealed containers (for example, tri-walls) with packing lists or cards attached. Custodial transfer of category II OSI is achieved by obtaining Government representatives' signatures on copies of the packing list when the containers are loaded into designated spaces.

5.5.5.3 Inventory and loading of OSIs. Inventory accuracy determination procedures for both category I and II OSI are contained in 5.5.8. Loading or turnover procedures for both CF and GF OSIs shall be developed. The procedures shall provide for the complete and orderly loading or turnover of OSIs to the Government. The ship's crew shall load and properly locate category I and II OSI aboard ship. Complete listings of shipboard locations for both categories of OSIs shall be prepared for approval of the NSA prior to commencement of the loading operation. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool. Material shall be loaded in a manner that ensures it is protected against theft, pilferage, or damage. The integrity of hazardous, semi-safe, or classified material shall be maintained. Receipts shall be obtained for all CF and GF OSIs loaded. Category I OSI receipts shall be obtained during site validation of the installed OSI; category II OSI shall be receipted for as previously described.

5.5.6 Expediting and follow-up. One hundred percent of the OSIs shall be provided prior to delivery or departure of the ship. When shortages exist at that time, such shortages shall be expedited until all items required by the shipbuilding contract have been delivered to the ship. The receipt of CF or GF OSIs shall continue to be reported after delivery or departure of the ship. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

5.5.7 Shortage lists. ROMIS, or an equivalent tool, shall be utilized to prepare shortage reports for OSI allowance shortages. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

5.5.8 Inventory accuracy. The complete and accurate records shall be maintained for any OSI that needs to be processed and loaded. Records and listings shall accurately reflect the location, quantity, and complete identification of each OSI loaded. Audits conducted for OSI processing procedures will be designed to provide reasonable assurance that the internal procedures being followed will result in documentation prepared for the Government; that documentation will reflect the OSI received at the facility and actually loaded. In conducting the audits, samples will be taken from category II OSIs that are packed for loading. This will involve the checking of contents of containers against packing lists and validation of other information contained on the material necessary for subsequent distribution to its end user. When errors are detected, they shall be corrected. Audits will be conducted periodically throughout the periods of construction, modernization, or conversion to identify early on any problems associated with the processing procedures to assess the degree of compliance with the procedures and to evaluate the necessity for modification to meet the previously stated objective of reasonable assurance. The NSA shall be assisted by making available personnel, facilities, and records required to perform the periodic audits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

5.6 Processing and integration of allowance documents. Allowance appendix data and documents shall be processed and integrated in the ship's loading COSAL. Unless otherwise prescribed by section 083 of the contract specifications, the Government will develop AAPs to:

a. Add or increase installed equipment configurations not included in the loading COSAL,

b. Decrease or delete equipment included in the loading COSAL and subsequently removed from the ship, and

c. Provide interim supply support for equipment included in the loading COSAL without complete SRI and OSI allowances.

The Government will provide a copy of the ship's loading COSAL, when produced. Copies of AAP additions and deletions, with supporting 1109 generated in ROMIS, will be provided as AAP development is completed by the Government. Data contained in the 1109 generated in ROMIS is defined in table A-II, in the column entitled "ISNSL". Upon receipt of AAPs and supporting supply aids, the 1109 data shall be processed into the SRI and OSI record using the procedures prescribed in 5.1.1.2. The AAP data shall be integrated into the loading COSAL by adjusting the SOEAPLs and the COSAL index to reflect AAP equipment changes and filing the AAPs in part 2 of the loading COSAL. Upon completion of AAP development, the Government will jointly verify the adjusted loading COSAL to ensure all AAPs have been properly recorded and included in the loading COSAL. Any disparities between the AAPs issued by the Government and those recorded in the COSAL shall be resolved. The SRI and OSI record and loading COSAL shall be adjusted (as necessary) to incorporate corrections resulting from the AAP verification. When all AAPs have been processed into the SRI and OSI record and integrated into the loading COSAL, the adjusted loading COSAL shall be returned with an ISL to the Government. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool. In addition, a stock record for each SRI record shall be prepared and provided. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

5.6.1 COSAL and SRI and OSI record changes. In conjunction with processing and integrating AAPs and AAP data into the loading COSAL and SRI and OSI record prescribed in 5.6, a record of changes made to the COSAL and SRI and OSI record shall be established and maintained. Changes are prescribed as additions to, deletions from, or modifications made to any part or section of the loading COSAL or SRI and OSI record required by an AAP. Upon completion of the AAP verification required in 5.6, all changes made to the loading COSAL and SRI and OSI record shall be reported. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

5.7 Other significant allowance documents. The procedures in this section relate specifically and only to those defined allowances of materials as they are presented in the below listed allowance documents, and the materials are shipped to the facility.

a. SPETERL.

b. VLAs, MET, and PHOTO allowances, as prepared by the aviation supply office.

c. AMAL and ADAL, as prepared by the NMLC.

d. Allowance of maps, charts, and publications, as prepared by the National Geospatial-Intelligence Agency.

e. Library book allowance, as prepared by the CNET.

f. General use consumables list (COSAL part III, section E).

g. Forms and publications (COSAL part III, section F).

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

5.7.1 SPETERL. The SPETERL identifies the latest known test equipment required to perform preventative and corrective maintenance at the organizational and intermediate levels on a total shipboard basis. The SPETERL provides information about test equipment quantities required and reported onboard, equipment/system application, APL numbers, substitutes, and excess/deficiency status. In addition to portable electrical/electronic test equipment, the SPETERL also includes special purpose electronic test equipment, built-in test equipment, and selected electro-mechanical test instruments. The SPETERL identifies and incorporates requirements for all categories of test and monitoring systems in a single document. The SPETERL is prepared by Naval Surface Warfare Center, Indian Head, Picatinny Detachment. The application/use for required test equipment shown under the prime equipment/systems application column is provided to assist the supply officer and maintenance officer in allocating test equipment resources among organizational elements. The SPETERL is comprised of two broad material categories, namely 7Z cognizance items and other (multiple cognizance) items. Refer to NAVSUP P-485 for additional details.

5.7.1.1 Processing of SPETERL items. SPETERL items shall be processed as an integral part of COSAL-related OSIs following the procedures in 5.5.

5.7.2 VLA, MET, and PHOTO support. The GF VLA, MET, and PHOTO allowances shall be processed as COSAL-related OSIs following the procedures in 5.5.

5.7.3 Medical and dental allowance. Medical and dental allowances of material shall be documented on an AMAL or ADAL provided by the NMLC Fort Detrick, MD. The NSA will provide supply aids identifying materials to be received at the facility.

5.7.3.1 Processing AMAL and ADAL items. AMAL and ADAL items received at the facility shall be turned over to the ship's senior medical or dental representative for processing. Storage facilities shall be provided (as necessary) until turnover to the ship's medical or dental department representative can be affected.

5.7.4 Oceanographic allowance. The NSA will provide the shipping information concerning materials to be received at the facility.

5.7.4.1 Receipt and inspection. When the material is received at the facility, it shall be turned over to the ship for material processing and reporting.

5.7.5 Library books. Library books received at the facility will be turned over to the ship for material processing and reporting.

5.7.6 GUCL. The GUCL shall be processed for SRIs and OSIs as COSAL-related SRIs and OSIs following procedures as specified in 5.3 for SRI and 5.5 for OSI. Refer to NAVSUP P-488 for more information on the GUCL.

5.7.7 Forms and publications (COSAL part III, section F). Part III, section F, will be provided by the NLL upon request from either the fleet introduction team or an authenticating source, such as the prospective commanding officer or the outfit supply activity.

5.7.7.1 Processing. Forms and publications received at the facility shall be turned over to the nucleus crew for processing. Facilities shall be provided for the nucleus crew to process and prepare for loading forms and publications received.

5.8 Loose hardware. Loose hardware is an exception OSI classification and will be assigned to categorize material only after it has been determined that no proper AEL classification can be applied. All CF OSIs required by contract specifications, drawings, or other authoritative source document shall be reported. All OSIs for which no AEL classification can be made will be classified as loose hardware. Deliverable data identified in the CDRL shall be prepared in ROMIS, or an equivalent tool.

5.8.1 Processing loose hardware. Loose hardware shall be processed as COSAL-related OSIs following the procedures specified in 5.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This standard contains requirements for standardizing fitting out procedures and defining fitting out responsibilities for new construction, conversion, and modernization shipbuilding programs. This standard is intended for use in all shipbuilding programs.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this standard.

b. When securing devices for bulkhead mounted repair parts conform to the shock requirements (see 5.3.5.11).

6.3 Subject term (key word) listing.

Fitting out responsibilities

Outfitting procedures

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

IDENTIFICATION OF TYPES AND FORMAT OF OUTFITTING INFORMATION AND DATA

A.1. GENERAL

A.1.1 Scope. This appendix identifies the types and format of information for use in completing fitting out requirements. This appendix is not a mandatory part of the standard. The information contained herein is intended for guidance only.

A.2 REFERENCED DOCUMENTS

Not applicable.

A.3 DEFINITIONS

Not applicable.

A.4 GENERAL REQUIREMENTS

A.4.1 Identification of information and data. Information and data to be provided, or that can be made available upon request to the Government, is identified in the following tables.

Table A-I - Identification of ISNSL reports and supply aids

Table A-II - Data content and format of 1109 generated in ROMIS for COSAL and ISNSL

A.4.1.1 Table A-I contents. Part I of table A-I identifies ISNSL forms (IF) reports that can accompany the increment stock number sequence list publications. Part II of table A-I identifies ISNSL supply aids (IA) produced with ISNSLs.

A.4.1.2 Table A-II contents. Table A-II identifies the data and format of 1109 generated in ROMIS that will be provided. As illustrated in table A-II, two types of 1109s are used in the fitting out process. Data contained in each type 1109 is identified by the “X” in the COSAL and ISNSL columns in table A-II. It should be noted that data content is not identical among the two types of 1109s, which are used for different purposes. COSAL 1109s are used for reconciling load COSAL allowances with the SRI and OSI allowances, which is addressed in 5.1.5 of this standard. ISNSL 1109s (e.g., the IA groups of 1109s in table A-I, part II) are used for initializing and modifying SRI and OSI records and are addressed in 5.1.1.1 and 5.1.1.2 of this standard.

A.5 DETAILED REQUIREMENTS

This section is not applicable to this standard.

A.6 NOTES

This section is not applicable to this standard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE A-I. ISNSL reports and supply aids.

I. IF Reports	
ISNSL	**Title**
IF-1	Total Requirements ISNSL Items – Total Ship to Date
IF-3	Contractor-Furnished Material SNSL (SRI) Adds Only
IF-4	Contractor-Furnished Material SNSL (OSI) Adds Only
IF-5	Government-Furnished Material SNSL (SRI) Adds Only
IF-6	Government-Furnished Material SNSL (OSI) Adds Only
IF-7	CFM Delete/Decrease Item Quantity Listing – SRI/OSI
IF-8	GFM Delete/Decrease Item Quantity Listing – SRI/OSI
IF-11	AR, FAB, and SEL Item Listing – Total Ship to Date
IF-12A	Cross Reference Listing – Old NIIN to New NIIN
IF-12B	Cross Reference Cards – Old NIIN to New NIIN
IF-13A	Cross Reference Listing – New NIIN to Old NIIN
IF-13B	Cross Reference Cards – New NIIN to Old NIIN
IF-14A	Contractor-Furnished Material SNSL – SRI/OSI Adds Only – Purchase Order (PO) Sequence
IF-14B	Procurement Document Number Cross Reference List
IF-14C	Part III, Section D, NIIN Alternate Number Cross Reference – CFM SNSL Adds Only
IF-15A	OSI Items (APL/AEL Sequence) Total Ship to Date
IF-15B	OSI Items (NIIN Sequence) Total Ship to Date
IF-16	Total Ship Special Category Item List
IF-17	Contractor-Furnished Material SNSL (SIR) Applied Assets Only
IF-18	Contractor-Furnished Material SNSL (OSI) Applied Assets Only
IF-19	Government-Furnished Material SNSL (SRI) Applied Assets Only
IF-20	Government-Furnished Material SNSL (OSI) Applied Assets Only
II. IA	
IA-1A	Contractor-Furnished Material 1109s – SRI – Adds
IA-1B	Contractor-Furnished Material 1109s – SRI – Deletes/Decreases
IA-2A	Contractor-Furnished Material 1109s – OSI – Adds
IA-2B	Contractor-Furnished Material 1109s – OSI – Deletes/Decreases
IA-3A	Government-Furnished Material 1109s – SRI – Adds
IA-3B	Government-Furnished Material 1109s – SRI – Deletes/Decreases
IA-4A	Government-Furnished Material 1109s – OSI – Adds
IA-4B	Government-Furnished Material 1109s – OSI Deletes/Decreases
IA-5	Government-Furnished Material 1348Ms – SRI – Adds
IA-6	Government-Furnished Material 1109Ms – OSI – Adds
IA-7A	Validation Aids – HME&O
IA-7B	Validation Aids – Electronic Adds
IA-7C	Validation Aids – Aviation Adds

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE A-I. ISNSL reports and supply aids – Continued.

ISNSL	Title
IA-8	Summarized Equipment Record Tape
IA-9	Stock Number Sequence Listing (SNSL) Work Tape
IA-10A	General Purpose Electronic Test Equipment (GPETE) 1109s – OSI Adds
IA-10B	General Purpose Electronic Test Equipment (GPETE) 1109s – OSI Deletes/Decreases
IA-11A	Government-Furnished Material – CRASP Header Cards-Ship to Date
IA-11B	Contractor-Furnished Material – CRASP Header Cards-Ship to Date
IA-12	Contractor-Furnished Material 1109s – OSI – Applied Assets
IA-13	Government-Furnished Material 1109s – SRI – Applied Assets
IA-14	Government-Furnished Material 1109s – OSI – Applied Assets
IA-15	Government-Furnished Material 1109s – SRI – Applied Assets
IA-16	General Purpose Electronic Test Equipment 1109s – Applied Assets

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE A-II. Data content and format of 1109 supply aids for COSAL and ISNSL.

Record Position		Data Field Description	Notes/Remarks	1109 Report Application	
Position	Interpret			COSAL	ISNSL
1-2	1-2	Cognizance Symbol	Interpret "P" in record position 1 if a reference number (manufacturing part number, etc.) is in record positions 4-22.	X	X
3	3	Material Control Code	--	X	X
4-16	--	NSN	The NSN will be interpreted in columns 4-19 with blank spaces left in columns 8, 11, and 15.	X	X
--	4-7	FSC	--	--	--
--	9-10	NCB	--	--	--
--	12-19	NIIN	--	--	--
17-18	20-21	Special Material Identification Code (SMIC)	When a SMIC code is used, an asterisk (*) will be designated and interpreted in column 22.	X	X
17-22	L20-25	Item Name	--	X	X
4-22	4-22	Reference Number	Repair part identification number other than NSN/NICN. Use only when NSN/NICN not available. SMIC (17-18) and name (17-22).	X	X
4-8	--	CAGE	--	--	--
9-22	--	Part/Reference Number	--	--	(Record position 4-16 only)
23	L33	Material Category Code	--	--	--
24-25	24-25	Unit of Issue	--	X	X
26-32	26-32	Unit Price	Dollars in columns 26-30; cents in columns 31-32. Decimal point always between cc 30 and 31.	X	X
33	33	Unit Price Code	--	X	--
34	23	Allowance Note Code (ANC)	The note code abstracted from the APL/AEL notes column applicable to this item.	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE A-II. Data content and format of 1109 supply aids for COSAL and ISNSL – Continued.

Record Position		Data Field Description	Notes/Remarks	1109 Report Application	
Position	Interpret			COSAL	ISNSL
35	L1	OSI Information	The following codes will be inserted to identify type of OSI: "F" – ANC "N" OSI item "R" – ANC "6" OSI item "O" – OSI items other than ANC "N" or "6"	X	X
36-46	34-44	Repairable Identification Code	CID/APL/AEL number in which this item is listed. Omit dash in position column 37 for AEL numbers. Number left justified.	X	X
47	45	Multi-Application Code	a. This column is blank if only one CID/APL/AEL number (DEN D008) is applicable to this item. b. If there is more than one application of this item, a trailer card will be provided for each additional application. The Master card will be identified by an alpha "M" in position column 47 and interpret space 45. The first APL number and the total allowance quantity for this item, as listed in COSAL SNSL, will be provided in the Master card. Each trailer card will be identified by an alpha "T" designated in record position 47 and interpreted in space 45. The trailer card will contain the same management data as the Master card, excluding allowance quantity.	X	X
48	46	Allowance Type Code	--	X	--
48	46	Procurement Responsibility Indicator	Use to denote the responsibility for procurement: "K" – Contractor "G" – Government-Furnished.	--	X
49-52	47-50	COSAL Allowance Quantity	--	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE A-II. Data content and format of 1109 supply aids for COSAL and ISNSL – Continued.

Record Position		Data Field Description	Notes/Remarks	1109 Report Application	
Position	Interpret			COSAL	ISNSL
53	L57	Military Essentiality Code – Parts to Component Fleet Ballistic Missile (FBM)	Covered by separate instruction.	X	--
53	L57	Military Essentiality Code – Parts to Component	For non-FBM ships: 1 – major importance to component 2 – minor importance to component	X	--
54	L56	Military Essentiality Code – Component/Mission	For non-FBM/non-Modified Fleet Logistics Support Improvement Program ships: N – non-vital V – vital	X	--
54	L56	Mission Criticality Code	For Modified Fleet Logistics Support Improvement Program ships.	X	--
54	57	Julian Date	--	--	X
55-57	L58-60	Population Weighted Military Essentiality Code	Covered by separate instruction.	X	--
58-61	--	Serial Number	--	--	X
62-65	--	Required Delivery Date	--	--	X
66-71	--	Supplementary Address	--	--	--
71	51	Equipage/Equipment Categorization Custody Code	Code denotes category of material (i.e., “R” for repair part).	X	--
72	57	ILO Control Code	--	X	--
72-75	57-60	Add-on Quantity	--	--	X (Quantity required; negative quantity is entered for deletes.)
73-75	58-60	NAVSEA-Funded Quantity	“ADD” quantity to be funded by NAVSEA COSAL allotment. Applicable only to items with simple objective access protocol control code “B” in position column 57. Provided for information only.	X	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

TABLE A-II. Data content and format of 1109 supply aids for COSAL and ISNSL – Continued.

Record Position		Data Field Description	Notes/Remarks	1109 Report Application	
Position	Interpret			COSAL	ISNSL
73-75	58-60	Decrease in Allowance Quantity	The difference between the old and new allowance quantity for storeroom items only. Position 72 to be left blank. Does not apply to FBM ships (ballistic missile submarine ship type).	X	--
76-80	53-56	UIC	--	X	X
NOTE: A maximum of 60 print spaces is available on each of the top two lines of the card. Unless otherwise specified by the letter "L" preceding the field indicating lower line printing, all data shall be printed on the upper left line.					

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Preparing activity:
Navy – SH
(Project PSSS-2024-016)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:04Z
Check the source to verify that this is the current version before use.