A-A-1681
January 19, 1982

COMMERCIAL ITEM DESCRIPTION

READER/PRINTER, MICROFORM
(1:24 SOURCE DOCUMENT AND 1:48 COM MICROFICHE)

The General Services Administration has authorized the use of this commercial item description.

Salient characteristics:

Type and style shall be as specified in the procurement documents.

Type I - Electrostatic printing with sensitized paper
Type II - Dry silver process printing
Type III - Other processes, excluding wet photographic processing

Style A - Single size copies, as specified below
Style B - Dual size copies; the magnifications, screen size, copy sizes and percent blowback shall be as specified

The reader/printers shall conform to the applicable requirements of UL 114. Acceptable evidence of such conformance shall be the UL Label, UL Listing Mark, or certified report from a recognized independent testing laboratory acceptable to the Government, indicating that the reader/printers have been tested and conform to UL 114.

The reader/printers shall include all of the following features and capabilities as a minimum. The functions not specifically described, but required for proper and satisfactory operation, shall be furnished. All characteristics specified herein are the minimum acceptable.

At 24X magnification, the reader shall display no less than one frame of 98-frame format microfiche. At 36X magnification, the reader shall display no less than one frame of 270-frame format microfiche. The screen shall clearly indicate the portion of the image that will be printed.

Front screen readers shall have light-absorbing black on all non-optional surfaces surrounding the screen. Rear screen readers shall have a fixed or detachable ambient light shield.

The fiche carrier with glass flat shall accept 4-inch by 6-inch fiche.

The reader shall have separate index grids for 1:24 source document and 1:48 COM microfiche.

The lamps shall be easily accessible and replaceable without requiring the use of special tools. Conspicuous warning signs shall be placed on or adjacent to parts or areas that may be of high voltage or other hazardous condition.

The reader/printer shall draw power from standard 110 to 120 V, 60 Hz alternating current. The power cord, complete with attached three-prong plug, shall be at least 6-feet long.

Focus, tone, and other operating or adjustment controls shall be readily accessible and identifiable.

The reader/printers shall be of appropriate size for table-top use, or be equipped with an appropriate work station.

Operating temperature shall be reached in less than five minutes.

Print time shall be 15 seconds or less for each copy.

The printer shall be capable of 8-1/2 inch by 11 inch, $\pm$ 1/2 inch, printing.

The paper used in the preparation of prints shall be at least 8-1/2 inches wide. The printer shall be either roll or sheet-fed. Rolls shall be at least 150 feet long, and the unit equipped with a cutting device for cutting the print to 11-inch lengths. The hopper for the sheet-fed units shall hold at least 150 sheets. Loading paper or adding chemicals shall be readily accomplished with minimum difficulty. Machines requiring a complete change or flush of existing chemicals as a rountine procedure are not acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.

The complete image of the print shall be a blowback of at least 71 percent of the 1:48 microimage and 92 percent of the 1:24 microimage.

The printer shall produce a positive image print from a negative image on a film four to nine mils thick.

Operating instructions shall be permanently mounted on the printer.

All prints shall be high contrast. It shall be possible to write on them within three seconds with pencil or ink.

Workmanship. Microform reader/printer shall be clean and free from faulty construction or any defect which affects appearance, serviceability, or durability.

The issue of UL standards in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

UL Standard 114 is available from Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil Downloaded: 202610-26T08:15Z
Check the source to verify that this is the current version before use.

GSA DC-01202208