A-A-1688
July 23, 1981

COMMERCIAL ITEM DESCRIPTION

TAPE, PRESSURE SENSITIVE ADHESIVE (PAPER, PHOTOGRAPHIC)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification UU-T-123.

This commercial item description covers photographic, pressure-sensitive adhesive tape.

Salient characteristics:

The tape shall be a flat black (matte, no gloss) creped paper for use in edging and blocking out purposes in the development and printing of photographic negatives; it also may be used in sealing cans of film.

The tape shall comply with the requirements below:

	Requirements	Test Method
Adhesion, oz./in. width Initial (min.)	10	ASTM D 3330
Elongation (percent) (min.)	6	ASTM D 3759
Tensile strength, lbs./in. width, (min.)	16	ASTM D 3759

Sampling and examination shall be according to the producer's standard practice as long as it provides equivalent assurance to that found in ASTM D 3715 with end item testing at an acceptance level (AQL) of 4 percent.

The issues of the ASTM standards in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Workmanship. The tape shall be uniformly constructed and free from defects which may impair usefulness of the material for the intended use. The adhesive shall be coated in a smooth uniform layer over the entire surface of the one side of the tape backing. The tape shall be evenly and tightly wound with no voids. The edges shall be clean cut. When unwound the tape shall not tear nor shall be adhesive separate from the backing.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

Note: Purchasers should specify length and width required.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

MILITARY INTERESTS:

User Activity:

Army - GL

Preparing activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:15Z
Check the source to verify that this is the current version before use.