A-A-168
April 17, 1981

COMMERCIAL ITEM DESCRIPTION

CLOTH, POLISHING (FOR ELECTRICAL CONTACT SURFACES)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification DDD-C-450.

The cloths covered by this commercial item description are intended for use in cleaning electrical contact surfaces of metallic component parts and hardware such as telephone switchboard plugs and jacks, relays and relay housings, potentiometer housing, contactor rings, switches, etc.

Salient characteristics:

The cloth shall be made from cotton and/or rayon and lightly napped on both sides. The finishing compound shall be silica based or of other suitable type that is effective in polishing electrical contact surfaces. The finishing compound and its method of application shall be in accordance with normal commercial practice. The size of each cloth shall be 11 x 13-1/2 inches, with a tolerance of 1/4 inch in either direction. All edges other than selvages shall be pinked or overedge stitched. The color shall be bleached white.

CHARACTERISTIC	REQUIREMENT	TEST METHOD
Breaking strength	warp - 25 lb. (min.) fill - 17 lb. (min.)	ASTM D 1682 (grab)
Weight	7.0 oz/yd (min.)	ASTM D 1910

The issues of ASTM D 1682 and 1910 in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product sold in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

Note: ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Preparing activity:

GSA-FSS

FSC 7920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.