[METRIC]
A-A-267B
January 28, 1998
Superseding
A-A-267A
April 23, 1982

COMMERCIAL ITEM DESCRIPTION

DEODORANT, GENERAL PURPOSE (AEROSOL AIR FRESHENER)

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. Scope. This commercial item description covers an aerosol air freshener to counteract malodors in occupied indoor areas such as public buildings and aircraft.

2. Salient Characteristics:

2.1 The product shall not contain formaldehyde.

2.2 The product shall leave a mild and pleasant odor immediately after spraying.

2.3 When used as directed on the container, the product shall counteract the odors from stale cigar and cigarette smoke, urine and fecal matter, vomit, food spillage, garbage, cooked foods, perspiration, and pets.

2.4 The product shall be packaged in an aerosol dispenser. The dispenser shall produce a spray in the form of a fine mist when moderate finger pressure is applied on the actuator. The dispenser shall stop the release of the spray immediately upon release of the pressure on the actuator. The dispenser shall deliver at least 98 percent by weight of its contents.

2.5 Delivery rate. When tested as specified in ASTM D 3069 -Delivery Rate of Aerosol Products, the dispenser shall have a delivery rate not less than 0.3 grams per second and not greater than 2.0 grams per second.

2.6 Net weight. The net weight of the contents of the aerosol dispenser shall be a minimum of 396 grams (14 ounces avoirdupois.)

Beneficial comments, recommendations, additions, deletions, clarification, etc., and any data which may improve this document, should be sent to: GSA, Paints and Chemicals Center, 400 15th Street, S.W., Auburn, WA 98001.

FSC 6840

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:06Z
Check the source to verify that this is the current version before use.

2.7 Flammability. When tested as specified in ASTM D 3065 -Flammability of Aerosol Products, the product shall meet the following requirements:

Flame projection	-	2.54 cm (1 inch), maximum
Tag O/C Flash Point	-	47^0 C (116^0 F), minimum
Closed Drum Test	-	45 seconds, minimum

2.8 Seepage. When tested as specified in ASTM D 3094 -Seepage Rage of Aerosol Products, the dispensers shall have a seepage rate no greater than 3.0 ml, using wide mouth eudiometer tubes similar to that in Figure 2 of ASTM D 3094.

2.9 Container stability. The filled containers shall not leak or be damaged by internal pressure when heated to 54^0 C (130^0 F.)

3. Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

NOTE: The contractor may use his normal quality assurance procedures for manufacture of this product; however, should a disagreement arise between the Government and its customer or between the Government and the manufacturer concerning compliance to the salient characteristics of this commercial item description, the test methods and tests stated in this commercial item description will be used to determine compliance of the product.

ASTM standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

PREPARING ACTIVITY:
GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.