COMMERCIAL ITEM DESCRIPTION

JACK, HYDRAULIC, HAND
(Self-contained)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification GGG-J-63.

This commercial item description covers hydraulic hand jacks with the pump, ram, and reservoir in an integral unit, and operated manually with a lever.

Salient characteristics:

Capacity. Jacks shall be furnished in the following capacities, as specified by the National Stock Number. The rated capacity of the jack shall be the load that the jack can safely raise to its maximum height, and maintain for at least ten minutes without lowering more than 1/4 inch.

National Stock Number (NSN)	Minimum Rated Capacity (Tons)	Maximum Collapsed Height (Inches)	Minimum Extended Height* (Inches)
5120-00-061-1301	1-1/2	8	14
5120-00-233-6829	3	9	16
5120-00-083-2844	3	10-1/8	20-1/2
5120-00-595-8396	8	9-1/2	17-7/8
5120-00-224-7330	12	9-1/8	16-1/2
5120-00-188-1788	20	11-1/4	16-7/16
5120-00-188-1790	30	11-1/4	17
5120-00-293-0555	100	10	13

*Includes screw extension.

Operating lever. A suitable lever to operate the pump shall be furnished.

Screw extension. Jacks with a 12-ton capacity or less may have a screw extension in the ram.

Center hole. The 100-ton jack shall be provided with a center hole for pulling.

Pump. The 30-ton and 100-ton jacks shall be furnished with a pump or pumps that provide for both high and low speed operation.

Pressure gauge. The 30-ton and 100-ton jacks shall have a threaded connection for the attachment of a pressure gauge.

Marking. Jacks shall be legibly and permanently marked with the rated capacity of the jack and the manufacturer's name or trademark.

Workmanship. The jacks shall be free from imperfections which may affect their appearance, serviceability, or durability. All parts shall be cleaned and free of extraneous materials, and burrs and sharp edges removed. Exposed surfaces shall be coated or finished in accordance with the manufacturer's standard practice, except that cadmium plating shall not be used.

GSA DC-81000189

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. Each jack shall be preserved and packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.