A-A-482
October 10, 1979

COMMERCIAL ITEM DESCRIPTION

ROUTER, ELECTRIC, PORTABLE

The General Services Administration has authorized the use of this commercial item description.

Salient characteristics:

Conform to the requirements of Underwriters' Laboratories Standard No. 45.
Motor with ball bearing construction mounted in a two-hand grip type base that will allow easy depth of cut adjustment.
Operate from a 120-VAC power source.
Maximum overall height, 8-1/2 inches.
Accessories: One 1/4-inch collet chuck.
One straight cutting guide.
One circular cutting guide.
Carrying case.
Complete set of operating and maintenance instructions.
Illustrated parts breakdown.
List of available accessory equipment.
All necessary chuck wrenches, special equipment, and tools to assure efficient operation in accordance with the operating instructions.

NSN	Collet chuck capacity (inch)	Minimum horsepower rating	Minimum operating current (amperes)	Minimum no-load speed (rpm)	Maximum weight without cord (pounds)
5130-00-035-6160	1/4	7/8	5.5	20,000	8
5130-00-177-7020	1/2	1-1/4	7.5	22,000	9

Workmanship. The router, including all parts and accessories, shall be free from fins, burrs, rust, external sharp or rough edges, imperfections, and any other defects which may impair serviceability, durability, or appearance.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. Each router, with accessory parts, shall be preserved and packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking shall be in accordance with the contract or order.

UL Standards are available from Underwriters' Laboratories, Inc., 1285 Melville Road, Long Island, NY 11746.

FSC 5130

GSA DC-01002460

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.