MIL-D-0043593A(GL)

12 November 1974
USED IN LIEU OF
MIL-D-43593
13 August 1968

MILITARY SPECIFICATION

DISPENSER, ICE, SELF-LEVELING, MOBILE; AND DISPENSER,

ICE, AUTOMATIC DISPENSING HEAD, MOBILE

This limited coordination Military specification has been prepared by the U.S. Army Natick Laboratories (GL), Natick, MA 01760, based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-D-43593. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE

1.1 Scope. This specification covers a mobile, self-leveling ice dispenser and a mobile ice dispenser with an automatic dispensing head.

1.2 Classification. The dispensers shall be of the following types, as specified (see 6.2).

Type I - Self-leveling
Type II - Automatic dispensing head

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

FF-C-77 - Casters: Institutional Duty

MILITARY

MIL-R-12323 - Refrigerators and Related Equipment, Packaging and Packing of

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130 - Identification, Marking of US Military Property
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing, with Appropriate Test Methods

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Society for Testing and Materials (ASTM)

Designation A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip

Designation A 554 - Welded Stainless Steel Mechanical Tubing

Designation A 276 - Stainless and Heat-Resisting Steel Bars, Hot Finished or Cold Finished

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Sanitation Foundation (NSF)

Standard No. 12 - Automatic Ice Making Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, P.O. Box 1468, Ann Arbor, MI 48106.)

Underwriters' Laboratories, Incorporated (UL)

Standard No. 73 - Motor Operated Appliances

(Application for copies should be addressed to Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611, Walt Whitman Road, Melville, Long Island, NY 11749, or 1655 Scott Boulevard, Santa Clara, CA 95050.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

95

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The dispensers shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Codes and standards. The type I dispenser shall comply with the applicable requirements of NSF Standard No. 12. The type II dispensers shall comply with the applicable requirements of NSF Standard No. 12 and UL Standard No. 73.

3.2.1 Compliance. Prior to commencing production, the supplier shall submit to the contracting officer or his authorized representative satisfactory evidence that the dispensers he proposes to furnish under this specification meet the applicable requirements of NSF Standard No. 12 and UL Standard No. 73 as follows.

3.2.1.1 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished dispenser, or

(2) A certification for the dispenser issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the dispensers are being procured, indicating that the dispensers have been tested and conform to NSF.

3.2.1.2 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the dispensers have been tested and conform to UL Standard No. 73.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

95

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial dispensers provided the completed item complies with all provisions of this specification.

3.3.1 Stainless steel.

3.3.1.1 Sheet and strip. Stainless steel sheet and strip shall conform to type 302 or 304 of ASTM A 167.

3.3.1.2 Tube. Stainless steel tube shall conform to grade MT-302 or MT-304 of ASTM A 554.

3.3.1.3 Angles and bar. Stainless steel angles and bar shall conform to type 302 or 304 of ASTM A 276.

3.4 Design and construction. The dispensers shall be caster mounted, and equipped with push handles, bumpers, drain pans, and drains. The dispensers shall show no evidence of parts failure, weld failure, parts separation, breakage or permanent deformation when static load tested as specified in 4.4.1, and obstacle tested as specified in 4.4.2. The fully loaded dispensers shall be towable with a force not exceeding 4 percent of gross weight and the wheels and swivels shall operate without chattering or binding when tow tested as specified in 4.4.3.

3.4.1 Type I. The type I dispenser shall have a storage capacity of not less than 175 pounds of cubes, cubelets, cracked or flaked ice with the lids closed when specified in 4.4.4, and shall be manual load, self-leveling, manual dispensing type consisting of an ice storage cabinet conforming to 3.5.1, self-leveling mechanism conforming to 3.5.2, lid or lids conforming to 3.5.3, casters conforming to 3.5.5, bumpers conforming to 3.5.6, push handle conforming to 3.5.7, and drain pan and drains conforming to 3.5.4. Overall dimensions including bumpers, push handles, and casters shall not exceed 30 inches in length, 19 inches in width, and 35 inches in height.

3.4.2 Type II. The type II dispenser shall have a storage capacity of not less than 165 pounds of cubes, cubelets, or cracked ice with the lids closed when tested as specified in 4.4.4, and shall be manual load, automatic dispensing type consisting of an ice storage cabinet conforming to 3.5.1, lid or lids conforming to 3.5.3, casters conforming to 3.5.5, bumpers conforming to 3.5.6, push handles conforming to 3.5.7, drain pan and drains conforming to 3.5.4, electric motor conforming to 3.5.9, power cord conforming to 3.5.10, and a dispensing tower conforming to 3.5.11. When specified the type II dispenser shall be equipped with a tray-rail conforming to 3.5.8 mounted on the dispensing side. The type II dispenser shall dispense ice directly into a glass or container when the actuating lever is depressed and shall stop when the actuating lever is released when tested as specified in 4.4.5. The dispenser tower shall dispense ice on the right or left side as specified. Overall dimensions, including bumpers, push handles, and casters shall not exceed 43 inches in length, 28 inches in width, 38 inches to top of ice bin cover, and 60 inches in height.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

95

3.5 Details of components.

3.5.1 Ice storage cabinet. The ice storage cabinet shall have a welded frame of stainless steel angles conforming to 3.3.1.3 not thinner than 11 gage nominal and an outer shell and inner liner of stainless steel conforming to 3.3.1.1 not thinner than 18 gage nominal. Seams on the inner shell shall not leak when tested as specified in 4.2.2.2. Seams on the outer shell shall be continuous welded. The space between outer shell and inner liner shall be completely filled with foamed-in-place or expanded foam insulation. Reinforcing plates shall be provided on the bottom corners of the cabinets for caster mounting.

3.5.2 Self-leveling mechanism. The self-leveling mechanism for type I dispensers shall maintain the ice at an optimum self-leveling position through the action of type 302 stainless steel, or chrome-vanadium springs counteracting the weight of the ice when tested as specified in 4.4.6. The mechanism shall be removable for repair or adjustment.

3.5.3 Lids. Lids for dispensers shall be fabricated of the stainless steel specified in 3.3.1.1 and shall be insulated with foamed-in-place or expanded foam insulation. Lids may be hinged or one piece, and shall be removable without use of tools for loading of ice and cleaning. When closed the lids shall form a close seal with the top of the cabinet when tested as specified in 4.4.7. The number and location of lids shall be in accordance with the manufacturer's standard practice.

3.5.4 Drains, drain pans, and drain fittings. The type I dispenser shall have a drain and a removable drain pan in accordance with the manufacturer's standard practice. The drain pan shall have a drain petcock. The type II dispenser shall have a 1-inch female pipe thread drain and a removable drain pan with a petcock or a shut off valve.

3.5.5 Casters. Each dispenser shall have four swivel casters mounted to the corner caster plates of the ice storage cabinet. Casters shall conform to type II, class A or B, style b, or c, mounting P, wheel diameter 5 inches, NSF approved of FF-C-77. The two casters on the service side of each dispenser shall have foot operated brakes. Casters shall be removable.

3.5.6 Bumpers. Each dispenser shall be equipped with horizontal continuous strip wrap-around bumpers, or a combination of strip and corner bumpers completely encircling the dispenser.

3.5.7 Push handles. Each dispenser shall have a push handle. Push handles for the type I dispensers shall be fabricated of 1-inch $\pm$ 1/8 stainless steel tube specified in 3.3.1.2. Push handles on the type II dispensers shall be in accordance with the manufacturer's standard practice. Push handles shall have bumpers in accordance with the manufacturer's standard practice. Handles on type II dispensers shall be mounted on the end opposite the dispensing tower.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

3.5.8 Tray rails. When specified (see 6.2) the type II dispensers shall have a drop type tray rail consisting of three 1-inch nominal diameter stainless steel tubes conforming to 3.3.1.2 and supporting hardware. The tray rail shall be mounted on the dispensing side of the ice storage cabinet and extend the full length of the dispenser. The ends of the tubes shall be closed. The height of the top of the tray rail shall be adjustable from 34 to 35 inches from the floor.

3.5.9 Electric motor. Unless otherwise specified (see 6.2), the electric motor for the type II dispenser shall operate on 115 volt, 60 hertz single phase current. The motor shall be not less than 1/4 horsepower.

3.5.10 Power cord. Each type II dispenser shall have a standard three conductor, type SJ, SJT, SJO, or STDD or heavier grease and oil resistant spring coil type power cord with an extended length of not less than 60 inches, and a coiled length of not more than 12 inches. The cord may be permanently attached to the cabinet or may be a separate component to plug in to a cabinet mounted power cord receptacle. The cord shall have three prong, twist lock attachment plug or plugs.

3.5.11 Dispensing tower. Each type II dispenser shall have a dispensing tower fabricated of any combination of the stainless steels specified in 3.3.1.1, 3.3.1.2 and 3.3.1.3 with a pressure actuated ice dispensing outlet with a manual set time control device to control the dispensing time from one to fifteen seconds when tested as specified in 4.4.5. Vibrators and augers shall be in accordance with the manufacturer's standard practice and may be mounted in the ice storage cabinet or be part of the dispensing tower. Dispensing towers shall be removable for cleaning and service or hinged to the storage cabinet and swing away for cleaning and service. The tower shall have a drain trough assembly beneath the ice dispensing outlet which drains into the drainage pan. At the option of the manufacturer the drain trough and drainage assembly may be an integral part of the top of the ice storage cabinet. There shall be not less than 10 inches of clear unobstructed height between the top of the drain trough and the bottom of the ice dispensing outlet. The tower shall be right hand dispensing or left hand dispensing as specified (see 6.2).

3.6 Finish. The finish shall be in conformance to NSF Standard No. 12.

3.7 Marking. Each dispenser shall be permanently and legibly marked with the manufacturer's name, trade name, or trademark of such known character as to be identifiable with said manufacturer. Marking shall be applied in accordance with MIL-STD-130.

3.8 Workmanship. All components and assemblies of the ice dispensers shall be free from dirt and other harmful extraneous materials, burrs, slivers, rough die, tool and grind marks, dents and cracks. Castings, molded parts and stampings, if used, shall be free of sand, fins, pits, blow holes, and sprues. External surfaces shall be free from sharp edges and corners, except when sharp corners are required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

3.8.1 Metal fabrication. Metal used in the fabrication of the ice dispensers shall provide for original quality surface finish and shall be free from kinks and unspecified bends. Forming and shearing shall not cause damage to the metal and shall be done neatly and accurately. Corners shall be square and true and all bends of a major nature shall be made with dies or fixtures to insure uniformity of size and shape.

3.8.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free of cracks, burn holes, undercuts or incomplete fusion. All scale and flux shall be removed from the finished weld area.

3.8.3 Threaded fasteners. Threaded fasteners and rivet holes shall be accurately punched or drilled and shall have burrs removed. Threaded fasteners shall not be broken, cracked or stripped and shall be securely torqued. Rivets shall fill the holes completely and the heads shall be in full contact with the surface of the member and concentric with the hole.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 In process inspection.

4.2.2.1 Process examination. Examination shall be made of the following fabrication process to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to the process and all items processed.

a. Installation of insulation as specified in 3.5.1 and 3.5.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

4.2.2.2 Intermediate testing. After fabrication of each inner liner, the drain hole shall be plugged and the liner filled to capacity with water. After thirty minutes, the liner shall be examined for leaks to determine compliance with 3.5.1.

4.2.3 End item inspection. The inspection lot shall be all dispensers of one type offered for inspection at one time.

4.2.3.1 Visual examination. The dispensers shall be examined for the defects in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Design type I and type II	Not type specified	X	
	Not manufacturer's standard product	X	
Workmanship general type I and type II	Any component missing or not as specified	X	
	Dirty	X	
	Burrs, slivers, rough die marks, tool marks, grind marks, dents, cracks, sharp edges, sharp corners	X	
Castings and stampings	Sand, fins, pits, blow holes, sprues	X	
Welds	Rough finish weld, crack, burn hole, undercut, incomplete fusion, scale or flux not removed	X	
Metal fasteners	Broken, cracked, stripped thread, crossed thread	X	
	Loose		X
	Rivet heads and peened ends not in full contact with joined metal surfaces		X
Push handles	Not equipped with bumpers	X	
Bumpers	Not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

95

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Workmanship general type I and type II (cont'd)			
Casters	Not size or type specified, two casters not equipped with foot operated brakes	X	
Lids	Not type specified	X	
Drains and drain pans	Missing, not as specified	X	
Marking	Missing, not legible, not as specified		X
Type I and type II dispensers	Self leveling mechanism not removable	X	
Tray rails (when specified)	Missing, not type specified, not mounted on side specified	X	
Dispensing tower	Not mounted on side specified	X	
Push handle	Not mounted on end opposite dispensing tower	X	
Power cord	Missing, not type specified	X	

4.2.3.2 Dimensional examination. The ice dispensers shall be examined for compliance with dimensions specified. Any dimension not within the specification tolerance shall be a defect. The inspection level shall be S-2 and the AQL shall be 4.0, expressed in terms of defects per hundred units.

4.2.3.3 End item testing. The tests specified in column 2 of table II shall be performed using an inspection level of S-2. Failure to pass any test shall be cause for rejection of the lot. The tests specified in column 3 of table II shall be performed on one production unit (see 6.3). Failure of any test shall be cause for rejection of the inspection lot.

4.2.4 Examination of preparation for delivery. An examination shall be made to determine that preparation for delivery, as specified in section 5 of this specification, is in conformance with MIL-R-12323.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

95

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the requirements of 3.3, shall be examined and validated.

4.4 Test methods. The test schedule shall be in accordance with table II.

TABLE II. Test methods

Column 1	Column 2	Column 3	Column 4	Column 5	Column 6
Type to be tested	Quality conformance	Production unit	Test	Test paragraph	Requirement paragraph
I and II		X	Static load test	4.4.1	3.4
I and II		X	Obstacle test	4.4.2	3.4
I and II		X	Tow test	4.4.3	3.4
I and II		X	Capacity test	4.4.4	3.4.1 and 3.4.2
II	X	X	Dispensing test	4.4.5	3.4.2 and 3.5.11
I	X	X	Self-leveling test	4.4.6	3.5.2
I and II	X		Lid seal test	4.4.7	3.5.3

4.4.1 Static load test. The dispensers shall be loaded with a weight of not less than twice their rated capacity. The weight shall be equally distributed within the storage cabinet and shall remain in place for not less than 10 minutes. The dispenser shall then be examined, the load removed, and the dispenser re-examined to determine compliance with 3.4. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.2 Obstacle test. The dispensers loaded to capacity with ice, or with weight equal to their capacities shall be rolled over a 1/4-inch obstacle ten times at a minimum speed of 2 miles per hour. The dispenser shall then be examined to determine compliance with 3.4. Any nonconformance with specified requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

4.4.3 Tow test. The dispensers loaded as specified in 4.4.2 shall be towed, utilizing a tension dynometer, on a level surface at a speed of not less than 2 miles per hour. After the dispenser has attained a speed of 2 miles per hour the tension dynometer shall be observed over a distance of not less than 100 feet. The maximum reading registered on the tension dynometer while the dispenser is traveling not less than 2 mph shall be used to determine the force required to move the dispenser to determine compliance with the towing requirements of 3.4. During the test the casters shall be observed to determine compliance with the chattering and binding requirements of 3.4. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.4 Capacity test. The dispensers shall be loaded with ice and the covers put in place and closed. The ice shall then be immediately removed and weighed to determine compliance with the capacity requirements of 3.4.1 or 3.4.2 as applicable. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.5 Dispensing test. The type II dispenser shall be loaded with ice and connected to the applicable electric power source. A container shall be placed against the actuating lever and removed not less than 10 times to determine compliance with the dispensing requirements and the stopping requirements of 3.4.2. The timing device shall then be set for a three second dispense and operated 10 times, then reset at 5 seconds, 10 seconds and 15 seconds and operated 10 times at each time setting. The time of dispensing at each setting shall be measured to determine compliance with the dispensing time control requirements of 3.5.11. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.6 Self-leveling test. The type I dispenser shall be loaded to full capacity with cubes, cubelets, cracked or flaked ice. The ice shall then be manually removed one scoop at a time using a 1-quart scoop until all ice has been removed. During the removal of the ice the self-leveling mechanism shall be observed to determine compliance with optimum level maintenance requirement of 3.5.2. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.7 Lid seal test. With the lid or lids in place and closed, a 0.005 inch leaf gage shall be inserted between the lid and the sealing face of the cabinet top to determine compliance with the sealing requirements of 3.5.3. The gage shall be inserted at midpoint of each side of lid and at the four corners of lid. Failure of the seal to offer resistance to the gage shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Levels A, B, and C. Preservation, packaging, packing, and marking for each level of protection shall be in accordance with the applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

95

requirements of MIL-R-12323, except that cushioning and blocking and bracing may be in accordance with MIL-STD-1186. In addition, if the casters are not removed from the dispenser prior to level A or B packing, the base of each shipping container shall be provided with cross loadbearing members to provide a minimum 1/2-inch clearance for the casters.

6. NOTES

6.1 Intended use. The dispensers covered by this specification are intended for dispensing ice in dining halls. The type I is for manual dispensing. The type II is for automatic metered dispensing.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of dispenser required (see 1.2).
(c) When tray rails are required on type II dispensers (see 3.5.8).
(d) When electric motor characteristics for type II dispensers are other than specified (see 3.5.9).
(e) Whether type II dispenser towers shall be right or left side (see 3.5.11).
(f) Selection of the applicable levels of preservation and packaging and packing (see 5.1).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

6.3 End item tests. Performance of the production unit tests as specified in column 3 of table II should be limited to one successful demonstration of compliance to the requirements of this specification for each contract.

Custodians:

Army - GL

Review activities:

Army - MD

Preparing activity:

Army - GL

Project No. 7320-A492

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

93

FOLD

DEPARTMENT OF THE ARMY
US Army Natick Laboratories
Natick, MA 01760
STSNL-TDG

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

Commander
US Army Natick Laboratories
ATTN: STSNL-TDG
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-D-0043593A(GL) DISPENSER, ICE, SELF-LEVELING, MOBILE; AND DISPENSER, ICE, AUTOMATIC DISPENSING HEAD, MOBILE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:47Z
Check the source to verify that this is the current version before use.