3 June 1975
SUPERSEDING
MIL-T-43610
27 November 1968

MILITARY SPECIFICATION

TRUCK, HAND, BOX, LAUNDRY, PLASTIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers plastic, laundry hand trucks (see 6.1).

1.2 Classification. The plastic hand trucks shall be of the following sizes, as specified (see 6.2).

Size 1 - 8 bushel
Size 2 - 12 bushel
Size 4 - 16 bushel

2. APPLICABLE DOCUMENTS

* 2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-390	-	Plastic, Molding and Extrusion Material, Polyethylene and Copolymers (Low, Medium and High Density)
FF-C-77	-	Casters, Rigid and Swivel (Institutional Duty)
PPP-B-601	-	Boxes, Wood, Cleated-Plywood

MILITARY

MIL-W-13518	-	Wood Preservative: Tetrachlorophenol and Pentachlorophenol, Surface Sealing Compound

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

United States Department of Commerce

Product Standard PS 1-66 - Softwood Plywood/Construction and Industrial

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The trucks covered by this specification shall be the regular commercial product of the manufacturer except for changes necessary to comply with the specification requirements. All trucks of the same size furnished under any one contract or purchase order shall be identical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

3.2 Materials. Materials not definitely specified shall be of the quality normally used for the purpose in commercial practice.

3.2.1 Polyethylene. The polyethylene shall conform to type I, general purpose, class L and M, grade 1 of L-P-390.

3.2.2 Plywood. Plywood shall be exterior type, group 1, grade B-C or better conforming to Product Standard PS 1-66. The thickness of the plywood shall be a minimum of 5/8-inch.

3.2.3 Sealer, wood preservative. The wood sealer shall conform to type II, class 2 of MIL-W-13518.

* 3.3 Construction. The hand trucks shall be constructed in accordance with the requirements specified herein and shall conform to the dimensions specified in table I. Nuts and bolts used in construction shall be cadmium or zinc plated.

TABLE I. Dimensions

Size	Commercial 2/ size designation	Body minimum (inches) Length 1/	Width 1/	Depth	Wheel diameter minimum (inches)
Size 1	8 Bushel	32-7/8	21-1/4	23	3
Size 2	12 Bushel	33-3/4	24	27-1/8	4
Size 4	16 Bushel	37-1/2	26	29-1/2	5

1/ Length and width measured inside top.

2/ The size truck specified shall be of the same capacity furnished commercially provided there is compliance with minimum dimensions.

* 3.3.1 Body. The truck body shall be fabricated from either polyethylene specified in 3.2.1, fiberglass, a combination of fiberglass and polyethylene, or acrylonitrile-butadiene-styrene (ABS) plastic. The body shall be of seamless, one-piece construction and shall have a wall thickness of not less than 0.190 inch after forming. The corners and edges shall be rounded and the top lip shall be rolled outward. The top lip shall be reinforced by either a tubular steel rod, a wooden frame, or a fiberglass rope placed around the perimeter of the truck, except reinforcements are not required when the thickness of the body and lip material exceeds 0.225 inch. When tubular steel reinforcing rod is utilized, wedge shaped gussets shall be fused to the body under the top lip. The rod shall be free floating so as to absorb shock without damaging the top of the truck. Bolts shall be integrally molded into the bottom of the body, spaced and located in a manner to receive the base and casters. The sides of the body shall be tapered for nesting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

3.3.2 Base. The base shall be constructed from either exterior plywood specified in 3.2.2 or galvanized steel sheet. A painted tubular steel frame or other reinforcement may be added at the bottom of the base of the truck body in accordance with the manufacturer's commercial practice for the purpose of providing protection against damage.

3.3.3 Casters. Unless otherwise specified (see 6.2) each truck shall have 4 casters mounted without overhang at the 4 corners of the base. Casters shall be type II, class B, style c, mounting p of FF-C-77. Casters shall be of the diameter shown in table I. Casters shall be provided with thread guards.

3.4 Finish. All voids on the sides and end of the plywood base when applicable shall be filled with a wood filler. After filling voids, the side and end surfaces of the base shall be sanded smooth, cleaned, given a coat of sealer specified in 3.2.3, and painted with a commercial gray protective coating. Tubular steel rods shall be painted or plated in accordance with the manufacturers commercial practice.

3.5 Marking. The hand truck shall be marked on the outside, and in a conspicuous location, with the manufacturer's name or trademark.

3.6 Workmanship. The completed hand truck shall be clean and properly assembled. Interior and exterior surfaces shall be smooth, free of tears, holes, cracks, burns, lumps, rough edges, imbedded dirt or foreign material, soft areas, thin sections, and any surface dirt which cannot be removed with soap and water.

3.6.1 Welding. All welds, when used, shall have a uniform bead contour throughout and shall be free from irregularities, craters, undercut, surface oxidation, pipes, and porosity. The metal in and adjacent to the welded area shall be free from cracks, holes, and imperfections indicative of poor fusion. Plated surfaces when damaged by welding shall be repaired using suitable coating compounds.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 In-process inspection. When plywood bases are furnished, inspection shall be made during the manufacturing process for the requirements specified in 3.4 to establish that no deviation is made from specified requirements. Whenever nonconformance is noted, correction shall be made to affected items and process.

4.2.3 End item inspection. The lot shall be all hand trucks of one size offered for inspection at one time. The sample unit shall be one complete hand truck.

4.2.3.1 Visual examination. Examination shall be made of the end item for defects in table II. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Design and construction	Trucks of one size, furnished at the same time, not identical	X	
	Sides of truck body not tapered for nesting	X	
	Nut, bolt, or caster not cadmium or zinc plated	X	
	Body not one piece	X	
	Corners and edges not rounded or top lip not rolled outward	X	
	Top lip not reinforced as specified (when provided)	X	
	Caster missing or not type specified	X	
	Thread guards missing	X	
	Trucks not identical throughout		X
	Plywood not painted (as applicable)		X
	Rod not painted or plated (as applicable)		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Workmanship	Body interior and exterior surfaces not smooth	X	
	Any cut, tear, hole, crack, burn, lump, blister, or mend in body	X	
	Any sharp or rough edge	X	
	Any imbedded dirt or foreign material	X	
	Any surface dirt which cannot be removed with soap and water	X	
	Any soft area	X	
	Visual evidence of thin area	X	
Welding	Welds not uniform bead, not free of craters, undercut, surface oxidation, pipes, or porosity; cracks or hole adjacent to welds (when applicable)		X
Marking	Illegible, incomplete, wrong location		X

4.2.3.2 Dimensional examination. Examination shall be made to determine compliance with dimensions and commercial size designations of table I and with wall thickness specified. Any dimension not within the established requirements shall be classified a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.2.4 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be as indicated in table III. The sample unit shall be one shipping container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

TABLE III. Examination of preparation for delivery

Examine	Defect
Marking (exterior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any nonconforming component; component missing or damaged

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of preparation for delivery (cont'd)

Examine	Defect
Workmanship	Inadequate application of components such as lumber blocking, bracing, cleats, and burlap backed felt
Contents	Number per container is more or less than required

4.2.4.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-601, examination for defects in strapping shall be in accordance with the appendix of that specification.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

* 5.1.1 Level A. Four trucks, of one size only, shall be nested into one another. Prior to nesting, the casters shall be covered with a piece of burlap-backed jute felt approximately 1/2 inch thick and the ends of the felt securely fastened to the caster with wire or twine. The casters on the bottom truck shall be left uncovered. Alternative to covering casters with felt, a fiberboard pad shall be placed in the bottom of the body of the three lowermost trucks to prevent casters from contacting the adjacent trucks. The size of the fiberboard pad shall be not less than 1/2 inch less than the inside dimensions of the bottom of the body of the truck.

* 5.1.2 Level C (Commercial Packaging). Trucks shall be packaged to afford adequate protection against physical damage during shipment from the supplier to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

* 5.2.1 Level A. Four trucks, packaged as specified in 5.1, shall be packed in a snug-fitting cleated plywood shipping container conforming to overseas type, style A, B or J, grade A or B, type 3 load of PPP-B-601. Lumber, blocking, and bracing shall be provided under the nested trucks to provide a minimum 1/2 inch clearance between the casters and bottom of the container. Shipping containers exceeding 200 pounds gross weight shall be provided with skids in accordance with PPP-B-601. Closure and strapping shall be in accordance with the appendix of PPP-B-601.

* 5.2.2 Level B. Four trucks, packaged as specified in 5.1, shall be packed as specified in 5.2, except the container shall conform to domestic type, grade B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

5.2.3 Level C (Commercial Packing). Trucks, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Trucks covered by this specification are intended to be used in laundries and dry cleaning plants for both soiled and clean laundry.

* 6.2 Ordering data. Procurement document should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2).
(c) Caster arrangement required if other than specified (see 3.3.3).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.4 Size 3 of MIL-T-43610 was deleted from this revision.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activity:

Army - MD

User activity

Navy - MC

Preparing activity:

Army - GL

Project No. 3510-0212

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-T-43610A - TRUCK, HAND, BOX, LAUNDRY, PLASTIC

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK DEVELOPMENT CENTER
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AMXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
US Army Natick Development Center
ATTN: AMXNM-TD G
Natick, MA 01760

NATICK OP 1 MAY 75

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:50Z
Check the source to verify that this is the current version before use.