
INCH-POUND
MIL-DTL-3954/15B
18 February 2015
SUPERSEDING
MIL-D-3954/15A
29 May 1974

MILITARY SPECIFICATION SHEET

DUMMY LOADS, ELECTRICAL, WAVEGUIDE
(FREQUENCY RANGE 1.12 TO 1.70 GIGAHERTZ)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the product described herein shall consist of this Specification Sheet and MIL-DTL-3954.




PREFORMED PKG. 2 REQD.
(ONE AS REPLACEMENT)

Inches	mm
.062	1.57
.125	3.18
.188	4.78
1.125	25.58
3.891	98.83
4.141	105.18
7.141	181.38
7.391	187.73
8.875	225.50
11.438	290.53
32.875	835.03

NOTES
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .005 (.13 mm).
3. Metric equivalents (to the nearest .01 mm) are given for general information only.
4. Screws, lockwashers and gasket are supplied with mating flange.
5. Quantity of fins required will be dependent on heat level requirement of the load.

FIGURE 1. Class 1 dummy load.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:54Z
Check the source to verify that this is the current version before use.



Inches	Mm	Inches	mm
.010	.25	.500	12.70
.02	.51	.750	19.05
.05	1.52	1.125	28.56
.052	1.57	1.75	44.45
.100	2.54	1.875	47.63
.109	2.77	2.500	63.50
.125	3.18	2.750	69.25
.250	6.35	3.00	76.2
.300	7.62	5.000	127.0
.375	9.38	11.00	379.4
		36.000	314.40

NOTES
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .005 (.13 mm).
3. Metric equivalents (to the nearest .01 mm) are given for general information only.
4. Screws, lockwashers and gasket are supplied with mating flange.

FIGURE 2. Class II dummy load.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:54Z
Check the source to verify that this is the current version before use.

TABLE I. Characteristics.

PIN	Class	Material	Flange equal to	VSWR max	Power		Pressure		Figure	Flow rate	Input temp.	Output temp.
					Average	Peak	Internal	Coolant chamber				
					(watts)	(kilowatts)	(psig)	(psig)		(GPM 1/)	(°C)	(°C)
M3954/15-01	I	AL	M3922/58-008 (UG-418B/U)	1.10	2/ 2,200	2,200	23		1			
M3954/15-02	II	AL	M3922/58-008 (UG-418B/U)	1.10	15,000	17,200	30	150	2	5	35	60
M3954/15-03	II	Copper	M3922/58-007 (UG-417B/U)	1.10	15,000	17,200	30	150	2	5	35	60
M3954/15-04	II	Corrosion resisting steel	M3922/58-007 (UG-417B/U)	1.10	15,000	17,200	30	150	2	5	35	60

1/ The flow rate was determined from the following formula:

$$Q = \frac{6.8P}{Cp\ \Delta T}$$

Where: Q = Minimum flow rate in GPM
P = Avg power in kilowatts
Cp = Specific heat of coolant.
ΔT = Coolant temperature rise in °F.

The calculations were made for Cp = 1 for water, a ΔT of 45°F and a safety factor of approximately 2. For different coolants of different temperature rises, a different flow rate would be necessary.

2/ This is a test power value. The average rated power is 8,000 watts.

TABLE II. Cross reference of PIN/ AN nomenclature.

PIN	AN nomenclature
M3954/15-01	DA-147/U

REQUIREMENTS:

Design and construction
Dimensions and configuration: See figures 1 and 2.
Weight:
Dry loads – 113 lbs max.
Liquid cooled load – 270 lbs max.

Performance characteristics: See table I.

Part or Identifying Number (PIN): M3954/15 – (dash number from table I).

Referenced documents. This document references MIL-DTL-3954.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:54Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5985-2015-005)

Review activities:
Army – AR, MI
Navy – AS, CG, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:54Z
Check the source to verify that this is the current version before use.