MILITARY SPECIFICATION

CRANE, WHEEL-MOUNTED: HYDRAULIC, ROUGH TERRAIN, 30-TON CAPACITY, FULL REVOLVING, 4 BY 4, DED

This amendment forms a part of Military Specification MIL-C-29352(MC), dated 17 July 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1:

Under "STANDARDS MILITARY", add "MS75058 - Connector, Receptacle, Electrical-Slave, 2 Contact, 24 Volt, Waterproof".

Under "DRAWINGS U.S. ARMY TANK AUTOMOTIVE COMMAND", delete "1920711682345 - Connector Receptacle, Electrical-Slave, 2 contact, 24 Volt, Waterproof".

PAGE 4

3.3.1, lines 8 and 9: Delete "capable of two- or four-wheel drive at the selection of the operator" and substitute "capable of four-wheel drive".

PAGE 5

3.3.2.2:

Line 13: After "angle", add "of the boom with".

Line 14: Delete "of".

Line 15: Delete "and angles".

PAGE 6

3.3.2.4, lines 5 and 6: Delete "of sufficient length to perform two-cable clamshell operations" and substitute "not less than 350 feet in length".

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:30Z
Check the source to verify that this is the current version before use.

PAGE 7

3.3.2.8:

Line 2: After "accessible", add "to the operator".

Line 5: Delete "pedal or" and substitute "pedal and".

3.3.3, line 5: Delete "The" and substitute "Prior to first article acceptance, the".

PAGE 8

3.3.3:

Subparagraph (k): Delete "Drawing No. 11682345" and substitute "MS75058".

After subparagraph (o), add new subparagraph as follows:

"(p) A means shall be furnished to prevent energizing the starter motor whenever the engine is running. The crane shall be provided with an interlock in the starting system, or other means, to prevent energizing the starter motor except when the directional control lever is in the neutral position."

3.3.4:

Line 2: Delete "with retarder".

Line 7: Delete "The crane" and substitute "Prior to first article acceptance, the crane".

PAGE 9

3.3.6, last line: Delete "of 60 pounds" and substitute "and sufficient air hose to reach and inflate each tire on the crane to not less than 60 lb_f/in^2".

3.3.7:

Line 7: Delete "override".

Line 8: Delete "lock out rear wheel oscillation" and substitute "prevent rear wheel oscillation when swinging 360 degrees".

Source: https://assist.dla.mil -- Downloaded: 20260-20T22:30Z
Check the source to verify that this is the current version before use.

PAGE 17

3.7(b)(2): Delete "27,600 pounds at 15-foot radius, and 18,800 pounds at a 20-foot radius".

PAGE 18

3.7.3: At end of paragraph, add "the swing lock or brake shall be a type which, once activated, will continue to function without constant operator control".

PAGE 21

4.7.1, line 10: Delete "be compared with" and substitute "not exceed the".

Preparing activity:
Navy - MC
Project No. 3810-N063

Source: https://assist.dla.mil -- Downloaded: 202610-20T22:30Z
Check the source to verify that this is the current version before use.