MILITARY SPECIFICATION

DISTRIBUTOR, WATER, TANK TYPE, SEMITRAILER
TRACTOR MOUNTED 7,000 GALLON CAPACITY, DED

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of commercial, low profile water distributor, (semitrailer tanker two-wheel tractor mounted) 7,000 gallon capacity, diesel engine driven, (hereinafter referred to as the unit) with salient features as specified herein.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified (see 6.2), the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

O-E-760 - Ethyl Alcohol (Ethanol) Denatured Alcohol, Proprietary Solvents and Special Industrial Solvents.
W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Storage.
TT-P-664 - Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
VV-F-800 - Fuel Oil, Diesel.

MILITARY

MIL-D-771 - Distributors, Bitumen and Water, Packaging of.
MIL-T-3351 - Tractor, Full-Tracked, Low-Speed; Tractor Wheeled Agricultural; and Tractor Wheeled, Industrial: and Their Attachments, Packaging of.
MIL-C-5501 - Cap and Plug, Protective, Dust and Moisture Seal.
MIL-C-21567 - Compound, Silicone, Soft Film.
MIL-P-46093 - Primer Coating, Synthetic (for Brake Drums).
MIL-B-46176 - Brake Fluid, Silicone, Automotive All Weather, Operational and Preservative.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

STANDARD

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DEPARTMENT OF LABOR (DoL)
OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies of DoL should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2.1 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DODISS and the supplement thereto, if applicable.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096).

TIRE AND RIM ASSOCIATION, INC.

T&RA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The unit shall be a diesel-engine-driven, semitractor, trailer tanker, two axle type, two driven wheels, and 7,000 gallon capacity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified (see 6.2), the contractor shall furnish a distributor for first article inspection and approval (see 4.2.1 and 6.2).

3.3 Standard commercial product. The unit shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the unit being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

3.4 Identical items. All units furnished under a specific contract shall be physically and mechanically identical. Parts, accessories, assemblies, and components are included in this requirement. Written approval for deviations must be obtained in advance from the contracting officer.

3.5 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification unless otherwise specified.

3.6 Safety. All moving parts, parts subject to high operating temperatures, and parts energized electrically which are of such a nature or so located as to become a hazard to operating and maintenance personnel shall be insulated, enclosed, or guarded to the extent necessary to eliminate the hazard. Protective devices shall not impair the operating functions. Platforms, steps, handholds, and rails shall be furnished and located where necessary, to assure safe, easy access by personnel to those areas requiring frequent maintenance or service. The unit shall comply with OSHA regulations in effect at the time of manufacture. The unit shall be provided with the following equipment:

a. Safety glass windshield with power operated windshield wiper.
b. Horn.
c. Backup alarm device conforming to SAE J994.
d. Seat belt for operator's seat conforming to SAE J386.
e. Rollover protective structure conforming to SAE J1040.
f. Adjustable air suspension seat.
g. Instrument panel (vandalism) protective guard.
h. Emergency steering system conforming to SAE J53.

3.7 Dimensions, cubes, and capacity. The unit shall conform to the dimensions, cubes, and capacity specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions, cubes, and capacities.

Capacity	7,000 gallons minimum
Unit width	12 feet maximum
Unit height	13 feet maximum
Overall length of unit	50 feet maximum
Travel speed (empty on level earth-haul road)	24 mph minimum

3.8 Roll-over protective structures (Rops). The unit shall be furnished with open canopy construction type Rops conforming to SAE J1040 and seat belts conforming to SAE J383 and J386. The Rops shall be labeled in accordance with SAE J1164. The manufacturer shall prepare certification that the Rops meets the SAE standard. Installation shall be in accordance with the Rops manufacturer's recommendations.

3.9 Operational temperature requirements. The unit shall be capable of starting and maintaining constant performance characteristics, at a stabilized temperature from -20° Fahrenheit (F) to +120°F, without special equipment or modifications other than the use of antifreeze proper lubricants; at any elevation from sea level and a maximum stabilized temperature of 102°F, and to maintain with sufficient power for operating up to a 5,000 foot elevation at a temperature of 107°F.

3.10 Tractor. The tractor shall be of the single axle type and support or incorporate as integral parts, the bumper, towing hook(s), crankcase guard, oscillating hitch assembly, operator's station, full power steering, hydraulic system, cold starting aids, power plant, power train, and emergency steering system conforming to SAE J53. Frame shall be mounted on two power driven, pneumatic-tired wheels. Crankcase guard shall protect the crankcase, flywheel housing, accessories, and other assemblies exposed to damage from projecting obstructions likely to be encountered during normal earthmoving operations. Crankcase guard shall be furnished with openings which shall provide easy access to points requiring periodic servicing and cleaning. Access openings shall be equipped with cover plates. The tractor shall have individual cab-located controls for operating the unit. Each control shall be clearly identified for the intended function with a corrosion-resistant nameplate. Tractor shall be capable of making a 90° turn with tank attached.

3.11 Trailer water tank. The trailer water tank shall have a minimum capacity of 7,000 gallons, and be equipped with not less than the following: Surge baffles, manhole (not less than 18 inches in diameter) with strainer and cover having a vent not less than 3 inches in diameter, hydraulic-motor-driven water pump having a rated capacity of not less than 1,200 gallons per minute at 2,000 revolutions per minute pump speed and 15 pounds per square inch or 35 foot head, rear sprayheads and gravity spraybar. Trailer water tank shall be single nondriven axle type with two wheels.

3.12 Brakes. The unit shall be equipped with service brakes, parking brakes, and an emergency stopping system that shall conform to the minimum performance requirements of SAE J1152. When brakes are air actuated, the air reservoir volume shall conform to SAE J813. Brake drum guards shall be furnished. Air reservoir(s) shall have moisture bleeder(s). Brakes shall be synchronized to apply the trailer brakes prior to application of the tractor brakes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.13 Wheels, rims, and tires. Wheels, rims, and tires shall be demountable as an assembly and interchangeable front to rear. Tires shall be wide base, tubeless, with rock type tread. Tire and rim sizes, ply rating and load rating shall conform to T&RA recommendations.

3.14 Power plant. The unit shall be equipped with a liquid-cooled diesel engine. The net horsepower rating of the flywheel shall be not less than 300 when determined as specified in SAE J816. The engine shall be capable of operation of diesel fuel conforming to VV-F-800 and shall be equipped with either glow plug or ether cold start aids. When an ether priming system is provided, it shall be of the measured shot type, controlled from the driver's compartment, with a reservoir of not less than 12 fluid ounces, and shall be inoperative when engine is warm.

3.15 Transmission and torque converter. The unit shall have a full torque power shift transmission. The transmission system shall provide not less than five forward speeds and one reverse speed. Torque converter oil coolers shall be furnished. Coolers shall maintain the oil entering the converters at a temperature not to exceed 240°F.

3.15.1 Accessories. The unit shall be furnished with the following accessories:

a. Two stage intake air cleaner with service indicator.
b. Full flow oil filter with bypass.
c. Primary and secondary fuel filters.
d. Hour meter.
e. Fuel tank with sufficient capacity for 8 hours operation.
f. Lubricating oil pressure indicator.
g. Coolant temperature indicator.
h. Electric cranking system.
i. Battery(s), moisture sealed and without filling of electrolyte.
j. Battery charging alternator/rectifier system.
k. Torque converter oil temperature indicator.
l. Battery charging indicator.
m. Heavy-duty radiator guard.
n. Tachometer.

3.16 Exhaust. The engine shall be equipped with an exhaust muffler, spark arrester (a muffler and spark arrester are not required if the engine is turbocharged), and stack; maximum sound level shall not exceed the recommended level of SAE J88A. Exhaust stack outlets shall be provided with rain caps or 90° bends.

3.17 Toolbox. The unit shall be provided with a toolbox made of sheet steel. The toolbox shall have a hinged lid which shall open not less than 90° and a drawbolt or spring loaded latch of a type that will keep the lid closed when the toolbox is subjected to vibration. Toolbox shall be securely fastened to the machine in a protected and accessible location. The toolbox shall be of sufficient size to hold the tools normally used to maintain the unit.

3.18 Lubrication. Lubrication shall be in accordance with the manufacturer's recommendations. Pressure lubrication shall not damage seals or other parts. All parts requiring lubrication shall be lubricated as specified in

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

section 5. A permanently attached standard commercial lubrication chart indicating the type and temperature rating of the lubricants used shall be furnished. Hydraulic lubrication fittings shall conform to SAE J534.

3.19 Lifting and tying down attachments. The unit shall be equipped with lifting and tying down attachments. Attachments shall conform to MIL-STD-209, type III. Attachments shall be indicated by a transportation plate, except tying down attachments may be identified by stenciling or other suitable marking of the unit. Tying down marking shall clearly indicate that the attachments are intended for tying down of the machine on the carrier when shipped.

3.20 Instruction plates. The unit shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment, and shall be securely affixed thereto.

3.21 Identification plate. The contracting officer will furnished to the Government inspector, the required identification plates. The contractor will be required to stamp all necessary data in the blank spaces thereon and securely affix said plates in a conspicuous place on each unit, assembly, and/or subassembly and parts as directed by the Government inspector. Nonferrous screws, rivets, or bolts of not less than 1/8-inch in diameter shall be used to affix the plates.

3.22 Electrical systems.

3.22.1 Ignition and starting system. The unit shall have a 24-volt electrical system. Not less than two batteries shall be furnished. Each battery shall be 12-volt potential. The total reserve capacity rating of the batteries shall be not less than 320 minutes and the total cold cranking rating of the batteries at ^{o}F shall be not less than 1200 amperes, measured in accordance with SAE J537. Batteries shall be furnished dry charged in accordance with W-B-131, without electrolyte, with sealed caps to prevent the intrusion of atmospheric moisture. Unit shall be provided with a battery box painted with acid-resistant paint. Unit shall be equipped with a generator or alternator having not less than a 35-ampere rating. All wiring shall be protected against wearing and weathering. A waterproof socket receptacle, with mating plug, electrically connected to the starting system shall be furnished to facilitate emergency starting and battery charging.

3.22.2 Lighting. The lighting system shall include the following:

a. Two headlamps.
b. Instrument panel lamps to illuminate all instruments.
c. One rearward directed floodlamp.
d. Two taillights and two stoplights. These lights may be a combination of both.

3.23 Cleaning, treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as oil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

3.24 Workmanship.

3.24.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.24.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.24.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.24.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.24.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

4.1.1 Material inspection. The contractor is responsible for insuring that supplies and materials are inspected for compliance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on the unit when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the distributor meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining distributors to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4.7, and the packaging inspection of 4.4.7 and packaging inspection of 4.5.

4.3 Examination. Each unit shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Test. The first article shall be subjected to the test specified in 4.4.1 through 4.4.7. Production units shall be tested as specified in 4.7. Failure to pass one or more tests shall be cause for rejection.

4.4.1 Performance tests. Each unit shall be subjected to the tests as specified below. Failure to pass any phase of these tests shall be cause for rejection. The tests shall, as a minimum, assure that each unit is capable of meeting the performance requirements as specified in section 3. The unit shall be cycled not less than two times. The tank shall be loaded to a capacity of not less than 7,000 gallons and each load shall be dumped without assistance from auxiliary equipment.

4.4.2 Preliminary examination. The unit shall be generally examined and inspected to determine acceptability on the basis of conformance to contract requirements.

4.4.3 Load-haul-dump test. The hauling distance for each cycle shall be not less than 1,500 feet.

4.4.4 Gradeability test. The unit loaded to the specified capacity shall negotiate an approximately 100 foot long, well compacted earth grade, having a minimum slope of 20 percent. The unit shall travel up and down this slope three times.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

4.4.5 Side hill slope test. Without any payload, the unit shall traverse longitudinally along a grade having a slope of not less than 30 percent. The grade shall be of compacted earth, having a minimum length of approximately 100 feet.

4.4.6 Travel speed test. The unit shall have an empty travel speed of not less than 24 miles per hour on a dry, level, earthen haul road. After completion of the test, the entire unit shall be examined for evidence of excessive heating, failure, slippage, malfunction, or deformation. Failure to pass any phase of the examination and testing shall be cause for rejection. Manufacturer's certified engineering calculations will be acceptable in lieu of a test covering the lifting and tying devices.

4.4.7 Production unit test. Fill each distributor with water and operate for a run-in period of 1 hour. Check for leaks, demonstrate operation of all controls, and make any adjustments. Any leak or malfunction of any component that cannot be corrected by adjustment shall constitute failure of this test.

4.5 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-D-771 and MIL-T-3351. The inspection shall consist of the quality conformance inspection.

5. PACKAGING

5.1 Preservation, packing, and marking. Each water distributor shall be preserved, packed, and marked as specified in MIL-D-771 except that the tractor and trailer chassis shall be preserved in accordance with MIL-T-3351 and the following requirements. The level of preservation and level of packing shall be as specified (see 6.2).

5.1.1 Brakes, levels A and B preservation.

5.1.1.1 General. Clean all surfaces as required to remove contaminants. Coat unpainted exterior surfaces of rods, levers, cables, clevises, linkage, and associated parts with type P-1 preservative. Remove brake drum covers and spray enclosed metallic components with primer TT-P-664 or MIL-P-46093. Spray coat brake drum friction surfaces with a very thin coat (0.5-0.75 mil thick) of primer. Coat friction surfaces of cams, adjusting screws, and anchor pins with type P-6 or P-7 preservative. Backoff all brake shoe adjusters for maximum clearance between brake drum and brake shoes. Do not apply coating of any type to contact surfaces of electric brakes. Adjust brake shoes to provide maximum clearance to drum surfaces and lined surfaces. In a conspicuous location in the operator's compartment, attach a weatherproof warning tag marked, "Brakes preserved. Do not apply brakes when vehicle is being moved. Use tow bar or similar arrangement for moving vehicle. Adjust brakes before placing equipment into operation." Markings shall be applied with waterproof material.

5.1.1.2 Hydraulic brakes and steering systems. Remove and disassemble the brake cylinder. Clean the cylinders, pistons, springs, and other metallic surfaces normally in contact with hydraulic brake fluid with alcohol conforming to O-E-760. Flush hydraulic lines with alcohol. Follow this by cleaning process C-8. Dry by procedure D-1. Coat the cylinders, pistons, springs, rubber cups, rubber dust boots, and other internal metallic and rubber parts with silicone protector, MIL-C-21567. Fill the hydraulic system and the hydraulic fluid supply reservoirs with silicone brake fluid,

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

MIL-B-46176. Bleed as necessary to assure the system is completely filled with fluid. After filling pressure bleeder reservoir, allow fluid to stand 3-5 minutes for air bubbles to escape, before replacing cap. In order to prevent air entrainment, if vehicle is manually bled, do not depress brake pedal over one half of travel.

5.1.1.3 Air-actuated brake system. The air-actuated brake systems shall be drained. Interior surfaces of the air-supply tanks shall be fogged with type P-9 or P-10 preservative. Excess preservative oil shall be drained. Threaded openings and the threads of drain plugs shall be coated with P-10. The drain plugs shall be reinstalled. Air line filters shall be drained and closed. The exhaust ports of relay emergency, quick-release, and relay valves not equipped with exhaust check valves shall be closed by inserting caps or plugs as applicable conforming to MIL-C-5501 or by sealing the ports with waterproof tape. Attach a waterproof tag to the valves and service lines indicating, "Remove (plugs, caps, or tape) from exhaust ports and valves before operating." Markings shall be applied with a waterproof material.

6. NOTES

6.1 Intended use. The water distributors are primarily intended for use in soil stabilization and soil compaction operations requiring the accurate distribution of water at predetermined rates. The water distributors can also be used for transporting or transferring water, for application of water for dust alleviation.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. When specifications and standards shall be other than as specified (see 2.1.1).
c. When a first article distributor is to be furnished for inspection and approval (see 3.2, 4.2.1, and 6.4).
d. Level of preservation and level of packing required (see 5.1).

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first article sample, or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Custodian:

Navy - YD

Preparing activity:

Navy - YD

Project No. 3825-N161

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. 3825-N161

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-D-29224(YD) DISTRIBUTOR, WATER, TANK TYPE, SEMITRAILER TRACTOR MOUNTED 7,000 GALLON CAPACITY, DED

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.