NOT MEASUREMENT SENSITIVE

MIL-D-29224A(YD)
22 May 1989
SUPERSEDING
MIL-D-0029224(YD)
9 May 1983
MIL-D-29224(YD)
14 July 1982

MILITARY SPECIFICATION

DISTRIBUTOR, WATER, TANK TYPE, SEMITRAILER TRACTOR MOUNTED 7,000 GALLON CAPACITY, DED

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of commercial, low profile water distributor, (semitrailer tanker, single axle tractor mounted) 7,000 gallon (gal) capacity, diesel engine driven, (hereinafter referred to as the distributor), with salient features as specified herein (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Storage.
VV-F-800 - Fuel Oil, Diesel.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3825

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-D-771 - Distributors, Bitumen and Water, Packaging of.
MIL-T-3351 - Tractor, Full-Tracked, Low-Speed; Tractor Wheeled Agricultural; and Tractor Wheeled, Industrial: and their Attachments, Packaging of.

STANDARDS

FEDERAL

FED-STD-595 - Colors.

MILITARY

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DEPARTMENT OF LABOR (DoL)

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE J53 - Minimum Performance Criteria for Emergency Steering of Wheels Earthmoving Construction Machines.
SAE J88 - Sound Measurement -- Earthmoving Machinery - Exterior.
SAE J276 - Steering Frame Lock for Articulated Loaders and Tractors.
SAE J383 - Motor Vehicle Seat Belt Anchorages Design Recommendations.
SAE J537 - Storage Batteries.
SAE J925 - Minimum Service Access Dimensions for Off-Road Machines.
SAE J994 - Alarm-Backup-Electric-Performance, Test, and Application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

SAE J386 - Operator Restraint Systems for Off-Road Work Machines.
SAE J534 - Lubrication Fittings.
SAE J1040 - Performance Criteria for Rollover Protective Structures (ROPS) for Construction, Earthmoving, Forestry, and Mining Machines.
SAE J1164 - Labeling of ROPS and FOPS.
SAE J1349 - Engine Power Test Code - Spark Ignition and Diesel.
SAE J1473 - Braking Performance - Rubber-Tired Earthmoving Machines.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

TIRE AND RIM ASSOCIATION, INC. (TRA)

TRA Yearbook.

(Application for copies should be addressed to the Tire and Rim Association, Inc., 3200 West Market Street, Akron, OH 44313.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Descriptions. The distributor shall be a diesel-engine-trailer tanker, two axle type, two driven wheels, and 7,000 gallon capacity.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.2.1 and 6.2).

3.3 Standard commercial product. The distributor shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the distributor being furnished. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.4 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. Unless otherwise specified, none of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification.

3.6 Safety. All moving parts, parts subject to high operating temperature, and parts energized electrically which are of such a nature or so located as to become a hazard to become a hazard to operating and maintenance personnel shall be insulated, enclosed, or guarded to the extent necessary to eliminate the hazard. Protective devices shall not impair the operating functions. Platforms steps, handholds, and rails shall be furnished and located where necessary, to assure safe, easy access by personnel to those areas requiring frequent maintenance of service. The unit shall comply with OSHA regulations in effect at the time of manufacture. The unit shall be provided with the following equipment:

a. Safety glass windshield with power operated windshield wiper.
b. Horn.
c. Backup alarm device conforming to SAE J994.
d. Seat belt for operator's seat conforming to SAE J386.
e. Fully enclosed cab with roll-over protective structures (Rops) conforming to SAE J1040.
f. Adjustable air suspension seat.
g. Instrument panel (vandalism) protective guard.
h. Emergency steering system conforming to SAE J53.

3.7 Dimensions, cubes, and capacity. The distributor shall conform to the dimensions, cubes, and capacities specified in table I.

TABLE I. Dimensions, cubes, and capacities.

Capacity	7,000 gallons minimum
Distributor width	12 feet maximum
Distributor height	13 feet maximum
Overall length of distributor	50 feet maximum
Travel speed (fully loaded on level earth-haul road)	24 mph minimum

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.8 Roll-over protective structures (Rops). The distributor shall be furnished with a fully enclosed construction type cab with integral Rops conforming to SAE J1040 and seat belts conforming to SAE J383 and SAE J386. The Rops shall be labeled in accordance with SAE J1164. The cab shall be furnished with two doors or one door and a window opposite the door. The window shall be designed as an emergency exit sized in accordance with SAE J925. Both doors or the door and the window shall be provided with a means to hold them in an open position. The cab shall be equipped with windshield wipers, and the manufacturers standard heater/defroster. When specified, the manufacturer shall provide his current air conditioning unit (see 6.2).

3.9 Operational temperature requirements. The distributor shall be capable of starting and maintaining constant performance characteristics, at a stabilized temperature from -20° Fahrenheit (°F) to +120°F, without special equipment or modifications other than the use of antifreeze and proper lubricants; at any elevation from sea level and a maximum stabilized temperature of 102°F, and to maintain with sufficient power for operating up to a 5,000 foot (ft) elevation at a temperature of 107°F.

3.10 Tractor. The tractor shall be of the single axle type and support or incorporate as integral parts, the bumper, towing hook(s), crankcase guard, oscillating hitch assembly, operator's station, full power steering, hydraulic system, cold starting aids, power plant, power train, and emergency steering system conforming to SAE J53. The tractor frame shall be mounted on two power driven, pneumatic-tired wheels. A crankcase guard shall protect the crankcase, flywheel housing, accessories, and other assemblies exposed to damage from projections and obstructions likely to be encountered during normal earthmoving operations. Crankcase guard shall be furnished with openings which shall provide easy access to points requiring periodic servicing and cleaning. The tractor shall have individual cab-located controls for operating the unit. Each control shall be clearly identified for the intended function with a corrosion-resistant nameplate. The tractor shall be capable of making a 90 degree (°) turn with tank attached.

3.11 Trailer water tank. The trailer tank shall have a minimum capacity of 7,000 gallons, and be equipped with not less than the following: Surge baffles, manhole (not less than 18 inches (in) in diameter) with strainer and cover having a vent not less than 3 inches in diameter, hydraulic motor-driven water pump with minimum capacity of 1,200 gallons per minute at 2,000 revolutions per minute (rpm) pump speed and 15 pounds per square inch (psi) or 35 foot head, rear sprayheads and gravity spraybar. Two pressure fed sprayheads mounted on the front of the tractor shall be provided. Trailer water tank shall be single axle nondriven axle type with two wheels. All sprayheads shall be individually controlled.

3.12 Brakes. The distributor shall be equipped with service brakes, parking brakes, and an emergency stopping system that shall conform to the minimum performance requirements of SAE J1473. Brake drum guards, or brake rotor guards shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.13 Wheels rims, and tires. Wheels, rims and tires shall be demountable as an assembly, and shall have tires that are interchangeable front to rear. Tire and rim sizes, ply rating and load rating shall conform to TRA yearbook recommendations.

3.14 Power plant. The distributor shall be equipped with a liquid-cooled diesel engine. The engine shall have a minimum of 300 net horse-power when determined as specified in SAE J1349. The engine shall be capable of operation with diesel fuel conforming to VV-F-800 and shall be equipped with either glow plug or ether cold start aids. When an ether priming system is provided, it shall be of the measured shot type, controlled from the driver's compartment, with a reservoir of not less than 12 fluid ounces, and shall be inoperative when the engine is warm.

3.15 Transmission and torque converter. The distributor shall have a full torque power shift transmission. The transmission system shall provide not less than five forward speeds and one reverse speed. Torque converter oil coolers shall be furnished. Coolers shall maintain the oil entering the converters at a temperature not to exceed 240°F.

3.15.1 Accessories. The distributor shall be furnished with the following accessories:

a. Two stage intake air cleaner with service indicator.
b. Full flow oil filter with bypass.
c. Primary and secondary fuel filters.
d. Hour meter.
e. Fuel tank with sufficient capacity for 8 hours operation
f. Lubricating oil pressure indicator.
g. Coolant temperature indicator.
h. Electric cranking system.
i. Batteries.
j. Battery charging alternator/rectifier system.
k. Torque converter oil temperature indicator.
l. Battery charging indicator.
m. Heavy-duty radiator guard.
n. Tachometer.
o. 50 feet of 1-1/2 inch hose with adjustable nozzle.

3.16 Exhaust. The engine shall be equipped with an exhaust muffler, spark arrester (a muffler and spark arrester are not required if the engine is turbocharged), and stack; maximum sound level shall not exceed the recommended level of SAE J88. Exhaust stack outlets shall be provided with rain caps or 90° bends.

3.17 Toolbox. The distributor shall be provided with a toolbox made of sheet steel. The tool box shall have a hinged lid which shall not open less than 90° and a drawbolt or spring loaded latch of a type that will keep the lid closed when the toolbox is subjected to vibration. The toolbox shall be securely fastened to the distributor in a protected and accessible location. The toolbox shall be of sufficient size to hold the tools normally used to maintain the distributor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.18 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high-pressure lubricating equipment, 1,000 pound-force per square inch (psi) or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location. The unit shall be lubricated prior to delivery with the type of lubricant specified in the operator's manual and grade of lubricant recommended for ambient temperature at the delivery point. The unit shall be conspicuously tagged to identify the lubricants and their temperature range.

3.19 Servicing and adjusting. Prior to acceptance of the distributor by the Government, the contractor shall service and adjust the distributor for immediate operational use as required in the operator's manual. The servicing and adjusting shall include at least the following:

a. Inflation of all tires.
b. Adjustment of brakes.
c. Proper functioning of all lighting and electrical systems.
d. Adjustment of engine to include tune-up.
e. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point.
f. Cooling system filled to capacity with a clean solution of equal parts by volume of water and antifreeze (ethylene glycol).

The distributor shall be conspicuously tagged to identify the lubricants and their temperature range.

3.20 Lifting and tiedown attachments. The distributor shall be equipped with lifting and tiedown attachments. Lifting and tiedown attachments shall conform to type II or type III of MIL-STD-209. A nonferrous transportation plate shall be provided and mechanically attached to the distributor. Transportation plates shall be inscribed with a diagram showing the lifting attachments and lifting slings, the capacity of each attachment, and the required length and size of each sling cable. A silhouette of the item furnished showing the center of gravity shall be provided on the transportation plate. Tiedown attachments may be identified by stenciling or other suitable marking. Tiedown marking shall indicate which attachments are intended for the tiedown of the distributor on the carrier when shipped. Lifting attachments shall be designed to exclude the use of spreader bars.

3.20.1 Articulation locks. Articulated frame units shall be provided with manufacturer designed articulation locks in accordance with SAE J276. The locks shall be used when shipping, lifting or lowering the tractor and water wagon as a total unit. An instruction plate shall be provided to describe this procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.20.2 Push frame. The push frame shall incorporate a push plate or roller, and towing hook(s) and shall be mounted on the rear of the distributor. The push plate or roller and frame shall withstand the forces applied to it without deformation or breakage when the distributor is pushed with another tractor of equivalent size.

3.22 Identification plate. An identification plate will be furnished by the contracting officer for each distributor. The contractor shall stamp all necessary data in the blank spaces of the plate provided for that purpose, and securely affix a plate to each distributor in a conspicuous place with nonferrous metal screws, rivets, or bolts not less than 1/8-inch in diameter. The applicable nomenclature contained in the contract item description shall be placed in the top blank.

3.23 Electrical Systems.

3.23.1 Ignition and starting systems. The unit shall have a 24-volt (V) electrical system. Not less than two batteries shall be furnished. Each battery shall be 12V potential. The total reserve capacity rating of the batteries shall be not less than 1200 amperes, measured in accordance with SAE J537. The battery shall be of the maintenance free type with the maintenance free characteristics listed in W-B-131. The distributor shall be furnished with a battery box painted with acid resistant paint. The distributor shall be equipped with an alternator having not less than a 35-ampere rating. All wiring shall be protected against wearing and weathering. A waterproof socket receptacle, with mating plug, electrically connected to the starting system shall be furnished to facilitate emergency starting and battery charging.

3.23.2 Lighting. The lighting system shall include the following:

a. Two headlamps.
b. Instrument panel lamps to illuminate all instruments.
c. One rearward directed floodlamp.
d. Two taillights and two stoplights. These lights may be a combination of both.

3.24 Cleaning, treatment, and painting. Surfaces which are to be painted shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be Green No. 14064, conforming to FED-STD-595, unless otherwise specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as soil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat of acrylic-based enamel. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

3.25 Workmanship.

3.25.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame-cutting, using tips suitable for the thickness of the metal, may be used instead of shearing and sawing. All bends shall be made by controlled means to ensure uniformity of shape and size. Precautions shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly. External surfaces shall be free from burrs, sharp edges and corners, except when sharp edges or sharp corners are required by design, or where they are not detrimental to safety.

3.25.2 Bolted connections. Boltholes shall be punched or drilled within manufacturer's design tolerances and shall have the burrs removed. Washers or lockwashers shall be provided, and all bolts, nuts, and screws shall be tight.

3.25.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.25.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.25.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perform its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practic to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on a distributor when a first article is required (see 3.2 and 6.2). This inspection shall include the examination of 4.3 and the tests of 4.4. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.3, the tests of 4.4, and the packaging inspection of 4.5. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Examination. Each distributor shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4 Tests. The first article shall be tested as specified in 4.1 thru 4.4.7. Each production unit shall be tested as specified in 4.4.7. Failure to pass any test shall constitute cause for rejection.

4.4.1 Performance tests. Each distributor shall be subjected to the tests as specified below. Failure to pass any phase of these tests shall be cause for rejection. The tests shall, as a minimum, assure that each unit is capable of meeting the performance requirements as specified in section 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

The distributor shall be cycled not less than two times. The tank shall be loaded to a capacity of not less than 7,000 gallons and each load shall be dumped without assistance from auxiliary equipment.

4.4.2 Preliminary tests. The distributor shall be generally examined and inspected to determine acceptability on the basis of conformance to contract requirements.

4.4.3 Load-haul-dump test. The hauling distance for each cycle shall be not less than 1,500 feet (ft).

4.4.4 Gradability test. The distributor, loaded to the specified capacity shall negotiate an approximately 100 foot long, well compacted earth grade, having a minimum slope of 20 percent (%). The distributor shall travel up and down this slope three times.

4.4.5 Side hill slope test. Without any payload, the distributor shall traverse longitudinally along a grade having a slope of not less than 30%. The grade shall be of compacted earth, having a minimum length of approximately 100 feet.

4.4.6 Travel and speed test. The distributor loaded to the specified capacity shall have travel speed of not less than 24 miles per hour (mph) on a dry, level, earthen haul road. After completion of the test, the entire distributor shall be examined for evidence of excessive heating, failure, slippage, malfunction, or deformation. Failure to pass any phase of the examination and testing shall be cause for rejection.

4.4.7 Production unit test. Fill each distributor with water and operate for a run-in period of one hour. Check for leaks, demonstrate operation of all controls, and make any adjustments. Any leak or malfunction of any component that cannot be corrected by adjustment shall constitute failure of this test.

4.5 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-D-771 and MIL-T-3351. The inspection shall consist of the quality conformance inspection.

5. PACKAGING

5.1 Preservation, packing, and marking. Each water distributor shall be preserved, packaged in accordance with the contractor's standard practice. When specified (see 6.2), the water distributor shall be preserved, packaged, and marked as specified in MIL-D-771 except that the tractor and trailer chassis shall be preserved in accordance with MIL-T-3351.

6. NOTES

(This section contains information of a general or explanataory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The water distributors are primarily intended for use in soil stabilization and soil compaction operations requiring the accurate distribution of water at predetermined rates. The water distributors can also be used for transporting or transferring water, for application of water for dust alleviation.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of the documents referenced (see 2.1.1 and 2.2).
c. When a first article distributor is to be furnished for inspection and approval (see 3.2, 4.2.1, and 6.4).
d. When the water distributor shall be preserved packaged, and and marked in accordance with MIL-D-771 and MIL-T-3351 (see 5.1).
e. When the manufacturers standard air conditioner shall be provided (see 3.8).
f. Color of finish coat required if other than specified (see 3.24).
g. When special lubrication is required.

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID'S are tailored to reflect the requirements of the specific acquisition. To ensure correct contractural application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirements for a DD Form 1423.

6.4 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a first article sample, a first production item, or a standard production item from the contractor's current inventory and the number of items to be tested as specified in 4.4. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Subject term (key word) listing

Compaction
Soil stabilization
Excavation
Construction equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Navy - YD

Preparing activity:
Navy - YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Code 156
Naval Construction Battalion Center
Port Hueneme, CA [illegible]-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-29224A(YD)	MILITARY SPECIFICATION – DISTRIBUTOR, WATER, TANK TYPE, SEMITRAILER TRACTOR MOUNTED 7,000 GALLON CAPACITY, DED

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T22:21Z
Check the source to verify that this is the current version before use.